



2019 | VOLUME 2

BROADCAST & CINEMA LENS CATALOG



INNOVATION
In TV Optics Since 1958

Toward 100 years anniversary



Canon
SEE IMPOSSIBLE





CANON BROADCAST ZOOM LENSES

Celebrating Canon's Storied History

Development of Broadcast Zoom Lenses

In 1958, Canon launched its broadcast lens business by introducing the innovative high zoom ratio 6.7 IF-1 lens. Ever since, Canon has continued to listen to the demands of broadcasters and cinematographers around the world by developing lenses based on industry trends.

Canon's Emmy®-Winning Lens Technology

Canon's highly regarded lens technology is a recipient of the Technology and Engineering Emmy® Award. The National Academy of Television Arts and Sciences awarded Canon a Technology & Engineering EMMY® Award in 2005 in recognition of our engineering creativity in Lens Technology Developments for Solid State Imager Cameras in High Definition Formats. We also received an EMMY® in 1996 for *"Implementation In Lens Technology to Achieve Compatibility with CCD Sensors."* In addition, we received an EMMY® in 2017 for "Large Format 4K Zoom Lenses".



CANON'S LENS TECHNOLOGY: WELCOME TO THE 4K/UHD ERA



UHDxs UHD-DIGISUPER 122



UHDxs UHD-DIGISUPER 111



UHDxs UHD-DIGISUPER 90



UHDxs CJ45ex9.7B



UHDxs CJ45ex13.6B



UHDxs CJ25ex7.6B



UHDdec CJ18ex28B



UHDdec CJ15ex8.5B



CN-E14.5-60mm T2.6 L S
CN-E14.5-60mm T2.6 L SP



CN-E30-300mm T2.95-3.7 L S
CN-E30-300mm T2.95-3.7 L SP



CN-E15.5-47mm T2.8 L S
CN-E15.5-47mm T2.8 L SP



CN-E30-105mm T2.8 L S
CN-E30-105mm T2.8 L SP



CN-E14mm T3.1 FP X



CN-E20mm T1.5 FP X



CN-E24mm T1.5 FP X



CN-E35mm T1.5 FP X



CN-E50mm T1.3 FP X



CN-E85mm T1.3 FP X



CN-E135mm T2.2 FP X

4K



UHDxs UHD-DIGISUPER 86



UHDxs UHD-DIGISUPER 27



UHDxs UHD-DIGISUPER 66



UHDxs CJ20ex7.8B



UHDxs CJ15ex4.3B



UHDxs CJ12ex4.3B



UHDgc CJ24ex7.5B



UHDgc CJ18ex7.6B



UHDgc CJ14ex4.3B



COMPACT-SERVO
18-80mm T4.4 EF



COMPACT-SERVO
70-200mm T4.4 EF



CINE-SERVO 17-120mm T2.95-3.9 EF
CINE-SERVO 17-120mm T2.95-3.9 PL



CINE-SERVO 50-1000mm T5.0-8.9 EF
CINE-SERVO 50-1000mm T5.0-8.9 PL



CN-E14mm T3.1 L F



CN-E20mm T1.5 L F



CN-E24mm T1.5 L F



CN-E35mm T1.5 L F



CN-E50mm T1.3 L F



CN-E85mm T1.3 L F



CN-E135mm T2.2

Broadcast Zoom Lens Lineup



Studio & Field
Lenses



ENG/EFP
Lenses



Pro-Video &
Remote-Controlled
Lenses

Broadcast Studio and Field Lenses

P. 14 - 15

4K UHD 2/3"	UHD-DIGISUPER 122 4K Premium UHDxs 	UHD-DIGISUPER 111 4K Premium UHDxs 	UHD-DIGISUPER 86 4K Premium UHDxs 
	UHD-DIGISUPER 90 4K UHDxs 	UHD-DIGISUPER 66 4K UHDxs 	UHD-DIGISUPER 27 4K Premium UHDxs 
HD 2/3"	DIGISUPER 100AF HDxs Auto Focus 	DIGISUPER 100 HDxs 	DIGISUPER 95 TELE HDxs 
	DIGISUPER 95 HDxs 	DIGISUPER 86AF HDxs Auto Focus 	DIGISUPER 80 HDxs 
	DIGISUPER 76 HDxs 	DIGISUPER 27AF HDxs Auto Focus 	DIGISUPER 27 HDxs 
			DIGISUPER 22 xs HDxs 

Broadcast ENG/EFP Lenses

P. 18, 19, 20

4K UHD 2/3"	CJ45ex13.6B 4K UHDxs 	CJ45ex9.7B 4K UHDxs 	CJ25ex7.6B 4K UHDxs 	CJ20ex7.8B 4K UHDxs 
	CJ15ex4.3B NEW 4K UHDxs 	CJ12ex4.3B 4K UHDxs 	CJ24ex7.5B 4K UHDGC 	CJ18ex7.6 4K UHDGC 
HD 2/3"	CJ14ex4.3B 4K UHDGC 	CJ18ex28B 4K UHDGC 	CJ15ex8.5B 4K UHDGC 	
	HJ40ex14B HDxs 	HJ40ex10B HDxs 	HJ21ex7.5B HDxs 	HJ17ex6.2B HDxs 
HD 1/3"	KJ22ex7.6B HDGC 	KJ17ex7.7B HDGC 	KJ10ex4.5B HDGC 	
	KT17ex4.3B HDGC 			

Pro-Video Lenses

P. 20

HD 2/3"	KJ20x8.2B (IRSD) HDGC 	KJ20x8.2B (KRSD) HDGC 	KJ13x6B HDGC 
	HD 1/2"	KH20x6.4 HDGC 	

Remote Controlled Lenses

P. 21

HD 2/3"	KJ22ex7.6B (ITS-ME/RE) 	KJ17ex7.7B (ITS-ME/RE) 	KJ20x8.2B (KTS) 
	HD 1/2"	KH20x6.4 (KTS) 	

CANON BROADCAST LENSES

Focal Length Table

Broadcast, Studio and Field Lenses (4K 2/3", HD 2/3")																									
Angle of view horizontal (16:9)	72.9°	66.7°	60.7°	60.1°	58.3°	57.2°	56.1°	54.6°	42.3°	39.1°	3.4°	3.1°	1.02°	0.92°	0.81°	0.80°	0.77°	0.69°	0.68°	0.67°	0.65°	0.59°	0.59°	0.55°	0.47°
Focal Length (mm)	6.5	7.3	8.2	8.3	8.6	8.8	9	9.3	12.4	13.5	161	180	540	600	675	690	710	800	810	820	840	925	930	1000	1178
UHD-DIGISUPER 122	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
UHD-DIGISUPER 111	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
UHD-DIGISUPER 90	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
UHD-DIGISUPER 86	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
UHD-DIGISUPER 66	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
UHD-DIGISUPER 27	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 100 AF	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 100	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 95 TELE	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 95	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 86 AF	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 80	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 76	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 27 AF	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 27	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								
DIGISUPER 22 xs	[Bar chart showing angle of view for focal lengths 6.5 to 1178 mm]																								

Broadcast ENG/EFM Lenses (4K 2/3", HD 2/3")																																			
Angle of view horizontal (16:9)	96.3°	93.7°	77.3°	75.5°	65.2°	64.6°	63.9°	63.2°	58.9°	52.7°	51.3°	38.9°	37.8°	35.5°	19.6°	12.2°	10.5°	9.1°	7.0°	5.2°	4.3°	4.2°	4.0°	3.5°	3.5°	3.4°	3.3°	3.1°	2.89°	1.4°	1.26°	1.1°	1.0°	0.9°	
Focal Length (mm)	4.3	4.5	6	6.2	7.5	7.6	7.7	7.8	8.5	9.7	10	13.6	14	15	28	45	52	60	65	78	106	128	131	137	156	158	164	168	180	190	400	437	500	560	612
CJ45ex13.6B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ45ex9.7B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ25ex7.6B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ20ex7.8B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ15ex4.3B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ12ex4.3B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ24ex7.5B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ18ex28B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ18ex7.6B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ15ex8.5B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
CJ14ex4.3B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
HJ40ex14B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
HJ40ex10B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
HJ21ex7.5B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
HJ17ex6.2B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
KJ22ex7.6B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
KJ17ex7.7B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		
KJ10ex4.5B	[Bar chart showing angle of view for focal lengths 4.3 to 612 mm]																																		


Broadcast ENG/EFM Lenses (HD 1/3")	
Angle of view horizontal (16:9)	58.3°
Focal Length (mm)	4.3
KT17ex4.3B	3.8°

Focal Length Table

Pro-Video Lenses (HD 2/3")	
Angle of view horizontal (16:9)	96.3° 93.7° 77.3° 75.5° 65.2° 64.6° 63.9° 63.2° 60.7° 58.9° 51.3° 47.1° 37.8° 35.5° 19.6° 12.2° 10.5° 9.1° 7.0° 5.2° 4.3° 4.2° 4.0° 3.5° 3.5° 3.4° 3.3° 3.1° 1.45° 1.4° 1.1° 1.15° 1.0°
Focal Length (mm)	4.3 4.5 6 6.2 7.5 7.6 7.7 7.8 8.2 8.5 10 11 14 15 28 45 52 60 78 106 128 131 137 156 158 164 168 180 385 400 500 525 560
KJ20x8.2B	
KJ13x6B	

Pro-Video Lenses (HD 1/2")	
Angle of view horizontal (16:9)	75.7° 57.1° 6.8° 3.1°
Focal Length (mm)	4.5 6.4 59 128
KH20x6.4	
KH13x4.5	

Understanding Canon Lens Naming Conventions



Canon Broadcast Lens Technology

Optical Performance

Superb Optical Materials Produce a High-Performance Lens


Fluorite · UD Glass · Hi-UD Glass

Unlike conventional optical glass, Fluorite has remarkably low dispersion properties. Realizing the effectiveness of Fluorite glass, Canon has put it to practical use in many lenses, primarily in the anterior section of zoom lenses to help correct telephoto chromatic aberration. Both UD¹ glass and Hi-UD glass² have dispersion properties similar to Fluorite and are effective for correcting chromatic aberration. Due to its high refractive characteristics, Hi-UD glass is especially known for its spherical aberration correction. Used in the anterior and zooming sections of a lens, Hi-UD glass is effective for controlling aberration fluctuation seen when focusing and zooming.




¹ UD-Ultra Low Dispersion.

² Hi-UD High Index Ultra Low Dispersion.



Air Sphere Coating

In the context of HDR Optical imaging, Air Sphere Coating (ASC) technology is a critically important new innovation in broadcast field lenses. This is a Canon-developed technology that is an additional layer deposited on top of the normal multilayer coatings that are used to minimize numerous internal reflections that conspire to lower light transmission efficiency and to contaminate deep black reproduction. ASC is an ultra-low refractive index silicon dioxide film that includes microscopic air spheres having a sub-nanometer diameter arranged in regular structure. Because



these spheres are microscopic when comparing to the wavelength of visible light and as they are in an ordered array, light does not scatter. In combination with the multilayer coatings, ASC achieves far lower reflectance and significantly reduces flare and ghosting.

Bokeh Effect


When shooting in macro, the focus position of the lens can be changed as the focal length is adjusted, when using the optional MCJ-S02 Macro Controller, creating a bokeh effect. This built-in feature can be utilized to support special techniques in which the focus position can be shifted within the same shot just by using the Macro Controller, allowing for subtle creative defocus effects. This can help provide a degree of creativity when shooting live events such as a concert.



High Quality, Compact Size and Weight

Large Aperture Aspheric Lens

Spherical aberration will increase as the diameter of a spherical lens increases. However, aspheric lenses form an ideal shape for aberration correction and are the desired lens type for improving optical performance. As they are more compact, aspheric lenses reduce the weight of the entire lens system. Through its optical design and large aperture processing techniques, Canon has developed compact, large aperture, high magnification field zoom aspheric lenses. As a result of this development, all high-magnification field zoom lenses released since 2000 have a constant total lens length regardless of zoom ratio.



Focus Breathing Suppression

Constant Angle Focusing System (CAFS)

CAFS is a technology that suppresses view-angle fluctuation (breathing) while focusing. The Zooming Effect of Focus is the phenomenon where the picture size (angle of view) changes when focusing. Canon's 32-bit CPU calculates and controls the zoom when focusing in order to counteract this phenomenon. As a result of CAFS, the UHD-DIGISUPER and DIGISUPER Series has zero Zooming Effect of Focus.

Advanced Design Technology to Help Minimize Various Aberrations

Image Stabilizer (IS)

Canon launched its first field zoom lens with a shift type anti-vibration mechanism in 2000*. Prior to that, Canon introduced the IS-20B anti-vibration adapter for portable zoom lenses. Those cutting-edge technologies, along with the Vari-angle Prism image stabilizer (VAP-IS) lens, helped to usher in the era of optical image stabilization in broadcasting lenses.


**Adopted for DIGISUPER 86 XS (XJ86 × 9.3 B). The world's first field zoom lens for broadcasting.*

Auto Focus

TTL Secondary Imaging Phase Difference Detection Method

The Secondary Imaging Phase Difference Detection Method, also used in single lens reflex EOS camera lenses, was adopted for broadcast autofocus systems. As a result of this Method, Canon's Auto Focus System has excellent focusing accuracy within the entire zoom range, along with outstanding focusing speed. Due to high performance servo motors, tracking a moving object at high speed can be possible even from a largely out of focus state.

Autofocus Two Types of Operation



AF Mode

Select DIGISUPER lenses provide two autofocus modes. "FULL TIME AF" provides continuous autofocus operation allowing the camera operator to focus on framing the subject. "PART TIME AF" allows for temporary autofocus use with manual focus. The modes can be switched on and off as needed, using the ACTIVE/HOLD switch.

AF In-Focus Display

By using the FDJ - P41 dedicated focus demand, you can change the size (3 options) and position of the AF in-focus frame displayed on the viewfinder*.

**To change the in-focus frame, it is necessary to interlock with the camera.*




Digital Technology

Digital Servo System/Digital Drive Unit

Since the release of the DIGISUPER 70 in 1995, Canon has been a leader in digital broadcast zoom lens control. Canon's ENG/EFP lenses, having the same digital technology, offer a wealth of features to make shooting more efficient. Canon's digital drive unit is installed in all ENG/EFP and Provideo broadcast lenses.

Shuttle Shot

At the touch of a button, this feature allows the operator to zoom back and forth instantly between any two positions at the maximum speed or at any speed memorized in the Speed Presets.




Normal view angle A

Field of view of shuttle memory B

Frame Preset

With the Frame Preset feature, a preset frame position can be saved and repeated multiple times.




Normal view angle A

The angle of view B


Speed Preset

Simply press a button to recall the preset zoom speed.



Zoom Servo Characteristics

Zoom Servo characteristics can be selected from two curvature options on the ZDJ-P01 zoom demand.



Zoom Servo Characteristics Example

Virtual Studio System

Canon has a series of HDxs and HDGC (IRSE/IASE version) lenses which are equipped with an enhanced digital drive unit. The digital drive unit's 16-bit encoder makes detection and output of positional information possible at a much higher resolution than an analog position sensor (equivalent to 10 bits). The 16-bit resolution rotary encoder built into the drive unit can be integrated into a virtual studio system. The encoders enable precise control as the zoom servo has a range of 0.5 second quick zooms to over a 5 minute super slow zoom. Repeatability in focus and iris control are also precise. Canon's technology has made the encoder device very small, allowing it to be installed in the existing drive unit without adding size or weight.

Further Improving Operational Efficiency

Type S Drive Unit

Canon has improved the operational efficiency of its lenses with the adoption of the Type S Drive Unit ^{*1}.

- Matches the aberration correction function on the camera without initialization at power-on
- Reduced power consumption by about 10% ^{*2} when using a battery as compared with previous versions
- Real and virtual images can easily be calibrated with high-precision position detection
- Three 20 PIN connectors allow for simultaneous full servo and virtual system operation
- Easy operation with straightforward menu and display

^{*1}: Please refer to page 6, *Understanding Canon Naming Conventions, Special Functions (2)*.

^{*2}: When zoom, focus & iris in operation.


Zoom Track

The zoom control range can be set within a more limited range on both the telephoto and wide-angle sides of UHD-DIGISUPER and DIGISUPER Series lenses. With these lenses and the optional ZDJ-P01 zoom demand, the zoom range can be set to virtually any range smaller than the full focal range of the lens. If not used to limit the zoom range, the feature can be used to memorize an additional preset zoom position.

Ergonomic Design

Compact and Lightweight Drive Unit

Canon's HDxs, and HDGC (IRSE/IASE models) Ergonomic Drive Units are tilted at an ideal angle of 12.5 degrees to realize good balance and comfort. An informational display has been added which now allows the user to customize the enhanced digital functions easily, precisely and fully. The enhanced digital functions are easily accessed and set using the Digital Function Selector, an X-Y axis switch located next to the display.



THE NEW ERA OF

NEW BCTV LENSES DESIGNED TO SUPPORT THE TRANSITION TO 4K UHD CONTENT CREATION

HDTV is now firmly established worldwide and HD production is expected to continue for many years to come. Ultra HDTV – generally referred to as UHD – has more recently emerged as the next generation of enhanced television service. In 2015 the International Telecommunications union published their ITU-R BT.2020 standard “Parameter Values for UHDTV Systems for Production and international Program Exchange” – that included both 4K UHD and 8K UHD production formats. This standard includes a Wide Color Gamut (WCG). In 2016 they published the ITU-R BT.2100 standard “Image Parameter Values for High Dynamic Range Television for use in Production and International Program Exchange”. This standard specifically applies the High Dynamic Range (HDR) to the HD, 4K UHD, and 8K UHD production formats (all exclusively progressive scan). In September 2017 the industry body – Ultra HD Forum – published their updated Guidelines on technologies and practices that support a commercially deployable Ultra HD real-time linear service with live and pre-recorded content in 2016, which is termed a “UHD Phase A” service. They include 4K UHD and 1080P HD (that includes both HDR and WCG).

These standards and guidelines have spurred increasing attention to the adoption of 4K UHD origination of sports, concerts, and major events. The anticipated protracted coexistence of HDTV and UHDTV has spawned a new generation of 2/3-inch multi format broadcast camera systems – from most of the major international camera manufacturers – that can selectively originate HD or UHD. To support this new era of mixed HD / UHD origination Canon has invested heavily into the development of an array of 2/3-inch 4K UHD broadcast lenses that encompass long zoom field lenses, a studio lens, and a broadening family of portable lenses.

STUDIO / FIELD BOX LENSES			EFP / ENG PORTABLE LENSES		
LENS SERIES	PERFORMANCE		LENS SERIES	PERFORMANCE	
UHD _{XS}	4K Premium	↑ 1080P/HDR/WCG	UHD _{XS}	4K	↑ 1080P/HDR/WCG
UHD _{XS}	4K		UHD _{GC}	4K	
HD _{XS}	HD		HD _{XS}	HD	
		HD _{GC}	HD		
			HD _{GC}	HD	

Simplistic mapping of the performance levels within the separate categories of box lenses and portable lenses.


IMPLICATIONS OF HDR AND WCG

Delivering the requisite high image sharpness required for 4K UHD – while simultaneously lowering traditional optical aberrations (that can be more exposed by the high resolution image sensors) – called for multiple innovations in lens design and manufacturing. Lateral chromatic aberration causes color misregistration on high contrast edges within the imagery – especially toward picture extremities. Longitudinal chromatic aberration causes color fringing on any speculars with this imagery. HDR and WCG further enhance the visibility of these

ENHANCED HDTV AND UHD TV

aberrations – because of the elevation in the color volume of the camera video – placing a greater onus on suppressing them to where they become subjectively invisible.

HDR




To support HDR the lens must accurately reproduce scene speculars and minimize optical artifacts stimulated by strong scene highlights.

UHD LENS PERFORMANCE HIERARCHY

In the case of the large box field and studio lenses and the portable EFP/ENG lenses Canon has created two performance levels in each. A special priority is assigned to elevating image sharpness (the essence of 4K UHD). An attendant high priority underlies design strategies that aggressively curtail the visibility of the two chromatic aberrations. Higher luminance levels and allied greater color volume associated with HDR / WCG combine to elevate the visibility of even small levels of these chromatic aberrations.

In the case of the Box lenses advanced design strategies allied with advanced optical glass materials are mobilized to maintain high image sharpness across the image plane, over the total focal ranges, and over a wide range of object distances. The 4K PREMIUM box lenses take these strategies to a particularly high level to further tighten those optical performance specifications.




In the case of the portable lenses, similar priorities apply. The UHDxs manifests higher sharpness and lower chromatic aberrations when compared to the UHDgc – although on a different scale to the box lenses.

MULTI-GROUP ZOOMING SYSTEM

In seeking longer focal ranges for the box field and studio lenses and some of the longer focal length portable lenses, challenges in achieving the requisite zooming speeds while also achieving UHD performance were escalated. This called for a radical new design approach to the zooming optical subsystems. The central goals were to achieve greater control over multiple lens aberrations to help ensure full 4K performance while at the same time expediting


an increase in the speed of the zooming action (when the digital drive unit is set to maximum zoom speed).



The traditional two group zooming system (right picture) is being replaced with a three group zooming system (left picture). Three movable groups move differentially with respect to each other over the zoom range. Design optimization consisted in balancing the weight of the three individual groups with their stroke distance during zooming action.

FLOATING FOCUSING SYSTEM

The focus optical subsystem entails high responsibility for numerous optical performance parameters and operational considerations. The lens maximum relative aperture is largely determined by the diameter of this lens input optical grouping. In addition, focus breathing (undesirable alteration to the field angle as the focus control is actuated) characteristics and aberration behavior are associated with this optical subsystem. Overall lens size and weight are heavily proportional to decisions made in the overall design of this system. Central to the design is curtailing the size and weight of the moving lens system. To help ensure UHD optical performance focus fluctuations must be suppressed – and this was accomplished by using two separate moving groups.



New innovations in a floating focus group support 4K UHD performance while curtailing size and weight

Broadcast Studio/Field Lenses

4K UHD 2/3"

	UHD-DIGISUPER 122 UHDxs		UHD-DIGISUPER 111 UHDxs		UHD-DIGISUPER 86 UHDxs		UHD-DIGISUPER 27 UHDxs	
Appearance	 4K Premium IMAGE STABILIZER		 4K Premium IMAGE STABILIZER		 4K Premium IMAGE STABILIZER		 4K Premium	
Model Name	UJ122x8.2B		UJ111x8.3B		UJ86x9.3B		UJ27x6.5B	
Zoom Ratio	122x		111x		86x		27x	
Focal Length	8.2 ~ 1000mm		8.3 ~ 925mm		9.3 ~ 800mm		6.5 ~ 180mm	
Maximum Relative Aperture	F1.7 (8.2 ~ 340mm) F5.0 (1000mm)		F1.7 (8.3 ~ 340mm) F4.65 (925mm)		F1.7 (9.3 ~ 340mm) F4.0 (800mm)		F1.5 (6.5 ~ 123mm) F2.2 (180mm)	
Angular Field of View	60.7°×36.5° (8.2mm) 0.55°×0.31° (1000mm)		60.1°×36.0° (8.3mm) 0.59°×0.33° (925mm)		54.6°×32.4° (9.3mm) 0.69°×0.39° (800mm)		72.9°×45.1° (6.5mm) 3.1°×1.7° (180mm)	
M.O.D.*	3.0m		3.0m		3.0m		0.6m	
Object Dimensions at M.O.D.*	314.8×177.1cm (8.2mm) 2.7×1.5cm (1000mm)		311.6×175.3cm (8.3mm) 2.9×1.6cm (925mm)		271.9×152.9cm (9.3mm) 3.3×1.9cm (800mm)		106.1×59.7cm (6.5mm) 3.8×2.1cm (180mm)	
Approx. Size (WxHxL)	9.9x10.1x25.1 in. (250.6×255.5×637.4mm)		9.9x10.1x25.1 in. (250.6×255.5×637.4mm)		9.9x10x25 in. (250.6×255.5×637.4mm)		9.9x10.1x21.7 in. (250.6×255.5×550mm)	
Approx. Weight	58.6 lbs (26.6kg) ※		58.6 lbs (26.6kg) ※		59.5 lbs (27.0kg) ※		47.4 lbs (21.5kg) ※	

4K UHD 2/3"

	UHD-DIGISUPER 90 UHDxs		UHD-DIGISUPER 66 UHDxs	
Appearance	 4K IMAGE STABILIZER		 4K IMAGE STABILIZER	
Model Name	UJ90x9B		UJ66x9B	
Zoom Ratio	90x		66x	
Focal Length	9 ~ 810mm		9 ~ 600mm	
Maximum Relative Aperture	F2.4 (9 ~ 486mm) F4.0 (810mm)		F1.7 (9 ~ 340mm) F3.0 (600mm)	
Angular Field of View	56.1°×33.4° (9mm) 0.68°×0.38° (810mm)		56.1°×33.4° (9mm) 0.92°×0.52° (600mm)	
M.O.D.*	3.0m		3.0m	
Object Dimensions at M.O.D.*	287.9×161.9cm (9mm) 3.3×1.9cm (810mm)		287.9×161.9cm (9mm) 4.4×2.5cm (600mm)	
Approx. Size (WxHxL)	9.9x10x24 in. (250.6×255.5×610mm)		9.9x10.1x24 in. (250.6×255.5×610mm)	
Approx. Weight	51.2 lbs (23.2kg) ※		51.1 lbs (23.2kg) ※	

※ Weight of lens body only (does not include servo module).
* M.O.D. = Minimum Object Distance.

UHD-DIGISUPER 122: Highlights

High Zoom Ratio and Long Focal Length

While displaying performance that surpasses 4K, the lens has the high zoom ratio (122x) and long focal length (1000 mm) desired by many in television production.

Elimination of Image "Lag" Following Operational Pan/Tilt Movements

The image stabilization system must be capable of distinguishing between unwanted physical perturbations to the lens-camera system and operational control of panning and tilting of the same. In the UHD-DIGISUPER 122 lens new correction strategies have been implemented. As a result, the vibration component of the sensor detection signal and the panning operation component can be separated rapidly and with high accuracy.

Ideally Suited to 4K Shooting

Lens is ideally suited for 4K UHD shooting required when telecasting live sports events and other applications.

Air Sphere Coating (ASC) Technology

This is a Canon-developed technology that is an additional layer deposited on top of the normal multilayer coatings that are used to minimize those many internal reflections that conspire to lower light transmission efficiency and to contaminate deep black reproduction.

Bokeh Effect Controller

When shooting in macro, the focus position of the UHD-DIGISUPER 122 can be changed as the focal length is adjusted, when using the optional MCJ-S02 Macro Controller. This built-in feature can be utilized to support special techniques in which the focus position can be shifted within the same shot just by using the Macro Controller, allowing for subtle creative defocus effects. This can help provide a degree of creativity when shooting live events such as a concert.



Compatibility with HD Lens Systems

The lens enables the use of the same Canon standard controllers for zoom and focus as well as servo modules currently used by HD equipment. It comes with a 20-pin connector compatible with virtual units and that enables high-accuracy position information of the zoom, focus and iris to be read out.

Broadcast Studio/Field Lenses

HD 2/3"

	DIGISUPER 100AF HDxs		DIGISUPER 100 HDxs		DIGISUPER 95 TELE HDxs		DIGISUPER 95 HDxs	
Appearance								
	IMAGE STABILIZER		IMAGE STABILIZER		IMAGE STABILIZER		IMAGE STABILIZER	
Model Name	XJ100x9.3B AF		XJ100x9.3B		XJ95x12.4B		XJ95x8.6B	
Zoom Ratio	100x		100x		95x		95x	
Focal Length	9.3 ~ 930mm 18.6 ~ 1860mm (2.0x)		9.3 ~ 930mm 18.6 ~ 1860mm (2.0x)		12.4 ~ 1178mm 24.8 ~ 2356mm (2.0x)		8.6 ~ 820mm 17.2 ~ 1640mm (2.0x)	
Maximum Relative Aperture	F1.7 (9.3 ~ 296mm) F4.7 (930mm)		F1.7 (9.3 ~ 296mm) F4.7 (930mm)		F2.5 (12.4 ~ 491mm) F6.0 (1178mm)		F1.7 (8.6 ~ 340mm) F8.2 (1640mm)	
Angular Field of View	54.6°×32.4° (9.3mm) 0.59°×0.33° (930mm)		54.6°×32.4° (9.3mm) 0.59°×0.33° (930mm)		42.3°×24.6° (12.4mm) 0.47°×0.26° (1178mm)		58.3°×34.9° (8.6mm) 0.67°×0.38° (820mm)	
M.O.D.*	3.0m		3.0m		3.0m		3.0m	
Object Dimensions at M.O.D.*	276.4×155.5cm (9.3mm) 2.8×1.6cm (930mm)		276.4×155.5cm (9.3mm) 2.8×1.6cm (930mm)		209.5×117.8cm (12.4mm) 2.3×1.3cm (1178mm)		298.1×167.7cm (8.6mm) 3.2×1.8cm (820mm)	
Approx. Size (WxHxL)	9.9x10x26 in. (250.6×255.5×661.5mm)		9.9x10x24 in. (250.6×255.5×610mm)		9.9x10x24 in. (250.6×255.5×610mm)		9.9x10x24 in. (250.6×255.5×610mm)	
Approx. Weight	59.3 lbs (26.8kg) ※		51.8 lbs (23.5kg) ※		51.1 lbs (23.2kg) ※		51.1 lbs (23.2kg) ※	

HD 2/3"

	DIGISUPER 86AF HDxs		DIGISUPER 80 HDxs		DIGISUPER 76 HDxs	
Appearance						
	IMAGE STABILIZER		IMAGE STABILIZER		IMAGE STABILIZER	
Model Name	XJ86x9.3B AF		XJ80x8.8B		XJ76x9B	
Zoom Ratio	86x		80x		76x	
Focal Length	9.3 ~ 800mm 18.6 ~ 1600mm (2.0x)		8.8 ~ 710mm 17.6 ~ 1420mm (2.0x)		9.0 ~ 690mm 18.0 ~ 1380mm (2.0x)	
Maximum Relative Aperture	F1.7 (9.3 ~ 340mm) F4.0 (800mm)		F1.7 (8.8 ~ 340mm) F3.5 (710mm)		F1.7 (9.0 ~ 340mm) F3.45 (690mm)	
Angular Field of View	54.6°×32.4° (9.3mm) 0.69°×0.39° (800mm)		57.2°×34.1° (8.8mm) 0.77°×0.44° (710mm)		56.1°×33.4° (9mm) 0.80°×0.45° (690mm)	
M.O.D.*	3.0m		3.0m		3.0m	
Object Dimensions at M.O.D.*	276.4×155.5cm (9.3mm) 3.2×1.8cm (800mm)		290.0×163.1cm (8.8mm) 3.7×2.1cm (710mm)		282.4×158.9cm (9mm) 3.8×2.1cm (690mm)	
Approx. Size (WxHxL)	9.9x10x26 in. (250.6×255.5×661.5mm)		9.9x10x24 in. (250.6×255.5×610mm)		9.9x10x24 in. (250.6×255.5×610mm)	
Approx. Weight	59.3 lbs (26.8kg) ※		51.1 lbs (23.2kg) ※		50.6 lbs (23.0kg) ※	

HD 2/3"

	DIGISUPER 27AF HDxs		DIGISUPER 27 HDxs		DIGISUPER 22 xs HDxs	
Appearance						
Model Name	XJ27x6.5B AF		XJ27x6.5B		XJ22x7.3B	
Zoom Ratio	27x		27x		22x	
Focal Length	6.5 ~ 180mm 13 ~ 360mm (2.0x)		6.5 ~ 180mm 13 ~ 360mm (2.0x)		7.3 ~ 161mm 14.6 ~ 322mm (2.0x)	
Maximum Relative Aperture	F1.5 (6.5 ~ 123mm) F2.2 (180mm)		F1.5 (6.5 ~ 123mm) F2.2 (180mm)		F1.8 (7.3 ~ 111.5mm) F2.6 (161mm)	
Angular Field of View	72.9°×45.1° (6.5mm) 3.1°×1.7° (180mm)		72.9°×45.1° (6.5mm) 3.1°×1.7° (180mm)		66.7°×40.6° (7.3mm) 3.4°×1.9° (161mm)	
M.O.D.*	0.6m		0.6m		0.8m	
Object Dimensions at M.O.D.*	106.1×59.7cm (6.5mm) 3.8×2.1cm (180mm)		106.1×59.7cm (6.5mm) 3.8×2.1cm (180mm)		118.1×66.4cm (7.3mm) 5.2×2.9cm (161mm)	
Approx. Size (WxHxL)	9.9x10.1x22.3 in. (250.6×255.5×567mm)		9.9x10.1x21.7 in. (250.6×255.5×550mm)		6.5x6.9x13.2 in. (165×175×336mm)	
Approx. Weight	51.4 lbs (23.3kg) ※		48.3 lbs (21.9kg) ※		13.42 lbs (6.1kg)	


※ Weight of lens body only (does not include servo module).
* M.O.D. = Minimum Object Distance.

Control Accessories for Studio/Field Lenses

DIGITAL UHD-DIGISUPER/DIGISUPER Series

For:
 UHD-DIGISUPER 122 / UHD-DIGISUPER 111 / UHD-DIGISUPER 90 / UHD-DIGISUPER 86 / UHD-DIGISUPER 66 /
 UHD-DIGISUPER 27 / DIGISUPER 100 / DIGISUPER 95 TELE / DIGISUPER 95 / DIGISUPER 80 / DIGISUPER 76 /
 DIGISUPER 27


FULL SERVO SYSTEM



KIT DETAIL

No.	DESCRIPTION
1-A.	Zoom Demand ZDJ-D02 (Digital Servo)
1-B.	Zoom Demand ZDJ-P01 (Digital Servo)
1-C.	Zoom Demand ZDJ-S01 (Digital Servo)
2-A.	Focus Demand FDJ-D02 (Digital Servo)
2-B.	Focus Demand FDJ-P01 (Digital Servo)
2-C.	Focus Demand FDJ-S01 (Digital Servo)
3.	Servo Module SMJ-E01 (2pcs)

SEMI-SERVO SYSTEM



KIT DETAIL


No.	DESCRIPTION
1-A.	Zoom Demand ZDJ-D02 (Digital Servo)
1-B.	Zoom Demand ZDJ-P01 (Digital Servo)
1-C.	Zoom Demand ZDJ-S01 (Digital Servo)
2.	Servo Module SMJ-E01
3.	Flexible Focus Controller FFP-T61
4.	Flexible Module FMJ-702
5.	Flexible Cable 36"
6.	Focus Demand FD1-S01 (Digital Servo)

For:
 DIGISUPER 100AF / DIGISUPER 86AF /
 DIGISUPER 27AF

For:
 All UHD-DIGISUPER /
 DIGISUPER Lenses

For:
 UHD-DIGISUPER 122/
 UHD-DIGISUPER 111


FULL SERVO SYSTEM



KIT DETAIL

No.	DESCRIPTION
1-A.	Zoom Demand ZDJ-D02 (Digital Servo)
1-B.	Zoom Demand ZDJ-P01 (Digital Servo)
1-C.	Zoom Demand ZDJ-S01 (Digital Servo)
2-A.	Focus Demand FDJ-P41 (Digital Servo)*3
2-B.	Focus Demand FD1-S01 (Digital Servo)
3.	Servo Module SMJ-E01 (2pcs)


FULL MANUAL SYSTEM



KIT DETAIL

No.	DESCRIPTION
1.	Flexible Zoom Controller FZP-T61
2.	Flexible Focus Controller FFP-T61
3.	Flexible Module FMJ-702 (2pcs)
4.	Flexible Cable 36" (2pcs)

BOKEH EFFECT CONTROLLER



*1: Switch Box is optionally available. The equivalent switches are integrated into Zoom Demands. It is recommended to have the Switch Box with Full Manual System.

*2: Lens Supporter is necessary for portable camera mounting. Some cameras need separate power supply for zoom and focus servo operation.

*3: For DIGISUPER 100AF, DIGISUPER 86AF, and DIGISUPER 27AF, FDJ-P41 is necessary to control the AF function. FDJ-P31 is also available for right hand users.

• Zoom Demand and Focus Demand with Pre-set Box is also available.


• For detail information, please contact a Canon Sales Office.

Control Accessories for Studio/Field Lenses

For:
DIGISUPER 22 xs

The DIGISUPER 22 xs can be used with our current optional Studio/Field lens controllers as well as those for our ENG lenses. At the same time, the lens also offers compatibility with our Compact Studio/Field demands by use of a conversion cable.


With Current ENG Demand (Standard)



KIT DETAIL

No.	DESCRIPTION	MODEL #
1	Digital Zoom Demand	ZSD-300D
2	Digital Focus Demand	FPD-400D


With Compact Field/Studio Demand



KIT DETAIL

No.	DESCRIPTION	MODEL #
1	Digital Zoom Demand	ZDJ-P01
2	Digital Focus Demand	FDJ-P01
3	Conversion Cable	BDC-21

With Current Field/Studio Demand



KIT DETAIL

No.	DESCRIPTION	MODEL #
1-a	Digital Zoom Demand	ZDJ-D02
2-a	Digital Focus Demand	FDJ-D02
2-b	Digital Focus Demand Propeller Type	FDJ-D12
3	Conversion Cable	BDC-11

The SUP-400 SUPPORTER is included as a standard component with the lens.

Studio/Field Lenses Mount Compatibility


To Use Camera Manufacturer's Original Mount Lens

Studio/Field lenses are made with mounts corresponding to each manufacturer's Studio/Field cameras. To make the lenses compatible with Portable Studio/Field Companion cameras, the correct lens Support System must be chosen from the following:

Standard HD Mount (BTA)

Panasonic, Ikegami, Hitachi, Thomson Grass Valley, Sony


Standard HD Mount Studio Camera Systems from Various Manufacturers



2/3" Portable Companion Cameras with Standard HD Mount System

Sony

Sony 2/3" Studio Camera




Lens with Sony Original Mount

Sony System Companion Portable Camera

Thomson Grass Valley-SDTV

LDK 2/3" Studio Camera



Lens with LDK Original Mount

Xpander LDK4489/Super Xpander LDK4488 Large Lens Adaptor
LDK System Companion Portable Camera

Please confirm with camera manufacturer regarding the proper supporter to use. Some manufacturers vary by camera model.

Broadcast ENG/EFP Lenses

4K UHD 2/3"

	CJ45ex13.6B UHDxs		CJ45ex9.7B UHDxs		CJ25ex7.6B UHDxs	
Appearance						
Model Name	CJ45ex13.6B IASE-V H		CJ45ex9.7B IASE-V H		CJ25ex7.6B IRSE S/IASE S	
Zoom Ratio	45x		45x		25x	
Focal Length	13.6 ~ 612mm	27.2 ~ 1224mm (2.0x)	9.7 ~ 437mm	19.4 ~ 874mm (2.0x)	7.6 ~ 190mm	15.2 ~ 380mm (2.0x)
Maximum Relative Aperture	F1:2.8 (13.6 ~ 312mm) F1:5.5 (612mm)	F1:5.6 (27.2 ~ 624mm) F1:11.0 (1224mm)	F1:2.0 (9.7 ~ 224mm) F1:3.9 (437mm)	F1:4.0 (19.4 ~ 448mm) F1:7.8 (874mm)	F1.8 (7.6 ~ 1108mm) F2.9 (190mm)	F3.6 (15.2 ~ 236mm) F5.8 (380mm)
Angular Field of View	38.9°×22.5° (13.6mm) 0.90°×0.51° (612mm)	20.0°×11.3° (27.2mm) 0.45°×0.25° (1224mm)	52.7°×31.1° (9.7mm) 1.26°×0.71° (437mm)	27.8°×15.8° (19.4mm) 0.63°×0.35° (874mm)	64.6°×39.1° (7.6mm) 2.89°×1.63° (190mm)	35.1°×20.1° (15.2mm) 1.458°×0.81° (380mm)
M.O.D.* from Lens Front	2.8m		2.8m		0.8m	
Object Dimensions at M.O.D.*	182.9×102.9cm (13.6mm) 4.2×2.4cm (612mm)	91.5×51.5cm (27.2mm) 2.1×1.2cm (1224mm)	254.3×143.0cm (9.7mm) 5.8×3.3cm (437mm)	127.2×71.5cm (19.4mm) 2.9×1.7cm (874mm)	93.9×52.8cm (7.6mm) 3.9×2.2cm (190mm)	48.1×27.1cm (15.2mm) 2.0×1.1cm (380mm)
Filter Thread Size (Hood/Lens Barrel)	- / 127mm P0.75		- / 127mm P0.75		105mm P1 / 94mm P1	
Approx. Size (WxHxL)	6.8×5.8×14.0 in. (173.2×147.5×355.0mm)		6.8×5.8×13.3 in. (173.2×147.5×337.0mm)		6.8×4.5×8.8 in. (169.6×114.4×223.6mm)	
Approx. Weight	12.4 lb (5.64kg)		12.3 lbs (5.60kg)		4.4 lb (1.99kg)	

4K UHD 2/3"

	CJ20ex7.8B UHDxs		CJ15ex4.3B UHDxs		CJ12ex4.3B UHDxs	
Appearance						
Model Name	CJ20ex7.8B IASE S		CJ15ex4.3B IASE S		CJ12ex4.3B IRSE S/IASE S	
Zoom Ratio	20x		15x		12x	
Focal Length	7.8 ~ 156mm	15.6 ~ 312mm (2.0x)	4.3 ~ 65mm	8.6 ~ 130mm (2.0x)	4.3 ~ 52mm	8.6 ~ 104mm (2.0x)
Maximum Relative Aperture	F1.8 (7.8 ~ 108mm) F2.6 (156mm)	F3.6 (15.6 ~ 216mm) F5.2 (312mm)	F1.8 (4.3 ~ 40mm) F2.9 (65mm)	F3.6 (8.6 ~ 80mm) F5.8 (130mm)	F1.8 (4.3 ~ 40mm) F2.4 (52mm)	F3.6 (8.6 ~ 80mm) F4.8 (104mm)
Angular Field of View	63.2°×38.2° (7.8mm) 3.5°×2.0° (156mm)	34.2°×19.6° (15.6mm) 1.8°×1.0° (312mm)	96.3°×64.2° (4.3mm) 8.4°×4.8° (65mm)	58.3°×34.9° (8.6mm) 4.2°×2.4° (130mm)	96.3°×64.2° (4.3mm) 10.5°×5.9° (52mm)	58.3°×34.9° (8.6mm) 5.3°×3.0° (104mm)
M.O.D.* from Lens Front	0.8m		0.30m		0.3m	
Object Dimensions at M.O.D.*	91.7×51.6cm (7.8mm) 4.8×2.7cm (156mm)	45.9×25.8cm (15.6mm) 2.4×1.4cm (312mm)	76.1×42.8cm (4.3mm) 4.9×2.8cm (65mm)	38.1×21.4cm (8.6mm) 2.5×1.4cm (130mm)	76.4×43.0cm (4.3mm) 6.0×3.4cm (52mm)	38.2×21.5cm (8.6mm) 3.0×1.7cm (104mm)
Filter Thread Size (Hood/Lens Barrel)	105mm P1 / 94mm P1		127mm P0.75 / -		127mm P0.75 / -	
Approx. Size (WxHxL)	6.7×4.5×9.1 in. (169.9×114.4×230.0mm)		6.4×4.2×9.8 in. (163.0×107.6×249.6mm)		6.4×4.3×9.8 in. (163.5×108.0×247.8mm)	
Approx. Weight	4.81 lb (2.18kg)		4.8 lb (2.19kg)		4.63 lbs (2.1kg) (IRSE S)	

4K UHD 2/3"

	CJ24ex7.5B UHD_{GC}		CJ18ex7.6B UHD_{GC}		CJ14ex4.3B UHD_{GC}	
Appearance						
Model Name	CJ24ex7.5B IRSE S/IASE S		CJ18ex7.6B IRSE S/IASE S		CJ14ex4.3B IRSE S/IASE S	
Zoom Ratio	24x		18x		14x	
Focal Length	7.5 ~ 180mm	15.0 ~ 360mm (2.0x)	7.6 ~ 137 mm	15.2 ~ 274 mm (2.0x)	4.3 ~ 60mm	8.6 ~ 120 mm (2.0x)
Maximum Relative Aperture	F1:1.8 (7.5 ~ 120mm) F1:2.7 (180mm)	F1:3.6 (15 ~ 240mm) F1:5.4 (360mm)	F1:1.8 (7.6 ~ 103mm) F1:2.4 (137mm)	F1:3.6 (15.2 ~ 206mm) F1:4.8 (274mm)	F1:1.8 (4.3 ~ 40 mm) F1:2.7 (60mm)	F1:3.6 (8.6 ~ 80mm) F1:5.4 (120mm)
Angular Field of View	65.2°×39.6° (7.5mm) 3.1°×1.7° (180mm)	35.5°×20.4° (15mm) 1.5°×0.9° (360mm)	64.6°×39.1° (7.6mm) 4.0°×2.3° (137mm)	35.1°×20.1° (15.2mm) 2.0°×1.1° (274mm)	96.3°×64.2° (4.3mm) 9.1°×5.2° (60mm)	58.3°×34.9° (8.6mm) 4.6°×2.6° (120mm)
M.O.D.* from Lens Front	0.80m		0.56m		0.30m	
Object Dimensions at M.O.D.*	96.0×54.0 cm (7.5mm) 4.1×2.3 cm (180mm)	48.0×27.0 cm (15mm) 2.1×1.2 cm (360mm)	65.5×36.8 cm (7.6mm) 3.8×2.1 cm (137mm)	32.8×18.4 cm (15.2mm) 1.9×1.1 cm (274mm)	76.4×43.0 cm (4.3mm) 5.2×2.9 cm (60mm)	38.2×21.5 cm (8.6mm) 2.6×1.5 cm (120mm)
Filter Thread Size (Hood/Lens Barrel)	105mm P1 / 94mm P1		- / 82mm P0.75		127mm P0.75 / -	
Approx. Size (WxHxL)	6.5×4.3×8.7 in. (164.6×109.1×221.4mm)		6.3×4.1×8.1 in. (160.5×105.0×206.2mm)		6.4×4.3×9.8 in. (163.5×108.0×247.8mm)	
Approx. Weight	4.0 lb (1.82kg, (IRSE S))		3.3 lb (1.65kg, (IRSE S))		4.7 lb (2.11kg, (IRSE S))	

* M.O.D. = Minimum Object Distance.

Broadcast ENG/EFP Lenses

4K UHD 2/3"

	CJ18e×28B  UHD GC	CJ15e×8.5B  UHD GC
Appearance		
Model Name	CJ18e×28B IASE S	
Zoom Ratio	18x	
Focal Length	28 ~ 500mm	56 ~ 1000mm (2.0x)
Maximum Relative Aperture	F2.8 (28 ~ 286mm) F4.9 (500mm)	F5.6 (56 ~ 572mm) F9.8 (1000mm)
Angular Field of View	19.5°×11.0° (28mm) 1.10°×0.62° (500mm)	9.8°×5.5° (56mm) 0.55°×0.31° (1000mm)
M.O.D.* from Lens Front	2.2m	
Object Dimensions at M.O.D.*	71.0×39.9cm (28mm) 4.1×2.3cm (500mm)	35.5×20.0cm (56mm) 2.1×1.2cm (1000mm)
Filter Thread Size (Hood/Lens Barrel)	127mm P0.75 / —	
Approx. Size (WxHxL)	7.0×4.8×10.6 in. (177.8×122.5×268.3mm)	
Approx. Weight	6.08 lb (2.76kg (IASE S))	

HD 2/3"

	HJ40e×14B  HD XS	HJ40e×10B  HD XS	HJ21e×7.5B  HD XS
Appearance			
Model Name	HJ40e×14B IASE-V H		HJ21e×7.5B IASE S
Zoom Ratio	40x		21x
Focal Length	14 ~ 560mm	28 ~ 1120mm (2.0x)	7.5 ~ 158mm
Maximum Relative Aperture	F2.8 (14 ~ 307mm) F5.1 (560mm)	F5.6 (28 ~ 614mm) F10.2 (1120mm)	F1.9 (7.5 ~ 116mm) F2.6 (158mm)
Angular Field of View	37.8°×21.8° (14mm) 1.0°×0.6° (560mm)	19.4°×11.0° (28mm) 0.5°×0.3° (1120mm)	65.2°×39.6° (7.5mm) 3.5°×2.0° (158mm)
M.O.D.* from Lens Front	2.8m		0.85m
Object Dimensions at M.O.D.*	177.1×99.5cm (14mm) 4.5×2.5cm (560mm)	88.6×49.8cm (28mm) 2.3×1.3cm (1120mm)	120.4×67.7cm (7.5mm) 5.6×3.2cm (158mm)
Filter Thread Size (Hood/Lens Barrel)	— / 127mm P0.75		127mm P0.75 / —
Approx. Size (WxHxL)	6.6×5.2×14 in. (167.5×133.0×355.5mm)		6.9×4.8×10.2 in. (175.2×122×260.1mm)
Approx. Weight	12.2 lbs (5.55 kg)		5.94 lbs (2.69kg)

HD 2/3"

	HJ17e×6.2B  HD XS
Appearance	
Model Name	HJ17e×6.2B IRSE S/IASE S
Zoom Ratio	17x
Focal Length	6.2 ~ 106mm
Maximum Relative Aperture	F1.8 (6.2 ~ 65.8mm) F2.9 (106mm)
Angular Field of View	75.5°×47.1° (6.2mm) 5.2°×2.9° (106mm)
M.O.D.* from Lens Front	0.4m
Object Dimensions at M.O.D.*	73.3×41.2cm (6.2mm) 4.1×2.3cm (106mm)
Filter Thread Size (Hood/Lens Barrel)	105mm P1 / —
Approx. Size (WxHxL)	6.5×4.4×9.5 in. (165.0×111.8×240.5mm)
Approx. Weight	4.34 lbs (1.97kg (IRSE S))

DISCONTINUED LENSES

Please note as of April 3, 2019 the following ENG/EFP HD 2/3" lenses have been discontinued: HJ18e×28B, HJ24e×7.5B, HJ14e×4.3 and HJ15e×8.5B.

Please consult with a Canon Account Manager regarding availability on the HJ18e×7.6B.

* M.O.D. = Minimum Object Distance.

Broadcast ENG/EFP Lenses

HD 2/3"

HD 1/3"

Appearance	 KJ22ex7.6B HDGC	 KJ17ex7.7B HDGC	 KJ10ex4.5B HDGC	 KT17ex4.3B HDGC				
Model Name	KJ22ex7.6B IRSE S/IASE S		KJ17ex7.7B IRSE S/IASE S		KJ10ex4.5B IRSE S/IASE S		KT17ex4.3B IRSE S	
Zoom Ratio	22x		17x		10x		17x	
Focal Length	7.6-168mm 15.2-336mm (2.0x)		7.7-131mm 15.4-262mm (2.0x)		4.5-45mm 9-90mm (2.0x)		4.3-73mm 8.6-146mm (2.0x)	
Maximum Relative Aperture	1:1.8 at 7.6-116.3mm 1:2.6 at 168mm		1:1.8 at 7.7-102.5mm 1:2.3 at 131mm		1:1.8 at 4.5-34.5mm 1:2.35 at 45mm		1:3.6 at 9-68.9mm 1:4.7 at 90mm	
Angular Field of View	64.6°x39.1° at 7.6mm 3.3°x1.8° at 168mm		63.9°x38.6° at 7.7mm 4.2°x2.36° at 131mm		34.6°x19.9° at 15.4mm 2.1°x1.18° at 262mm		93.7°x61.9° at 4.5mm 12.2°x6.9° at 45mm	
M.O.D.* from Lens Front	0.8m		0.6m		0.3m		0.6m	
Object Dimensions at M.O.D.*	95.0x53.4cm at 7.6mm 4.4x2.5cm at 168mm		68.5x38.5cm at 7.7mm 4.2x2.4cm at 131mm		34.3x19.3cm at 15.4mm 2.1x1.2cm at 262mm		74.1x41.7cm at 4.5mm 6.4x3.6cm at 45mm	
Filter Thread Size (Hood/Lens Barrel)	105mm P1 / 94mm P1		— / 82mm P0.75		127mm P0.75 / —		— / 82mm P0.75	
Approx. Size (WxHxL)	6.5x4.4x8.6 in. (164.7x111.8x218.6mm)		6.3x4.2x7.8 in. (159.3x106.6x197.8mm)		6.6x4.4x9.4 in. (168.2x111.8x237.7mm)		6.3x4.2x7.8 in. (159.3x106.6x197.3mm)	
Approx. Weight (IRSE/IASE)	4.0 lbs (1.82kg)/4.19 lbs (1.90kg)		3.26 lbs (1.48kg)/3.44 lbs (1.56kg)		4.04 lbs (1.83kg)/4.22 lbs (1.91kg)		3.26 lbs (1.48kg)	

Pro-Video Lenses

HD 2/3"

Appearance	 KJ20x8.2B HDGC	 KJ20x8.2B HDGC	 KJ13x6B HDGC
Model Name	KJ20x8.2B IRSD		KJ13x6B KRSD
Zoom Ratio	20x		13x
Focal Length	8.2-164mm 16.4-328mm (2.0x)		6-78mm
Maximum Relative Aperture	1:1.9 at 8.2-115.4mm 1:2.7 at 164mm		1:2.0 at 6-58mm 1:2.7 at 78mm
Angular Field of View	60.7°x36.5° at 8.2mm 3.4°x1.9° at 164mm		77.3°x48.5° at 6mm 7.0°x4.0° at 78mm
M.O.D.* from Lens Front	0.9m		0.4m
Object Dimensions at M.O.D.*	98.2x55.2cm at 8.2mm 5.0x2.8cm at 164mm		74.3x41.8cm at 6mm 5.4x3.0cm at 78mm
Filter Thread Size (Hood/Lens Barrel)	— / 82mm P0.75		105mm P1 / —
Approx. Size (WxHxL)	6.4x4.1x8.2 in. (163.3x104.1x208.0mm)		6.5x4.1x8.3 in. (165.4x104.1x211.7mm)
Approx. Weight	3.13 lbs (1.42kg)		3.51 lbs (1.59kg)

HD 1/2"

Appearance	 KH20x6.4 HDGC
Model Name	KH20x6.4 KRSD SY14
Zoom Ratio	20x
Focal Length	6.4-128mm
Maximum Relative Aperture	1:1.4 at 6.4-89.6mm 1:2.0 at 128mm
Angular Field of View	57.1°x34.1° at 6.4mm 3.1°x1.8° at 128mm
M.O.D.* from Lens Front	0.9m
Object Dimensions at M.O.D.*	89.8x50.5cm at 6.4mm 4.6x2.6cm at 128mm
Filter Thread Size (Hood/Lens Barrel)	— / 82mm P0.75
Approx. Size (WxHxL)	6.4x4x7.2 in. (163.3x101.6x182.5mm)
Approx. Weight	2.8 lbs (1.27kg)

* M.O.D. = Minimum Object Distance.

Remote Control Lenses

HD 2/3"

HDTV	KJ22ex7.6B	KJ17ex7.7B
Appearance		
Model Name	KJ22ex7.6B ITS-ME/RE	KJ17ex7.7B ITS-ME/RE
Zoom Ratio	22x	17x
Image Size	2/3"	2/3"
Built-in Extender	2.0x	2.0x
Range of Focal Length (with Extender)	7.6-168mm 15.2-336mm (2.0x)	7.7-131mm 15.4-262mm (2.0x)

HDTV	HD 2/3"	HD 1/2"
Appearance	KJ20x8.2B 	KH20x6.4 
Model Name	KJ20x8.2B KTS	KH20x6.4 KTS*2
Zoom Ratio	20x	20x
Image Size	2/3"	1/2"
Built-in Extender	N/A	N/A
Range of Focal Length	8.2-164mm	6.4-128mm

*2: Specifically designed for Sony HDC-X300/X310.

DISCONTINUED LENSES

Please note as of April 3, 2019 the following Lenses have been discontinued: HJ18ex28B, HJ15ex8.5B, HJ24ex7.5B, HJ18ex7.6B, HJ14ex4.3B, KT20x5B, and KH13x4.5.

Broadcast ENG/EFP, Pro Video Lens Optical Accessories

Adaptor Type Converters/Attachments

CATEGORY	MODEL	CJ45e×13.6B CJ45e×9.7B	CJ15e×4.3B CJ12e×4.3B CJ14e×4.3B CJ18e×8.5BB CJ18e×28B KJ10e×4.5B HJ40e×14B HJ40e×10B HJ21e×7.5B	HJ17e×6.2B KJ13×6B	CJ15e×8.5B	CJ25e×7.6B CJ20e×7.8B CJ24e×7.5B KJ22e×7.6B	CJ18e×7.6B KJ20×8.2B KT17e×4.3B KJ17e×7.7B KH20×6.4
TELESIDE CONVERTER *1	T15HG					●	●
WIDE CONVERTER *1	W80HG					●	●
WIDE ATTACHMENT *1	WA75HG					●	●
FISHEYE ATTACHMENT *1	FEA60HG					●	●
ADAPTER RING	ACC-85 III						●
	ACC-98 II				*2	●	*2
CLOSE-UP LENS	82CL-UP800H				● *2		● *2
	82CL-UP1300H				●		●
	105CL-UP800HG					●	
UV FILTER	UV / 82				●		●
	UV / 94					●	
	UV / 105			●		●	
	UV / 127		●				
	UV / 127-H	●	●				
CLEAR FILTER	CL/127MM		●				
	CL/127MM-H	●	●				
POLARIZATION FILTER	PL / 82				●		●
	PL / 105			●		●	
	PL / 127		●				

*1: An adapter ring is necessary to attach it to the lens. *2: Close-up lens supported for SD.

• The number of each filter type name, indicates the screw diameter. Screw pitch: screw diameter 82 mm = 0.75 mm, thread diameter 127 mm = 0.75 mm, thread diameter other than the left = 1.00 mm

The following items have been discontinued: W80H Wide Converter.

The following lenses have been discontinued: HJ18e×28B, HJ24e×7.5B, HJ18e×7.6B, HJ14e×4.3B, KH13×4.5B

Mount Converters for Different Image Format Size Cameras

Canon offers a variety of Mount Converters to be used between a lens and a camera of different image format sizes. Each converter will extend the effective Angular Field of View of the associated lens according to the Shift Ratio listed below.

	Converter	Image Size Conversion			Electronic Conversion
		Lens *4	Camera	Shift Ratio to Telephoto Side	
	LO-32BMT	2/3" B4 Mount	1/2" Sony *5	Approx. 1.4x	N/A
	LCV-40B	2/3" B4 Mount	1/2 Standard Mount *6	Approx. 1.4x	N/A
	LCV-42T	2/3" B4 Mount	1/3" Standard Mount	Approx. 1.8x	N/A
	LCV-41E	2/3" B4 Mount	Sony PMW-EX3	Approx. 1.4x	Lens Cable (12 pin) EX3 Hot Shoe (14 pin)

*4: The converters are to be used with lenses weighing less than 4.4 lbs (2.0kg). *5: Sony's Hot Shoe mount camera, excluding PMW-EX3.

*6: 1/2" Camera of standard type mount (Panasonic, JVC, Grass Valley).

Broadcast ENG/EFP, Pro Video Lens Optical Accessories

Converter/Attachments

TELE-SIDE CONVERTER



- The use of the telephoto converter would shift the focal length of a lens with a factor of 1.5x.
- F No. of the original lens is not affected.
- Only the telephoto side of the lens can be used. The picture corners are eclipsed at wide angle.
- The minimum object distance becomes 2.25x that of the original lens.

CHANGE IN FOCAL LENGTH

Model	M.O.D.	Eclipse Point
CJ24ex7.5B	1.8m	f:100mm
KJ17ex7.7B	1.35m	f:60mm

WIDE CONVERTER



- The wide converter W80/W80Y-85 would shift the focal length of a lens with a factor of 0.8x.
- F No. of the original lens is not affected.
- The minimum object distance becomes 0.64x with the W80/W80Y-85.

CHANGE IN FOCAL LENGTH

Model	Master Lens	With Wide Converter
CJ24ex7.5B	7.5-180mm	6.0-144mm
KJ17ex7.7B	7.7-131mm	6.2-104.8mm

FISH-EYE ATTACHMENT



- The zoom lens becomes a fish-eye fixed focal length lens (distorted image) with the fish-eye attachment.
- The use of a fish-eye attachment would shift the focal length of a lens with a factor of 0.6x.
- Focus is adjusted by use of the macro lever.

CHANGE IN FOCAL LENGTH

Model	Master Lens	With Fish-Eye Attachment
CJ24ex7.5B	7.5-180mm	4.5mm
KJ17ex7.7B	7.7-131mm	4.6mm

WIDE ATTACHMENT



- The zoom lens becomes a wider fixed focal length lens with the wide attachment.
- The use of the wide attachment would shift the focal length of a lens with a factor of 0.75x.
- Focus is adjusted by use of the macro lever.

CHANGE IN FOCAL LENGTH

Model	Master Lens	With Wide Attachment
CJ24ex7.5B	7.5-180mm	5.6mm
KJ17ex7.7B	7.7-131mm	5.8mm

POLARIZED LIGHT FILTER



- Used to intercept light reflected from the surface of water or glass.
- The polarizer is threaded on to a lens hood.

Extenders



- The X2.0-B4 extender mounts in between a camera and lens to magnify an image.
- The extender doubles the focal length of the master lens and doubles the F-number.

Model	Applicable Lenses
X2.0-B4	Applicable to all B4 type mount Canon 2/3" lenses.

Broadcast ENG/EFP, Pro Video Lens Optical Accessories

Close-Up Lenses



- A close-up lens is used to shorten the M.O.D.* of the master lens for close-up shooting.
- The maximum object distance becomes the focal length of the close-up lens.
- The minimum object distance is calculated by the following formula:

$$\text{New minimum object distance} = \text{fc} \times \text{S} / (\text{fc} + \text{S})$$

fc = Focal length of the close-up lens

S = M.O.D.* of the master lens

Imaging range for KJ17ex7.7B with close-up lenses

KJ17ex7.7B (16:9)	82CL-UP800H				82CL-UP1300H			
	Tele end : 131mm		Wide end : 7.7mm		Tele end : 131mm		Wide end : 7.7mm	
	Focusing Scale (mm)	∞	0.6	∞	0.6	∞	0.6	∞
Object Distance (mm)	800	343	800	343	1300	411	1300	411
Object Dimensions (mm)	58x33	24x14	989x556	376x212	95x53	29x16	1634x919	455x256

Model	Applicable Lenses
82CL-UP800H ^{*1}	HJ18ex7.6B, HJ15ex8.5B, KJ17ex7.7B, KJ20x8.2B, KH20x6.4, KT17ex4.3B, KT20x5
82CL-UP1300H ^{*1}	HJ18ex7.6B, HJ15ex8.5B, KJ17ex7.7B, KJ20x8.2B, KH20x6.4, KT17ex4.3B, KT20x5
105CL-UP900H ^{*1}	HJ24ex7.5B, KJ22ex7.6B
105CL-UP800HG	CJ20ex7.8B, CJ24ex7.5B, HJ24ex7.5B, KJ22ex7.6B

*M.O.D. = Minimum Object Distance.

* 1: Not recommended for 4K shooting.

Broadcast ENG/EFP, Pro Video Lens Accessories

Compatible Zoom/Focus Control List

OPERATION	CATEGORY	MODEL	CJ45ex13.6B CJ45ex9.7B HJ40ex14B HJ40ex10B	CJ25ex7.6B CJ24ex7.5B CJ20ex7.8B CJ18ex28B CJ18ex7.6B CJ15ex8.5B CJ15ex4.3B	CJ14ex4.3B CJ12ex4.3B HJ21ex7.5B HJ17ex6.2B KJ22ex7.6B KJ17ex7.7B KJ10ex4.5B KT17ex4.3B	KJ20x8.2B KJ13x6B KH20x6.4
FOCUS	FOCUS DEMAND	FPD-400D	●		●	● ^{*1}
	DRIVE UNIT	FPM-77				●
		FPM-420D			● (IRS,KRS)	
	FLEX CONTROLLER	FFC-200	● ^{*3}		● ^{*2}	●
		FFC-15				●
	FLEXIBLE CABLE (32 INCHES)	FC-40	● ^{*3}		● ^{*2}	●
	OUTLET	FFM-100			● ^{*2}	
FM-12					●	
FFM-300		● ^{*3}				
ZOOM	ZOOM DEMAND	ZSD-300D	●		●	● ^{*1}
	PROVIDED ZOOM	ZSD-15MII				●
	SERVO GRIP	ZSG-200M	● ^{*1}		● ^{*1}	●

* 1: A unit that can be attached using a conversion cable.

* 2: Please be aware use of these controllers will result in a lower image quality MTF.

* 3: These accessories are not recommended for use with CJ45ex9.7B and CJ45ex13.6B.

Broadcast ENG/EFP, Pro Video Lens Optical Accessories

Focus Controller



Zoom Controller



■ Conversion Cable is Necessary When Using with the Following Combinations

Model Name	Applicable Lens	Adapter Cable	Lens Side Pin#	Control Side Pin#
FPM-420D	Analog Drive Lens	CC-1220	12	20
FPD-400D		CC-0620	6	20
ZSD-300D		CC-0820	8	20

Control Accessories for Digital Drive ENG/EFP Lenses


CJ45ex13.6B / CJ45ex9.7B / CJ25ex7.6B / CJ20ex7.8B / CJ12ex4.3B / CJ18ex28B / CJ15ex8.5B / CJ24ex7.5B / CJ18ex7.6B / CJ14ex4.3B / HJ40ex14B / HJ40ex10B / HJ21ex7.5B / HJ17ex6.2B / KJ22ex7.6B / KJ17ex7.7B / KJ10ex7.5B / KT17ex4.3B

■ Recommended Kit Configurations

MS-210D

for all listed
IASE S/IRSE S/KRSE S
Lenses


SEMI-SERVO KIT



SS-41-D

for all listed
IRSE S/KRSE S Lenses


FULL SERVO KIT



SS-41-IASD

for all listed
IASE S Lenses


FULL SERVO KIT



SS-42-IAS


for all listed
IASE S Lenses

FULL SERVO KIT



DIGITAL Control Accessories of Digital Drive ENG/EFP Lenses

Applicable Component Detail



#	UNIT	DESCRIPTION
①	FFM-100	Flex Focus Module
②	FFM-300	Flex Focus Module
③	FFM-200*1	Flex Dual Module
④	FFM-400*1,2	Flex Dual Module
⑤	FC-40	Flex Cable
⑥	FFC-200	Flex Focus Controller
⑦	FZC-100*1	Flex Zoom Controller
⑧	FPM-420D*1	Focus Positional Servo Module
⑨	FPD-400D*1	Focus Positional Demand
⑩	ZSD-300D*1	Zoom Demand
⑪	ZSG-200M	Zoom Servo Grip
⑫	CR-10	Clamper
⑬	CC-2008	20p-8p Cable

*1: FZC-100, FFM-200, FFM-400, FPD-400, FPM-420 and ZSD-300A/M are discontinued.

*2: Analog FPD-400 is also applicable, however, CC-2006 conversion cable is necessary to connect between IASD/IASE Digital Drive Lens and FPD-400.

*3: Analog ZSD-300A/M is also applicable but CC-2008 is needed to connect between IASE S digital drive lens and ZSD-300A/M.

● The controllers support the new DD functions.

Applicable Kit Detail

For IRSE S Type Lenses

	Kit Name	Zoom		Focus	
		System	Component	System	Component
Zoom Servo Only	(ZR-1D)	ZR-1D	20	—	—
	—	ZR-2(A)	21, 22, 28	—	—
Semi-Servo	MS-210D	ZR-1D	20	FR-2	2, 8, 10
	MS-220	ZR-2(A)	21, 22, 28	FR-2	2, 8, 10
Full Servo	SS-41-D	ZR-1D	20	FPS-4D	13, 17
Full Manual	—	FZC-1	6, 8, 11	FR-2 (w/o 2)	8, 10

For IASE S Type Lenses (Except HJ40ex, CJ45ex)

	Kit Name	Zoom		Focus	
		System	Component	System	Component
Zoom Servo Only	(ZR-1D)	ZR-1D	20	—	—
	—	ZR-2(A)	21, 22, 28	—	—
Semi-Servo	MS-210D	ZR-1D	20	FR-2	2, 8, 10
	MS-220	ZR-2(A)	21, 22, 28	FR-2	2, 8, 10
Full Servo	SS-41-IASD	ZR-1D	20	FPS-4D	17
	SS-42-IASD	ZR-2(A)	21, 22, 28	FPS-4D	17
Full Manual	—	FZC-1	6, 8, 11	FR-2 (w/o 2)	8, 10

For CJ45ex13.6B, CJ45ex9.7B, HJ40ex14B and HJ40ex10B

	Kit Name	Zoom		Focus	
		System	Component	System	Component
Zoom Servo Only	—	ZR-1D	20	—	—
	—	ZR-2(A)	21, 22, 28	—	—
Semi-Servo	—	ZR-1D	20	FR-2	3, 8, 10
	—	ZR-2(A)	21, 22, 28	FR-2	3, 8, 10
Full Servo	SS-41-IASD	ZR-1D	20	FPS-4D	17
	SS-42-IASD	ZR-2(A)	21, 22, 28	FPS-4D	17
Full Manual	—	FZC-1	6, 8, 11	FR-2 (w/o 2)	8, 10


■ Recommended kit configuration.

ANALOG Control Accessories for Analog Drive HDgc Lenses

Recommended Kit Configuration


MS-15 SEMI-SERVO KIT

for all Pro-video ENG lenses




MS-22 SEMI-SERVO KIT

for all Pro-video ENG lenses




MS-21D SEMI-SERVO KIT

for all Pro-video ENG lenses



*1: "A" or "M" type demands depend upon camera. Type "A" demands are no longer available from Canon.

Applicable Component Detail



#	UNIT	DESCRIPTION
①	FM-12	Flex Focus Module
②	FM-70*	Flex Dual Module
③	FC-40	Flex Cable
④	FFC-15	Flex Focus Controller
⑤	FFC-200	Flex Focus Controller
⑥	FZC-100*	Flex Zoom Controller
⑦	ZSD-15A II / M II Zoom Demand ²	A (A or M types, depends on applicable camera) M
⑧	ZSD-300A/M Zoom Demand ²	A (A or M types, depends on applicable camera) M
⑨	ZSD-300D	Zoom Demand
⑩	ZSG-200A/M Zoom Servo Grip ²	A (A or M types, depends on applicable camera) M
⑪	CR-10	Clamper
⑫	GA-70*	Grip Adapter
⑬	EC-80	Zoom Extension Cable (8P)
⑭	CC-0820	Conv. Cable (8pM-20pF)

*FM-70, FZC-100, and GA-70 are discontinued.

*2: ZSD-15A II, ZSD-300A/M, ZSG-200A, and FPD-400 are no longer available from Canon stock.

Applicable Kit Detail

	Kit Name	Zoom		Focus	
		System	Component	System	Component
Zoom Servo Only	—	ZSD-15	16	—	—
	—	ZR-1	17	—	—
	—	ZR-2(A)	19, 20, 26	—	—
	—	ZR-2(B)	19, 21*	—	—
Semi-Servo	MS-15	ZSD-15	16**	FRC-15	1, 8, 9**
	MS-21	ZR-1	17	FR-2	1, 8, 10
	MS-21D	ZR-1D	18, 28	FR-2	1, 8, 10
	MS-22	ZR-2(A)	19, 20, 26	FR-2	1, 8, 10
Full Manual	FZC-1	FZC-1	5*, 8, 11	FR-2(w/o 1)	8, 10

* ② & ⑫ are not applicable to YH14x7.3 and YH16x7.

**In USA, ⑦ and ④ are available only as MS-15 kit configuration and not as individual products.

 Recommended kit configuration.

CINEMA LENS LINEUP

ZOOM Series

Canon Cinema Zoom Lenses offer superb optical performance that exceeds 4K resolution and are designed to meet the most demanding of high-end productions. They combine fluorite and aspherical lens elements, the latest in advanced optical coatings and superior lens designs for outstanding edge-to-edge image quality.



COMPACT ZOOM Series

Canon Cinema Compact Zoom Lenses offer 4K resolution in form factors that enable more flexible, less intrusive shooting. They also feature a constant T-number (2.8) throughout their zoom ranges as well as the latest advancements in lens design for outstanding image quality and minimal distortion.

SUMIRE PRIME Series

Canon is introducing a new line of cinema prime lenses named “SUMIRE Prime” (pronounced “Soo-mee-ray”) – associated with a floral gentleness and beauty. A unique optical design introduces a nuanced look as the lens aperture approaches its maximum setting – subtly modifying the textural renderings of the human facial close-up. It also smooths the transition to the fall-off portions of the scene resulting in a pleasing bokeh. This combination adds emotional expressiveness to a memorable scene.



PRIME Series

The flexible series of Canon Cinema Prime Lenses offers spectacular 4K-image quality and a full-frame image circle, in lightweight, compact designs. They feature high optical speed, produce remarkably sharp 4K images and superb contrast, and maintain tightly controlled focus breathing and geometric distortion. Low T-numbers enable better low-light shooting.

CINE-SERVO Series

Canon CINE-SERVO Lenses support cinema production as well as 4K content creation for broadcast. Featuring a servo drive unit, they can be ideal for shooting scenarios where mobility is key.

COMPACT-SERVO Series

COMPACT-SERVO lenses combine the benefits of compact size and light weight for outstanding mobility. Designed to shoot video, these lenses combine the functionality of our EF lenses with the video shooting features of our Cinema lenses.

ZOOM Lens Series

➔ P. 36



CN-E14.5-60mm T2.6 L S
CN-E14.5-60mm T2.6 L SP



CN-E30-300mm T2.95-3.7 L S
CN-E30-300mm T2.95-3.7 L SP

COMPACT ZOOM Lens Series

➔ P. 36



CN-E15.5-47mm T2.8 L S
CN-E15.5-47mm T2.8 L SP



CN-E30-105mm T2.8 L S
CN-E30-105mm T2.8 L SP

SUMIRE PRIME Lens Series

➔ P. 37



CN-E14mm T3.1 FP X CN-E20mm T1.5 FP X CN-E24mm T1.5 FP X CN-E35mm T1.5 FP X CN-E50mm T1.3 FP X CN-E85mm T1.3 FP X CN-E135mm T2.2 FP X

PRIME Lens Series

➔ P. 37



CN-E14mm T3.1 L F CN-E20mm T1.5 L F CN-E24mm T1.5 L F CN-E35mm T1.5 L F CN-E50mm T1.3 L F CN-E85mm T1.3 L F CN-E135mm T2.2

CINE-SERVO Lens Series

➔ P. 38



CN7x17 KAS S/E1
CN7x17 KAS S/P1



CN20x50 IAS H/E1
CN20x50 IAS H/P1

COMPACT-SERVO Lens Series

➔ P. 38



CN-E18-80mm T4.4 L IS KAS S



CN-E70-200mm T4.4 L IS KAS S



ZSG-C10

MEETING THE DEMANDS OF THE 4K ERA

Canon Cinema Lens Technology

Optical Performance

Crystal Clear Canon Optical Technology

Super 35mm,* High quality 4K/HDR


From the center to the periphery of our cinema lenses, a high-quality 4K/HDR image is achieved for both single focus and zoom lenses within the entire zoom range. Canon's optical technologies are combined to help correct various aberrations and provide high contrast while achieving a high resolution of about 80 lines/mm throughout the Super 35 mm sensor.

**The PRIME Lens series also supports the image size of Full Frame or APS-H.*




Focus Breathing Suppression

Focus breathing is caused when the focus group moves and exerts a "zooming" effect. In order to prevent this, cinema lenses implement a 3-group inner focus method and a new floating method to help minimize field angle fluctuation and achieve stable framing.



11 Blade Aperture

Halos from points of light at night or from rays of sunlight in shots that show the sun take on the shape of the Iris blades. The odd number of blades make the iris aperture look circular even when the Iris is contracted, enabling beautiful, round highlight bokeh.



Warm Color Balance

Cinema lens color balance, ideal for movie production, reproduces warm skin tones. Color balance is strictly uniform across all Canon cinema lenses making lens substitution during the same scene possible. Anti-reflection film technology, including super spectral coatings and thorough corrections for slight color variations caused by glass components allow Canon lenses to achieve this effect.



Flange Back Adjustment

A flange back adjustment mechanism is installed on the lens mounts to allow for back focus adjustments.

** Excluding PRIME Lens series.*

■ **Luminous Index**

The focus index on the front lens barrels is printed with luminescent paint to improve visibility at night and in dark studio conditions.



Dust/Splash Resistant Seals and Casing*

Our CN-E EF prime and Sumire Prime lenses use dust and splash resistant rubber gaskets at the casing joints.

** Lenses are not designed to be submersible in water or exposed to heavy rain.*



■ **Cinema Lens Focal Distance Table**

ZOOM Lenses							
Angle of view horizontal (1.78:1)*1	79.2°		43.6°		22.6°		4.6°
Focal Distance (mm)	14.5		30		60		300
CN-E14.5-60mm T2.6 L	[Red bar spanning from 14.5 to 60 mm]						
CN-E30-300mm T2.95-3.7 L			[Red bar spanning from 30 to 300 mm]				

COMPACT ZOOM Lenses							
Angle of view horizontal (1.78:1)*2	75.5°		43.6°		28.6°		13.0°
Focal Distance (mm)	15.5		30		47		105
CN-E15.5-47mm T2.8 L	[Red bar spanning from 15.5 to 47 mm]						
CN-E30-105mm T2.8 L			[Red bar spanning from 30 to 105 mm]				

SUMIRE PRIME Lenses							
Angle of view horizontal (1.78:1)*2	82.6°	63.2°	54.3°	38.7°	27.6°	16.5°	10.4°
Focal Distance (mm)	14	20	24	35	50	85	135
CN-E14mm T3.1 FP X	●						
CN-E20mm T1.5 FP X		●					
CN-E24mm T1.5 FP X			●				
CN-E35mm T1.5 FP X				●			
CN-E50mm T1.3 FP X					●		
CN-E85mm T1.3 FP X						●	
CN-E135mm T2.2 FP X							●

PRIME Lenses							
Angle of view horizontal (1.78:1)*2	82.6°	63.2°	54.3°	38.7°	27.6°	16.5°	10.4°
Focal Distance (mm)	14	20	24	35	50	85	135
CN-E14mm T3.1 L F	●						
CN-E20mm T1.5 L F		●					
CN-E24mm T1.5 L F			●				
CN-E35mm T1.5 L F				●			
CN-E50mm T1.3 L F					●		
CN-E85mm T1.3 L F						●	
CN-E135mm T2.2 L F							●

CINE-SERVO Lenses							
Angle of view horizontal (1.78:1)*2	71.8°		27.6°	11.7°			1.4°
Focal Distance (mm)	17		50	120			1000
CN7×17 KAS S	[Red bar spanning from 17 to 120 mm]						
CN20×50 IAS H			[Red bar spanning from 50 to 1000 mm]				

COMPACT-SERVO Lenses							
Angle of view horizontal (1.78:1)*2	68.7°		19.9°	17.5°			7.0°
Focal Distance (mm)	18		70	80			200
CN-E70-200mm T4.4 L IS KAS S			[Red bar spanning from 70 to 200 mm]				
CN-E18-80mm T4.4 L IS KAS S	[Red bar spanning from 18 to 80 mm]						

*1: When the screen size is 24.0 × 13.5 mm. *2: When the screen size is 24.6 × 13.8 mm.

NEW
LINE OF CINEMA
PRIME LENSES

Sumire Prime



Gentle and Beautiful Skin Tone

Smooth Bokeh

Canon is introducing a new line of cinema prime lenses – appropriately named “SUMIRE Prime”. Pronounced “Soo-mee-ray” in Japanese. It is associated with a floral gentleness and beauty. In addition to bright T-stops and Canon’s renowned warm imagery, a unique optical design introduces a nuanced look as the lens aperture approaches its maximum setting – subtly modifying the textural renderings of the human facial close-up. It also smooths the transition to the fall-off portions of the scene resulting in a pleasing bokeh. This combination adds emotional expressiveness to a memorable scene.



PL MOUNT

- CN-E14mm T3.1 FP X
- CN-E20mm T1.5 FP X
- CN-E24mm T1.5 FP X
- CN-E35mm T1.5 FP X
- CN-E50mm T1.3 FP X
- CN-E85mm T1.3 FP X
- CN-E135mm T2.2 FP X

SUMIRE PRIME Lens Series: Highlights

Covers Full-frame, Super 35mm and APS-C Sensors

The lenses are also compatible with the large imaging area of cameras equipped with a full-size 35mm-equivalent CMOS sensor.

Phosphorescent Indicators

To improve visibility in nighttime and dark area shooting, indicator markings with phosphorescent paint have been adopted for the front barrel (for right-side viewing).

Artistically Pleasing Image Rendering And Warm Colors

The original lens composition with large diameter aspheric lens and anomalous dispersion glass offers more solid and artistically pleasing image rendering. This brings out the impressive image quality of 4K cinema images in all their glory. And the warm color tones have been made consistent throughout the series to artistically pleasing capture people’s facial expressions and enable better depiction of the subject’s texture.

Minimized Focus Breathing

The lens controls focus breathing, which realizes stability in images even when bokeh effects occur due to refocusing.

Unified Front Lens Diameter, Gear Position

Compact Zoom and Prime lenses have the same front lens diameter and consistent gear positions, so lenses within each series can be switched without adjusting the rig setup.

Sumire Prime Lens Series



11-Blade Iris

With the increased number of iris blades, users can get natural bokeh that appears more circular, from maximum to minimum aperture. The use of an odd number of blades diffuses light rays in high-brightness subjects and renders images more artistically pleasing.

PL Mount

PL mounts, which are in high demand in the cinema market, have been adopted to support a variety of cameras used in this market.

Soft, Natural Bokeh Effects

The bright T-number of the PRIME lens and multi-blade iris diaphragm produce natural blur effects closer to a circle, from maximum to minimum aperture. This enables more three-dimensional bokeh even with super wide angle lenses that have deeper depth of field, broadening the range of visual expression.



ZOOM / COMPACT ZOOM Lens Series: Highlights

Easy-to-Read Controls

Focus, Zoom, and Iris markings are provided on angled surfaces. These markings are easy to read from behind the camera.

Support Industry-Standard Cameras

Covers Super 35mm and APS-C sensors.

Light, Compact

Small and light to meet a variety of shooting needs.

Marked on Both Sides

Lenses are marked on both sides. This makes markings visible from either side of the lens.

Switchable Unit for Focus Marking

The outer piece on marked focus rings can be switched from non-metric to metric labeling.

Comfortable Usability

Control rings maintain the right amount of resistance while offering exceptional usability with consistent operating torque.

Inner Focus

Helps minimize focus-induced changes in the angle of view.

Unified Front Lens Diameter, Gear Position

Uniform gear positions within the same categories eliminate the need for accessory gear position adjustment when switching lenses.

Zoom Lens Series



Compact Zoom Lens Series



Flange-Back Adjustment Mechanism

A covered flange-back adjustment mechanism is included, with broadcast applications in mind.



Attractive Bokeh

11-Blade Circular Aperture enables soft, beautiful background bokeh.

PRIME Lens Series: Highlights

Covers Full-frame, Super 35mm and APS-C Sensors

The lenses are also compatible with the large imaging area of cameras equipped with a full-size 35mm-equivalent CMOS sensor.

Light, Compact

Small and light among many conventional cinema lenses, to meet a variety of shooting needs.

Standard Accessories Supported

Supports industry-standard accessories such as power-drive devices and matte boxes.

Accepts 105mm filters (except for 14mm)

PL or other individual filters 105mm in diameter can be attached to the end of the lens, enabling filter work in handheld shooting or other scenarios without using a matte box.

Phosphorescent Indicators

To improve visibility in nighttime and dark area shooting, indicator markings with phosphorescent paint have been adopted for the front barrel (for right-side viewing).

Fast Aperture

Enables shooting with the shallow DOF and broad bokeh that large sensors offer.

Unified Front Lens Diameter, Gear Position

Compact Zoom and Prime lenses have the same front lens diameter and consistent gear positions, so lenses within each series can be switched without adjusting the rig setup.

Prime Lens Series



11-Blade Iris

With the increased number of iris blades, users can get natural bokeh that appears more circular, from maximum to minimum aperture. The use of an odd number of blades diffuses light rays in high-brightness subjects and renders images more artistically pleasing.

EF Mount

Communication functions with Cinema EOS Cameras. It works seamlessly with our Cinema EOS cameras, allowing you to take full advantage of the camera's features and functionality.

Switchable Unit for Focus Marking

The outer piece on marked focus rings can be switched from non-metric to metric labeling.



Consistent Torque

Control Rings maintain the right amount of resistance while offering outstanding usability with consistent operating torque.

CINE-SERVO 50-1000mm: Highlights

Support Industry-Standard Cameras

Covers Super 35mm and APS-C sensors.
Covers Full Frame and APS-H with Built-in 1.5x Extender.

Robust and Durable Housing Structure

20x Zoom Magnification

Ultra Telephoto 50-1000mm Focal Range

Removable Servo Drive Unit

Removable servo drive unit with various user setting capabilities.

Accessory Connectors

Three 20-pin connectors for externally operated accessories and a 16-bit metadata output for virtual studio systems.



Multiple Communication Capability with Compatible Cameras

11-Blade Iris Provides Natural Bokeh

Designed for Cinema and Broadcast Applications

Compact and Lightweight

Compact and lightweight lens available in an EF mount and PL mount that can be converted at an authorized Canon service facility.



EF Mount



PL Mount

Support High Quality 4K/HDR Shooting

High optical performance with support for Super35mm large format cameras.

Built-In 1.5x Optical Extender

Cover the image size of Full Frame or APS-H Camera.



CINE-SERVO 17-120mm: Highlights

Support Industry-Standard Cameras

Covers Super 35mm and APS-C sensors.

High Durability and Ruggedness

7x Zoom Magnification

Wide 17-120mm Focal Range

Ergonomic Design

Ergonomically designed drive unit for ease of operation.

Removable Servo Drive Unit

Removable servo drive unit with various user setting capabilities.

Accessory Connectors

Three 20-pin connectors for externally operated accessories and a 16-bit metadata output for virtual studio systems.



Multiple Communication Capability with Compatible Cameras

11-Blade Iris Provides Natural Bokeh

Designed for Cinema and Broadcast Applications

Compact and Lightweight

Compact and lightweight lens available in an EF mount and PL mount that can be converted at an authorized Canon service facility.



EF Mount



PL Mount



Support High Quality 4K/HDR Shooting

High optical performance with support for Super35mm large format cameras.

Drive Unit

Removable Drive Unit

Canon CINE-SERVO lenses include a drive unit that provides the same user experience as found in our broadcast zoom lenses. Removing the drive unit allows for full manual operation of the lenses.



■ No Initialization

Initialization of the drive unit is not required at power-on. Initialization is required at power-on for conventional drive units. Immediate startup helps contribute to more efficient shooting.

Compatible With Standard Broadcast Demands

Demand Supported

Compatible with Canon's standard broadcast industry demands such as ZSD-300D and FPD-400D. Canon's 8-pin demand* can be connected via a conversion cable.

Enables High-Precision, Natural Composition

Virtual Studio System

A high precision 16-bit encoder (zoom and focus only) makes connection to various virtual studio systems possible. Three, 20-pin terminals allow a virtual connection even when zoom and focus demands are connected.



* Iris operation is also possible by connecting FDJ-P01 via conversion cable. It will be selected as either virtual output or iris operation.

Peripheral Illumination Correction

EF Mount Communication Protocol Support¹

Information communication is possible via CINEMA EOS SYSTEM cameras and mounts. It is possible to record lens information at the time of shooting and peripheral illumination correction².

¹: ZOOM Lenses are excluded. Only EF mounted lenses are supported.

²: Some lenses require a camera firmware update. Some lenses are scheduled to be handled by firmware update.

Supports Broadcast Industry Standards

12-Pin Serial Communication*

Supports 12-pin serial communication which is a broadcasting communication standard.

* Applicable lens: CINE-SERVO Lens series.

It is necessary for the camera side to support 12 pin serial communication.

Supports Communication Standards of Film Production Industry

/i Technology Compatible*

Canon's PL-mount CINE-SERVO lenses are compatible with Cooke's "/i Technology" communication standard which has been widely adopted throughout the video production industry. Focus/zoom/aperture position data can be sent to the corresponding camera, recorded and displayed.

* Applicable lens: PL mount lens of CINE-SERVO Lens series only.

The camera side must support /i Technology.

Communication is possible when drive unit is installed.

COMPACT-SERVO Lens Series: Highlights

Refined Iris Mechanism

- Seamless Manual Control Capability
- 9-Blade Iris
- Iris Closing

Compatible with EF-mount Cameras

Practical Layout of Switches

High Level 4K Optical Performance

Covers Super 35mm and APS-C Sensors



Image Stabilization

Minimized Focus Breathing

Supports a Wide Range of Accessories

Compact and Lightweight for Increased Mobility

Dual Pixel CMOS Auto-Focus (DAF)

Enhanced Servo Drive Unit

- Servo Control Capability for all Zoom, Focus, and Iris
- Compatible with broadcast style servo lens controllers
- Optional ZSG-C10 Grip

COMPACT-SERVO **4K**

ZOOM Lens Series

Appearance	CN-E14.5-60mm T2.6 L S CN-E14.5-60mm T2.6 L SP 		CN-E30-300mm T2.95-3.7 L S CN-E30-300mm T2.95-3.7 L SP 	
Model Name	CN-E14.5-60mm T2.6 L S	CN-E14.5-60mm T2.6 L SP	CN-E30-300mm T2.95-3.7 L S	CN-E30-300mm T2.95-3.7 L SP
Mount	EF Mount	PL Mount	EF Mount	PL Mount
Zoom Ratio	4.1x		10x	
Focal Length	14.5 ~ 60mm		30 ~ 300mm	
Max. Relative Aperture (T-Number)	T2.6 14.5 ~ 60mm		T2.95 30 ~ 240mm / T3.7 300mm	
Iris Blades	11		11	
Angle of View	1.5:1 36.0x24.0mm	79.2°×49.9° 14.5mm 22.6°×12.8° 60mm *1	43.6°×25.4° 30mm 4.6°×2.6° 300mm *1	
	1.9:1 26.2x13.8mm	80.6°×50.9° 14.5mm 23.2°×13.1° 60mm *2	44.6°×25.9° 30mm 4.7°×2.6° 300mm *2	
M.O.D. (Minimum Object Distance)	0.70m/2'4"		1.5m/5'	
Object Dimensions at M.O.D	1.5:1 36.0x24.0mm	65.2×36.7cm 14.5mm 15.0×8.4cm 60mm *1	98.8×55.6cm 30mm 9.6×5.4cm 300mm *1	
	1.9:1 26.2x13.8mm	66.9×37.5cm 14.5mm 15.4×8.6cm 60mm *2	101.3×56.8cm 30mm 9.9×5.6cm 300mm *2	
Front Diameter	136.0mm		136.0mm	
Filter Diameter	—		—	
Approx. Size (WxHxL)	5.35x6.42x12.83 in. (136.0×163.1×326.0mm)	5.35x6.42x12.52 in. (136.0×163.1×318.0mm)	5.67x6.58x13.78 in. (144.0×167.1×350.1mm)	5.67x6.58x13.47 in. (144.0×167.1×342.1mm)
Approx. Weight	9.9 lbs (4.5kg)		12.79 lbs (5.8kg)	

※ Lenses compatible with Super 35mm Sensor cameras.

*1: Aspect ratio 1.78: 1, Screen size 24.0 x 13.5 mm. *2: Aspect ratio 1.78:1, Screen size 24.6 x 13.8 mm

COMPACT ZOOM Lens Series

Appearance	CN-E15.5-47mm T2.8 L S CN-E15.5-47mm T2.8 L SP 		CN-E30-105mm T2.8 L S CN-E30-105mm T2.8 L SP 	
Model Name	CN-E15.5-47mm T2.8 L S	CN-E15.5-47mm T2.8 L SP	CN-E30-105mm T2.8 L S	CN-E30-105mm T2.8 L SP
Mount	EF Mount	PL Mount	EF Mount	PL Mount
Zoom Ratio	3x		3.5x	
Focal Length	15.5 ~ 47mm		30 ~ 105mm	
Max. Relative Aperture (T-Number)	T2.8 15.5 ~ 47mm		T2.8 30 ~ 105mm	
Iris Blades	11		11	
Angle of View	1.5:1 36.0x24.0mm	75.5°×47.1° 15.5mm 28.6°×16.3° 47mm *1	43.6°×25.4° 30mm 13.0°×7.4° 105mm *1	
	1.9:1 26.2x13.8mm	80.4°×48.0° 15.5mm 31.1°×16.7° 47mm *2	47.2°×25.9° 30mm 14.2°×7.5° 105mm *2	
M.O.D. (Minimum Object Distance)	0.50m/1'8"		0.60m/2'	
Object Dimensions at M.O.D	1.5:1 36.0x24.0mm	43.6×24.5cm 15.5mm 14.1×7.9cm 47mm *1	32.3×18.2cm 30mm 9.3×5.2cm 105mm *1	
	1.9:1 26.2x13.8mm	47.6×25.1cm 15.5mm 15.4×8.1cm 47mm *2	35.3×18.6cm 30mm 10.2×5.4cm 105mm *2	
Front Diameter	114mm		114mm	
Filter Diameter	UV/105 P1		UV/105 P1	
Approx. Size (WxHxL)	4.49x4.92x8.74 in. (114.0×125.0×222.0mm)	4.49x4.92x8.43 in. (114.0×125.0×214.0mm)	4.49x4.92x8.58 in. (114.0×125.0×218.0mm)	4.49x4.92x8.26 in. (114.0×125.0×210.0mm)
Approx. Weight	4.85 lbs (2.2kg)		4.85 lbs (2.2kg)	

※ Lenses compatible with Super 35mm Sensor cameras.

*1: Aspect ratio 1.78: 1, Screen size 24.0 x 13.5 mm. *2: Aspect ratio 1.78:1, Screen size 24.6 x 13.8 mm

SUMIRE PRIME Lens Series

Sumire Prime

						
CN-E14mm T3.1 FP X	CN-E20mm T1.5 FP X	CN-E24mm T1.5 FP X	CN-E35mm T1.5 FP X	CN-E50mm T1.3 FP X	CN-E85mm T1.3 FP X	CN-E135mm T2.2 FP X
PL Mount	PL Mount	PL Mount				
–	–	–	–	–	–	–
14mm	20mm	24mm	35mm	50mm	85mm	135mm
T3.1	T1.5	T1.5	T1.5	T1.3	T1.3	T2.2
11	11	11	11	11	11	11
104.3°×81.2° *1	84.0°×61.9° *1	73.7°×53.1° *1	54.4°×37.8° *1	39.6°×27.0° *1	23.9°×16.1° *1	15.2°×10.2° *1
82.6°×52.5° *2	63.2°×38.1° *2	54.3°×32.1° *2	38.7°×22.3° *2	27.6°×15.7° *2	16.5°×9.3° *2	10.4°×5.9° *2
0.20m / 8"	0.30m / 12"	0.30m / 12"	0.30m / 12"	0.45m / 18"	0.95m / 3'2"	1.0m / 3'3"
25.2×16.8cm *1	33.8×22.5cm *1	28.8×19.2cm *1	20.2×13.5cm *1	25.0×16.7cm *1	34.4×22.9cm *1	21.1×14.1cm *1
17.2×9.7cm *2	23.1×13.0cm *2	19.7×11.0cm *2	13.8×7.7cm *2	17.1×9.6cm *2	23.5×13.2cm *2	14.4×8.1cm *2
114mm	114mm	114mm	114mm	114mm	114mm	114mm
–	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter
4.66x4.66x3.39 in. (118.4x118.4x86.0mm)	4.66x4.66x3.68 in. (118.4x118.4x93.5mm)	4.66x4.66x3.68 in. (118.4x118.4x93.5mm)	4.66x4.66x3.68 in. (118.4x118.4x93.5mm)	4.66x4.66x3.68 in. (118.4x118.4x93.5mm)	4.66x4.66x3.68 in. (118.4x118.4x93.5mm)	4.66x4.66x4.24 in. (118.4x118.4x107.6mm)
2.65 lbs (1.2kg)	2.65 lbs (1.2kg)	2.65 lbs (1.2kg)	2.43 lbs (1.1kg)	2.43 lbs (1.1kg)	2.87 lbs (1.3kg)	3.09 lbs (1.4kg)

※ Lenses compatible with Full-frame and Super 35mm Sensor cameras.
*1: Aspect ratio 1.5:1, Screen size 36.0 × 24.0 mm. *2: Aspect ratio 1.78:1, Screen size 24.6 × 13.8 mm.

PRIME Lens Series

						
CN-E14mm T3.1 L F	CN-E20mm T1.5 L F	CN-E24mm T1.5 L F	CN-E35mm T1.5 L F	CN-E50mm T1.3 L F	CN-E85mm T1.3 L F	CN-E135mm T2.2 L F
EF Mount	EF Mount	EF Mount				
–	–	–	–	–	–	–
14mm	20mm	24mm	35mm	50mm	85mm	135mm
T3.1	T1.5	T1.5	T1.5	T1.3	T1.3	T2.2
11	11	11	11	11	11	11
104.3°×81.2° *1	84.0°×61.9° *1	73.7°×53.1° *1	54.4°×37.8° *1	39.6°×27.0° *1	23.9°×16.1° *1	15.2°×10.2° *1
82.6°×52.5° *2	63.2°×38.1° *2	54.3°×32.1° *2	38.7°×22.3° *2	27.6°×15.7° *2	16.5°×9.3° *2	10.4°×5.9° *2
0.20m / 8"	0.30m / 12"	0.30m / 12"	0.30m / 12"	0.45m / 18"	0.95m / 3'2"	1.0m / 3'3"
24.8×16.5cm *1	33.8×22.5cm *1	28.8×19.2cm *1	20.1×13.4cm *1	24.9×16.6cm *1	34.3×22.9cm *1	21.1×14.1cm *1
16.9×9.5cm *2	23.1×13.0cm *2	19.7×11.0cm *2	13.7×7.7cm *2	17.0×9.5cm *2	23.4×13.1cm *2	14.4×8.1cm *2
114mm	114mm	114mm	114mm	114mm	114mm	114mm
–	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter	UV/105 P1 filter
4.66x4.66x3.70 in. (118.4x118.4x94.0mm)	4.66x4.66x4.0 in. (118.4x118.4x101.5mm)	4.66x4.66x4.0 in. (118.4x118.4x101.5mm)	4.66x4.66x4.0 in. (118.4x118.4x101.5mm)	4.66x4.66x4.0 in. (118.4x118.4x101.5mm)	4.66x4.66x4.0 in. (118.4x118.4x101.5mm)	4.66x4.66x4.55 in. (118.4x118.4x115.6mm)
2.65 lbs (1.2kg)	2.65 lbs (1.2kg)	2.65 lbs (1.2kg)	2.43 lbs (1.1kg)	2.43 lbs (1.1kg)	2.87 lbs (1.3kg)	3.09 lbs (1.4kg)

※ Lenses compatible with Full-frame and Super 35mm Sensor cameras.
*1: Aspect ratio 1.5:1, Screen size 36.0 × 24.0 mm. *2: Aspect ratio 1.78:1, Screen size 24.6 × 13.8 mm.

CINE-SERVO Lens Series

Appearance		CN7×17 KAS S/E1 CN7×17 KAS S/P1		CN20×50 IAS H/E1 CN20×50 IAS H/P1	
Model Name		CN7×17 KAS S/E1	CN7×17 KAS S/P1	CN20×50 IAS H/E1	CN20×50 IAS H/P1
Mount		EF Mount	PL Mount	EF Mount	PL Mount
Zoom Ratio		7×		20×	
Focal Length		17 ~ 120mm		50 ~ 1000mm	75 ~ 1500mm ^{*3}
Max. Relative Aperture (T-Number)		T2.95 17 ~ 91mm / T3.9 120mm		T5.0 (50-560mm) / T8.9 (1000mm)	T7.5 (75-840mm) / T13.35 (1500mm) ^{*3}
Iris Blades		11		11	
Angle of View	1.5:1 36.0x24.0mm	71.8°×44.2° 17mm 11.7°×6.6° 120mm ^{*1}		27.6°×15.7° 50mm 1.4°×0.8° 1000mm ^{*1}	18.6°×10.5° 75mm 0.9°×0.5° 1500mm ^{*1 *3}
	1.9:1 26.2x13.8mm	75.2°×44.2° 17mm 12.5°×6.6° 120mm ^{*2}		29.4°×15.7° 50mm 1.5°×0.8° 1000mm ^{*2}	19.8°×10.5° 75mm 1.0°×0.5° 1500mm ^{*2 *3}
M.O.D. (Minimum Object Distance)		0.85m/2.8'		3.5m/11.5'	
Object Dimensions at M.O.D	1.5:1 36.0x24.0mm	86.3×48.4cm 17mm 12.0×6.7cm 120mm ^{*1}		139.3×78.1cm 50mm 7.3×4.1cm 1000mm ^{*1}	92.9×52.1cm 75mm 4.9×2.7cm 1500mm ^{*1 *3}
	1.9:1 26.2x13.8mm	92.1×48.5cm 17mm 12.7×6.7cm 120mm ^{*2}		148.3×78.1cm 50mm 7.8×4.1cm 1000mm ^{*2}	98.9×52.1cm 75mm 5.2×2.7cm 1500mm ^{*2 *3}
Front Diameter		114mm		136.0mm	
Filter Diameter		CL/112mm		CL/127mm-H, UV/127mm-H	
Approx. Size (WxHxL)		6.86x4.92x10.35 in. (174.2×125.0×262.9mm)	6.86x4.92x10.04 in. (174.2×125.0×254.9mm)	6.89x6.72x16.27 in. (175.0×170.6×413.2mm)	6.89x6.72x15.95 in. (175.0×170.6×405.2mm)
Approx. Weight		6.39 lbs (2.9kg)		14.55 lbs (6.6kg)	

※ Lenses compatible with Super 35mm Sensor cameras.

*1: Aspect ratio 1.78:1, Screen size 24.6 x 13.8 mm. *2: Aspect ratio 1.9:1, Screen size 26.2 x 13.8 mm. *3: When using the built-in extender.

COMPACT-SERVO Lens Series

Appearance		CN-E18-80mm T4.4 L IS KAS S		CN-E70-200mm T4.4 L IS KAS S	
Model Name		CN-E18-80mm T4.4 L IS KAS S		CN-E70-200mm T4.4 L IS KAS S	
Mount		EF Mount		EF Mount	
Zoom Ratio		4.4×		2.8×	
Focal Length		18 ~ 80mm		70 ~ 200mm	
Max. Relative Aperture (T-Number)		T4.4 18 ~ 80mm		T4.4 70 ~ 200mm	
Iris Blades		9		9	
Angle of View	1.5:1 36.0x24.0mm	68.7°×41.9° 18mm 17.5°×9.9° 80mm ^{*1}		19.9°×11.3° 70mm 7.0°×4.0° 200mm ^{*1}	
	1.9:1 26.2x13.8mm	72.1°×41.9° 18mm 18.6°×9.9° 80mm ^{*2}		21.2°×11.3° 70mm 7.5°×4.0° 200mm ^{*2}	
M.O.D. (Minimum Object Distance)		0.5m/1.7'		1.2m/4.0'	
Object Dimensions at M.O.D	1.5:1 36.0x24.0mm	43.4×24.3cm 18mm 9.5×5.3cm 80mm ^{*1}		31.3×17.5cm 70mm 11.5×6.4cm 200mm ^{*1}	
	1.9:1 26.2x13.8mm	46.2×24.3cm 18mm 10.1×5.3cm 80mm ^{*2}		33.3×17.5cm 70mm 12.2×6.4cm 200mm ^{*2}	
Front Diameter		84mm		84mm	
Filter Diameter		77MM Protect Filter, PL-C B 77MM		77MM Protect Filter, PL-C B 77MM	
Approx. Size (WxHxL)		3.67x4.22x7.18 in. (93.4×107.2×182.3mm)		3.67x4.22x7.18 in. (93.4×107.2×182.3mm)	
Approx. Weight		2.65 lbs (1.2kg) (including servo unit)		2.76 lbs (1.25kg) (including servo unit)	

※ Lenses compatible with Super 35mm Sensor cameras.

*1: Aspect ratio 1.78:1, Screen size 24.6 x 13.8 mm.

*2: Aspect ratio 1.9:1, Screen size 26.2 x 13.8 mm.

COMPACT-SERVO Lens Accessories

ZSG-C10



- Rocker seesaw
- Start/Stop button^{*1}
- ONE-SHOT AF button^{*1}
- 20 PIN cable^{*2}
- Flexible mounting angle.

※ Sold separately.

※ Support strut, bracket, hex wrench included.

*1: For compatible cameras, please visit our website:
cinemaeos.usa.canon.com

*2: For connection to the lens body.

CINE-SERVO Lens / COMPACT-SERVO Lens Accessories

Category	Model	Notes	CN7×17 KAS S/E1 CN7×17 KAS S/P1	CN20×50 IAS H/E1 CN20×50 IAS H/P1	CN-E18-80mm CN-E70-200mm
Focus Demand	FPD-400D	There is no need for an optional cable.	●	●	● ※1 ※2
	FDJ-D02	BDC - 11 cable (20p - 18p) is required.	●	●	—
	FDJ-P01	BDC - 21 cable (20p - 12p) is required.	●	●	—
	FDJ-S01	BDC - 21 cable (20p - 12p) is required.	●	●	—
Zoom Demand	ZSD-300D	There is no need for an optional cable.	●	●	● ※1 ※2
	ZSD-15MII	CC-2008 Cable (20p - 8p) is required.	●	●	● ※1 ※2
	ZDJ-D02	BDC-11 cable (20p-18p) is required.	●	●	—
	ZDJ-P01	BDC - 21 cable (20p - 12p) is required.	●	●	—
	ZDJ-S01	BDC - 21 cable (20p - 12p) is required	●	●	—
Iris Demand	FDJ-D02	BDC - 11 cable (20p - 18p) is required.	●	●	—
	FDJ-P01	BDC - 21 cable (20p - 12p) is required.	●	●	—
Demand Cable	BDC-21	20p-12p cable. Required for FDJ-P01 / ZDJ-P01.	●	●	—
	BDC-11	20p - 18p cable. Required for FDJ-D02 / ZDJ-D02.	●	●	—
	CC-2008	20p - 8p cable. Required for ZSD-15II	●	●	●
Clear Filter	77MM Protect Filter	77MM Protect filter	—	—	●
	CL/127MM-H	CL/127MM-H	●	●	—
	CL/112MM	CL/112MM	●	—	—
Polarization Filter	PL-C B 77MM	PL-C B 77MM	—	—	●
Close-Up Lens	CL-UP500D 77MM	CL-UP500D 77MM	—	—	●
Lens Holder	LH-CN7/02	Used when you want to improve the degree of freedom of Focus ring rotation operation. (The lens support attached to the main unit is supported on the front side.)	●	—	—
Power Cable	C-ZLPR*	For power supply from external battery. 12-pin - Dtap cable.	●	●	—


* Made by IDX.

※ 1: Multiple controllers can not be connected at the same time (because there is only one connector). When installing the ZSG - C10 and enabling the operation on the grip side, you can not connect the external controller.

※ 2: For use in studio configurations, an optional Zacuto Z-CNYC. Y-cable can be used to connect zoom and focus controllers to each lens. This configuration allows for simultaneous zoom and focus operation with COMPACT-SERVO lenses.



Lens System Basic Configuration



* Some vignetting occurs when used in combination with RED's Epic system.

※ The optional Zacuto® Z-CNYC Y-cable allows for simultaneous use of zoom and focus controllers with both Compact-Servo lenses.

High Definition PTZ Cameras



BU-47H

BU-47H

Outdoor Remote Control Pan-Tilt System

To meet the diverse needs of outdoor broadcasters, cable networks, businesses, industrial entities, weather monitoring, and traffic POV, Canon has created a solution for cost-effective, turnkey, remotely-controllable Pan-Tilt-Zoom (PTZ) HD Camera systems allowing users to extend creative flexibilities. Canon has harnessed multiple unique technologies and experience in HD optics and digital cameras, robotics, and control software to produce a cost-effective, integrated HD lens-camera PTZ product offering outstanding HD picture quality. The BU-47H is a rugged yet elegant outdoor PTZ system following a legacy of decades of Canon expertise in designing such systems. A sister product, the BU-51H, has a design tailored for indoor applications.

HD PTZ Cameras

Appearance	
Model Name	BU-47H
Operation Condition	Outdoor
Operation Angle	Pan: 340° Tilt: +30° ~ -50°
Operation Speed	Panning: 0.5° ~ 25°/s Tilting: 0.3° ~ 20°/s
Repeatability	Less than ±10 arc degrees
Wiper	Built-in Electric Wiper
Mic Input	Jack provided, pedestal section
Input/Output Connectors	DC terminal, Control (RS-422), SDI out, SD composite, Genlock, Aux out
Video Output	HD-SDI (embedded audio) BNC output x 1 (receptacle unit) SD analog composite BNC output x 1
Genlock Input	BNC (receptacle unit) (tri-level/black burst)
Operating Temperature	5°C to 40°C, less than 90% humidity (no condensation)
Wind Velocity-Resistance	Normal Operation: 0-55m / s Operation Possible: 55 ~ 78m / s * Non Destruction: 78 ~ 134m / s
Noise	NC55 below
Power Source	DC10.5-15V, 80W
Dustproof Waterproof Efficiency	IP45
Image Sensor	1/3" CMOS x 3 (HD CMOS PRO)
Range Of Focal Length / F No.	f=4.1-73.8mm / F1.6-2.8
Zoom Ratio	18x Optical Zoom (1.5x digital extender)
Dimensions (W x D x H) (Including Camera & Lens)	15.19x13.2x15.35 in. (386x337x390 mm)
Weight (Including Camera & Lens)	37.4 lbs (Approx. 16.9kg)

*Some functions may be limited depending on operating environment.

Learn with Canon In Person

usa.canon.com/canonlivelearning

- Hands-on, in-person learning
- Led by accomplished photographers including Canon Explorers of Light
- Offered in beautiful locations across the country
- Test-drive your Canon dream gear




Learn with Canon Online

Free Online Learning

usa.canon.com/learn

- Get inspired with free, easily accessible online content
- Comprehensive resources including tips and tricks, tutorial videos, downloadable guides and more
- Regularly updated with new content for all skill levels



Interactive Online Classes

usa.canon.com/onlinelearning

- Immersive courses help you advance to the next level of photography
- Self-paced learning through videos, interactive content, PDF guides and more
- Hosting by industry experts on a variety of topics
- Get stuck? Canon Support will personally answer your questions



CUSTOMER SATISFACTION

Canon is committed to total customer satisfaction. In order to optimize customer satisfaction, Canon's aim is to support users by developing new lens technologies, high-quality technical service systems, and other sales support.

Canon's U.S.A. Service & Support Network

CANON OFFERS PROFESSIONAL SERVICE AND REPAIR FOR **BROADCAST & CINEMA LENS CUSTOMERS** IN THE FOLLOWING REGIONS:

- BURBANK, CA
- COSTA MESA, CA
- ITASCA, IL
- LYNDHURST, NJ
- MISSISSAUGA, ON
- MEXICO CITY, MX
- RIO DE JANEIRO, BR
- SANTIAGO, CL
- SÃO PAULO, BR

CANON OFFERS A VAST NETWORK OF SERVICE & SUPPORT FACILITIES THROUGHOUT THE AMERICAS, INCLUDING WORLD CLASS TECH SUPPORT AND FACTORY-LEVEL REPAIR SERVICE:

- MELVILLE, NY (SERVICE DROP OFF POINT)
- NEWPORT NEWS, VA (CONSUMER SERVICE & REPAIR)
- CHESAPEAKE, VA (CANON TECHNICAL SUPPORT)
- ALBUQUERQUE, NM (CANON TECHNICAL SUPPORT)

SUPPORT MATTERS

Join The Growing Ranks of Pros That Rely on Canon Professional Service, Support and Education.

Focused on Professionals

Since 1958, Canon has been delivering world-class service & support to the broadcast industry offering customized solutions for medium and large organizations that own extensive quantities of Canon Imaging products.

BROADCAST LENS SERVICES

- ✓ On-site service available
- ✓ Fast repair, minimal downtime
- ✓ Direct, personal support from industry experts Nationwide service network
- ✓ State-of-the-art facilities
- ✓ Customized services for unique needs



INNOVATION
In TV Optics Since 1958
Toward 100 years anniversary

For more information, call 1-800-423-LENS.



What Level of Canon Professional Services is Best for My Needs?

usa.canon.com/aboutcps

Canon Professional Services (CPS) membership qualification is determined by the equipment you own.

	SILVER	GOLD	PLATINUM	CINEMA
Typical Member Equipment	1 DSLR & 1 EF Lens	2 DSLRs & 2 EF Lenses	2+ DSLRs & 3+ EF/L Lenses	C300 or Higher
Exclusive Member Hotline ¹ Technical Support and Member Services	✓	✓	✓	✓
Repair Discounts	No	20% OFF	30% OFF	30% OFF
Expedited Repair Services ²	Standard	✓	✓	✓
Repair & Evaluation Loan Equipment ³ Priority Access for Platinum Members	No	✓	✓	✓
Equipment Maintenance Service ⁴ Number of DSLR or Lenses (per year)	No	5/year	10/year	10/year
CPS Lounge Services at Shows and Media Events	✓	✓	✓	✓
Discounts for Canon Live Learning Events	No	✓	✓	✓



¹ Excluding Canon USA observed holidays and periods where unavailability is due to circumstances beyond Canon USA's control.
² As a CPS Platinum member, your gear will be serviced and shipped the business day after the estimate is approved or we will offer you a loaner. Products eligible for Next Business Day Turnaround Time include: EOS DSLR, EF Lenses, Speedlites, and Battery Grips. (Cinema Cameras, Cinema Lenses and all other accessories are excluded). See Repair Turnaround Time under Platinum Repair Service Term and Conditions for more details.
³ Platinum members are allowed to evaluate each available item twice for the lifetime of the product.
⁴ Gold, Platinum & Cinema membership includes 11-Point EF Lens Maintenance Service and/or 18-point Digital SLR Maintenance Service.



pro.usa.canon.com/support
800-423-LENS

For more info: pro.usa.canon.com

@CanonUSApro
 @CanonUSA
 @CanonUSAprovideo
 @CanonUSA

The size and weight of all lenses within this brochure may vary according to the applicable camera models.

©2019 Canon U.S.A., Inc. all rights reserved.

Certain images and effects are simulated. Specifications and availability are subject to change without notice. Products not shown to scale. Weight and dimensions are approximate. Not responsible for typographical errors. Canon is a registered trademark of Canon Inc. in the United States and may also be a registered trademark or trademark in other countries. All other product and brand names are trademarks, or service marks of their respective owners and are hereby acknowledged.

PRINTED IN U.S.A.

0216W969 09/19



INNOVATION

In TV Optics Since 1958

Toward 100 years anniversary

1-800-OK-CANON
usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747 U.S.A.