










Common Enclosure Installations by Type of Mount

WALL MOUNTS		
WALL MOUNT	POLE WALL MOUNT	CORNER WALL MOUNT
 <p>Bracket</p> <p>Wall</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* (Bracket is included with both models)</p>	 <p>A-BK3/A-BK3S</p> <p>Pole</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* with A-BK3(aluminum)/A-BK3S(stainless)</p>	 <p>A-CM3</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* with A-CM3</p>
PENDANT MOUNTS		
EXISTING PIPE PENDANT MOUNT	NEW PIPE PENDANT MOUNT WITH CEILING ATTACHMENT	PENDANT MOUNT
 <p>1.5" NPT Pipe</p> <p>A-CP100NPT</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* with A-CP100NPT (1.5" NPT pipe not included)</p>	 <p>1.5" NPT Pipe</p> <p>A-CM100NPT A-CP100NPT</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* with A-CP100NPT and A-CM100NPT (1.5" NPT pipe not included)</p>	 <p>A-CM100</p> <p>A-ODW5C(OW)* or A-ODW7C(OW)* with A-CM100</p>
SURFACE MOUNTS		
VANDAL WALL SURFACE MOUNT (CANON)	NON-VANDAL WALL SURFACE MOUNT (ASC)	NON-VANDAL CEILING SURFACE MOUNT
 <p>A-SWD5ZWB600</p> <p>VB-M600 with A-SWD5ZWB600</p>	 <p>A-SWD5WB</p> <p>A-SWD5* with A-SWD5WB</p>	 <p>A-SWD5CA</p> <p>A-SWD5ZC* with A-SWD5CA</p>

*Enclosures selected are shown for example purposes only -- see charts inside for complete list of enclosures available and security cameras compatible with each.

©2012 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Some of the images and effects are simulated. Canon is a registered trademark of Canon Inc. in the United States and may also be a trademark or registered trademark in other countries. IMAGEANYWARE is a trademark of Canon. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

For more info:
Call 1-800-OK-CANON (1-800-652-2666)
usa.canon.com/ipsecuritycameras

Canon
image*ANYWARE*

0154W946

SECURITY CAMERA ENCLOSURES AND ACCESSORIES

Superb quality optics, exceptional imaging, and operational integrity have long defined what makes Canon unique and a step above the rest. Our advanced IP Security Cameras highlight these advantages and our full line of Security Camera Enclosures and Accessories help to ensure the highest quality performance of these cameras, and exceed the needs of even the most demanding security professionals.

Built with sophisticated, advanced materials that include ABS (UV-protected) plastic, polycarbonate and durable aluminum and steel, these high quality enclosures provide protection against inclement weather (including many challenging conditions), intentional manipulation or vandalism, dust and overall wear-and-tear.

Available in surface-mount, outdoor wall-mount and recessed, with special features on select models that include a heater and blower to maintain proper temperatures, and ultra-compact designs to minimize appearance, Canon's Security Camera Enclosures and Accessories complement the impressive performance of our IP Security Cameras.



Canon

Indoor Enclosures and Accessories

	PRODUCT NAME	DR40-C-VB	SR600-VB	VB-RD51S-C	VB-RD41S-C	SR-500-S-VB	A-ID5C5	A-SWD5C	A-SWD5ZC	A-SWD5VC
ITEM CODE	4963B001 (Clear) 4963B002 (Smoked)	5091B001	2823B002 (Clear) 2812B001 (Smoked)	2112B004 (Clear) 2112B001 (Smoked)	3935B001	1381V109 (Clear) 1381V110 (Smoked)	1381V113 (Clear) 1381V114 (Smoked)	2064V111 (Clear) 2064V112 (Smoked)	1381V118 (Clear) 1381V119 (Smoked)	
IMAGE										
DESCRIPTION	Indoor Recessed Clear/Smoked Dome Housing	Indoor Recessed Mounting Kit	Indoor Recessed Clear/Smoked Dome Housing	Indoor Recessed Clear/Smoked Dome Housing	Indoor Recessed Mounting Kit	Indoor Recessed Mount Plenum Dome	Indoor Surface Mount Dome	Indoor Surface Mount Vandal Dome	Indoor Surface Mount Vandal Dome	
DOME SIZE	5 inches	5 inches	5 inches	5 inches	5 inches	5 inches	5 inches	5 inches	5 inches	
INSTALL	Indoor Recessed	Indoor Recessed	Indoor Recessed	Indoor Recessed	Indoor Recessed	Indoor Recessed	Indoor Surface	Indoor Surface	Indoor Surface	
MAKER	Canon	Canon	Canon	Canon	Canon	ASC	ASC	ASC	ASC	
COMPATIBILITY	VB-M40	●					●	●	●	
	VB-M600VE		●							
	VB-M600D		●							
	VB-C60			●			●	●	●	
	VB-C300				●		●	●	●	
	VB-C500VD					●				
	VB-C500D					●	●	●		
	VC-C50IR						▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK
	HEATER BLOWER							▲ Option A-SWD5VCHB	▲ Option A-SWD5VCHB	▲ Option A-SWD5VCHB
	SPECIFICATIONS	IP RATING							IP54 IP66	IP66
VANDAL TOUGH									●	●
PLENUM READY							●			
PoE PLUS (1 CABLE SOLUTION)							●	●	●	●
POWER								▲ 24VAC/25W with Heater	▲ 24VAC/25W with Heater	▲ 24VAC/25W with Heater
WEIGHT		1.687 lbs (765 g)	0.87 lbs (395 g)	1.15 lbs (522 g)	0.82 lbs (372 g)	0.87 lbs (395 g)	2.75 lbs (1.25 kg)	2.64 lbs (1.20 kg)	2.42 lbs (1.10 kg)	5.0 lbs (2.30 kg)
OPERATING ENVIRONMENT		14 - 122F -10 - 50°C Humid 20-85% RH (No condensing)	14 - 122F -10 - 50°C With Heater -22 - 122F -30 - 50°	14 - 122F -10 - 50°C Humid 20-85% RH (No condensing)	14 - 122F -10 - 50°C Humid 20-85% RH (No condensing)	14 - 122F -10 - 50°C Humid 20-85% RH (No condensing)	N/A	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C

Outdoor Enclosures and Accessories

	PRODUCT NAME	A-ODW5C(OW)	A-ODW5CS(OW)	A-ODW7C(OW)	A-ODW7CS(OW)	A-ODW5C12(OW) (12VDC)	A-ODW7C12(OW) (12VDC)	A-OH15FBHSET-G(OW)	
ITEM CODE	1381V094 (Clear) 1586V910 (Smoked)	1381V096 (Clear) 1381V918 (Smoked)	1381V097 (Clear) 1586V919 (Smoked)	1381V099 (Clear) 1586V921 (Smoked)	1923V392 (Clear) 1923V393 (Smoked)	1923V396 (Clear) 1923V397 (Smoked)	1381V126		
IMAGE									
DESCRIPTION	Outdoor Wall Mount Clear/Smoked Dome with Heater & Blower	A-ODW5C(OW) with Sunshield	Outdoor Wall Mount Clear/Smoked Dome with Heater & Blower	A-ODW7C(OW) with Sunshield	12VDC model of A-ODW5C(OW)	12VDC model of A-ODW7C(OW)	Outdoor Box Housing with Heater & Blower and Wall Bracket		
DOME SIZE	5 inches	5 inches	7 inches	7 inches	5 inches	7 inches	—		
INSTALL	Outdoor Wall	Outdoor Wall	Outdoor Wall	Outdoor Wall	Outdoor Wall	Outdoor Wall	Outdoor Wall		
MAKER	ASC	ASC	ASC	ASC	ASC	ASC	ASC		
COMPATIBILITY	VB-M40	●	●	●	●	●	●		
	VB-M700F							●	
	VB-C60	●	●	●	●	●	●		
	VB-C300	●	●	●	●	●	●		
	VB-C500D	●	●	●	●	●	●		
	VB-C50FSi							●	
	VC-C50iR	▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK	▲ Option A-VC50BRK		
	HEATER BLOWER	●	●	●	●	●	●	●	
	SPECIFICATIONS	IP RATING	IP54 IP66	IP54 IP66	IP54 IP66	IP54 IP66	IP54 IP66	IP54 IP66	IP33 IP43
		VANDAL / TOUGH			●	●		●	
PoE PLUS		●	●	●	●	●	●	●	
POWER		24VAC/25W with Heater	24VAC/25W with Heater	24VAC/25W with Heater	24VAC/25W with Heater	24VAC/25W with Heater	24VAC/25W with Heater	24VAC/25W with Heater	
WEIGHT		8.59 lbs (3.9 kg)	9.92 lbs (4.5 kg)	10.1 lbs (4.6 kg)	11.9 lbs (5.4 kg)	8.59 lbs (3.9 kg)	10.1 lbs (4.6 kg)	3.96 lbs (1.8 kg)	
OPERATING ENVIRONMENT		With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	With Heater -4 - 104F -20 - 40°C	

Accessories

	PRODUCT NAME	A-SWD5ZWB600	A-SWD5ZWB	A-SWD5WB	A-SWD5CA	A-SWD5BH2
ITEM CODE	2178V433	1968V994	1381V123	1381V124	2120V067	
IMAGE						
DESCRIPTION	Wall Mount Bracket	Wall Mount Bracket	Indoor Wall Bracket	Indoor Ceiling Adapter	Blower & Heater	
COMPATIBILITY	VB-M600VE	●	▲ Option A-SWD5ZWB-2 Plate			
	VB-M600D	●	▲ Option A-SWD5ZWB-2 Plate			
	A-SWD5C			●	●	●
	A-SWD5ZC		●			●
	A-SWD5VC		●			●

Accessories

	PRODUCT NAME	A-BK3 / A-BK3S	A-CP100NPT	A-CM100	A-CM100NPT	A-CM3	A-CA15G	A-SY15
ITEM CODE	1381V106 / 2120V066	1381V102	1381V100	1381V101	1381V107	1381V127	1381V128	
IMAGE								
DESCRIPTION	Pole Mount Adapter	Mounting Coupler (for 1.5" NPT pipe)	Ceiling Mount Bracket	Ceiling Mount Bracket (for 1.5" NPT pipe)	Corner Mount Adapter	Ceiling Mount Adapter	Sunshield	
COMPATIBILITY	A-ODW5C(OW)	●	●	●	●	●		
	A-ODW5CS(OW)	●	●	●	●	●		
	A-ODW7C(OW)	●	●	●	●	●		
	A-ODW7CS(OW)	●	●	●	●	●		
	A-ODW5C12(OW) (12VDC)	●	●	●	●	●		
	A-ODW5C12(OW) (12VDC)	●	●	●	●	●		
	A-OH15FBHSET-G(OW)						●	●