

REALiS PRO AV INSTALLATION SERIES INTERCHANGEABLE LENSES

Canon offers a choice of Pro AV Series interchangeable high-resolution projection lenses for its line of REALiS Pro AV Installation Series projectors. These lenses are designed to deliver high-quality imagery and installation flexibility, with a wide range of throw distances and other optical performance benefits to suit many different projection environments.

Canon REALiS Pro AV Installation Series interchangeable lenses provide the color accuracy and image quality that users expect from a fixed projection lens, combined with installation flexibility to meet various projection needs. All of the lenses in the REALiS Pro AV Installation Series include features developed from Canon's industry-leading EOS technology, including aspherical lens elements for very low distortion and Ultra Low Dispersion (UD) elements to help reduce chromatic aberration. There is also minimal image quality change and minimal light loss throughout the zoom range. This family of lenses is also similarly sized to fit within the space of Canon REALiS Pro AV Installation Series projectors, thus providing flexibility in mounting options.



Standard Zoom Lens RS-IL01ST

- Throw Ratio
WUX5000: 1.49 - 2.24:1
WUX4000: 1.49 - 2.24:1
WX6000: 1.62 - 2.43:1
SX6000: 1.57 - 2.36:1
- 1.5x Powered Optical Zoom Lens
- F number: F1.89 - 2.65
- Focal Length:
f=23.0 - 34.5 mm
- Optimized for
40 to 600 in. Screens

Long Focus Zoom Lens RS-IL02LZ

- Throw Ratio
WUX5000: 2.19 - 3.74:1
WUX4000: 2.19 - 3.74:1
WX6000: 2.38 - 4.06:1
SX6000: 2.31 - 3.94:1
- 1.7x Powered Optical Zoom Lens
- F number: F1.99 - 2.83
- Focal length:
f=34.0 - 57.7 mm
- Optimized for
40 to 600 in. Screens

Ultra Wide Angle Lens RS-IL03WF

- Throw Ratio
WUX5000: 0.80:1
WUX4000: 0.80:1
WX6000: 0.87:1
SX6000: 0.85:1
- 0.8x Fixed Ultra Wide Angle Lens
- F number: F2.0
- Focal length:
f=12.8 mm
- Optimized for
40 to 300 in. Screens

Ultra Long Focus Zoom Lens RS-IL04UL

- Throw Ratio
WUX5000: 3.76 - 7.35:1
WUX4000: 3.76 - 7.35:1
WX6000: 3.86 - 7.54:1
SX6000: 3.74 - 7.32:1
- 1.95x Ultra Long Focus Zoom Lens
- F number: F2.34 - 2.81
- Focal length:
f=53.6 - 105.6 mm
- Optimized for
60 to 600 in. Screens

Short Focus Zoom Lens RS-IL05WZ

- Throw Ratio
WUX5000: 1.00 - 1.50:1
WUX4000: 1.00 - 1.50:1
WX6000: 1.03 - 1.54:1
SX6000: 1.06 - 1.58:1
- 1.5x Short Focus Zoom Lens
- F number: F2.09 - 2.34
- Focal length:
f=15.56 - 23.34 mm
- Optimized for
40 to 600 in. Screens

REALiS PRO AV INSTALLATION SERIES INTERCHANGEABLE LENSES

SPECIFICATIONS

STANDARD ZOOM LENS RS-IL01ST

	ITEM CODE		4966B001
	THROW RATIO	WUX5000 / WUX4000	1.49 - 2.24:1
		WX6000	1.62 - 2.43:1
		SX6000	1.57 - 2.36:1
	F NUMBER		F1.89 - 2.65
	FOCAL LENGTH		f=23.0 - 34.5 mm
	ZOOM RATIO AND FOCUS		1.5x Optical Zoom (Powered)
	SCREEN SIZE		40 - 600 inches
	LENS SHIFT	WUX4000 / WUX5000 / WX6000	(V) -15% ~ 55% (H) ±10%
		SX6000	(V) -12% ~ 50% (H) ±10%
OPTICAL CONSTRUCTION		11 groups in 14 elements	

LONG FOCUS ZOOM LENS RS-IL02LZ

	ITEM CODE		4967B001
	THROW RATIO	WUX5000 / WUX4000	2.19 - 3.74:1
		WX6000	2.38 - 4.06:1
		SX6000	2.31 - 3.94:1
	F NUMBER		F1.99 - 2.83
	FOCAL LENGTH		f=34.0 - 57.7 mm
	ZOOM RATIO AND FOCUS		1.7x Optical Zoom (Powered)
	SCREEN SIZE		40 - 600 inches
	LENS SHIFT	WUX4000 / WUX5000 / WX6000	(V) -15% ~ 55% (H) ±10%
		SX6000	(V) -12% ~ 50% (H) ±10%
OPTICAL CONSTRUCTION		11 groups in 15 elements	

ULTRA WIDE ANGLE LENS RS-IL03WF

	ITEM CODE		4968B001
	THROW RATIO	WUX5000 / WUX4000	0.80:1
		WX6000	0.87:1
		SX6000	0.85:1
	F NUMBER		F2.0
	FOCAL LENGTH		f=12.8 mm
	ZOOM RATIO AND FOCUS		Fixed (Powered)
	SCREEN SIZE		40 - 300 inches
	LENS SHIFT	WUX4000 / WUX5000 / WX6000	(V) ±5% (H) ±2%
		SX6000	(V) ±5% (H) ±2%
OPTICAL CONSTRUCTION		10 groups in 14 elements	

ULTRA LONG FOCUS ZOOM LENS RS-IL04UL

	ITEM CODE		6064B001
	THROW RATIO	WUX5000 / WUX4000	3.76 - 7.35:1
		WX6000	3.86 - 7.54:1
		SX6000	3.74 - 7.32:1
	F NUMBER		F2.34 - 2.81
	FOCAL LENGTH		f=53.6 - 105.6 mm
	ZOOM RATIO AND FOCUS		1.95x Optical Zoom (Powered)
	SCREEN SIZE		60 - 600 inches
	LENS SHIFT	WUX4000 / WUX5000 / WX6000	(V) -15% ~ 55% (H) ±10%
		SX6000	(V) -12% ~ 50% (H) ±10%
OPTICAL CONSTRUCTION		11 groups in 16 elements	

SHORT FOCUS ZOOM LENS RS-IL05WZ

	ITEM CODE		8168B001
	THROW RATIO	WUX5000 / WUX4000	1.00 - 1.50:1
		WX6000	1.03 - 1.54:1
		SX6000	1.06 - 1.58:1
	F NUMBER		F2.09 - 2.34
	FOCAL LENGTH		f=15.56 - 23.34 mm
	ZOOM RATIO AND FOCUS		1.5x Optical Zoom (Powered)
	SCREEN SIZE		40 - 600 inches
	LENS SHIFT	WUX4000 / WUX5000 / WX6000	(V) -15% ~ 55% (H) ±10%
		SX6000	(V) -12% ~ 50% (H) ±10%
OPTICAL CONSTRUCTION		11 groups in 15 elements	

©2014 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.



For more info:
1-800-OK-CANON (1-800-652-2666)
pro.usa.canon.com