Canon
SEE IMPOSSIBLE

FAXPHONE L190

Revolutionizing Today's Workspace

Multifunction Laser Fax Machine

- 33.6 Kbps Super G3 fax for quick results[1]
- Up to 512 sheets of memory capacity allows multiple faxes to be stored[2]
- 40 one-touch speed dials and 200 coded dials for a comprehensive address book
- Telephone handset included as standard
- Quick first print arives in ust 5.8 seconds[4]
- Print and copy at the same speed of up to 26 pages per minute[3]
- Low energy consumption uses just 1.3W in Energy Saver mode
- Single Cartridge system for easy supplies replenishment
- Duplex Versatility - fax, print, and copy two-sided documents with ease

FAX 33.6 kbps | 26 ppm | QUICK 1st PRINT | 40 Speed Dials With Handset Included | 50 Sheets ADF | Memory Up To 512 Pages | ECO-CONSCIOUS

Technical Information

FAX SPECIFICATIONS

Modem Speed
33.6 Kbps (Super G3)[1]

Fax Resolution
Up to 200 x 400 dpi (super fine)

Transmission Time
Approx. 3.0 seconds per page

Memory Capacity
Up to 512 sheets[2]

Speed Dialing
40 one-touch speed dials; 200 coded dials

Group Dialing
239 destinations

Sequential Broadcasting
250 destinations

PC Fax
Yes (TX only)

Fax Features
Fax Forwarding, Dual Access, Remote Reception, Distinctive Ring Pattern Detection, Error Correction Mode, Auto Redial, Fax Activity Reports

Telephone Handset
Included

PRINTER SPECIFICATIONS

Print Speed
Up to 16 ppm (2-sided, plain paper letter)[3]
Up to 26 ppm (1-sided, plain paper letter)[3]

First Print Time
Approx. 5.8 seconds (letter)[4]

Printer Language
UFR II LT (Host-based)

Print Resolution
Up to 600 x 600 dpi (1200 x 600 dpi quality)

Print Size
Up to 8.5" x 14"

Print Memory
128MB (shared)

Print Features
Watermark, Page Composer, Toner Saver

COPIER SPECIFICATIONS

Copy Speed
Up to 16 ppm (2-sided, plain paper letter)
Up to 26 ppm (1-sided, plain paper letter)

First Copy Time
Approx. 8.7 seconds[5]

Copy Resolution
Up to 600 x 600 dpi

Halftones
256 levels

Maximum # of Copies
99 copies

Reduction/Enlargement
25% - 400% in 1% increments

Copy Size
Platen: Up to 8.5" x 11"; ADF: 5.5" x 5" to 8.5" x 14"

Copy Features
Collate, 2 on 1, 4 on 1, ID Card Copy

Features and specifications are subject to change without notice.

PAPER HANDLING SPECIFICATIONS

Standard Paper Source(s)
250-sheet cassette[6]

Document Feeder
50-sheet Duplex[6]

Paper Output
Approx. 100 sheets (face down)

Paper Weight
16 to 43 lb. bond

Media Sizes
Letter, Legal, Statement, Executive, A4, A5, B5, B6

Media Types
Plain Paper, Heavy Paper, Recycled Paper, Transparency, Label, Envelope

Envelope Capacity
20 envelopes

CONNECTIVITY & SOFTWARE SPECIFICATIONS

Standard Interface(s)
USB 2.0 Hi-Speed[7]

Operating Systems
Windows® 7, Windows Vista®, Windows XP and Mac OS X 10.5.8 & up

Cable Included
Power Cord, Phone Cable (USB not included)

Drivers available for download from www.usa.canon.com

ENVIRONMENTAL SPECIFICATIONS

Power Consumption
During Operation: Approx. 520W
Standby: Approx. 4.5W
Energy Saver: Approx. 1.3W

Noise Level[8]
During Operation: 6.5 B or less (sound power)
50 dB or less (sound pressure)
During Standby: 4.3 B or less (sound power)
Inaudible (sound pressure)

General Specifications

CPU
Canon Custom Processor (133 MHz)

Dimensions
18.6" (W) x 17.5" (D) x 14.1" (H)

Unit Weight (without/with cartridge)
30.0 lbs./31.3 lbs.

Package Weight
Approx. 40.6 lbs.

Warranty
1 year limited exchange/carry-in warranty[9] (Extended warranty available)

Cartridge 128
Yields approximately 2,100 pages based on ISO/IEC Standard

Cartridge Type
Single Cartridge System

LCD Display
5-row backlit LCD

Duty Cycle
Up to 10,000 pages per month

Languages
English, French, Spanish, Portuguese

Ordering Information

FAXPHONE and Accessories

FAXPHONE® L190	6356B002AA
Cartridge 128 (yields approx. 2,100 pages based on ISO/IEC Standard)	3500B001AA
FAXPHONE® L190 Virtual CarePAK (2 Year Carry-in/Exchange CarePAK)	6521A109AA
FAXPHONE® L190 E-CarePAK (2 Year Carry-in/Exchange CarePAK)	5707B025AA

1 The Public Switched Telephone Network currently supports fax modem speeds of 28.8Kbps or lower, depending on telephone line conditions. Sending and receiving fax machines need to conform to ITU-T v.34 guidelines.
2 Based on ITU-T #1 Chart (standard mode).
3 Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type and orientation of paper.
4 May vary depending on the output environment.
5 Letter size, after being restored from energy saver mode.
6 Based on 20 lb. bond paper.
7 USB 2.0 Hi-Speed requires Windows® 7, Windows Vista®, Windows XP/2000 or Mac OS X operating systems. For Windows 98, Me and Mac OS X v. 10.2 to 10.2.6 operating systems, the printer/scanner will operate at USB 1.1 specifications.
8 Declared noise emission in accordance with ISO 9296.
9 Warranty program is subject to certain conditions and restrictions. See the warranty card for details.

USA.CANON.COM

Canon
SEE IMPOSSIBLE

Canon, imageCLASS, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2019 Canon U.S.A., Inc. All rights reserved.

1019R2-L190-PDF-IH