

Product Specifications



Main Unit

System Type

Color Digital Multifunction Imaging System

Functions

Standard: **C1030:** Copy, Print (UFR II LT), Scan, Send
C1030iF: Copy, Print (UFR II LT, PCL), Scan, Send, Fax
 Optional: **C1030:** Print (PCL, PostScript 3 Emulation), Fax
C1030iF: PostScript 3 Emulation

Operation Panel

3.5" TFT Color LCD Screen

Memory

Standard: 768MB RAM
 Maximum: 768MB RAM

Network Interface Connection

Ethernet 10/100Base-TX

Other Interface

Standard: USB 2.0 (Host)x2
 USB 2.0 (Device)x1

Copy/Print Speed (Color/BW)

Up to 22/30 ppm (Letter)

Paper Sources (20 lb. Bond)

Standard: 250-sheet Paper Cassette
 100-sheet Stack Bypass
 Optional: 500-sheet Paper Cassette Feeder
 Maximum: 850 Sheets

Output Paper Capacity

250 Sheets

Output Paper Sizes

Drawers: Legal, Letter, Executive
 Bypass: Legal, Letter, Statement, Executive, Envelopes (COM10 No. 10/Monarch/DL/ISO-B5/ISO-C5)
 Custom Size (3" x 5" to 8-1/2" x 14")

Acceptable Paper Weights

Drawers: 16 lb. Bond to 32 lb. Bond (60 to 120g/m²)
 Bypass: 16 lb. Bond to 47 lb. Bond (60 to 176g/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Letter and Legal)

Warm-up Time

From Power On: 60 Seconds or Less
 From Sleep Mode: 19 Seconds or Less

Power Requirements

120V-127V, 60Hz, 15A

Plug

NEMA 5-15P

Power Consumption

Maximum: Less than 1300W
 From Sleep Mode: 1W

Dimensions (H x W x D)

24-7/8" x 21-1/2" x 20-3/4"
 (632mm x 546mm x 527mm)

Installation Space (W x D)

21-1/2" x 44-7/8" (546mm x 1140mm) (with drawer pulled out and back cover open)

Weight

Approximately 96 lb. (44kg)

Toner (Estimated Yield at 5% Coverage)

Black: 6,000 Images
 Color (CMYK): 6,000 Images

Document Feeder

Scan Method

Duplexing Automatic Document Feeder

Acceptable Originals

Paper Size: Statement to Legal
 Paper Weight: **One-sided Scanning (1 page):** 13 to 34 lb. Bond (50 to 128g/m²)*
One-sided Scanning (more than 2 pages): 13 to 28 lb. Bond (50 to 105g/m²)**
Two-sided Scanning: 17 to 28 lb. Bond (64 to 105g/m²)

Scan Speed (BW/Color; Letter)

20 ipm (300 dpi)
 20 ipm (600 dpi)

Paper Capacity (20 lb. Bond)

50 Sheets

Copy Specifications

First-Copy-Out Time (Letter)

Platen Glass: Less than 13 Seconds

Feeder: Less than 19 Seconds

Multiple Copies

1 to 99

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

50% - 200% (1% Increments)

Preset Reductions

50%, 64%, 78%

Preset Enlargements

129%, 200%



Main Unit (continued)

Print Specifications

Processor

Canon Custom Processor (Shared)

Memory

Standard: 768MB RAM

Maximum: 768MB RAM

Printing Resolution

600 x 600 dpi (2400 dpi Enhanced x 600 dpi)

PDL Support

Standard: **C1030:** UFR II LT
C1030iF: UFR II LT, PCL 5c/6

Optional: **C1030:** PCL 5c/6, PostScript 3 Emulation
C1030iF: PostScript 3 Emulation

Print Driver Supported OS

UFR II LT, PostScript 3 Emulation: Windows® (Windows 2000/XP/Windows Vista®/Windows 7/Server 2003/Server 2008), Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0, XenDesktop 2.0/2.1/3.0/4.0, Macintosh® (OS X 10.4 or Greater), SAP (PS3 only)

PCL 5e/6: Windows (Windows 2000/XP/Windows Vista/Windows 7/Server 2003/Server 2008), Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0, XenDesktop 2.0/2.1/3.0/4.0, SAP

Direct Print

Supported Media: USB Memory, SD Secure Digital Memory Card, SDHC Memory Card, Compact Flash (CF) Card: Type I/II (3.3V), Microdrive, Memory Stick, Memory Stick PRO, miniSD Card,[†] microSD Card,[†] Memory Stick Duo,[†] Memory Stick PRO Duo[†]

Data Format: TIFF, JPEG

Scan Specifications

Network TWIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Send Specifications

Sending Method

E-Mail, I-Fax, File Server (FTP, SMB), Super G3 Fax (Standard on C1030iF, Optional for C1030)

Color Mode

Color, BW

Scan Resolution (dpi)

TIFF, PDF (BW) (OCR): 100 x 100, 150 x 150, 200 x 100, 200 x 200, 200 x 400, 300 x 300, 400 x 400, 600 x 600
JPEG, PDF (Color) (OCR): 100 x 100, 150 x 150, 200 x 200, 300 x 300, 600 x 600
PDF (Color) (Compact) (OCR): 300 x 300

Address Book Capacity

Max. 300 Destinations (Includes 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP)

E-Mail/I-Fax: SMTP, POP3, I-Fax (Simple)

File Formats

TIFF, JPEG, PDF, PDF (Compact), PDF (OCR)

I-Fax Data Format

TIFF

Security Specifications

Department ID Management, User ID Management, IPv6, Restricting Features (Restricting New Addresses on Address Book, Address Book Password, Allow Fax Driver TX, Restrict Recall, Confirm Entered Fax Numbers, Restrict Sequential Broadcast, Restrict USB Interface), MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, IEEE802.1x, User Authentication Features for Send Operation, Serverless Secure Print^{▲▲▲}

Environmental Information

- ENERGY STAR® Qualified
- RoHS Compliant
- Ecomark
- Blue Angel

Optional Accessories

Super G3 Fax Board-AB1

(Optional for C1030, Standard on C1030iF)

Maximum Number

of Connection

Lines: 1

Modem Speed: 33.6 Kbps

Compression Method: MH, MR, MMR, JBIG

Resolution (dpi): 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size: Statement to Legal

Cassette Feeding Unit-AB1

Paper Capacity: 550 Sheets x 1 Cassette (20 lb. Bond)

Acceptable Paper Weight: 16 lb. Bond to 32 lb. Bond (60 to 120g/m²)

Acceptable Paper Size: Legal, Letter, Executive

Acceptable Paper Type: Plain, Recycled, Color Heavy (16 lb. Bond to 32 lb. Bond [60 to 120g/m²])

Dimensions (H x W x D): 12" x 17-3/8" x 21-3/8" (304mm x 440mm x 543mm)

Weight: Approximately 28.7 lb. (13kg)

Other Optional Accessories

- Cabinet Type-A^{††}
- Handset-J1^{†††}
- Barcode Printing Kit-C1[▲]
- Card Reader-E1^{▲▲}
- Card Reader Attachment Kit-F1
- Braille Label Kit-E1
- Serverless Secure Print Module^{▲▲▲}

^{*} 17 to 34 lb. (64 to 128g/m²) when copying originals smaller than LTR/A4.

^{**} 17 to 28 lb. (64 to 105g/m²) when copying originals smaller than LTR/A4.

[†] Memory cards that can be inserted into the slot using an adapter.

^{††} The Cassette Feeding Unit-AB1 and Cabinet Type-A cannot both be installed at the same time.

^{†††} Requires Fax capability for use.

[▲] Requires PCL Printer Kit-AK1 for C1030.

^{▲▲} Requires Card Reader Attachment Kit-F1 for installation.

^{▲▲▲} Late availability.

Canon

image*ANYWARE*

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.

©2013 Canon U.S.A., Inc. All rights reserved.

1212RA-C1030SRS-PDF-CR

