

PRODUCT SPECIFICATIONS



Main Unit

Type

Monochrome Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
 Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

Standard: 10.1" TFT LCD WSVGA Color Flat-panel
 Optional: 10.4" TFT LCD SVGA Color Upright-panel

Memory

3.0 GB RAM

Hard Disk Drive

Standard: 250 GB
 Maximum: 1 TB

Mirroring Hard Disk Drive

Optional (250 GB, 1 TB), Method: Raid1

Interface Connection

Network
 Standard: 1000Base-T/100Base-TX/10Base-T,
 Wireless LAN (IEEE 802.11 b/g/n)
 Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
 USB 2.0 x1 (Device)
 Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 4,200 Sheets
 Maximum: 7,860 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 1,500-sheet Paper Drawers, Dual
 550-sheet Paper Cassettes, 100-sheet
 Stack Bypass
 Optional: 3,660-sheet Paper Deck
 (POD DECK LITE-C1 or
 PAPER DECK UNIT-E1)

Paper Output Capacity (LTR, 20 lb. Bond)

With Copy Tray: 250 Sheets
 With External 3,660 Sheets
 Finishers:

Finishing Capabilities

With External
 Finishers: Collate, Group, Offset, Staple, Staple
 On Demand, Staple-free Staple, Booklet,
 Hole Punch, Document Insertion, C and Z
 Folding

Supported Media Types

Paper Drawers (1/2): Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond
 Paper (3/4): Thin, Plain, Recycled, Color, Heavy,
 Cassettes (3/4): Pre-punched, Letterhead, Bond, Tab.
 Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Bond, Transparency, Labels,
 Letterhead, Tab, Tracing!
 POD DECK LITE-C1: Thin, Plain, Recycled, Color, Heavy, Pre-
 punched, Letterhead, Bond, Transparency,
 Labels, Tab
 PAPER DECK UNIT-E1: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond

Supported Media Sizes

Paper Drawers (1/2): Letter
 Paper Cassettes (3/4): 11" x 17", Legal, Letter, Letter-R, Executive,
 Statement-R, Custom Size (5-1/2" x 7-1/8"
 to 11-3/4" x 19-1/4")
 Stack Bypass: 11" x 17", Legal, Letter, Letter-R, Executive,
 Statement-R, Custom Size
 (4" x 5-7/8" to 11-3/4" x 19-1/4"), Free Size
 (4" x 7-1/8" to 11-3/4" x 19-1/4")
 POD DECK LITE-C1: 11" x 17", Legal, Letter, Letter-R, Executive,
 Statement-R, Custom Size (5-1/2" x 7-1/8"
 to 11-3/4" x 19-1/4")
 PAPER DECK UNIT-E1: Letter

Supported Media Weights

Paper Decks/	14 lb. Bond to 80 lb. Cover (52 to 220 g/m ²)
Cassettes:	
Stack Bypass:	14 lb. Bond to 140 lb. Index (52 to 256 g/m ²)
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m ²)

Warm-up Time

From Power On:	Approx. 30 Seconds ²
From Sleep Mode:	Approx. 30 Seconds ³
Quick Startup Mode:	Approx. 4 Seconds ⁴

Dimensions (W x D x H)

26-3/8" x 30-5/8" x 48"
(670 mm x 779 mm x 1220 mm)

Installation Space (W x D)

Basic:	Stack Bypass Extended+ Cassette Drawers open + Copy Tray: 60-3/8" x 53-1/4" (1533 mm x 1353 mm)
Fully Configured:	Booklet Finisher + Paper Deck + Insertion and Folding Unit + Puncher Unit + Cassette Drawers open: 95-7/8" x 53-1/4" (2436 mm x 1353 mm)

Weight

Approx. 515.9 lb. (234 kg)⁵

Print Specifications

Print Speed

6575i III:	Up to 75 ppm (Letter) Up to 58 ppm (Letter-R) Up to 45 ppm (Legal) Up to 37 ppm (11" x 17")
6565i III:	Up to 65 ppm (Letter) Up to 50 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")
6555i III:	Up to 55 ppm (Letter) Up to 43 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR III, PCL®6, Adobe® PS® 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁶

Supported File Types

PDF, TIFF, JPEG, EPS,⁷ XPS

Printing from Mobile and Cloud

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts:	93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese) ⁸ , Barcode Fonts ⁹
PS fonts:	136 Roman

Operating System¹⁰

UFR III:	Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)
PCL:	Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016
PS:	Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)
PPD:	MAC OS X (10.3.9 or later), Windows 7 / 8.1/ 10

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing

Copy Specifications

Copy Speed

6575i III:	Up to 75 ppm (Letter) Up to 58 ppm (Letter-R) Up to 45 ppm (Legal) Up to 37 ppm (11" x 17")
6565i III:	Up to 65 ppm (Letter) Up to 50 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")
6555i III:	Up to 55 ppm (Letter) Up to 43 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")

First-Copy-Out Time (Letter)

6575i III:	As fast as 3.1 seconds
6565i III:	As fast as 3.3 seconds
6555i III:	As fast as 3.3 seconds

Copy Resolution (dpi)

Reading:	600 x 600
Printing:	1200 x 1200

Multiple Copies

Up to 9,999 Copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Skip Blank Originals

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original:	13 lb. Bond to 80 lb. Cover (50 to 220 g/m ²)
CL Original:	17 lb. Bond to 80 lb. Cover (64 to 220 g/m ²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: up to 4.4 lb. (2 kg)]
Max. Platen Scanning Size: 11-3/4" x 17" (297 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows 7/8.1/10
Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning
BW: 120 ipm (300 dpi)/120 ipm (600 dpi)
Color: 120 ipm (300 dpi)

Double-sided Scanning
BW: 240 ipm (300 dpi)/150 ipm (600 dpi)
Color: 220 ipm (300 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File:	FTP, SMB v3.0, WebDAV
Email:	SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard:	TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word)
Optional:	PDF (Trace & Smooth, User Signature), XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications (Optional)

Maximum Number of Connection Lines

4

Modem Speed

Super G3:	33.6 Kbps
G3:	14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Windows (Windows 7/8.1/10)
Client PC:

Concurrent Connections (Max.):

SMB: 64
WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)
Approx. 480 GB (With Optional 1 TB HDD)

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function,
Printing a PDF File with a Password, imageWARE Secure
Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW
Online Express,¹¹ User Authentication,
Department ID Authentication, (Device
and Function Level Log-in), Access
Management System
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM),
Hard Disk Password Lock, Hard Disk
Drive Erase, Mail Box Password Protection,
Hard Disk Drive Encryption (FIPS140-2
Validated), Verify System at Startup,
McAfee Embedded Control¹²
Optional: Hard Disk Drive Mirroring, Hard Disk Drive
removal, IEEE 2600.2 Common Criteria
Certification, Data Loss Prevention
(Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac
Address Filtering, IPsec, TLS Encrypted
Communication, SNMP V3.0, IEEE
802.1X, IPv6, SMTP Authentication, POP
Authentication before SMTP, S/MIME,
SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Adobe
LiveCycle® Rights Management ES2.5
Integration, Encrypted PDF, Encrypted
Secure Print, Device Signature
Optional: User Signature, Document Scan Lock

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F
Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

120-127 V AC, 60 Hz, 16 A

Plug (Main Unit)

NEMA 5-20P

Power Consumption

Maximum: Approx. 2,032 W
Standby: Approx. 237.3 W¹³
Sleep mode: 0.9 W¹⁴

Consumables

Toner

GPR-38 Black Toner

Toner Yield (Estimated @ 6% Coverage)

56,000 Images

Fiery Print Controller Specifications (Optional)

Name

imagePASS-Y3 (External)

System

Fiery FS350Pro

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

PCL 6, Adobe PS 3

Memory

8 GB

Hard Disk Drive

500 GB

Processor

Intel Pentium G4400 (3.3 GHz)

Fonts

PS: 138 Adobe PS Fonts
PCL: 113 PCL Fonts

Supported Operating Systems

Windows 8.1 (32 and 64 bit)/Windows 7 (32 and 64 bit)/
Windows Server 2012 R2 (64 bit only)/Windows 10 (32
and 64 bit)/Windows Server 2016 (64 bit only), MAC OS
(10.11 or higher)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T),
USB3.0 x 2 (Rear), 3 (front on Fiery QuickTouch™)
USB2.0 x 4 (Rear)

Network Protocols

TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD,
IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100,
SNTP, 802.1X, DHCP, DNS, NTP)

Fiery Print Controller Features

Fiery Command WorkStation6/Paper Catalog/Fiery Remote
Scan/Fiery Hot Folders & Virtual Printers/Fiery JDF

Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND
COMPOSE, Removable Hard Disk Drive, Fiery ImageViewer

Dimensions (W x D x H)

8" x 9-3/4" x 15-1/8" (203 mm x 248 mm x 384 mm)

Paper Supply Options

PAPER DECK UNIT-E1

Paper 3,660 Sheets [20 lb. Bond (80 g/m²)]
Capacity:
Paper Size: Letter
Paper Weight: 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)
Power Source: From the Main Unit
Dimensions 14-1/4" x 24-7/8" x 22-1/2"
(W x D x H): (363 mm x 630 mm x 572 mm)
Weight: Approx. 75.0 lb. (34 kg)

POD DECK LITE-C1

Paper 3,660 Sheets [20 lb. Bond (80 g/m²)]
Capacity:
Paper Size: 11"x17", Legal, Letter, Letter-R, Executive,
Statement-R, and Custom Size
(5-1/2" x 7-1/8" to 11-3/4" x 19-1/4")
Paper Weight: 14 lb. Bond to 140 lb. Index
(52 to 256 g/m²)
Power Source: 120-127 V AC, 60 Hz, 2.2 A
Dimensions 24-7/8" x 27" x 22-5/8"
(W x D x H): (633 x 686 x 574 mm)
Weight: Approx. 149.9 lb. (68 kg)

Output Options

STAPLE FINISHER-V2

Number of
Trays: 3
Tray A (Upper) Letter/Executive/Statement-R
Capacity:¹⁵ 250 Sheets 11" x 17"/Legal/Letter-R
125 Sheets
Tray B (Middle) Letter/Executive/Statement-R
Capacity:¹⁵ 250 Sheets
11" x 17"/Legal/Letter-R
125 Sheets
Tray C (Lower) Letter/Letter-R/Executive/Statement-R
Capacity:¹⁵ 3,000 Sheets
11" x 17"
1,500 Sheets

Acceptable 14 lb. Bond to 140 lb. Index
Paper Weight: (52 to 256 g/m²)
Staple Corner, Double
Position:
Staple Capacity:
Corner Staple and Double Staple:
Letter/ 65 Sheets [24 lb. Bond (90 g/m²)]
Executive:
11" x 17"/ 30 Sheets [24 lb. Bond (90 g/m²)]
Legal/
Letter-R:
Staple-Free Staple:
11"x17"/ 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m²)]
Letter: 4 Sheets [17.3 to 21.7 lb. Bond
(65 to 81.4 g/m²)] 3 Sheets
[21.7 to 28 lb. Bond (81.5 to 105 g/m²)]
65 sheets [24 lb. Bond (90 g/m²)]

Staple On Demand:
Power Source: From the Main Unit
Dimensions 25-7/8" x 24-1/2" x 47-1/8"
(W x D x H): (656 x 623 x 1,195 mm)¹⁶
Weight: Approx. 77.2 lb. (35 kg)

BOOKLET FINISHER-V2

Number of 3
Trays:
Tray A (Upper) Letter/Executive/Statement-R
Capacity:¹⁵ 250 Sheets
11" x 17"/Legal/Letter-R 125 Sheets
Tray B (Middle) Letter/Executive/Statement-R
Capacity:¹⁵ 250 Sheets
11" x 17"/Legal/Letter-R 125 Sheets
Tray C (Lower) Letter/Executive/Statement-R
Capacity:¹⁵ 3,000 Sheets
11" x 17" 1,500 Sheets

Acceptable 14 lb. Bond to 140 lb. Index
Paper Weight: (52 to 256 g/m²)
Staple Corner, Double
Position:

Staple Capacity:
Corner Staple and Double Staple:
Letter/ 65 Sheets [24 lb. Bond (90 g/m²)]
Executive:
11" x 17"/ 30 Sheets [24 lb. Bond (90 g/m²)]
Legal/
Letter-R:
Staple-Free Staple:
11"x17"/ 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m²)]
Letter: 4 Sheets [17.3 to 21.7 lb. Bond
(65 to 81.4 g/m²)]
3 Sheets [21.7 to 28 lb. Bond
(81.5 to 105 g/m²)]
65 Sheets [24 lb. Bond (90 g/m²)]

Staple On Demand:
Saddle-Stitch 11" x 17", Legal, Letter-R, Custom Size
Paper Size: 7-3/4" x 10-5/8" to 11-3/4" x 17"
Paper Capacity 20 sheets x 10 sets [14 to 20 lb. Bond (52 to
of Saddle- 81 g/m²)] [including 1 cover Sheet up to 140 lb.
Stitch Mode: Index (256 g/m²)]
Power Source: From the Main Unit
Dimensions 25-7/8" x 24-1/2" x 47-1/8"
(W x D x H): (656 x 623 x 1,195 mm)¹⁶
Weight: Approx. 127.9 lb. (58 kg)

2/3 HOLE PUNCHER-A1¹⁷

Acceptable 14 lb. Bond to 140 lb. Index
Punch Paper (52 to 256 g/m²)
Weight:
Acceptable Two holes 11" x 17", Legal, Letter,
Punch Paper Letter-R, Executive
Size: Three holes 11" x 17", Letter, Executive
Power Source: From the Main Unit

COPY TRAY-R1

Capacity: 250 Sheets [20 lb. Bond (80 g/m²)]
Acceptable 14 lb. Bond to 140 lb. Index
Paper Weight: (52 to 256 g/m²)
Dimensions 16-1/2" x 15" x 6-7/8"
(W x D x H): (420 mm x 382 mm x 175 mm)
Weight: Approx. 2.4 lb. (1.1 kg)

DOCUMENT INSERTION UNIT-P1¹⁸

Number of Insertion Trays:	1 Tray
Acceptable Insertion Paper Size:	11" x 17", Legal, Letter, Letter-R, Executive
Acceptable Insertion Paper Weight:	16 lb. Bond to 140 lb. Index (60 to 256 g/m ²)
Capacity:	100 Sheets [20 lb. Bond (80 g/m ²)]
Power Source:	100-240 V AC, 50/60 Hz, 1.0 A
Dimensions (W x D x H):	26-1/8" x 26-3/4" x 48-7/8" (662 mm x 679 mm x 1242 mm)
Weight:	Approx. 88.2 lb. (40 kg)

DOCUMENT INSERTION/FOLDING UNIT-J1¹⁷

Number of Insertion Trays:	1 Tray
Acceptable Insertion Paper Size:	11" x 17", Legal, Letter, Letter-R, Executive
Acceptable Insertion Paper Weight:	16 lb. Bond to 140 lb. Index (60 to 256 g/m ²)
Capacity:	100 Sheets [20 lb. Bond (80 g/m ²)]
Supported Fold Types:	C-Fold, Z-Fold
C-Fold Paper Size/ Weight:	Letter-R/ 16 to 28 lb. Bond (60 to 105 g/m ²)
C-Fold Output Capacity:	40 Sheets [20 lb. Bond (80 g/m ²)]
Z-Fold Paper Size/ Weight:	11" x 17", Legal, Letter-R/16 to 28 lb. Bond (60 to 105 g/m ²)
Z-Fold Output Capacity:	30 Sheets [20 lb. Bond (80 g/m ²)]
Power Source:	100-240 V AC, 50/60 Hz, 1.0 A
Dimensions (W x D x H):	9-3/4" x 26-3/4" x 48-7/8" (247 mm x 679 mm x 1,242 mm)
Weight:	Approx. 168 lb. (76 kg)

Hardware Options

Card Readers

MiCARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-A4

Others

PRINTER COVER-H1
TAB FEEDING ATTACHMENT KIT-B1
STAMP INK CARTRIDGE-C1, STAMP UNIT-B1
UPRIGHT CONTROL PANEL-H1
UTILITY TRAY-B1

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B2

Data Security

HDD MIRRORING KIT-J1
2.5INCH/250GB HDD-N1
2.5INCH/1TB HDD-P1
REMOVABLE HDD KIT-AL1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

imagePASS-Y3
REMOVABLE HARD DISK DRIVE KIT-B6
FIERY IMPOSE
FIERY COMPOSE
FIERY IMPOSE AND COMPOSE
FIERY IMAGE VIEWER

System Accessories

SERIAL INTERFACE KIT-K3
MEAP WEB CONNECTION KIT V5.33¹⁹

Fax Accessories

SUPER G3 FAX BOARD-AS2
SUPER G3 2ND LINE FAX BOARD-AS2
SUPER G3 3RD/4TH LINE FAX BOARD-AS2
REMOTE FAX KIT-A1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1

Staples

STAPLE CARTRIDGE-X1²⁰
STAPLE CARTRIDGE-Y1²¹

¹ Some types of tracing paper cannot be used.

² Time from device power-on, until copy ready (not print reservation).

³ Time from exiting Sleep mode to when printing is operational.

⁴ Time from device power-on to when key operations can be performed on the touch panel.

⁵ Includes Main Unit, ADF, and Consumables.

⁶ PDF print from Websites is supported.

⁷ EPS can be printed directly only from the Remote User Interface.

⁸ Requires the optional PCL International Font Set-A1.

⁹ Requires the optional Barcode Printer Kit-D1.

¹⁰ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹¹ No charge for this solution; however activation is required.

¹² Requires Unified Firmware Platform v3.9.

¹³ Standby Reference Value: measured one unit.

¹⁴ 0.9 W sleep mode not available in all circumstances due to certain settings.

¹⁵ With 20 lb. Bond (80 gsm) paper.

¹⁶ When the extension tray is not extended.

¹⁷ When the extension tray and rotary tray are extended.

¹⁸ Requires either Staple Finisher-V2 or Booklet Finisher-V2.

¹⁹ No charge for this option; however it does need to be ordered.

²⁰ Used for corner/double stapling only, 3 cartridges per case, 5,000 staples per cartridge.

²¹ Used for booklet finishing only, 2 cartridges per case, 2,000 staples per cartridge.



AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2019 Canon U.S.A., Inc. All rights reserved.

1019R3-1RA65xxIIISS-PDF-IH



To learn about Canon's many awards, visit
usa.canon.com/awards.