

Product Specifications



Main Unit

System Type

Monochrome Digital Multifunction Imaging System

Functions

Copy, Print (UFR II, PCL 5e/6, Adobe® PostScript® 3™), Fax (Up to 2 Lines), Scan, Send, Store

Operation Panel

7" WVGA Full-Color, TFT Screen

Memory

Standard: 1.5 GB RAM
Maximum: 1.5 GB RAM

Hard Disk Drive

Standard: 80 GB
Maximum: 80 GB

Network Interface Connection

Ethernet 10/100 Base-TX, Ethernet 1000 Base-TX

Other Interface

USB 2.0 x3 (Host), USB 2.0 (Device)

Copy/Print Speed (BW)

Letter:	500iF:	Up to 52/52 ppm
	400iF:	Up to 42/42 ppm
Legal	500iF:	Up to 43/43 ppm
	400iF:	Up to 40/40 ppm

First-Copy-Out Time (Letter)

5 Seconds or Less

Paper Sources (20 lb. Bond)

Standard: 550-sheet Paper Cassette
100-sheet Stack Bypass
Optional: 550-sheet Paper Cassette (Up to 3)
Maximum: 2,300 Sheets

Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets
Maximum: 500 Sheets (with Staple Finisher-R1)

Output Paper Sizes

Cassettes: Legal, Letter, Statement, Executive, Custom size [5-1/2" x 8-1/4" to 8-1/2" x 14" (139.7 mm x 210 mm to 216 mm x 355.6 mm)], and Envelopes (COM10, Monarch, DL, ISO-C5)*
Bypass: Legal, Letter, Statement, Executive, Custom size [3-7/8" x 5-1/2" to 8-1/2" x 14" (99 mm x 139.7 mm to 216 mm x 355.6 mm)], and Envelopes (COM10, Monarch, DL, ISO-C5)
Other Options: Envelope Feeder Attachment (COM10, Monarch, DL, ISO-C5)*

Acceptable Paper Weights

Cassettes: 17 lb. Bond to 28 lb. Bond (64 to 105 g/m²)
Bypass: 17 lb. Bond to 34 lb. Bond (64 to 128 g/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Statement to Legal)

Paper Weights: Up to 28 lb. Bond (128 g/m²)

Media Support

Plain 1 [17 lb. Bond to 21 lb. Bond (64 to 80 g/m²)], Plain 2 [22 lb. Bond to 24 lb. Bond (81 to 90 g/m²)], Recycled [17 lb. Bond to 21 lb. Bond (64 to 80 g/m²)], Color [17 lb. Bond to 24 lb. Bond (64 to 90 g/m²)], Heavy 1 [25 lb. Bond to 28 lb. Bond (91 to 105 g/m²)], Heavy 2 [29 lb. Bond to 34 lb. Bond (106 to 128 g/m²)], Transparency [40 lb. Bond to 67 lb. Cover (151 to 181 g/m²)]**, Pre-punched [20 lb. Bond to 21 lb. Bond (75 to 80 g/m²)], Bond [20 lb. Bond to 24 lb. Bond (75 to 90 g/m²)], Labels [40 lb. Bond to 67 lb. Cover (151 to 181 g/m²)], Envelopes

Warm-up Time

From Power On: 34 Seconds
From Sleep Mode: 10 Seconds or Less
Quick Startup Mode: Within 7 Seconds or Less***

Power Requirements/Plug

120 V AC, 60 Hz, 10.0 A, NEMA 5-15

Power Consumption

Maximum: 1.5 kW
Sleep Mode: 1 W

Dimensions (H x W x D)

24-7/8" x 22-1/8" x 22-3/8" (633 mm x 560 mm x 567 mm)

Installation Space (W x D)

Without Staple Finisher-R1: 34-3/4" x 40-7/8" (881 mm x 567 mm)
With Staple Finisher-R1: 50-1/4" x 40-7/8" (1276 mm x 567 mm)

Weight

Approx. 107 lb. (48.7 kg)^A

Toner (Estimated Yield @ 5% Coverage)

15,200 Images

Main Unit (continued)

Image Reader Unit

Scan Resolution

Up to 600 x 600 dpi

Acceptable Originals (Glass)

Sheet, Book, 3-Dimensional Objects [up to 4.4 lb. (2 kg)]

Maximum Original Size

Legal (8-1/2" x 14")

Document Feeder

Scan Method

Duplexing Automatic Document Feeder

Acceptable Originals

Paper Sizes: Legal, Letter, Statement

Paper One-sided scanning: 11 lb. Bond to 34 lb. Bond
Weights: (42 to 128 g/m²), Two-sided scanning: 13 lb. Bond to 34 lb. Bond (50 to 128 g/m²)

Scan Speed (BW/Color; Letter)

Simplex: 52 ipm (600 dpi)/52 ipm (300 dpi)

Duplex: 33 ipm (600 dpi)/33 ipm (300 dpi)

Paper Capacity (20 lb. Bond)

100 Sheets

Copy Specifications

Multiple Copies

1 to 999

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25 - 400% (1% Increments) from Platen Glass

25 - 200% (1% Increments) from Document Feeder

Preset Reductions

78%, 64%, 50%, 25%

Preset Enlargements

400%, 200%, 129%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel, Standard Keys, Reset, Job Duration Display, Reserved Copying, ID Management, Counter Check

Special Copy Features

ID Card Copy, Shift, Frame Erase, Scan Image Check, Mode Memory, Recall, Sharpness, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date

Print Specifications

Processor

Canon Dual Custom Processor (Shared)

Engine Resolution

1200 x 1200 dpi

PDL Support

UFR II, PCL 5e/6, Adobe® PostScript® 3™

Print Driver Supported OS

UFR II, Adobe PostScript 3:

Windows® (XP/Vista™/7/8), Windows Server (2003/2008/2008 R2/SBS 2011/2012), Windows Terminal Server (2003/2008/2008 R2/2012), Microsoft Clustering Server (2003/2008/2008 R2/2012), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 4.0/5.0/5.5/5.6), VMware (vSphere 4/5/5.1), SAP (PS3 Only), Macintosh® (OS X 10.5.8 or later)

PCL 5e/6:

Windows® (Windows XP/Vista™/7/8; Windows Server 2003/2008/2008 R2/SBS 2011/2012), Windows Terminal Server (2003/2008/2008 R2/2012), Microsoft Clustering Server (2003/2008/2008 R2/2012), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 4.0/5.0/5.5/5.6), VMware (vSphere 4/5/5.1), SAP

Direct Print Support

Standard: TIFF, JPEG, PDF, EPS**

Optional: XPS***

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Objective, Toner Reduction, Poster Printing, Form Overlay

Scan Specifications

Network TWAIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Universal Send Specifications

Sending Method

E-mail, I-Fax, File Server (FTP, SMB, WebDAV), Super G3 Fax

Color Mode

Auto (Color, Gray), Auto (Color, Black), Full Color, Grayscale, BW

Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

Address Book Capacity

Max. 1,800 Destinations (Incl. 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Web), PDF/XPS (OCR), PDF/A-1b, XPS, XPS (Compact), OOXML (OCR) (.pptx)

Optional: PDF (Trace & Smooth), PDF (Encrypted), PDF/XPS (Digital Signature)

I-Fax Data Format

Color: TIFF (MH, MR, MMR)

BW: TIFF (MH, MR, MMR)

Universal Send Features

Two-sided Original, Original Type Selection, Density Adjustment, Sharpness, Erase Frame, Delayed Send, Preview, File Name, Subject/Message, Reply-to, Sender's Name (TTI), E-Mail Priority, Send to Myself, Send to My Folder

Fax Specifications

Number of Connection Lines

Standard: 1

Optional: Line 2

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size

Statement to Legal

Fax Features

Job Forwarding, Density Adjustment, Sharpness, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Job Done Notice, Original Type Selection, Two-sided Original, Direct Send, On-Hook Dialing

Main Unit (continued)

Store Specifications

Advanced Box

Store To Remote Advanced Box:* Supported
Print/View from Remote Advanced Box:* Supported

Memory Media

Standard: USB Memory

Security Specifications

Standard

Department ID Management, Single Sign On-H, Access Management System (Device and Function Level Log-in), Secured Print, Trusted Platform Module, IPv6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), Send to Myself (only), Send to My Personal Folder (only), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, IEEE 802.1x (wired/wireless), SMTP Authentication, POP Authentication before SMTP, HDD Initialize (Up to 9x) HDD Erase (Up to 3x), HDD Lock, IPsec, Adobe® LiveCycle® Rights Management ES2.5 Integration

Optional

HDD Encryption, Encrypted Secure Print, Encrypted PDF, Secure Watermark, IEEE 2600.1 Common Criteria Certification**

Environmental Information

ENERGY STAR® Qualified

RoHS Compliant

Blue Angel

EPEAT® Rated

WEEE Directive

Optional Accessories

Paper Supply Options

Cassette Module-AA1

Paper
Capacity: 550 Sheets [20 lb. Bond (80 g/m²)]
Acceptable
Paper Weight: 17 lb. Bond to 28 lb. Bond (64 to 105 g/m²)
Acceptable Legal, Letter, Statement, Executive, Custom size
Paper Size: [5-1/2" x 8-1/4" to 8-1/2" x 14" (139.7 mm x 210 mm to 216 mm x 355.6 mm)]

Power Source/
Maximum Power
Consumption: From the Main Unit/Approx. 20 W
Dimensions 4-3/4" x 21-1/4" x 19-3/4"
(H x W x D): (248 mm x 565 mm x 650 mm)
Weight: Approx. 17 lb. (7.7 kg)

Envelope Cassette-E1

Paper
Capacity: 50 sheets
Acceptable
Paper Size: COM10, Monarch, DL, ISO-C5
Feeding
Speed: 12 cpm
Dimensions 3-1/4" x 21-1/4" x 18-7/8"
(H x W x D): (96 mm x 54 mm x 480 mm)
Weight: Approx. 5.5 lb. (2.5 kg)

Output Options

Staple Finisher-R1

Number of
Trays: 1
Total Output
Capacity: **No finishing, Collate, Group mode:** 500 sheets [or 2-7/8" (73.5 mm) in height]
Collate + Offset, Group + Offset mode: 500 sheets [or 2-7/8" (73.5 mm) in height]
Staple mode: 20 sets [or 2-7/8" (73.5 mm) in height]
Acceptable
Paper Weight: 17 lb. Bond to 34 lb. Bond (64 to 128 g/m²)
Acceptable
Paper Size: Legal, Letter, Statement, Executive, Custom size [3-7/8" x 5-1/2" to 8-1/2" x 14" (99 mm x 139.7 mm to 216 mm x 355.6 mm)], and Envelopes

Staple
Positions: Corner Stapling (Legal, Letter, Executive)
Maximum
Stapling: **Corner Staple mode:**
50 sheets [17 lb. to 24 lb. Bond (64 to 90 g/m²)]
Capacity: 50 sheets [25 lb. to 28 lb. Bond (91 to 105 g/m²)]
30 sheets [29 lb. to 34 lb. Bond (106 to 128 g/m²)]
Type of Staple: Staple-PI (5,000 x 2)
Power Source/
Maximum Power
Consumption: From the Main Unit/Approx. 50 W
Dimensions 10-3/8" x 31-3/8" x 15-5/8"
(H x W x D): [263 mm x 798 mm x 395 mm
(when the auxiliary tray is extended)]
Weight: Approx. 23.1 lb. (10.5 kg)

Other Optional Accessories

- Copy Card Reader-F1
- IC Card Reader Box-A1
- Universal Keyboard Stand-A1
- Card Reader Assembly for Universal Keyboard Stand
- Super G3 2nd Line Fax Board-AM1
- PCL International Font Set-B1
- Barcode Print Kit-D1
- Direct Print Kit (For PDF/XPS)-H1
- Universal Send Trace & Smooth PDF Kit-A1
- Send Security Feature Set-D1
- Universal Send Digital User Signature Kit-C1
- Remote Operators Software-B1
- Encrypted Secure Print Software-D1
- IR-ADV Security Kit-H1 For IEEE 2600.1 Common Criteria Certification**
- HDD Data Encryption Kit-C6
- Secure Watermark-B1
- Web Access Software-H1
- ADF Access Handle-A1
- Braille Label Kit-F1

* Can be set to Cassette 2 only.
** Not available on top cassette.
*** If "Quick Startup Settings for Main Power" is set to On, it takes seven seconds until the key operation on the touch-panel display is available after turning on the main power.
▲ Includes consumables except for Toner.
▲▲ EPS can be printed directly only from Remote User Interface.
▲▲▲ XPS cannot be printed directly from Web Access Software.
• Requires imageRUNNER ADVANCE device with Advanced Box.
** Available approximately six months after launch.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, MEAP, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. imageWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2018 Canon U.S.A., Inc. All rights reserved.

