

**Detector**

Method	Cassette Size Detector, Scintillator & Amorphous Silicon (a-Si)
Scintillator	CsI (CsI: TI)
Sensor	LANMIT (Large Area New-MIS sensor and TFT)
Pixel Pitch	125 Microns
Pixels	2,800 x 3,408 Pixels (9.5 Megapixels)
Imaging Area	Approx. 14 x 17 in (35 x 43 cm)
Standard	Sensor Unit, X-Ray Interface Box (optional), Battery Charger, Detector
Configuration	Check-In Unit, Wireless Access Point (Including A/C Power)

**Battery**

Recharge Time	Less Than 3 Hours
Performance	Approximately 140 Images

**Image Acquisition and Processing**

Image Processing	Standard Advanced Multi-Frequency Processing
A/D	16-bit
Grayscale Output	12 bit or 16 bit selectable
Preview Image	Approximately 1-2 Seconds After X-ray Exposure
Full Image Display	Approximately 5-6 Seconds After X-ray Exposure

**Data Output and Network Connection**

Wireless Standard	IEEE 802.11n (5 & 2.4 GHz)
DICOM	DICOM 3.0 Compatible, Print Management (SCU), Storage (SCU), MWL (SCU), MPPS (SCU)

**Electrical and Environmental**

Operating Environment	Sensor Unit: 41-95°F (5-35°C), Humidity 30-80% RH (non-condensing)
-----------------------	--

**Physical Characteristics**

Dimensions (W x L x H)	15.1 x 18.1 x 0.6 in (384 x 460 x 15 mm) (Detector unit only)
Weight	7.3 lbs (3.3 kg) (with battery)

*Specifications are subject to change without notice.*