

AVAILABLE MODELS	OCÉ ARIZONA 400 SERIES, EXTRA LARGE TABLE	OCÉ ARIZONA 400 SERIES, STANDARD SIZE TABLE
	OCÉ ARIZONA 440 XT PRINTER - with 4 ink channels	OCÉ ARIZONA 440 GT PRINTER - with 4 ink channels
Rigid media size	98.4" x 120" (2.50 m x 3.05 m)	49" x 98.4" (1.25 m x 2.50 m)
Rigid media thickness	2" (50.8 mm)	2" (50.8 mm)
Océ VariaDot imaging technology	6 to 42 picoliter droplets, 636 nozzles, one printhead/channel, single row design	6 to 42 picoliter droplets, 636 nozzles, one printhead/channel, single row design
White Ink	Standard on Océ Arizona 480 XT printer and Océ Arizona 460 XT printer	Standard on Océ Arizona 480 GT printer and Océ Arizona 460 GT printer
Varnish	Standard on Océ Arizona 480 XT printer and Océ Arizona 460 XT printer	Standard on Océ Arizona 480 GT printer and Océ Arizona 460 GT printer
CM2 capability	Standard on Océ Arizona 480 XT printer	Standard on Océ Arizona 480 GT printer
PRINT MEDIA AND SPEEDS*		
Express print speed	368 ft.2/hr. (34.2 m2/hr.)	353 ft.2/hr. (32.8 m2/hr.)
Production-Squared (CM²)	272 ft.2/hr. (25.3 m2/hr.) Océ Arizona 480 XT printer only	264 ft.2/hr. (24.5 m2/hr.) Océ Arizona 480 GT printer only
Production Quality-Squared (CM²)	226 ft.2/hr. (21.0 m2/hr.)	219 ft.2/hr. (20.3 m2/hr.)
Quality	155 ft.2/hr. (14.4 m2/hr.)	151 ft.2/hr. (14.0 m2/hr.)
Fine Art	126 ft.2/hr. (11.7 m2/hr.)	122 ft.2/hr. (11.3 m2/hr.)
High definition	66 ft.2/hr. (6.1 m2/hr.)	64 ft.2/hr. (5.9 m2/hr.)
UV curing technology	110 mm, high output/low heat UV arc lamp with integrated shutter/reflector	110 mm, high output/low heat UV arc lamp with integrated shutter/reflector
Roll Media	Available option, up to 86.6" (2.2 m)	Available option, up to 86.6" (2.2 m)