

AVAILABLE MODELS	OCÉ ARIZONA 600 SERIES, EXTRA LARGE TABLE	OCÉ ARIZONA 600 SERIES, STANDARD SIZE TABLE
	OCÉ ARIZONA 640 XT PRINTER - with 4 ink channels	OCÉ ARIZONA 640 GT PRINTER - with 4 ink channels
Rigid media size	98.4" x 120" (2.50 m x 3.05 m)	49" x 98.4" (1.25 m x 2.50 m)
Rigid media thickness	2" (50.8 mm)	2" (50.8 mm)
Océ VariaDot imaging technology	6 to 42 picoliter droplets, 636 nozzles, two printheads/color, dual row design	6 to 42 picoliter droplets, 636 nozzles, two printheads/color, dual row design
White Ink	Standard on Océ Arizona 660 XT printer	Standard on Océ Arizona 660 GT printer
Varnish	Standard on Océ Arizona 660 XT printer	Standard on Océ Arizona 660 GT printer
CM2 capability	Standard on Océ Arizona 660 XT printer	Standard on Océ Arizona 660 GT printer
PRINT MEDIA AND SPEEDS*		
Express print speed	696 ft.2/hr. (64.7 m2/hr.)	657 ft.2/hr. (60 m2/hr.)
Production-Squared (CM²)	535 ft.2/hr. (49.7 m2/hr.) Océ Arizona 660 XT printer only	498 ft.2/hr. (46.3 m2/hr.) Océ Arizona 660 GT printer only
Production	431 ft.2/hr. (40 m2/hr.)	404 ft.2/hr. (37.5 m2/hr.)
Quality-Squared (CM²)	358 ft.2/hr. (33.3 m2/hr.)	337 ft.2/hr. (31.3 m2/hr.)
Quality	325 ft.2/hr. (30.2 m2/hr.)	306 ft.2/hr. (28.4 m2/hr.)
Fine Art	259 ft.2/hr. (24.0 m2/hr.)	244 ft.2/hr. (22.7 m2/hr.)
High definition	Not available	Not available
UV curing technology	171 mm, high output/low heat UV arc lamp with integrated shutter/reflector	171 mm, high output/low heat UV arc lamp with integrated shutter/reflector
Roll Media	Available option, up to 86.6" (2.2 m)	Available option, up to 86.6" (2.2 m)