

Flatbed Scanner Units

The optional Flatbed Scanner Units are devices designed to complement Canon's imageFORMULA document scanners and widen the variety and types of documents that can be scanned to include bound, thick, and fragile documents.

Simple Connectivity

- USB Connection
 - ✓ Between imageFORMULA scanner and PC

Flexible Operation

- Single scanner operation for both imageFORMULA scanner and Flatbed Unit
- Save captured images from imageFORMULA scanner and Flatbed Unit as a single file
- Pre-Configured Scan Jobs

Adaptable Hardware

- Two piece document cover
 - ✓ "Open Scanning" for books and bound documents



Flatbed Scanner Unit 101

Advanced Image Processing & Document Handling

- Versatile document support
 - ✓ Up to legal size document scanning (FBSU101)
 - ✓ Up to ledger size document scanning (FBSU201)
 - ✓ Books and bound documents scanning
 - ✓ Plastic cards
- High resolution scanning
 - ✓ Up to 1200 dpi (FBSU101)
- Ambient light canceling mode

Environment in Mind

- Meets Energy Star Guidelines for energy efficiency
- Complies with RoHS and WEEE directives



Flatbed Scanner Unit 201

Product Specifications – FBSU101

Document Feeding:	Manual	Dimensions (H x W x D):	11.4" x 20.2" x 3.5" (with cover closed)
Document Size:	Up to 8.5" x 14.0"	Weight:	7.7 lb.
Light Source:	LED	Interface:	Hi-Speed USB 2.0
Scanning Element:	CCD	Power Consumption:	< 15.2W max. (Energy Saving Mode: <5.1W)
Output Modes:	Binary (B&W, Error Diffusion, Advanced Text Enhancement II), Grayscale (256-level), Color (16M)	Supported OS:	Microsoft Windows 2000 (32-bit), Windows XP Pro (32-bit/64-bit), Windows XP Home (32-bit), Windows Vista® (32-bit/64-bit), Windows 7 (32-bit/64-bit)
Optical Resolution:	1200 dpi	Bundled Software:	ISIS / TWAIN Drivers
Output Resolution	100/150/200/300/400/600/1200 dpi	Item Number:	4101B002
Grayscale:	8-bit	Other Features:	Ambient Light Canceling, Auto Color Detection, Auto Page Size Detection, Border Removal, Color Dropout/Color Enhancement, Deskew, Edge Emphasis, Moiré Reduction, MultiStream, Prevent Bleed-Through/Remove Background, Punch Hole Removal, Text Enhancement, Text Orientation Recognition, User Preferences
Color:	24-bit	Applicable Models:	DR-2010C / DR-2510C DR-3010C DR-4010C DR-6010C DR-6050C / DR-7550C / DR-9050C
Scanning Speeds:	(Conditions: Pentium 4 3.2 GHz CPU, 1 GB memory, LTR size)		
<u>Color</u>	1200 dpi	37 seconds	
	600 dpi	10 seconds	
	400 dpi	8 seconds	
	300 dpi	4 seconds	
	200 dpi	3 seconds	
	150 dpi	3 seconds	
	100 dpi	3 seconds	
<u>Grayscale, B&W</u>	1200 dpi	35 seconds	
	600 dpi	6 seconds	
	400 dpi	5 seconds	
	300 dpi	3 seconds	
	200 dpi	3 seconds	
	150 dpi	3 seconds	
	100 dpi	3 seconds	

Product Specifications – FBSU201

Document Feeding:	Manual	Dimensions (H x W x D):	3.8" x 22.5" x 17.2" (with cover closed)
Document Size:	Up to 11.7" x 17.0"	Weight:	18.7 lb.
Light Source:	LED	Interface:	Hi-Speed USB 2.0
Scanning Element:	CCD	Power Consumption:	< 21W max. (Energy Saving Mode: <3.1W)
Output Modes:	Binary (B&W, Error Diffusion, Advanced Text Enhancement II), Grayscale (256-level), Color (16M)	Supported OS:	Windows XP (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows 7 (32-bit/64-bit)
Optical Resolution:	600 dpi	Bundled Software:	ISIS / TWAIN / WIA Drivers
Output Resolution	100/150/200/240/300/400/600 dpi	Item Number:	6240B002
Grayscale:	8-bit	Other Features:	Ambient Light Canceling, Auto Color Detection, Auto Page Size Detection, Border Removal, Color Dropout/Color Enhancement, Deskew, Edge Emphasis, Moiré Reduction, MultiStream, Prevent Bleed-Through/Remove Background, Punch Hole Removal, Text Enhancement, Text Orientation Recognition, User Preferences
Color:	24-bit	Applicable Models:	DR-M160 DR-6030C DR-6050C / DR-7550C / DR-9050C DR-X10C
Scanning Speeds:	(Conditions: Core2Duo 3.0GHz CPU, 3 GB memory, 11x17 size)		
<u>Color</u>	600 dpi	15 seconds	
	300 dpi	5 seconds	
	200 dpi	5 seconds	
	150 dpi	5 seconds	
<u>Grayscale, B&W</u>	600 dpi	7 seconds	
	300 dpi	4 seconds	
	200 dpi	4 seconds	
	150 dpi	4 seconds	