



REALiS SX6000 PRO AV PROJECTOR


A Bright Performer

Equipped with new LCOS (Liquid Crystal on Silicon) display panels featuring an improved pixel-spacing aperture ratio of 96% for virtually seamless imagery – and enhanced by Version 4.1 of Canon's revolutionary AISYS (Aspectual Illumination System) optical technology – the REALiS SX6000 Pro AV Projector displays exceptional 6000 lumen video and still images at SXGA+ (1400 x 1050) resolution. Added advantages to the SX6000's advanced imaging technologies include better white balance, improved reliability and durability, and outstanding energy efficiency. Advanced color tools (6-axis Color Adjustment, Color Correction IC, and 3D Color LUT) also provide high color reproducibility. Multiple image modes, integrated test patterns, a choice of three optional genuine Canon projection lenses, expanded interfaces (including DVI-I and HDMI 1.3), an advanced wired remote control and installer-friendly features makes the REALiS SX6000 a superb choice for many presentation venues.



Key Features

- ▶ 6000 Lumen Brightness
- ▶ Native SXGA+ (1400 x 1050) Resolution
- ▶ 1000:1 Contrast Ratio
- ▶ 96% Aperture Ratio LCOS Panels
- ▶ AISYS 4.1 Optical Technology
- ▶ Advanced White Balance
- ▶ Improved Reliability and Durability
- ▶ Increased Burn-In Resistance
- ▶ Outstanding Energy Efficiency



Integrated test patterns controllable from the remote control enable adjustment of the image angle, gradation, and color tone. System faults can also be isolated.

Recommended For:

- ▶ Higher Education
- ▶ Houses of Worship
- ▶ Museums
- ▶ Conference Centers
- ▶ Engineering Labs
- ▶ Government and Military
- ▶ Photo Studios/Galleries

REALiS SX6000

Canon



REALiS SX6000 PRO AV PROJECTOR

PRODUCT NAME: REALiS SX6000 ITEM CODE: 5749B002 UPC CODE: 013803142563

SPECIFICATIONS

BASIC	IMAGING DEVICE		0.72" LCOS Reflective LCD Panels x 3
	ASPECT RATIO		4:3
	NATIVE RESOLUTION		1400 x 1050 (SXGA+)
	BRIGHTNESS		6000 Lumens
	UNIFORMITY		88%
	CONTRAST RATIO		1000:1
		KEYSTONE CORRECTION	VERTICAL
HORIZONTAL			± 20°
IMAGE ADJUSTMENTS	IMAGE MODES		Standard, Presentation, Vivid Photo, Photo/sRGB, Dynamic, Video, Cinema, User 1-5
	MOUNTING		Ceiling, Rear, Rear-Ceiling, Upward, Downward
	TILT ANGLE		Adjustable feet up to 6 degrees
INPUT SIGNALS	DIGITAL PC INPUT		UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
	ANALOG INPUT		UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA
	SCANNING FREQUENCY		H Freq. 15.625-75 KHz V Freq. 50-60.317 Hz Max dot clock 162 MHz
	DIGITAL VIDEO INPUT		1080p / 1080i / 720p / 576p / 480p
	COMPONENT INPUT		1080p / 1080i / 720p / 576p / 576i / 480p / 480i
TERMINALS	INPUT	DVI-I 29PIN	Analog PC / Digital PC input
		HDMI	Version 1.3 Deep Color Digital PC / Digital Video Input
		MINI D-SUB 15PIN	Analog PC / Component Video Input
		MINI JACK	Stereo Input x 2
	CONTROL	MINI JACK	Wired remote control connection x1
		D-SUB 9 PIN	RS-232C Control
		RJ-45	Network (100BASE-TX / 10BASE-T)
BUILT-IN SPEAKER		5W (Mono)	
LAMP	LAMP	TYPE	330W NSH (AC)
		LAMP LIFE	3000 Hours
REMOTE CONTROL	REMOTE CONTROL	SENSOR	Wireless Infrared, Front/Back Wired Remote Control Connection
RATINGS	FAN NOISE		40dB
	POWER	CONSUMPTION	435W / 1.7W (Standby) / 0.35W (Standby with LAN off)
		VOLTAGE	AC100 ~ 240V, 50 / 60 Hz
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C) 85% RH or less
		STORAGE	14° ~ 140° F (-10° ~ 60° C)
	DIMENSIONS (W X D X H)		15 x 6.69 x 16.9 in. (without lens, including protruding parts)
	WEIGHT		18.74 lb. (without lens)

OPTIONAL ACCESSORIES


Item Code No.	Description
4966B001	Standard Zoom Lens RS-IL01ST
4967B001	Long Focus Zoom Lens RS-IL02LZ
4968B001	Ultra Wide-Angle Lens RS-IL03WF
5017B001	Replacement Lamp RS-LP07
4971B001	Replacement Air Filter RS-FL01
5750B001	Wired Remote Controller RS-RC05
4969B001	Ceiling Mount RS-CL11
3096B001	Ceiling Extension RS-CL08 (16" ~ 24")
3097B001	Ceiling Extension RS-CL09 (24" ~ 39")
5471B001	Top Cover RS-TC01 (Dark Grey)

Accessories



Three high-resolution interchangeable Genuine Canon projection lenses are available for the REALiS SX6000 Pro AV Projector. These include a 1.5x Standard Zoom, a 0.8x Ultra Wide-Angle lens, and a 1.7x Long-Focus Zoom. Each lens features advanced low-distortion and high-resolution optical technologies originally developed for Canon's world-renowned line of EF lenses.

Connectability



Expanded interface options include DVI-I, HDMI 1.3, and analog RGB inputs. Control connections include a network-ready RJ-45 port and RS-232C serial connection. A separate stereo mini-jack input enables direct connection with the hand-held remote-control, if desired.

©2012 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Some of the images and effects are simulated. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

Canon
image*ANYWARE*

For more info:
Call 1-800-OK-CANON (1-800-652-2666)
pro.usa.canon.com

LENS SPECIFICATIONS

PRODUCT NAME			SX6000
3 LENS OPTIONS	RS-IL01ST STANDARD ZOOM LENS	PROJECTION LENS	F1.89 ~ 2.65 / f= 23.0 ~ 34.5 mm
		LENS SHIFT*	(Vertical) Down 12% ~ Up 50% / (Horizontal) Left 10% ~ Right 10%
		ZOOM	1.5 x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" to 600"
		PROJECTION DISTANCE	4.3-31.5 ft (1.3-9.6 m), 100": 10.5 - 15.7 ft (3.2-4.8 m)
		THROW RATIO	1.5:1 ~ 2.21:1
	RS-IL02LZ LONG FOCUS ZOOM LENS	PROJECTION LENS	F1.99 - 2.83 / f= 34.0 ~ 57.7 mm
		LENS SHIFT*	(Vertical) Down 12% ~ Up 50% / (Horizontal) Left 10% ~ Right 10%
		ZOOM	1.7 x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" to 600"
		PROJECTION DISTANCE	6.23 ~ 46.59 ft (1.9-14.2 m) / 100": 15.4 ~ 26.24 ft (4.7 ~ 8.0 m)
		THROW RATIO	2.1:1 ~ 3.72:1
	RS-IL03WF ULTRA WIDE-ANGLE LENS	PROJECTION LENS	F2.0 / f= 12.8 mm
		LENS SHIFT*	(Vertical) Down 5% ~ Up 5% / (Horizontal) Left 2% ~ Right 2%
		ZOOM	Fixed
		FOCUS	Powered
		SCREEN SIZE	40" to 300"
		PROJECTION DISTANCE	2.3 - 17.1 ft (0.7 - 5.2 m) / 100": 5.6 ft (1.7 m)
		THROW RATIO	0.8:1

*The maximum upward shift and the maximum horizontal shift cannot be used simultaneously.