

<b>PRODUCT NAME</b>	<b>REALiS WUX4000</b>
<b>ITEM CODE</b>	<b>4964B002</b>
<b>UPC CODE</b>	<b>013803131642</b>



**Suggested List Price:**

**\$8,999.00**

### FEATURES

- **Native WUXGA Resolution (1920 x 1200)** - Display true wide screen content in high resolution.
- **LCOS Technology** - High image quality and reliability
- **4th Generation AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **4000 Lumens** - Bright, crisp images
- **Three Optional Interchangeable Lenses** - Standard, Tele Zoom Lens, and Wide Angle Lens
- **Motorized Lens Shift** - The image can be moved without physically tilting the projector
- **Vivid Photo Mode** - can brightly & vividly express skin tones more naturally
- **Color Correction IC** - 6-axis color adjustment and 3D LUT color reproduction
- **HDMI Deep Color Ver. Input** - Supports full 1080p high definition signal
- **Network Ready RJ-45 Port** - Manage and control multiple projectors from a networked pc
- **Easy-Accessible Lamp, Filter, and Optics Consumption Parts** - The projector's lamp can be replaced from the back, and the filter replaced from the side. The WUX4000 is designed to allow easy parts replacement, even when suspended from a ceiling
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired\*

### CONTENTS OF KIT

- REALiS WUX4000 Projector
- Lens Cap
- Remote Control (with AAA batteries)
- VGA-VGA Computer Cable
- User Manual

### OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
4966B001	RS-IL01ST STANDARD LENS	799.00
4967B001	RS-IL02LZ LONG FOCUS ZOOM LENS	2,499.00
4968B001	RS-IL03WF ULTRA WIDE ANGLE LENS	2,499.00
4965B001	RS-LP06 REPLACEMENT LAMP	579.00
4969B001	RS-CL11 CEILING MOUNT	999.00
4970B001	RS-RC04 REMOTE CONTROLLER	TBD
3096B001	RS-CL08 CEILING EXTENSION: (16" - 24")	379.00
3097B001	RS-CL09 CEILING EXTENSION: (24" - 39")	399.00
4971B001	RS-FL01 REPLACEMENT FILTER	TBD

### PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
REALiS WUX4000	00.0 x 00.0 x 00.0 in (000 x 000 x 000 mm)	00.00 lbs (0.00 kg)

\* All prices, specifications, and availability subject to change without prior notice. Canon is a registered trademark of Canon Inc. IMAGEANYWARE is a trademark of Canon.

Effective: March 2011

### SPECIFICATIONS

<b>BASIC</b>	<b>IMAGING DEVICE</b>	0.7" LCOS Reflective LCD panels x 3		
	<b>ASPECT RATIO</b>	16 : 10		
	<b>NATIVE RESOLUTION</b>	1920 x 1200 (WUXGA)		
	<b>BRIGHTNESS</b>	4000 Lumens		
	<b>UNIFORMITY</b>	88%		
	<b>CONTRAST</b>	1000:1		
<b>KEYSTONE CORRECTION</b>	<b>VERTICAL</b>	± 20 degrees for Standard / Long Focus Zoom Lens ± 13 degrees for Ultra Wide-Angle Lens		
	<b>HORIZONTAL</b>	-11 to +20 degrees for Standard Lens ± 20 degrees for Long Focus Zoom / Ultra Wide-Angle Lens		
<b>IMAGE ADJUSTMENTS</b>	<b>IMAGE MODE</b>	PC: Standard, Presentation, Vivid Photo, Photo/sRGB, Users(1-5) Video: Standard, Dynamic, Photo/sRGB, Video, Cinema, Users(1-5)		
	<b>COLOR PROCESSING</b>	3D-LUT		
	<b>MOUNTING</b>	Ceiling, Rear, Rear-Ceiling, Upwards, Downwards		
	<b>TILT ANGLE</b>	Adjustable feet up to 6 degrees		
<b>INPUT SIGNALS</b>	<b>DIGITAL PC INPUT</b>	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA		
	<b>ANALOG PC INPUT</b>	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA		
	<b>SCANNING FREQUENCY</b>	H:15 - 75 kHz, V: 50 - 85 kHz		
	<b>DOT CLOCK</b>	162 MHz or less		
	<b>DIGITAL VIDEO INPUT</b>	1080p / 1080i / 720p / 576p / 480p		
	<b>COMPONENT INPUT</b>	1080p / 1080i / 720p / 576p / 480p / 480i		
<b>TERMINALS</b>	<b>INPUT</b>	<b>DVI-D 24PIN</b>	Digital RGB Input	
		<b>HDMI (Ver. 1.3)</b>	(supports Deep Color) Digital RGB/ Digital Video Input	
		<b>MINI D-SUB 15PIN</b>	Analog RGB / Component Video Input / SBNC	
	<b>MINI-JACK</b>	Stereo x 2		
	<b>OUTPUT</b>	<b>MINI-JACK</b>	Stereo x 1	
	<b>CONTROL</b>	<b>D-sub 9pin</b>	RS-232C	
<b>NETWORK</b>		RJ-45		
	<b>SPEAKER</b>	5W		
<b>LAMP</b>	<b>TYPE</b>	330W NSH (AC)		
	<b>POWER (NORMAL/QUIET)</b>	300 / 264 W		
	<b>LAMP LIFE (NORMAL/QUIET)</b>	3000 / 4000 Hours		
<b>REMOTE CONTROL</b>	<b>SENSOR</b>	Wireless Infrared, Front / Back		
<b>RATINGS</b>	<b>FAN NOISE (NORMAL/QUIET)</b>	39 / 36dB		
	<b>POWER</b>	<b>CONSUMPTION (NORMAL / ECO / STANDBY)</b>	450W / 390W / 0.5W (with LAN off)	
		<b>VOLTAGE</b>	AC100 to 240V, 50/60Hz	
	<b>TEMPERATURE</b>	<b>OPERATING</b>	41° to 95° F (5° to 35° C)	
		<b>STORAGE</b>	-22° to 104° F (-30° to 60° C), 5%RH - 90%RH	
	<b>DIMENSIONS (W x D x H)</b>	14.96" x 16.92" x 5.90" without lens		
<b>WEIGHT</b>	18.7 lbs without lens			

### OPTIONAL LENS SPECIFICATIONS

<b>OPTICS</b> 3 Optional Lenses	<b>RS-IL01ST STANDARD ZOOM LENS</b>	<b>PROJECTION LENS</b>	F1.89 - 2.65 / f= 23.0 - 34.5 mm
		<b>LENS SHIFT</b>	Vertical= 3.5 : 6.5 - 10.5 : 0.5 / Horizontal= 4.6 - 6.4
		<b>ZOOM</b>	1.5x Optical Zoom (Powered)
		<b>FOCUS</b>	Powered
		<b>SCREEN SIZE</b>	40" x 300"
		<b>PROJECTION DISTANCE</b>	4.26 to 31.49 ft. (1.3 - 9.6 m) / 100": 10.49 - 15.74 ft. (3.2 - 4.8 m)
	<b>THROW RATIO</b>	1.5:1 - 2.25:1	
	<b>RS-IL02LZ LONG FOCUS ZOOM LENS</b>	<b>PROJECTION LENS</b>	F2.0 - 2.8 / f= 34.0 - 57.7 mm
		<b>LENS SHIFT</b>	Vertical= 3.5 : 6.5 - 10.5 : 0.5 / Horizontal= 4.6 - 6.4
		<b>ZOOM</b>	1.7x Optical Zoom (Powered)
		<b>FOCUS</b>	Powered
		<b>SCREEN SIZE</b>	40" x 300"
<b>PROJECTION DISTANCE</b>		6.23 to 46.58 ft. (1.9 - 14.2 m) / 100": 15.4 - 26.24 ft. (4.7 - 8.0 m)	
<b>THROW RATIO</b>	2.2:0 - 3.75:1		
<b>RS-IL03WF ULTRA WIDE ANGLE LENS</b>	<b>PROJECTION LENS</b>	F2.0 / f= 12.8 mm	
	<b>LENS SHIFT</b>	Vertical= 4.5 : 5.5 - 5.5 : 4.5 / Horizontal= 4.8 : 5.2 - 5.2 : 4.8	
	<b>ZOOM</b>	1.0x Optical Zoom (Powered)	
	<b>FOCUS</b>	Powered	
	<b>SCREEN SIZE</b>	40" x 300"	
	<b>PROJECTION DISTANCE</b>	2.29 to 17.06 ft. (0.7 - 5.2 m) / 100": 5.67 ft. (1.73 m)	
<b>THROW RATIO</b>	0.8:1		