

PRODUCT NAME	REALiS WUX5000 D
ITEM CODE	5748B008
UPC CODE	660685047327



FEATURES

- **Native WUXGA Resolution (1920 x 1200)** - Display true widescreen content in high resolution.
- **LCOS Technology** - High image quality and reliability
- **4th Generation AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **5000 Lumens** - More brightness for large venues, crisp sharp image quality
- **Three Optional Interchangeable Lenses** - Standard, Telephoto, and Fixed Short Focus Lenses
- **Motorized Lens Shift** - Image can be moved without physically tilting the projector
- **DICOM Mode** - 21 level adjustment for grayscale gradation with Pre-Set Mode
- **Vivid Photo Mode** - Smooth, natural skin tones and brilliant color
- **Color Correction IC** - 6-axis color adjustment and 3D LUT color reproduction
- **HDMI Deep Color Ver. 1.3 Input** - Supports full 1080p high definition
- **Network Ready RJ-45 Port** - Manage and control multiple projectors from a networked PC
- **Easy Maintenance Access to Consumable Parts** - The projector's filter can be replaced from the side of the projector, the lamp can be replaced from the rear of the projector, and the PS optical filter element of the projector can be replaced from the top of the projector.
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality in the event an end user's projector needs to be repaired*

*Based on availability. For complete details contact your Canon sales representative.

CONTENTS OF KIT

- **REALiS WUX5000 D Projector**
- **VGA-VGA Computer Cable**
- **Remote Control** (with AAA batteries)
- **User's / Installation Manual (CD)**
- **Power Cord**
- **Warranty Card**

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION
4966B001	RS-IL01ST STANDARD LENS
4967B001	RS-IL02LZ LONG FOCUS ZOOM LENS
4968B001	RS-IL03WF ULTRA WIDE ANGLE LENS
5017B001	RS-LP07 REPLACEMENT LAMP
4969B001	RS-CL11 CEILING MOUNT
4970B001	RS-RC04 REMOTE CONTROLLER
3096B001	RS-CL08 CEILING EXTENSION: (16" - 24")
3097B001	RS-CL09 CEILING EXTENSION: (24" - 39")
4971B001	RS-FL01 REPLACEMENT FILTER

PACKAGING INFORMATION

PROJECTOR	W x H x D	WEIGHT
REALiS WUX5000 D	15.0" x 6.7" x 16.9" (380mm x 170mm x 430mm)	18.7 lbs (8.5 kg)

SPECIFICATIONS

BASIC	IMAGING DEVICE	0.71" LCOS Reflective LCD panels x 3	
	ASPECT RATIO	16:10	
	NATIVE RESOLUTION	1920 x 1200 (WUXGA)	
	BRIGHTNESS	5000 (Normal), 4000 (Quiet) Lumens	
	UNIFORMITY	88%	
	CONTRAST	1000:1	
KEYSTONE CORRECTION	VERTICAL	-11° ~ +20° for Standard Lens ±20° for Telephoto Lens ±13° for Fixed Short Focus Lens	
	HORIZONTAL	±20° for Standard, Telephoto, and Fixed Short Focus Lenses	
IMAGE ADJUSTMENTS	IMAGE MODE	PC: Standard/Presentation, Vivid Photo, User (1-5) Video: Dynamic, Photo/sRGB/Video, Cinema, User (1-5) DICOM Simulation Mode	
	COLOR ADJUST	Color (Level, Temperature, Balance) Gain & Offset (R,G,B)	
	MOUNTING	Ceiling, Rear, Rear-Ceiling, Upwards, Downwards	
	TILT ANGLE	Adjustable feet up to 6 degrees	
VIDEO INPUT SIGNAL	SCANNING FREQUENCY	H:15 ~ 75 kHz, V: 50 ~ 60 Hz	
	ANALOG PC INPUT	WUXGA/UXGA/WSXGA+/WXGA+/SXGA+/WXGA/SXGA/XGA/SVGA/VGA	
	DIGITAL PC INPUT	WUXGA/UXGA/WSXGA+/WXGA+/SXGA+/WXGA/SXGA/XGA/SVGA/VGA	
	COMPONENT VIDEO INPUT	1080p / 1080i / 720p / 576p / 576i / 480p / 480i	
	DIGITAL VIDEO INPUT	1080p / 1080i / 720p / 576p / 480p	
	DOT CLOCK	162 MHz or less	
TERMINALS	INPUTS	ANALOG PC INPUT	Mini D-sub 15pin (VGA)
		DIGITAL PC INPUT	HDMI, DVI-D 24pin
		ANALOG VIDEO INPUT	Mini D-sub 15pin (Component)
		DIGITAL VIDEO INPUT	HDMI, DVI-D 24pin
	OUTPUTS	AUDIO OUTPUT	3.5mm (Stereo)
		CONTROL	SERIAL 9-pin D-Sub (RS-232C) NETWORK RJ-45 WIRELESS REMOTE Infrared (Front/Back Sensor)
	BUILT-IN SOUND	SPEAKER	5W (Mono)
	LAMP	TYPE	330W NSH (AC)
LAMP LIFE		3000 H (Normal/Quiet)	
LAMP POWER		336W (Normal), 264W (Quiet)	
RATINGS	FAN NOISE	40dB (Normal), 36dB (Quiet)	
	POWER CONSUMPTION	450W (Normal), 365W (Quiet)	
	STANDBY POWER	1.7W (w/Network), 0.35 (w/o Network)	
	POWER REQUIREMENT	AC100 - 240V, 50/60Hz	
	OPERATING TEMPERATURE	41° - 95° F (5° - 35° C)	
	STORAGE ENVIRONMENT	14° - 140° F (-10° - 60° C)	
	DIMENSIONS (W x H x D)	15.0" x 6.7" x 16.9" including protruding parts, without lens	
	WEIGHT	18.7 lb. without lens	

OPTIONAL LENS SPECIFICATIONS

OPTICS 3 Optional Lenses	RS-IL01ST STANDARD ZOOM LENS	PROJECTION LENS	F1.89 - 2.65 / f= 23.0 - 34.5 mm
		LENS SHIFT	Vertical= -15% ~ 55% / Horizontal= ±10%
		ZOOM	1.5x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" - 600"
		PROJECTION DISTANCE	4.3 - 95.1 ft. (1.3 - 29 m) / 100": 10.5 - 15.8 ft. (3.2 - 4.8 m)
	RS-IL02LZ TELEPHOTO LENS	THROW RATIO	1.5:1 - 2.21:1
		PROJECTION LENS	F1.99 - 2.83 / f= 34.0 - 57.7 mm
		LENS SHIFT	Vertical= -15% ~ 55% / Horizontal= ±10%
		ZOOM	1.7x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" - 600"
RS-IL03WF FIXED SHORT FOCUS LENS	PROJECTION DISTANCE	6.2 - 159.1 ft. (1.9 - 48.5 m) / 100": 15.4 - 26.3 ft. (4.7 - 8.0 m)	
	THROW RATIO	2.2:1 - 3.72:1	
	PROJECTION LENS	F2.0 / f= 12.8 mm	
	LENS SHIFT	Vertical= ±5% / Horizontal ±2%	
	ZOOM	Fixed	
	FOCUS	Powered	
	SCREEN SIZE	40" - 300"	
	PROJECTION DISTANCE	2.3 - 17.1 ft. (0.7 - 5.2 m) / 100": 5.7 ft. (1.7 m)	
	THROW RATIO	0.8:1	

Specifications in RED are TBD.

All specifications and availability are subject to change without prior notice.

Canon is a registered trademark of Canon Inc.

Effective: January 2012