

PRODUCT NAME	REALiS SX7 Mark II
ITEM CODE	4233B002
UPC CODE	013803119404



Suggested List Price:

\$6,999.99

FEATURES

- **Native SXGA+ Resolution (1400 x 1050)** - Supports wide screen computer displays
- **LCOS Technology** - High image quality and reliability
- **AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **4000 Lumens** - Bright, crisp images
- **1.7x Powered Zoom Lens** - Genuine Canon Optics
- **Short Throw Distance** - Project a 100" screen from only 9.8 feet away
- **Photo Image Mode** - Make precise adjustments to ensure optimum color accuracy
- **Adobe RGB and sRGB** - Exceptional color matching of photographic images
- **Advanced Color Management System** - 6-axis color adjustment
- **Auto Setup** - Automatic input signal and keystone correction
- **Guidance Functions** - On screen help provides easy, step-by-step operation
- **Off and Go** - Internal fan makes it possible to unplug the projector and go
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired*

* Based on availability, for complete details contact your Canon sales representative

CONTENTS OF KIT

- **REALiS SX7 Mark II Projector**
- **Power Cable**
- **DVI-VGA Computer Cable**
- **Component Video Cable**
- **Lens Cap**
- **Remote Control (with AAA batteries)**
- **Soft Carrying Case**
- **Warranty Card**

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
2396B001	RS-LP04 REPLACEMENT LAMP	579.00
3095B001	RS-CL07 CEILING MOUNT	999.00
3096B001	RS-CL08 CEILING EXTENSION : (16" - 24")	379.00
3097B001	RS-CL09 CEILING EXTENSION : (24" - 39")	399.00
7502A001	LV-CA29 DVI-D CABLE	69.00
0610B001	RS-CA01 RS-232C CABLE (9.8")	60.00
1025V632	RS-232C CONTROL CABLE (18")	10.00
1261V591	T-WC070 WIDE CONVERTER LENS	1,499.00
1332V132	REALiS PROJECTOR CASE	269.00

PACKAGING INFORMATION

PROJECTOR	H x W x D	WEIGHT
REALiS SX7 Mark II	15.4 x 19.8 x 10.7 in (392 x 502 x 272 mm)	19.2 lbs (8.7 kg)

SPECIFICATIONS

BASIC	IMAGING DEVICE	0.7" Reflective LCD Panels (LCOS x 3)	
	ASPECT RATIO	4:3	
	NATIVE RESOLUTION	SXGA+ (1400 x 1050)	
	BRIGHTNESS	4000 Lumens	
	UNIFORMITY	88%	
	CONTRAST	1000:1	
	KEystone	VERTICAL	+/- 20 degrees (Auto/Manual)
	HORIZONTAL	+/- 20 degrees (Manual)	
OPTICS	PROJECTION LENS	F1.85 - 2.5, f=21.7 - 35.8mm	
	LENS OFFSET	9:1, Fixed	
	ZOOM	1.7x Powered, 12x Digital zoom	
	FOCUS	Powered	
	SCREEN SIZE	40" - 300"	
	PROJECTION DISTANCE COVERAGE	3.9 - 29.5 ft (1.2 - 9.m) 100": 9.8 - 16.1 ft (3.0 - 4.9m)	
	THROW RATIO	1.46 - 2.43:1	
IMAGE ADJUSTMENTS	IMAGE MODE	Standard, Presentation, Movie, Adobe RGB, sRGB	
	COLOR ADJUST	Dynamic Gamma, 6-Axis (RGBCMY) Color Adjustment	
	WALL CORRECTION	Auto / Manual	
	IMAGE FLIP	None / Ceiling Mounted / Rear / Rear, Ceiling Mounted	
	TILT ANGLE	Adjusting foot up to 10 degrees	
INPUT SIGNALS	DIGITAL PC INPUT	SXGA+ / SXGA / WXGA / XGA / SVGA / VGA	
	SCANNING FREQUENCY	H:15-100 kHz, V:50-100 Hz	
	ANALOG PC INPUT	UXGA / SXGA+ / SXGA / WXGA / XGA / SVGA / VGA	
	SCANNING FREQUENCY	H:15-100 kHz, V:50-100 Hz	
	DOT CLOCK	170MHz or less	
	VIDEO INPUT	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
	COMPONENT INPUT	1080i / 1035i / 720p / 576p / 576i / 480p / 480i	
	DIGITAL VIDEO INPUT	1080i / 1035i / 720p / 576p / 480p	
	TERMINALS	INPUT	DVI-I 29PIN
D-SUB 15PIN			Analog PC Input x 2
RCA			Composite Video Input
OUTPUT		STEREO MINI-JACK	Stereo Audio Input x 3
		D-SUB 15PIN	Analog PC output
CONTROL		STEREO MINI-JACK	Stereo Audio Output x 1
		RS-232	D-sub 9pin
LAMP	BUILT-IN SPEAKER	1W (Mono)	
	TYPE	275W NSH (AC)	
REMOTE CONTROL	LAMP LIFE (NORMAL/QUIET)	2000 / 3000 Hours	
	SENSOR	Wireless Infrared, Front/Back	
RATINGS	MOUSE CONTROL	Mouse Control Receiver (USB)	
	FAN NOISE (NORMAL/QUIET)	35/31 dB	
	POWER	CONSUMPTION (NORMAL/QUIET/STANDBY)	360W / 290W / 7W
		VOLTAGE	AC100 to 240V, 50/60Hz
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C)
		STORAGE	-22° to 104° F (-30° to 60° C), 5%RH ~ 90%RH
DIMENSIONS (W x D x H)	10.5" x 13.2" x 4.5" (226mm x 336mm x 114mm)		
WEIGHT	10.6 lbs (4.8 kg)		

* All prices, specifications, and availabilities subject to change without prior notice.