

<b>PRODUCT NAME</b>	<b>REALiS WUX10 Mark II</b>
<b>ITEM CODE</b>	<b>4231B002</b>
<b>UPC CODE</b>	<b>013803119381</b>



**Suggested List Price:**

**\$12,999.00**

### FEATURES

- **Native WUXGA Resolution (1920 x 1200)** - Display true wide screen content in high resolution
- **LCOS Technology** - High image quality and reliability
- **AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **3200 Lumens** - Bright, crisp images
- **Newly Designed 1.5X Zoom Lens** - Genuine Canon Optics
- **Photo Mode** - Make precise adjustments to ensure optimum color accuracy
- **10:0 Lens Offset** - Minimizes the need for keystone correction
- **Advanced Color Management System** - 6-axis color adjustment
- **Deep Color Ver. 1.3 HDMI Input** - Supports full 1080p high definition signal
- **Network Ready RJ-45 Port** - Manage and control multiple projectors from a networked pc
- **Auto Setup** - Automatic input signal and keystone correction
- **Guidance Functions** - On screen help provides easy, step-by-step operation
- **Off and Go** - Internal fan makes it possible to unplug the projector and go
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired\*

\* Based on availability, for complete details contact your Canon sales representative

### CONTENTS OF KIT

- REALiS WUX10 Mark II Projector
- Power Cable
- DVI-VGA Computer Cable
- Component Video Cable
- Lens Cap
- Remote Control (with AAA batteries)
- Soft Carrying Case
- Warranty Card

### OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
2396B001	RS-LP04 REPLACEMENT LAMP	579.00
3095B001	RS-CL07 CEILING MOUNT	999.00
3096B001	RS-CL08 CEILING EXTENSION : (16" - 24")*	379.00
3097B001	RS-CL09 CEILING EXTENSION : (24" - 39")*	399.00
7502A001	LV-CA29 DVI-D CABLE	69.00
1332V132	REALiS PROJECTOR CASE	269.00

\* Extension for RS-CL07 Ceiling Mount

### PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
REALiS WUX10 Mark II	15.4 x 19.8 x 10.5 in (391 x 503 x 267 mm)	18.38 lbs (8.24 kg)

### SPECIFICATIONS

<b>BASIC</b>	<b>IMAGING DEVICE</b>	0.7" Reflective LCD Panels (LCOS x 3)		
	<b>ASPECT RATIO</b>	16:10		
	<b>NATIVE RESOLUTION</b>	WUXGA (1920 x 1200)		
	<b>BRIGHTNESS</b>	3200 Lumens		
	<b>UNIFORMITY</b>	88%		
	<b>CONTRAST</b>	1000:1		
	<b>VERTICAL KEYSTONE</b>	+/- 20 degrees (Auto/Manual)		
<b>OPTICS</b>	<b>PROJECTION LENS</b>	F1.85 - 2.65, f=21.8 - 31.9mm		
	<b>LENS OFFSET</b>	10:0, Fixed		
	<b>ZOOM</b>	1.5x Powered, 12x Digital zoom		
	<b>FOCUS</b>	Powered		
	<b>SCREEN SIZE</b>	40" - 300"		
	<b>PROJECTION DISTANCE COVERAGE</b>	3.9 - 29.9 ft (1.2 - 9.1m) 100°: 9.8 - 16.1 ft. (3.0 - 4.9m)		
	<b>THROW RATIO</b>	1.48 - 2.18:1		
<b>IMAGE ADJUSTMENTS</b>	<b>IMAGE MODE</b>	Standard, Presentation, Movie, sRGB, Photo		
	<b>COLOR ADJUST</b>	Dynamic Gamma, 6-Axis (RGBCMY) Color Adjustment		
	<b>WALL CORRECTION</b>	Auto / Manual		
	<b>IMAGE FLIP</b>	None / Ceiling Mounted / Rear / Rear, Ceiling Mounted		
<b>INPUT SIGNALS</b>	<b>TILT ANGLE</b>	Adjusting foot up to 10 degrees		
	<b>DIGITAL PC INPUT</b>	WUXGA / UXGA / WSXGA+ / SXGA+ / WSXGA / SXGA / WXGA / XGA / SVGA / VGA		
	<b>SCANNING FREQUENCY</b>	H:15-75 kHz, V:50-85 Hz		
	<b>ANALOG PC INPUT</b>	WUXGA / UXGA / WSXGA+ / SXGA+ / WSXGA / SXGA / WXGA / XGA / SVGA / VGA		
	<b>SCANNING FREQUENCY</b>	H:15-75 kHz, V:50-85 Hz		
	<b>DOT CLOCK</b>	170MHz or less		
	<b>VIDEO INPUT</b>	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N		
	<b>COMPONENT INPUT</b>	1080p / 1080i / 1035i / 720p / 576p / 576i / 480p / 480i		
	<b>DIGITAL VIDEO INPUT</b>	HDMI: 1080p / 1080i / 1035i / 720p / 576p / 480p		
	<b>TERMINALS</b>	<b>INPUT</b>	<b>DVI-I 29PIN</b>	Digital PC input / Analog PC input / Digital Video input
			<b>HDMI</b>	Version 1.3 Deep Color / Digital Video Input
<b>D-SUB 15PIN</b>			Analog PC Input x 1	
<b>RCA</b>			Composite Video Input	
<b>STEREO MINI-JACK</b>			Stereo Audio Input x 3	
<b>OUTPUT</b>		<b>D-SUB 15PIN</b>	N/A	
		<b>STEREO MINI-JACK</b>	Stereo Audio Output x 1	
<b>CONTROL</b>		<b>RS-232</b>	D-sub 9pin	
		<b>RJ-45</b>	Yes	
<b>BUILT-IN SPEAKER</b>		1W (Mono)		
<b>LAMP</b>	<b>TYPE</b>	275W NSH (AC)		
	<b>LAMP LIFE (NORMAL/QUIET)</b>	2000 / 3000 Hours		
<b>REMOTE CONTROL</b>	<b>SENSOR</b>	Wireless Infrared, Front/Back		
<b>RATINGS</b>	<b>FAN NOISE (NORMAL/QUIET)</b>		35/31 dB	
	<b>POWER</b>	<b>CONSUMPTION (NORMAL/QUIET/STANDBY)</b>	400W / 330W / 11W	
		<b>VOLTAGE</b>	AC100 to 240V, 50/60Hz	
	<b>TEMPERATURE</b>	<b>OPERATING</b>	41° to 95° F (5° to 35° C)	
		<b>STORAGE</b>	-22° to 104° F (-30° to 60° C), 5%RH ~ 90%RH	
	<b>DIMENSIONS (W x D x H)</b>		11.2 x 13.2 x 4.5 in (284 x 336 x 114 mm)	
	<b>WEIGHT</b>		10.9 lbs (4.94 kg)	

\* All prices, specifications, and availabilities subject to change without prior notice.