

PRODUCT NAME	LV-7490
ITEM CODE	5315B002
UPC CODE	013803137088



FEATURES

- **Native XGA Resolution (1024 x 768)** - Display laptops and monitors
- **4000 Lumens High Brightness** - Bright, sharp images
- **Long Lamp Life** - Up to 6000 hours of usage in quiet mode
- **Long Filter Life** - Up to 5500 hours in Eco mode
- **Auto Setup Function** - Execute the three auto setting functions of auto input, auto keystone, and auto PC with a push of a button
- **Computer Sync** - Projector automatically syncs with your computer when an input signal is detected
- **Closed Captioning** - Display closed captioning information
- **Wall Color Correction** - Include color correction for even whiteboards
- **10-Watt Speakers** - Clearly hear audio in large rooms
- **Network Connectivity** - Built in RJ-45 port for easy remote management
- **Easy Access Lamp** - Easily replace the lamp when the projector is installed on the ceiling
- **Quiet Operation** - As low as 29 dB
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired*

CONTENTS OF KIT

- **LV-7490 Projector**
- **(LV-RC03) Remote Control** (with AAA batteries)
- **Lens Cap** (with strap)
- **VGA-VGA Computer Cable**
- **CD-ROM**
- **AC Power Cord**
- **Quick Start Guide**

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION
5322B001	LV-LP34 REPLACEMENT LAMP
5325B001	LV-CL17 PROJECTOR ATTACHMENT
5326B001	LV-CL18 CEILING ATTACHMENT
5327B001	LV-CL19 HIGH CEILING ATTACHMENT
9270A001	LV-CA32 COMPONENT CABLE
5330B001	LV-RC03 PROJECTOR REMOTE CONTROL

PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
LV-7490	00.0 x 00.0 x 00.0 in (000 x 000 x 000 mm)	00.00 lbs (0.00 kg)

SPECIFICATIONS

BASIC	IMAGING DEVICE	0.63" Active Matrix x 3 with MLA	
	ASPECT RATIO	4 : 3	
	NATIVE RESOLUTION	XGA (1024 x 768)	
	BRIGHTNESS	4000 Lumens	
	UNIFORMITY	85%	
	CONTRAST	2000:1	
	AUTO IRIS	No	
	VERTICAL KEYSTONE	+/- 30 degrees (Auto/Manual)	
OPTICS	PROJECTION LENS	F1.6 - 1.76, f=22.3 - 26.8 mm	
	LENS OFFSET	9:1	
	ZOOM	1.2x Zoom (Manual)	
	FOCUS	Manual	
	SCREEN SIZE	40" - 300"	
	PROJECTION DISTANCE COVERAGE	4.59 - 41.66 ft. (1.4 - 12.7 m)	
IMAGE ADJUSTMENTS	IMAGE MODE	Presentation, Standard, High Contrast, Cinema, Blackboard (Green), Colorboard, User 1-4	
	IMAGE FLIP	Ceiling, Rear, Rear-Ceiling, Upwards, Downwards	
	TILT ANGLE	Adjusting foot up to 10 degrees	
IMAGE SIGNAL	ANALOG PC INPUT	WUXGA / UXGA / WSZGA+ / SXGA+ / SXGA / WXGA+ / WXGA / XGA / SVGA / VGA / MAC	
	SCANNING FREQUENCY	H:15-100 kHz, V:50-100 Hz	
	DOT CLOCK	TBD	
	COMPOSITE / S-VIDEO INPUT	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N / PAL-60	
TERMINALS	INPUT	MINI D-SUB 15PIN	Analog RGB / Component video / S-video input
		MINI D-SUB 15PIN	Analog RGB input
		RCA	Composite Video input
		MINI DIN4	S-Video input
		MINI-JACK	Stereo Audio input x 2
		MINI-JACK	Mic/Stereo Audio input
	OUTPUT	MINI-JACK	Stereo Audio output
	CONTROL	D-SUB 9PIN	RS-232C
		NETWORK	RJ-45
	BUILT-IN SPEAKER		10W (Mono)
LAMP	TYPE	245W UHP (AC)	
	LAMP LIFE (NORMAL/QUIET)	3000 / 5000 Hours	
	LAMP POWER (NORMAL / Eco 1/ Eco 2)	245 / 170 / 136 W	
REMOTE CONTROL	SENSOR	Wireless Infrared, Front	
	FAN NOISE (QUIET / NORMAL)	29 / 35dB	
RATINGS	POWER	VOLTAGE	AC100 to 240V, 50/60Hz
		100V CONSUMPTION	322W / 226W / 184W / 121W
		120V CONSUMPTION	386.4W / 271.2W / 220.8W / 134.4W
		100V STANDBY CONSUMPTION	6.2W / 0.5W
		120V STANDBY CONSUMPTION	7.44W / 0.6W
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C)
		STORAGE	14° to 140° F (-10° to 60° C), 5%RH - 90%RH
	DIMENSIONS (W x D x H)		13.78" x 10.02" x 3.44"
WEIGHT		7.28 lbs	