

Voluntary Product Accessibility Template (VPAT)

Name of Product: Canon DR-10CII

Date: February 17, 2017

Note: This document was prepared based on normal walk-up functionality. It does not include maintenance and troubleshooting procedures. **The information contained in this document is proprietary information and is not for reproduction, publication or manipulation in any way or form.** This template addresses a multitude of DR-X10CII features; however, any specific inquiries should be made to the Canon Government Marketing Representative.

The rules below refer to the Electronic and Information Technology Accessibility Standards (covered by Section 508 of the Rehabilitation Acts of 1998) issued by the Architectural and Transportation Compliance Board. Comments in the “Supporting Features” column are based on the Information Technology Industry Council’s suggested language for use when filling out the Voluntary Product Accessibility Template. The Remarks and Explanations column provides additional information on the evaluation results, and explains the standard functions of the **Canon DR-X10CII** that can accommodate users with disabilities.

Summary Table Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
Section 1194.21 Software Applications and Operating Systems	Supports with exceptions*	
Section 1194.22 Web-based internet information and applications	Not applicable	
Section 1194.23 Telecommunications Products	Not applicable	
Section 1194.24 Video and Multi-media Products	Not applicable	
Section 1194.25 Self-Contained, Closed Products	Supports with exception*	
Section 1194.26 Desktop and Portable Computers	Not applicable	
Section 1194.31 Functional Performance Criteria	Supports with exception*	
Section 1194.41 Information, documentation	Supports with exception *	

*Please refer to the following pages for detailed information on supporting features and exceptions.

Section 1194.21 Software Applications and Operating Systems - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) When software is designed to run on a system that has a keyboard, product functions shall be executable from keyboard where the function itself or the result of performing a function can be discerned textually.	Supports	
(b) Applications shall not disrupt or disable activated features of other products that are identified as accessibility features, where those features are developed and documented according to industry standards. Applications also shall not disrupt or disable activated features of any operating system that are identified as accessibility features where the application programming interface for those accessibility features has been documented by the manufacturer of the operating system.	Supports	
(c) A well-defined on-screen indication of the current focus shall be provided that moves among interactive interface elements as the input focus changes. The focus shall be programmatically exposed so that Assistive Technology can track focus and focus changes.	Supports	
(d) Sufficient information about a user interface element including the identity, operation and state of the element shall be available to Assistive Technology. When an image represents a program element, the information conveyed by the image must also be available in text.	Supports with exceptions	Brightness and Contrast control in the driver setting are conveyed by image only.
(e) When bitmap images are used to identify controls, status indicators, or other programmatic elements, the meaning assigned to those images shall be consistent throughout an application's performance.	Supports	
(f) Textual information shall be provided through operating system functions for displaying text. The minimum information that shall be made available is text content, text input caret location, and text attributes.	Supports	
(g) Applications shall not override user selected contrast and color selections and other individual display attributes.	Supports	
(h) When animation is displayed, the information shall be displayable in at least one non-animated presentation mode at the option of the user.	Not applicable	The driver/ utility software does not utilize animation.
(i) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Not applicable	
(j) When a product permits a user to adjust color and contrast settings, a variety of color selections capable of producing a range of contrast levels shall be provided.	Not applicable	The product does not permit the user to adjust color and contrast settings.
(k) Software shall not use flashing or	Not applicable	The driver/ utility software does

VPAT (DR-X10CII)

<p>blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.</p>		<p>not have a flash or blink frequency greater than 2Hz and lower than 55Hz.</p>
<p>(l) When electronic forms are used, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.</p>	<p>Supports with exceptions</p>	<p>Brightness/contrast control and gamma setting in the driver setting screen are conveyed by image only.</p>

Section 1194.25 Self-Contained, Closed Products - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive	Supports with compatible AT.	Assistive Technology may be required for visually disabled users; however, in such cases it is assumed that AT will already be running on the user's PC.
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Not applicable	
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with Section 1194.23 (k) (1) through (4).	Supports with exception	See below (k)(1)-(k)(4) for more details.
(k)(1) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be tactilely discernible without activating the controls or keys.	Supports	All keys are tactilely discernible.
(k)(2) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be operable with one hand and shall not require tight grasping, pinching, twisting of the wrist. The force required to activate controls and keys shall be 5 lbs. (22.2N) maximum.	Supports with exception	Opening the upper unit requires a force greater than 5 lbs (22.2N).
(k)(3) Products which have mechanically operated controls or keys shall comply with the following: If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character.	Not applicable	There is no key repeat.
(k)(4) Products which have mechanically operated controls or keys shall comply with the following: The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound.	Supports	
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable	There is no function to deliver voice output.
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user	Not applicable	There is no function to deliver voice output.

VPAT (DR-X10CII)

selectable. A function shall be provided to automatically reset the volume to the default level after every use.		
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Not applicable	
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	The product does not permit the user to adjust color and contrast settings.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	The product does not flicker.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	Not applicable	Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility.
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	Not applicable	Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	Not applicable	Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	Not applicable	Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility.

Section 1194.31 Functional Performance Criteria - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for Assistive Technology used by people who are blind or visually impaired shall be provided.	Supports	
(b) At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged print output working together or independently, or support for Assistive Technology used by people who are visually impaired shall be provided.	Supports	
(c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided.	Supports	
(d) Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided.	Not applicable	There is no audio information.
(e) At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided.	Not applicable	There is no voice operated function.
(f) At least one mode of operation and information retrieval that does not require fine motor control or simultaneous actions and that is operable with limited reach and strength shall be provided.	Supports with exception	Action to open the upper unit only shall require higher than 5 lbs (22.2N) maximum.

Section 1194.41 Information, Documentation and Support		
Criteria	Supporting Features	Remarks and explanations
(a) Product support documentation available to end-users is available in alternate formats upon request, at no additional charge.	Supports.	Product support documentation will be provided upon request in electronic format, at no additional charge.
(b) End-users have access to a description of the accessibility and compatibility features of products in alternate formats and alternate methods upon request, at no additional charge.	Supports with exceptions.	An evaluation of the accessibility features of products will be provided upon request in electronic format, at no additional charge.
(c) Support services for products accommodate the communication needs of end-users with disabilities.	Supports.	Canon U.S.A., Inc. provides support services accommodating users with disabilities through OKCANON assistance, TTY support at (866) 251-3752. Canon otherwise available to U.S. federal government agencies through Federal Relay.

This document is for informational purposes only. This information is based on Canon’s current understanding of 36 CFR Part 1194 - Electronic and Information Technology Accessibility Standard and Section 508 of the Rehabilitation Act. It is not intended to address applicability of these laws to a particular end-user, customer, application or procurement.

All product design and specifications are subject to change. Some of the information may be based upon data collected or tests conducted on similar product modules.

The information in this Voluntary Product Accessibility Template (VPAT) should not be considered a contractual agreement by Canon. FURTHER, THE INFORMATION AND MATERIALS PROVIDED IN THIS VPAT ARE “AS IS” WITHOUT WARRANTIES OF ANY KIND, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. Canon does not warrant the accuracy and completeness of the information or materials in this VPAT. Canon may make changes to the information in this VPAT, or to the products described in this VPAT at any time, without notice.