

Voluntary Product Accessibility Template (VPAT)

Name of Product: Canon imageCLASS MF7280 System

Date: February 07, 2006

Note: This document was prepared based on normal walk-up functionality. It does not include maintenance and troubleshooting procedures. The information contained in this document is proprietary information and is not for reproduction, publication or manipulation in any way or form. This template addresses a multitude of Canon imageCLASS MF7280 features; however, any specific inquiries should be made to the Canon Government Marketing Representative.

The rules below refer to the Electronic and Information Technology Accessibility Standards (covered by Section 508 of the Rehabilitation Act of 1998) issued by the Architectural and Transportation Compliance Board. Comments in the “Supporting Features” column are based on the Information Technology Industry Council’s suggested language for use when filling out the Voluntary Product Accessibility Template. The Remarks and Explanations column provides additional information on the evaluation results, and explains the standard functions of the Canon imageCLASS MF7280 that can accommodate users with disabilities.

Voluntary Product Accessibility Template (Summary Table)

| Criteria | Supporting Features | Remarks and explanations |
|--|-----------------------------|---|
| Section 1194.21 Software Applications and Operating Systems | Supports. * | Printer Driver and Remote User Interface (Remote UI) evaluated. |
| Section 1194.22 Web-based Internet Information and Applications | Supports. * | Remote UI evaluated. |
| Section 1194.23 Telecommunications Products | Not Applicable. | |
| Section 1194.24 Video and Multi-media Products | Not Applicable. | |
| Section 1194.25 Self-Contained, Closed Products | Supports with exceptions. * | |
| Section 1194.26 Desktop and Portable Computer | Not Applicable. | |
| Section 1194.31 Functional Performance Criteria | Supports with exceptions. * | |
| Section 1194.41 Information, Documentation, and Support | Supports. * | |

*Please refer to the following pages for detailed information on supporting features and exceptions.

Voluntary Product Accessibility Template (Detailed Table)

Section 1194.21 Software Applications and Operating Systems

| Criteria | Supporting Features | Remarks and explanations |
|---|--|---|
| <p>(a) When software is designed to run on a system that has a keyboard, product functions shall be executable from a keyboard where the function itself or the result of performing a function can be discerned textually.</p> | <p>Supports [Printer Driver & Remote UI]</p> | <p>The Printer Driver and Remote UI allow the user to move through the software using the “Tab” and “Shift + Tab” keys. Operations may be executed using the “Enter” key.</p> <p>[Printer Driver] When used with the “Alt” key, the “Access Key” allows the user to jump directly to the desired location to adjust settings. Almost all settings can be accessed this way.</p> <p>[Remote UI] “Access Key” functionality as explained above not available.</p> |
| <p>(b) Applications shall not disrupt or disable activated features of other products that are identified as accessibility features, where those features are developed and documented according to industry standards. Applications also shall not disrupt or disable activated features of any operating system that are identified as accessibility features where the application programming interface for those accessibility features has been documented by the manufacturer of the operating system and is available to the product developer.</p> | <p>Supports.</p> | |
| <p>(c) A well defined on-screen indication of the current focus shall be provided that moves among interactive interface elements as the input focus changes. The focus shall be programmatically exposed so that Assistive Technology can track focus and focus changes.</p> | <p>Supports.</p> | |
| <p>(d) Sufficient information about a user interface element including the identity, operation and state of the element shall be available to Assistive Technology. When an image represents a program element, the information conveyed by the image must also be available in text.</p> | <p>Supports.</p> | |
| <p>(e) When bitmap images are used to identify controls, status indicators, or other programmatic elements, the meaning assigned to those images shall be consistent throughout an application's performance.</p> | <p>Supports.</p> | |
| <p>(f) Textual information shall be provided through operating system functions for displaying text. The minimum information that shall be made available is text content, text input caret location, and text attributes.</p> | <p>Supports.</p> | |

| | | |
|--|-------------------|---|
| (g) Applications shall not override user selected contrast and color selections and other individual display attributes. | Supports. | |
| (h) When animation is displayed, the information shall be displayable in at least one non-animated presentation mode at the option of the user. | Not applicable. | The Printer Driver does not use animation. |
| (i) Color-coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element. | Supports. | The Printer Driver does not use color-coding. |
| (j) When a product permits a user to adjust color and contrast settings, a variety of color selections capable of producing a range of contrast levels shall be provided. | Not applicable. | The product does not permit the user to adjust color and contrast settings. |
| (k) Software shall not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz. | Not applicable. | The Printer Driver does not have an element with a flash or blink. |
| (l) When electronic forms are used, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues. | Supports. | |
| (m) When a web page requires that an applet, plug-in or other application be present on the client system to interpret page content, the page must provide a link to a plug-in or applet that complies with 1194.21(a) through (l). | Not Applicable. | |
| (n) When electronic forms are designed to be completed on-line, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues. | Not Applicable. | |
| (o) A method shall be provided that permits users to skip repetitive navigation links. | Does not support. | |
| (p) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required. | Not Applicable. | |

Section 1194.22 Web-based Internet Information and Applications (Assessment for Remote UI)

| Criteria | Supporting Features | Remarks and explanations |
|--|----------------------------|---------------------------------|
| (a) A text equivalent for every non-text element shall be provided (e.g., via "alt", "longdesc", or in element content). | Supports. | |
| (b) Equivalent alternatives for any multimedia presentation shall be synchronized with the presentation. | Not Applicable. | |
| (c) Web pages shall be designed so that all information conveyed with color is also available without color, for example from context or markup. | Supports. | |
| (d) Documents shall be organized so they are readable without requiring an associated style sheet. | Not Applicable. | |
| (e) Redundant text links shall be provided for each active region of a server-side image map. | Not Applicable. | |
| (f) Client-side image maps shall be provided instead of server-side image maps except where the regions cannot be defined with an available geometric shape. | Not Applicable. | |
| (g) Row and column headers shall be identified for data tables. | Not Applicable. | |
| (h) Markup shall be used to associate data cells and header cells for data tables that have two or more logical levels of row or column headers. | Not Applicable. | |
| (i) Frames shall be titled with text that facilitates frame identification and navigation. | Not Applicable. | |
| (j) Pages shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz. | Not Applicable. | |
| (k) A text-only page, with equivalent information or functionality, shall be provided to make a web site comply with the provisions of this part, when compliance cannot be accomplished in any other way. The content of the text-only page shall be updated whenever the primary page changes. | Not Applicable. | |
| (l) When pages utilize scripting languages to display content, or to create interface elements, the information provided by the script shall be identified with functional text that can be read by Assistive Technology. | Not Applicable. | |

Section 1194.25 Self-Contained, Closed Products

| Criteria | Supporting Features | Remarks and explanations |
|--|---|---|
| (a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology. | Supports with exceptions. | The Remote UI provides alternative access to the Copy functions for users with some types of disabilities (through a third party screen reader, speech recognition software, etc.). |
| (b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required. | Supports through equivalent facilitation. | Although the Auto clear function has no alert warning with sound, if the user selected [0=OFF], there is no time limit. |
| (c) Where a product utilizes touch screens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4). | Supports with exceptions. | Refer to details in subsections 1194.23(k1) through 1194.23(k4) below. |
| (1194.23k-1) Product which have mechanically operated controls or keys, shall comply with the following: Controls and keys shall be tactilely discernible without activating the controls or keys. | Supports through equivalent facilitation. *Keys on the LCD panel are not tactilely discernible. To the best of Canon's knowledge, tactilely discernible LCD panels are a commercial impossibility at this time due to the very nature of LCD panels. | -All hard keys are tactilely discernible. A Braille Label Kit is available as an option. -The numeric keys can be tactilely discerned by a convex dot on the Number 5 key. -The Start and Stop keys are tactilely discernible by their unique shapes and sizes. |
| (1194.23k-2) Controls and keys shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate controls and keys shall be 5 lbs. (22.2 N) maximum. | Supports with exceptions. | Exceptions: -Removing / inserting cassettes, and opening the Stack Bypass Tray (power more than 22.2N needed). -Adjusting the display contrast (turning is required). |
| (1194.23k-3) If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character. | Supports through equivalent facilitation. | |
| (1194.23k-4) The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound. | Does not Support. | Operational results of key toggle controls or keys are only indicated on the LCD and LED. |
| (d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided. | Not Applicable. | |
| (e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime. | Not Applicable. | |
| (f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the | Not Applicable. | |

| | | |
|--|-----------------|---|
| environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use. | | |
| (g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element. | Supports. | |
| (h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided. | Not Applicable. | |
| (i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz. | Supports. | |
| (j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls. | Supports. | -Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility. |
| (j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor. | Supports. | -Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility. |
| (j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor. | Supports. | -Because the product is a desktop model, the position of the machine can be adjusted to accommodate users with varying degrees of mobility. |
| (j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane | Supports. | |

Section 1194.31 Functional Performance Criteria

| Criteria | Supporting Features | Remarks and explanations |
|---|--------------------------|---|
| (a) At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for Assistive Technology used by people who are blind or visually impaired shall be provided. | Supports with exception. | -When a screen reader or screen magnifier is used with the Remote UI, users who are blind can operate basic functions from a PC. -All hard keys are tactilely discernable. A Braille set is available as an option. -Operation status can be determined through audio tones that confirm key entry, error, and job done. -Automatic Document Feeder guarantees proper document placement. -Only copy functions addressed. |
| (b) At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged print output working together or independently, or support for Assistive Technology used by people who are visually impaired shall be provided. | Supports with exceptions | -When a screen reader or screen magnifier is used with the Remote UI, users who are visually impaired can operate basic functions from a PC. -Operation status can be determined through audio tones that confirm key entry, error, and job done. -Automatic Document Feeder guarantees proper document placement. -Only copy functions addressed. |
| (c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided. | Supports. | |
| (d) Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided. | Supports. | |
| (e) At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided. | Supports. | |
| (f) At least one mode of operation and information retrieval that does not require fine motor control or simultaneous actions and that is operable with limited reach and strength shall be provided. | Supports with exceptions | Exceptions: -Removing / inserting cassettes, and opening the Stack Bypass Tray (a force of more than 22.2N is needed). -Adjusting the display contrast (turning is required). |

Section 1194.41 Information, Documentation, and Support

| Criteria | Supporting Features | Remarks and explanations |
|--|--------------------------|---|
| (a) Product support documentation available to end-users is available in alternate formats upon request, at no additional charge. | Supports. | Product support documentation will be provided upon request in electronic format, at no additional charge. |
| (b) End-users have access to a description of the accessibility and compatibility features of products in alternate formats and alternate methods upon request, at no additional charge. | Supports with exceptions | An evaluation of the accessibility features of products will be provided upon request in electronic format, at no additional charge. |
| (c) Support services for products accommodate the communication needs of end-users with disabilities. | Supports. | Canon U.S.A., Inc. provides support services accommodating users with disabilities through OK CANON assistance, TTY support at (866) 251-3752. Canon otherwise available to U.S. federal government agencies through Federal Relay. |

This document is for informational purposes only. This information is based on Canon’s current understanding of 36 CFR Part 1194 - Electronic and Information Technology Accessibility Standards and Section 508 of the Rehabilitation Act. It is not intended to address applicability of these laws to a particular end-user, customer, application or procurement.

All product design and specifications are subject to change. Some of the information may be based upon data collected or tests conducted on similar product modules.

The information in this Voluntary Product Accessibility Template (VPAT) should not be considered a contractual agreement by Canon. FURTHER, THE INFORMATION AND MATERIALS PROVIDED IN THIS VPAT ARE “AS IS” WITHOUT WARRANTIES OF ANY KIND, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. Canon does not warrant the accuracy and completeness of the information or materials in this VPAT. Canon may make changes to the information in this VPAT, or to the products described in this VPAT at any time, without notice.