



ACCESS

NetFront™

NF3 for iR Series Web Access Software Function Specification Element/Attribute

Rev.1.0



NetFront™

NF3 for iR Series Web Access Software Function Specification Element/Attribute Rev.1.0

Created on Nov 1 , 2005

ACCESS Co., Ltd.

* The copyrights of all text and images included in this document belong to ACCESS CO., LTD.

* No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express prior written permission of ACCESS CO., LTD.

Altering the contents of this document and reproducing or transmitting the altered document are prohibited without the express prior written permission of ACCESS CO., LTD.

* Software specifications and other content in this document are subject to change without prior notice.

* The information described here may contain technical inaccuracies or typographical errors.

ACCESS CO., LTD assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.

Copyright © 2002-2005 ACCESS CO., LTD. All rights reserved

Table of Contents

1. HTML/XHTML.....	4
2. CSS.....	53
3. ECMAScript Properties/Methods.....	65
4. ECMAScript Statements.....	73
5. ECMAScript Operators.....	76
6. ECMAScript Types and Literals.....	79
7. DOM0 ECMAScript Binding.....	81
8. DOM Core Level1,2.....	86
9. DOM Event Level2.....	92
10. DOM HTML Level1,2.....	95

Chapter 1

HTML/XHTML

O: Supported

X: Not Supported

-: The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

** : The display might be different according to the installed font.

This document describes whether each feature is supported or not supported.

In the imageRUNNER(iR) series (hereafter Canon machine), the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

* "justify" and "char" are not supported for this attribute.

(none)	Cannot describe as A initial (default) value of the attribute. the result is dependent on the situation, or existence of the attribute matters, or depends on the image size, or the attribute is required. (* indicates "common attribute")
(preference)	Configurable according to the platform.
(script)	Script related attribute.
(n/a)	The attribute is not supported.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
The global structure of a document										
HyperText Markup Language										
	HTML		O	O	O	O	O	O		
		version	O	O	O	O	O	O	(none)	
		fragments	X	X	X	X	X	X	(n/a)	Browser vendor extension
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
The document head										
	HEAD		O	O	O	O	O	O		
		profile	O	X	O	O	O	X	(n/a)	It does not affect rendering
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	TITLE		O	O	O	O	O	O		
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	META		O	O	O	O	O	O		
		http-equiv	O	O	O	O	O	O	(none)	
		name	O	O	O	O	O	O	(none)	Can parse and retrieve the contents of name.
		content	O	O	O	O	O	O	(n/a)	Partial support with http-equiv The attribute content in element meta is supported if http-equiv is refresh, expires, pragma, cache-control, or Set-Cookie.
		scheme	O	X	O	X	O	X	(n/a)	It does not affect rendering
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	NEXTID		X	X	X	X	X	X		Obsolete Specification
		N	X	X	X	X	X	X	(n/a)	Obsolete Specification
The background sound										
	BGSOUND		X	X	X	X	X	X		i-mode extension
		balance	X	X	X	X	X	X	(n/a)	i-mode extension
		loop	X	X	X	X	X	X	(n/a)	i-mode extension
		src	X	X	X	X	X	X	(n/a)	i-mode extension
		volume	X	X	X	X	X	X	(n/a)	i-mode extension
		delay	X	X	X	X	X	X	(n/a)	i-mode extension
The document body										
	BODY		O	O	O	O	O	O		
		background	O	X	X	X	X	O	(preference)	
		text	O	X	X	X	X	O	(preference)	
		link	O	X	X	X	X	O	(preference)	
		vlink	O	X	X	X	X	O	(preference)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		alink	O	X	X	X	X	O	(preference)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		bgcolor	O	X	X	X	X	O	(preference)	
		onload	O	X	X	X	X	O	(script)	
		onunload	O	X	X	X	X	O	(script)	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		bgproperties	X	X	X	X	X	O	(preference)	
		topmargin	X	X	X	X	X	O	(none)	
		leftmargin	X	X	X	X	X	O	(none)	
		bottommargin	X	X	X	X	X	O	(none)	
		rightmargin	X	X	X	X	X	O	(none)	
		scroll	X	X	X	X	X	O	"auto"	
		nowrap	X	X	X	X	X	X	(n/a)	Browser vendor extension
		marginwidth	X	X	X	X	X	O	(none)	
		marginheight	X	X	X	X	X	O	(none)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
The grouping elements	DIV		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		nowrap	X	X	X	X	X	X	(n/a)	Browser vendor extension	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	xmlns	X	X	O	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
	SPAN			O	X	O	O	O			
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			style	O	X	X	O	O	O	(none)*	
			onclick	O	X	X	O	X	O	(script)	
			ondblclick	O	X	X	O	X	X	(n/a)	
			onmousedown	O	X	X	O	X	O	(script)	
			onmouseup	O	X	X	O	X	O	(script)	
onmouseover			O	X	X	O	X	O	(script)		
onmousemove			O	X	X	O	X	X	(script)		
onmouseout			O	X	X	O	X	O	(script)		
onkeypress			O	X	X	O	X	X	(n/a)		
onkeydown			O	X	X	O	X	X	(n/a)		
onkeyup			O	X	X	O	X	X	(n/a)		
xml:lang			X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
xmlns			X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
The headings			O	O	O	O	O				
	H1	id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.	
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
	H2			O	O	O	O	O			
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			style	O	X	X	O	O	O	(none)*	
			align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
			onclick	O	X	X	O	X	O	(script)	
			ondblclick	O	X	X	O	X	X	(n/a)	
			onmousedown	O	X	X	O	X	O	(script)	
onmouseup			O	X	X	O	X	O	(script)		
onmouseover			O	X	X	O	X	O	(script)		
onmousemove			O	X	X	O	X	X	(script)		
onmouseout			O	X	X	O	X	O	(script)		
onkeypress			O	X	X	O	X	X	(n/a)		
onkeydown			O	X	X	O	X	X	(n/a)		
onkeyup			O	X	X	O	X	X	(n/a)		
xml:lang			X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.			
H3			O	O	O	O	O				
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.	
		onclick	O	X	X	O	X	O	(script)		
ondblclick	O	X	X	O	X	X	(n/a)				

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	H4		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	H5		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
		onclick	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks		
		ondblclick	O	X	X	O	X	X	(n/a)			
		onmousedown	O	X	X	O	X	O	(script)			
		onmouseup	O	X	X	O	X	O	(script)			
		onmouseover	O	X	X	O	X	O	(script)			
		onmousemove	O	X	X	O	X	X	(script)			
		onmouseout	O	X	X	O	X	O	(script)			
		onkeypress	O	X	X	O	X	X	(n/a)			
		onkeydown	O	X	X	O	X	X	(n/a)			
		onkeyup	O	X	X	O	X	X	(n/a)			
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		H6		O	O	O	O	O				
				id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
				class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
				lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
				dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
				title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
				style	O	X	X	O	O	O	(none)*	
				align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
onclick	O			X	X	O	X	O	(script)			
ondblclick	O			X	X	O	X	X	(n/a)			
onmousedown	O			X	X	O	X	O	(script)			
onmouseup	O			X	X	O	X	O	(script)			
onmouseover	O			X	X	O	X	O	(script)			
onmousemove	O			X	X	O	X	X	(script)			
onmouseout	O			X	X	O	X	O	(script)			
onkeypress	O			X	X	O	X	X	(n/a)			
onkeydown	O			X	X	O	X	X	(n/a)			
onkeyup	O			X	X	O	X	X	(n/a)			
xml:lang	X			X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
xmlns	X			X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
Author Information	ADDRESS		O	X	O	O	O	**	Display differ depending on the installed fonts.			
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
		style	O	X	X	O	O	O	(none)*			
		onclick	O	X	X	O	X	O	(script)			

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
The COMMENT element	COMMENT		X	X	X	X	X	X		Obsolete Specification
Text										
Bi-directional override	BDO		O	X	X	O	X	X		
		lang	O	X	X	X	X	X	(n/a)	
		dir	O	X	X	O	X	X	(n/a)	
The phrase elements	EM		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	STRONG		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	DFN		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	CODE		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	SAMP		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	KBD		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	VAR		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	CITE		O	X	O	O	O	**		Display differ depending on the installed fonts.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
ABBR			O	X	O	O	O			
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
onkeypress	O	X	X	O	X	X	(n/a)			
onkeydown	O	X	X	O	X	X	(n/a)			
onkeyup	O	X	X	O	X	X	(n/a)			
xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
ACRONYM			O	X	O	O	O			
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.			
Quotations	BLOCKQUOTE		O	O	O	O	O	O			
		cite	O	X	O	O	O	O	(none)		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		Q		O	X	O	O	O			
			cite	O	X	O	O	O	O	(none)	
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
	xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
	xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
Subscripts and superscripts	SUB		O	X	X	O	X	O			
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	X	O	(none)*		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
			xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	SUP		O	X	X	O	X	O			
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Lines and Paragraphs	P		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		align	O	O	X	X	X	O	(none)	"justify" are not supported for this attribute.
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	BR		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		style	O	X	X	O	O	O	(none)*		
		clear	O	O	X	X	X	O	(none)		
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		PRE		O	O	O	O	O			
			width	O	X	X	X	X	X	(n/a)	
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			style	O	X	X	O	O	O	(none)*	
			onclick	O	X	X	O	X	O	(script)	
			ondblclick	O	X	X	O	X	X	(n/a)	
			onmousedown	O	X	X	O	X	O	(script)	
			onmouseup	O	X	X	O	X	O	(script)	
			onmouseover	O	X	X	O	X	O	(script)	
			onmousemove	O	X	X	O	X	X	(script)	
			onmouseout	O	X	X	O	X	O	(script)	
			onkeypress	O	X	X	O	X	X	(n/a)	
			onkeydown	O	X	X	O	X	X	(n/a)	
			onkeyup	O	X	X	O	X	X	(n/a)	
			cols	X	X	X	X	X	X	(n/a)	Resource required and rarely used
			wrap	X	X	X	X	X	X	(n/a)	Resource required and rarely used
			xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		NOBR		X	X	X	X	X		Browser vendor extension	
		WBR		X	X	X	X	X		Browser vendor extension	
	Marking document changes		INS	O	X	X	O	X	O		
			cite	O	X	X	O	X	O	(n/a)	It does not affect rendering
			datetime	O	X	X	O	X	X	(n/a)	It does not affect rendering
			id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
dir			O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
title			O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
style			O	X	X	O	X	O	(none)*		
onclick			O	X	X	O	X	O	(script)		
ondblclick			O	X	X	O	X	X	(n/a)		
onmousedown	O	X	X	O	X	O	(script)				
onmouseup	O	X	X	O	X	O	(script)				

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
	DEL			O	X	X	O	X	O		
			cite	O	X	X	O	X	O	(none)	It does not affect rendering
			datetime	O	X	X	O	X	X	(n/a)	It does not affect rendering
			id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			style	O	X	X	O	X	O	(none)*	
			onclick	O	X	X	O	X	O	(script)	
			ondblclick	O	X	X	O	X	X	(n/a)	
			onmousedown	O	X	X	O	X	O	(script)	
			onmouseup	O	X	X	O	X	O	(script)	
			onmouseover	O	X	X	O	X	O	(script)	
			onmousemove	O	X	X	O	X	X	(script)	
			onmouseout	O	X	X	O	X	O	(script)	
			onkeypress	O	X	X	O	X	X	(n/a)	
			onkeydown	O	X	X	O	X	X	(n/a)	
	onkeyup	O	X	X	O	X	X	(n/a)			
xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.			
xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.			
Text	LISTING		X	X	X	X	X	X		Browser vendor extension	
	PLAINTEXT		X	O	X	X	X	O			
	XMP		X	X	X	X	X	X		Browser vendor extension	
The BLINK element	BLINK		X	X	X	X	X	O			
The MARQUEE element	MARQUEE		X	X	X	X	X	O			
		behavior	X	X	X	X	X	O	"scroll"		
		bgcolor	X	X	X	X	X	O	(none)		
		direction	X	X	X	X	X	O	"left"		
		height	X	X	X	X	X	O	(none)		
		hspace	X	X	X	X	X	O	(none)		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		loop	X	X	X	X	X	O	If the value of the behavior attribute is "slide", and the loop attribute is omitted, then it scrolls only one time. Otherwise, if the loop attribute is specified, then it scrolls continuously.	
		scrollamount	X	X	X	X	X	O	(none)	
		scrolldelay	X	X	X	X	X	O	(none)	
		truespeed	X	X	X	X	X	X	(n/a)	Browser vendor extension
		vspace	X	X	X	X	X	O	(none)	
		width	X	X	X	X	X	O	(none)	
The ruby elements	RUBY		X	X	X	O	X	X		
		name	X	X	X	O	X	X	(n/a)	
	RB		X	X	X	O	X	X		
	RT		X	X	X	O	X	X		
		name	X	X	X	O	X	X	(n/a)	
	RP		X	X	X	O	X	X		
Lists										
Unordered lists	UL		O	O	O	O	O	O		
		type	O	X	X	X	X	O	(none)	
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:ins	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
ordered lists	OL		O	O	O	O	O	O		
		type	O	X	X	X	X	O	(none)	
		start	O	X	X	X	O	O	*1*	
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		seqnum	X	X	X	X	X	X	(n/a)	Browser vendor extension
xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
list items	LI		O	O	O	O	O	O		
		type	O	X	X	X	X	O	(none)	
		value	O	X	X	X	O	O	""	
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
Definition lists	DL		O	O	O	O	O	O			
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		DT		O	O	O	O	O			
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
			style	O	X	X	O	O	O	(none)*	
			onclick	O	X	X	O	X	O	(script)	
			ondblclick	O	X	X	O	X	X	(n/a)	
			onmousedown	O	X	X	O	X	O	(script)	
			onmouseup	O	X	X	O	X	O	(script)	
			onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
	DD		O	O	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
The DIR and MENU elements	DIR		O	O	X	X	X	O		
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		onclick	O	X	X	X	X	O	(script)	
		ondblclick	O	X	X	X	X	X	(n/a)	
		onmousedown	O	X	X	X	X	O	(script)	
		onmouseup	O	X	X	X	X	O	(script)	
		onmouseover	O	X	X	X	X	O	(script)	
		onmousemove	O	X	X	X	X	X	(script)	
		onmouseout	O	X	X	X	X	O	(script)	
		onkeypress	O	X	X	X	X	X	(n/a)	
		onkeydown	O	X	X	X	X	X	(n/a)	
		onkeyup	O	X	X	X	X	X	(n/a)	
		xml:lang	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
	MENU		O	O	X	X	X	O		
		compact	O	X	X	X	X	X	(n/a)	No Browser Support it
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		onclick	O	X	X	X	X	O	(script)	
		ondblclick	O	X	X	X	X	X	(n/a)	
		onmousedown	O	X	X	X	X	O	(script)	
		onmouseup	O	X	X	X	X	O	(script)	
		onmouseover	O	X	X	X	X	O	(script)	
		onmousemove	O	X	X	X	X	X	(script)	
		onmouseout	O	X	X	X	X	O	(script)	
		onkeypress	O	X	X	X	X	X	(n/a)	
		onkeydown	O	X	X	X	X	X	(n/a)	
		onkeyup	O	X	X	X	X	X	(n/a)	
		xml:lang	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Tables										
The TABLE element	TABLE		O	X	O	O	O	O		
		summary	O	X	O	O	O	X	(n/a)	It does not affect rendering
		align	O	X	X	X	X	O	(none)	
		width	O	X	X	O	X	O	(none)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		bgcolor	O	X	X	X	X	O	(none)	
		frame	O	X	X	O	X	O	(none)	Resource required and rarely used
		rules	O	X	X	O	X	O	(none)	
		border	O	X	X	O	X	O	(none)	
		cellspacing	O	X	X	O	X	O	(none)	
		cellpadding	O	X	X	O	X	O	"1"	
		background	X	X	X	X	X	O	"transparent"	
		bordercolor	X	X	X	X	X	O	(none)	
		bordercolordark	X	X	X	X	X	X	(n/a)	Browser vendor extension
		bordercolorlight	X	X	X	X	X	X	(n/a)	Browser vendor extension
		cols	X	X	X	X	X	X	(n/a)	Browser vendor extension
		height	X	X	X	X	X	O	(none)	Browser vendor extension
		hspace	X	X	X	X	X	X	(n/a)	Browser vendor extension
		vspace	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Table Captions	CAPTION		O	X	O	O	O	O		width:% specified in the caption attribute is not supported.
		align	O	X	X	X	X	O	(none)	In the case of left, the vertical coordinate is the same as top and the horizontal coordinate is left-aligned in the table width. In the case of right, the vertical coordinate is the same as top and the horizontal coordinate is right-aligned in the table width.
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		valign	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Row groups	THEAD		O	X	X	O	X	O		
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		align	O	X	X	O	X	X	(n/a)	Resource reqired and rarely used
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	X	O	X	X	(n/a)	Resource reqired and rarely used
		bgcolor	X	X	X	X	X	O	(none)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	TFOOT		O	X	X	O	X	O		
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		align	O	X	X	O	X	X	(n/a)	Resource reqired and rarely used
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		valign	O	X	X	O	X	X	(n/a)	Resource required and rarely used	
		bgcolor	X	X	X	X	X	O	(none)		
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		xml:ns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		TBODY		O	X	X	O	X	O		
			id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	class		O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	lang		O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	dir		O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	title		O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	style		O	X	X	O	X	O	(none)*		
	onclick		O	X	X	O	X	O	(script)		
	ondblclick		O	X	X	O	X	X	(n/a)		
	onmousedown		O	X	X	O	X	O	(script)		
	onmouseup		O	X	X	O	X	O	(script)		
	onmouseover		O	X	X	O	X	O	(script)		
	onmousemove		O	X	X	O	X	X	(script)		
	onmouseout		O	X	X	O	X	O	(script)		
	onkeypress		O	X	X	O	X	X	(n/a)		
	onkeydown		O	X	X	O	X	X	(n/a)		
	onkeyup		O	X	X	O	X	X	(n/a)		
	align		O	X	X	O	X	X	(n/a)	Resource required and rarely used	
	char		O	X	X	O	X	X	(n/a)	No Browser Support it	
	charoff		O	X	X	O	X	X	(n/a)	No Browser Support it	
	valign		O	X	X	O	X	X	(n/a)	Resource required and rarely used	
	bgcolor		X	X	X	X	X	O	(none)		
	xml:lang		X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	xml:ns		X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	Column groups		COLGROUP		O	X	X	O	X	O	
			span	O	X	X	O	X	O	"1"	
			width	O	X	X	O	X	O	(none)	
			id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
class			O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
lang			O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
dir			O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
title			O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
style			O	X	X	O	X	O	(none)*		
onclick			O	X	X	O	X	X	(script)		
ondblclick			O	X	X	O	X	X	(n/a)		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onmousedown	O	X	X	O	X	X	(script)	
		onmouseup	O	X	X	O	X	X	(script)	
		onmouseover	O	X	X	O	X	X	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	X	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		align	O	X	X	O	X	X	(n/a)	Resource required and rarely used
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	X	O	X	O	"middle"	
		bgcolor	X	X	X	X	X	O	(none)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	COL		O	X	X	O	X	O		
		span	O	X	X	O	X	O	"1"	
		width	O	X	X	O	X	O	(none)	
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	X	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	X	(script)	
		onmouseup	O	X	X	O	X	X	(script)	
		onmouseover	O	X	X	O	X	X	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	X	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		align	O	X	X	O	X	X	(n/a)	Resource required and rarely used
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	X	O	X	O	"middle"	
		bgcolor	X	X	X	X	X	O	(none)	Browser vendor extension
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Table rows	TR		O	X	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		bgcolor	O	X	X	X	X	O	(none)	
		align	O	X	O	O	O	O	(none)	"justify" and "char" are not supported for this attribute.
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	O	O	O	O	"middle"	
		height	X	X	X	X	X	O	(none)	
		width	X	X	X	X	X	X	(n/a)	
		background	X	X	X	X	X	O	"transparent"	
		bordercolor	X	X	X	X	X	O	(none)	
		bordercolordark	X	X	X	X	X	X	(n/a)	Browser vendor extension
		bordercolorlight	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Table cells	TH		O	X	O	O	O	**		Display differ depending on the installed fonts.
		headers	O	X	O	O	O	X	(n/a)	It does not affect rendering
		scope	O	X	O	O	O	X	(n/a)	It does not affect rendering
		abbr	O	X	O	O	O	X	(n/a)	It does not affect rendering
		axis	O	X	O	O	O	X	(n/a)	It does not affect rendering
		rowspan	O	X	O	O	O	O	"1"	
		colspan	O	X	O	O	O	O	"1"	
		nowrap	O	X	X	X	X	O	(none)	
		width	O	X	X	X	X	O	(none)	
		height	O	X	X	X	X	O	(none)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		bgcolor	O	X	X	X	X	O	(none)	
		align	O	X	O	O	O	O	(none)	"justify" and "char" are not supported for this attribute.
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	O	O	O	O	"middle"	
		background	X	X	X	X	X	O	"transparent"	
		bordercolor	X	X	X	X	X	O	(none)	
		bordercolordark	X	X	X	X	X	X	(n/a)	Browser vendor extension
		bordercolorlight	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	TD		O	X	O	O	O	O		
		headers	O	X	O	O	O	X	(n/a)	It does not affect rendering
		scope	O	X	O	O	O	X	(n/a)	It does not affect rendering
		abbr	O	X	O	O	O	X	(n/a)	It does not affect rendering
		axis	O	X	O	O	O	X	(n/a)	It does not affect rendering
		rowspan	O	X	O	O	O	O	"1"	
		colspan	O	X	O	O	O	O	"1"	
		nowrap	O	X	X	X	X	O	(none)	
		width	O	X	X	X	X	O	(none)	
		height	O	X	X	X	X	O	(none)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		bgcolor	O	X	X	X	X	O	(none)	
		align	O	X	O	O	O	O	(none)	"justify" and "char" are not supported for this attribute.
		char	O	X	X	O	X	X	(n/a)	No Browser Support it
		charoff	O	X	X	O	X	X	(n/a)	No Browser Support it
		valign	O	X	O	O	O	O	"middle"	
		background	X	X	X	X	X	O	"transparent"	
		bordercolor	X	X	X	X	X	O	(none)	
		bordercolordark	X	X	X	X	X	X	(n/a)	Browser vendor extension
		bordercolorlight	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Links										
Anchor										
	A		O	O	O	O	O	O		
		name	O	O	X	X	X	O	""	
		href	O	O	O	O	O	O	(none)	Fragment jump is valid only for <a> and
		hreflang	O	X	O	O	O	X	(n/a)	partial support for stylesheet
		type	O	X	O	O	O	X	(n/a)	partial support for stylesheet
		rel	O	X	O	O	O	X	(n/a)	It does not affect rendering
		rev	O	X	O	O	O	X	(n/a)	It does not affect rendering
		charset	O	X	O	O	O	X	(n/a)	partial support for stylesheet
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		shape	O	X	X	O	X	O	"rect"	
		coords	O	X	X	O	X	O	(none)	
		onfocus	O	X	X	X	X	O	(script)	
		onblur	O	X	X	X	X	O	(script)	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		target	O	X	X	X	X	O	"_self"	
		tabindex	O	X	O	O	O	X	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		accesskey	O	X	O	O	O	O	(none)	After the execution, an event handler of control is initiated.
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Document relationships	LINK		O	X	O	O	O	O		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		href	O	X	O	O	O	O	(none)	
		hreflang	O	X	O	O	O	X	(n/a)	Resource required and rarely used
		type	O	X	O	O	O	O	(n/a)	Only type="text/css" is supported
		rel	O	X	O	O	O	O	(n/a)	Only "rel=stylesheet" is supported
		rev	O	X	O	O	O	X	(n/a)	It does not affect rendering
		media	O	X	O	O	O	X	(n/a)	partial support for stylesheet
		target	O	X	O	O	O	X	(n/a)	
		charset	O	X	O	O	O	X	(n/a)	Resource required and rarely used
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Path information	BASE		O	O	O	O	O	O		
		href	O	O	O	O	O	O	Same as the URL of the page	
		target	O	X	X	X	X	O	"_self"	
Objects, Images, and Applets										
Including an image	IMG		O	O	O	O	O	O		
		src	O	O	O	O	O	O	(none)	
		longdesc	O	X	O	O	O	X	(n/a)	It does not affect rendering
		name	O	X	X	X	X	O	(none)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		alt	O	O	O	O	O	O	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		ismap	O	X	X	O	X	O	(none)	
		usemap	O	X	X	O	X	O	(none)	
		align	O	O	X	X	X	O	(none)	
		width	O	O	O	O	O	O	(none)	
		height	O	O	O	O	O	O	(none)	
		border	O	O	X	X	X	O	(none)	
		hspace	O	O	X	X	X	O	(none)	
		vspace	O	O	X	X	X	O	(none)	
		onload	X	X	-	-	-	O	(script)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	IMAGE		X	X	X	X	X	X		Browser vendor extension
Generic inclusion	OBJECT		O	X	O	O	O	O		
		classid	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		codebase	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		codetype	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		data	O	X	O	O	O	O	(none)	
		type	O	X	O	O	O	O	(none)	
		archive	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		declare	O	X	O	O	O	O	(none)	
		standby	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		tabindex	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		usemap	O	X	X	O	X	O	(n/a)	
		name	O	X	O	O	O	O	(none)	
		align	O	X	X	X	X	X	(n/a)	
		width	O	X	O	O	O	O	(n/a)	
		height	O	X	O	O	O	O	(n/a)	
		border	O	X	X	X	X	X	(n/a)	
		hspace	O	X	X	X	X	O	(n/a)	
		vspace	O	X	X	X	X	O	(n/a)	
		accesskey	X	X	X	X	X	X	(n/a)	
		code	X	X	X	X	X	X	(n/a)	Browser vendor extension
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Object initialization	PARAM		O	X	O	O	O	O		
		name	O	X	O	O	O	O	(n/a)	PARAM tags can be used only for OBJECT tags
		value	O	X	O	O	O	O	(n/a)	PARAM tags can be used only for OBJECT tags
		valuetype	O	X	O	O	O	X	(n/a)	valuetype="data"
		type	O	X	O	O	O	X	(n/a)	object not supported for rendering, but for retrieving information for Java
		id	O	X	O	O	O	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Including an applet	APPLET		O	X	X	X	X	X		
		codebase	O	X	X	X	X	X	(n/a)	
		code	O	X	X	X	X	X	(n/a)	
		name	O	X	X	X	X	X	(n/a)	
		archive	O	X	X	X	X	X	(n/a)	
		object	O	X	X	X	X	X	(n/a)	
		width	O	X	X	X	X	X	(n/a)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		height	O	X	X	X	X	X	(n/a)	
		id	O	X	X	X	X	X	(n/a)	
		class	O	X	X	X	X	X	(n/a)	
		title	O	X	X	X	X	X	(n/a)	
		style	O	X	X	X	X	X	(n/a)	
		alt	O	X	X	X	X	X	(n/a)	
		align	O	X	X	X	X	X	(n/a)	
		hspace	O	X	X	X	X	X	(n/a)	
		vspace	O	X	X	X	X	X	(n/a)	
		mayscript	X	X	X	X	X	X	(n/a)	Browser vendor extension
src	X	X	X	X	X	X	(n/a)	Browser vendor extension		
The EMBED element	EMBED		X	X	X	X	X	O		
		align	X	X	X	X	X	X	(n/a)	Browser vendor extension
		alt	X	X	X	X	X	X	(n/a)	Browser vendor extension
		border	X	X	X	X	X	X	(n/a)	
		code	X	X	X	X	X	X	(n/a)	Browser vendor extension
		codebase	X	X	X	X	X	X	(n/a)	Browser vendor extension
		frameborder	X	X	X	X	X	X	(n/a)	
		height	X	X	X	X	X	O	(none)	
		hidden	X	X	X	X	X	O	(none)	
		hspace	X	X	X	X	X	O	(none)	
		name	X	X	X	X	X	X	(n/a)	Browser vendor extension
		palette	X	X	X	X	X	X	(n/a)	Browser vendor extension
		pluginspage	X	X	X	X	X	X	(n/a)	Browser vendor extension
		pluginurl	X	X	X	X	X	X	(n/a)	Browser vendor extension
		src	X	X	X	X	X	O	(none)	
		type	X	X	X	X	X	O	(none)	
		units	X	X	X	X	X	X	(n/a)	Browser vendor extension
vspace	X	X	X	X	X	O	(none)			
width	X	X	X	X	X	O	(none)			
optional_param	X	X	X	X	X	X	(n/a)	Browser vendor extension		
The NOEMBED element	NOEMBED		X	X	X	X	X	O		
Image maps	MAP		O	X	X	O	X	O		
		name	O	X	X	X	X	O	(none)	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	AREA		O	X	X	O	X	O		
		shape	O	X	X	O	X	O	"rect"	
		coords	O	X	X	O	X	O	(none)	
		nohref	O	X	X	O	X	O	(none)	
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		alt	O	X	X	O	X	X	(n/a)	
		href	O	X	X	O	X	O	(none)	
		target	O	X	X	X	X	O	"_self"	
		tabindex	O	X	X	O	X	X	(none)	
		accesskey	O	X	X	O	X	O	(none)	After the execution, an event handler of control is initiated.
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		onfocus	O	X	X	X	X	O	(script)	
		onblur	O	X	X	X	X	O	(script)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Style Sheets										
Header style information	STYLE		O	X	X	O	O	O		
		type	O	X	X	O	O	O	"text/css"	
		media	O	X	X	O	O	O	"screen"	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		title	O	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:lang	X	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xml:space	X	X	X	O	O	-	"default"	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Alignment, font styles, and horizontal rules										
The center	CENTER		O	O	X	X	X	O		
Font style elements	TT		O	X	X	O	X	**		Display differ depending on the installed fonts.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	I		O	X	X	O	O	**		Display differ depending on the installed fonts.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	B		O	X	X	O	O	**		Display differ depending on the installed fonts.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	BIG		O	X	X	O	O	**		Display differ depending on the installed fonts.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	SMALL		O	X	X	O	O	**		Display differ depending on the installed fonts.
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	STRIKE		O	X	X	X	X	O		
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	S		O	X	X	X	X	O		
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	U		O	X	X	X	X	O		
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Font modifier elements	FONT		O	X	X	X	X	O		
		size	O	X	X	X	X	O	(none)	
		color	O	X	X	X	X	O	(none)	
		face	O	X	X	X	X	X	(n/a)	Font System dependent
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		xml:lang	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
	BASEFONT		O	X	X	X	X	O		BASEFONT doesn't change the font size. "color" takes effect only when it is defined in HEAD tags.
		size	O	X	X	X	X	O	(none)	
		color	O	X	X	X	X	O	(none)	
		face	O	X	X	X	X	X	(n/a)	Font System dependent
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		xml:lang	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Rules	HR		O	O	X	O	O	O		In NF3 specification, an HR tag is not handled as a text character. Because of this, the HR tag is not affected by specification of text-align.
		align	O	O	X	X	X	O	(none)	
		noshade	O	O	X	X	X	O	(none)	
		size	O	O	X	X	X	O	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		width	O	O	X	X	X	O	(none)	
		id	O	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	X	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	X	(script)	
		onmouseup	O	X	X	O	X	X	(script)	
		onmouseover	O	X	X	O	X	X	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	X	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		color	X	X	X	X	X	O	(none)	
		xml:lang	X	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Frames										
Layout of frames	FRAMESET		O	X	X	X	X	O		
		rows	O	X	X	X	X	O	"100%"	
		cols	O	X	X	X	X	O	"100%"	
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		onload	O	X	X	X	X	O	(script)	
		onunload	O	X	X	X	X	O	(script)	
		border	X	X	X	X	X	O	(none)	
		bordercolor	X	X	X	X	X	O	(none)	
		frameborder	X	X	X	X	X	X	(n/a)	
		framespacing	X	X	X	X	X	X	(n/a)	Browser vendor extension
	FRAME		O	X	X	X	X	O		
		name	O	X	X	X	X	O	(none)	
		longdesc	O	X	X	X	X	X	(n/a)	It does not affect rendering
		src	O	X	X	X	X	O	(none)	
		noresize	O	X	X	X	X	O	(none)	
		scrolling	O	X	X	X	X	O	"auto"	
		frameborder	O	X	X	X	X	O	(none)	
		marginwidth	O	X	X	X	X	O	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		marginheight	O	X	X	X	X	O	(none)	
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
Alternate content	NOFRAMES		O	X	X	X	X	O		
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	X	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		onclick	O	X	X	X	X	O	(script)	
		ondblclick	O	X	X	X	X	X	(n/a)	
		onmousedown	O	X	X	X	X	O	(script)	
		onmouseup	O	X	X	X	X	O	(script)	
		onmouseover	O	X	X	X	X	O	(script)	
		onmousemove	O	X	X	X	X	X	(script)	
		onmouseout	O	X	X	X	X	O	(script)	
		onkeypress	O	X	X	X	X	X	(n/a)	
		onkeydown	O	X	X	X	X	X	(n/a)	
		onkeyup	O	X	X	X	X	X	(n/a)	
		xml:lang	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Inline frames	IFRAME		O	X	X	X	X	O		
		longdesc	O	X	X	X	X	X	(n/a)	It does not affect rendering
		name	O	X	X	X	X	O	(none)	
		width	O	X	X	X	X	O	(none)	
		height	O	X	X	X	X	O	(none)	
		id	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	X	X	O	(none)*	
		src	O	X	X	X	X	O	(none)	
		frameborder	O	X	X	X	X	O	(none)	
		marginwidth	O	X	X	X	X	O	(none)	
		marginheight	O	X	X	X	X	O	(none)	
scrolling	O	X	X	X	X	O	"auto"			
align	O	X	X	X	X	O	(none)			

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
Forms											
The FORM element	FORM		O	O	O	O	O	O			
		action	O	O	O	O	O	O	(none)	Submits only when "action" is specified	
		method	O	O	O	O	O	O	"GET"		
		enctype	O	O	O	O	O	O	"application/x-www-form-urlencoded"		
		accept-charset	O	X	X	O	X	O	(none)		
		accept	O	X	X	O	X	X	(n/a)	Resource required and rarely used	
		name	O	X	X	X	X	O	(none)		
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		target	O	X	X	X	X	O	"_self"		
		onsubmit	O	X	X	X	X	O	(script)		
		onreset	O	X	X	X	X	O	(script)		
		onclick	O	X	X	O	X	O	(script)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	O	(script)		
		onmouseup	O	X	X	O	X	O	(script)		
		onmouseover	O	X	X	O	X	O	(script)		
		onmousemove	O	X	X	O	X	X	(script)		
		onmouseout	O	X	X	O	X	O	(script)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	The INPUT element	INPUT		O	O	O	O	O	O		
			id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		disabled	O	X	X	O	X	O	(none)		
		tabindex	O	X	X	O	X	X	(none)		
		accesskey	O	X	O	O	O	O	(none)	After the execution, an event handler of control is initiated.	
	onfocus	O	X	X	X	X	O	(script)			

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		onblur	O	X	X	X	X	O	(script)	
		onselect	O	X	X	X	X	X	(n/a)	Resource required and rarely used
		onchange	O	X	X	X	X	X	(script)	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	Not supported except for Image
		onmousemove	O	X	X	O	X	X	(script)	Not supported except for Image
		onmouseout	O	X	X	O	X	O	(script)	Not supported except for Image
		onkeypress	O	X	X	O	X	X	(script)	type = text , type = password
		onkeydown	O	X	X	O	X	X	(script)	type = text , type = password
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		type = text	O	O	O	O	O	O		
		maxlength	O	O	O	O	O	O	(none)	
		name	O	O	O	O	O	O	(none)	
		size	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		readonly	O	X	X	O	X	O	(none)	
		type = password	O	O	O	O	O	O		
		maxlength	O	O	O	O	O	O	(none)	
		name	O	O	O	O	O	O	(none)	
		size	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		readonly	O	X	X	O	X	O	(none)	
		type = checkbox	O	O	O	O	O	O		
		checked	O	O	O	O	O	O	(none)	
		name	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		type = radio	O	O	O	O	O	O		
		checked	O	O	O	O	O	O	(none)	
		name	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		type = submit	O	O	O	O	O	O		
		name	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		type = reset	O	O	O	O	O	O		
		name	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		type = file	O	X	X	O	X	O		
		accept	O	X	X	O	X	X	(n/a)	Resource required and rarely used
		maxlength	O	X	X	O	X	X	(n/a)	Resource required and rarely used
		name	O	X	X	O	X	O	(none)	
		size	O	X	X	O	X	O	(none)	
		value	O	X	X	O	X	O	""	
		type = hidden	O	O	O	O	O	O		
		name	O	O	O	O	O	O	(none)	
		value	O	O	O	O	O	O	""	
		type = image	O	X	X	O	X	O		
		align	O	X	X	X	X	O	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		alt	O	X	X	O	X	O	(none)	
		border	X	X	X	X	X	O	(none)	
		height	X	X	X	X	X	O	(none)	
		ismap	O	X	X	O	X	O	(none)	
		name	O	X	X	O	X	O	(none)	
		src	O	X	X	O	X	O	(none)	
		usemap	O	X	X	O	X	O	(none)	
		value	O	X	X	O	X	O	""	
		width	X	X	X	X	X	O	(none)	
		type = button	O	X	X	O	X	O		
		name	O	X	X	O	X	O	(none)	
		value	O	X	X	O	X	O	""	
The BUTTON element	BUTTON		O	X	X	O	X	O		The vertical display position of a button label character string in the BUTTON attribute is top aligned.
		name	O	X	X	O	X	O	(none)	
		value	O	X	X	O	X	O	""	
		type	O	X	X	O	X	O	"submit"	
		id	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	X	O	(none)*	
		disabled	O	X	X	O	X	O	(none)	
		accesskey	O	X	X	O	X	O	(none)	After the execution, an event handler of control is initiated.
		tabindex	O	X	X	O	X	X	(none)	
		onfocus	O	X	X	X	X	O	(script)	
		onblur	O	X	X	X	X	O	(script)	
		onclick	O	X	X	O	X	O	(script)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	O	(script)	
		onmouseover	O	X	X	O	X	O	(script)	
		onmousemove	O	X	X	O	X	X	(script)	
		onmouseout	O	X	X	O	X	O	(script)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	X	O	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Selection List	SELECT		O	O	O	O	O	O		
		name	O	O	O	O	O	O	(none)	
		size	O	O	O	O	O	O	(none)	
		multiple	O	O	O	O	O	O	(none)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
		style	O	X	X	O	O	O	(none)*		
		disabled	O	X	X	O	X	O	(none)		
		tabindex	O	X	X	O	X	X	(none)		
		onfocus	O	X	X	X	X	O	(script)	Excluding "label"	
		onblur	O	X	X	X	X	O	(script)	Excluding "label"	
		onchange	O	X	X	X	X	O	(script)		
		onclick	O	X	X	O	X	X	(n/a)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	X	(n/a)		
		onmouseup	O	X	X	O	X	X	(n/a)		
		onmouseover	O	X	X	O	X	X	(n/a)		
		onmousemove	O	X	X	O	X	X	(n/a)		
		onmouseout	O	X	X	O	X	X	(n/a)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
onkeyup	O	X	X	O	X	X	(n/a)				
accesskey	X	X	X	X	X	O	(none)	After the execution, an event handler of control is initiated.			
	xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
	xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
Pre-selected options	OPTGROUP		O	X	X	O	O	X		Graphis System dependent	
		label	O	X	X	O	O	X	(n/a)	Graphis System dependent	
		id	O	X	X	O	O	X	(n/a)		
		class	O	X	X	O	O	X	(n/a)		
		lang	O	X	X	X	X	X	(n/a)		
		dir	O	X	X	O	X	X	(n/a)		
		title	O	X	X	O	O	X	(n/a)		
		style	O	X	X	O	O	X	(n/a)		
		disabled	O	X	X	O	O	X	(n/a)	Graphis System dependent	
		onclick	O	X	X	O	X	X	(n/a)		
		ondblclick	O	X	X	O	X	X	(n/a)		
		onmousedown	O	X	X	O	X	X	(n/a)		
		onmouseup	O	X	X	O	X	X	(n/a)		
		onmouseover	O	X	X	O	X	X	(n/a)		
		onmousemove	O	X	X	O	X	X	(n/a)		
		onmouseout	O	X	X	O	X	X	(n/a)		
		onkeypress	O	X	X	O	X	X	(n/a)		
		onkeydown	O	X	X	O	X	X	(n/a)		
		onkeyup	O	X	X	O	X	X	(n/a)		
			xml:lang	X	X	X	O	O	X	(n/a)	
			xmlns	X	X	X	O	O	X	(n/a)	
	OPTION		O	O	O	O	O				
	selected		O	O	O	O	O	(none)			

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		value	O	X	O	O	O	O	""	
		label	O	X	X	O	X	X	(n/a)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		disabled	O	X	X	O	X	X	(n/a)	
		onclick	O	X	X	O	X	X	(n/a)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	X	(n/a)	
		onmouseup	O	X	X	O	X	X	(n/a)	
		onmouseover	O	X	X	O	X	X	(n/a)	
		onmousemove	O	X	X	O	X	X	(n/a)	
		onmouseout	O	X	X	O	X	X	(n/a)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Text Area	TEXTAREA		O	O	O	O	O	O		
		name	O	O	O	O	O	O	(none)	
		rows	O	O	O	O	O	O	(none)	
		cols	O	O	O	O	O	O	(none)	
		disabled	O	X	X	O	X	O	(none)	
		readonly	O	X	X	O	X	O	(none)	
		tabindex	O	X	X	O	X	X	(none)	
		accesskey	O	X	O	O	O	O	(none)	After the execution, an event handler of control is initiated.
		onfocus	O	X	X	X	X	O	(script)	
		onblur	O	X	X	X	X	O	(script)	
		onselect	O	X	X	X	X	X	(n/a)	Resource required and rarely used
		onchange	O	X	X	X	X	O	(script)	
		id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		style	O	X	X	O	O	O	(none)*	
		onclick	O	X	X	O	X	O	(script)	

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	O	(script)	
		onmouseup	O	X	X	O	X	X	(script)	
		onmouseover	O	X	X	O	X	X	(n/a)	
		onmousemove	O	X	X	O	X	X	(n/a)	
		onmouseout	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.		
Single Line Prompt	ISINDEX		O	X	X	X	X	X		Resource required
	prompt	O	X	X	X	X	X	X	(n/a)	Resource required
	action	X	X	X	X	X	X	X	(n/a)	Resource required
	id	O	X	X	X	X	X	X	(n/a)	
	class	O	X	X	X	X	X	X	(n/a)	
	lang	O	X	X	X	X	X	X	(n/a)	
	dir	O	X	X	X	X	X	X	(n/a)	
	title	O	X	X	X	X	X	X	(n/a)	
	style	O	X	X	X	X	X	X	(n/a)	
	xml:lang	X	X	X	X	X	X	X	(n/a)	
xmlns	X	X	X	X	X	X	X	(n/a)		
Form Label	LABEL		O	X	O	O	O	O		Resource required
	for	O	X	O	O	O	O	O	(none)	Resource required
	id	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	class	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	lang	O	X	X	X	X	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	dir	O	X	X	O	X	-	(n/a)	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	title	O	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	style	O	X	X	O	O	O	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.	
	accesskey	O	X	O	O	O	O	(none)	After the execution, an event handler of control is initiated.	
	onfocus	O	X	X	X	X	X	(n/a)	Resource required	
	onblur	O	X	X	X	X	X	(n/a)	Resource required	
	onclick	O	X	X	O	X	X	(n/a)		
	ondblclick	O	X	X	O	X	X	(n/a)		
	onmousedown	O	X	X	O	X	O	(n/a)		
	onmouseup	O	X	X	O	X	O	(n/a)		
	onmouseover	O	X	X	O	X	O	(n/a)		
	onmousemove	O	X	X	O	X	X	(n/a)		
	onmouseout	O	X	X	O	X	O	(n/a)		
	onkeypress	O	X	X	O	X	X	(n/a)		
	onkeydown	O	X	X	O	X	X	(n/a)		
onkeyup	O	X	X	O	X	X	(n/a)			

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
		xml:lang	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
		xmlns	X	X	O	O	O	-	(none)*	The browser internally administrates this attribute value. There is no visual effect even if the attribute is specified.
Adding structure to forms	FIELDSET		O	X	X	O	O	X		Resource required
		align	X	X	X	X	X	X	(n/a)	Resource required
		id	O	X	X	O	O	X	(n/a)	
		class	O	X	X	O	O	X	(n/a)	
		lang	O	X	X	X	X	X	(n/a)	
		dir	O	X	X	O	X	X	(n/a)	
		title	O	X	X	O	O	X	(n/a)	
		style	O	X	X	O	O	X	(n/a)	
		onclick	O	X	X	O	X	X	(n/a)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	X	(n/a)	
		onmouseup	O	X	X	O	X	X	(n/a)	
		onmouseover	O	X	X	O	X	X	(n/a)	
		onmousemove	O	X	X	O	X	X	(n/a)	
		onmouseout	O	X	X	O	X	X	(n/a)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	O	X	(n/a)	
		xmlns	X	X	X	O	O	X	(n/a)	
	LEGEND		O	X	X	O	X	X		Resource required
		accesskey	O	X	X	O	X	X	(n/a)	Resource required
		align	O	X	X	X	X	X	(n/a)	Resource required
		id	O	X	X	O	X	X	(n/a)	
		class	O	X	X	O	X	X	(n/a)	
		lang	O	X	X	X	X	X	(n/a)	
		dir	O	X	X	O	X	X	(n/a)	
		title	O	X	X	O	X	X	(n/a)	
		style	O	X	X	O	X	X	(n/a)	
		onclick	O	X	X	O	X	X	(n/a)	
		ondblclick	O	X	X	O	X	X	(n/a)	
		onmousedown	O	X	X	O	X	X	(n/a)	
		onmouseup	O	X	X	O	X	X	(n/a)	
		onmouseover	O	X	X	O	X	X	(n/a)	
		onmousemove	O	X	X	O	X	X	(n/a)	
		onmouseout	O	X	X	O	X	X	(n/a)	
		onkeypress	O	X	X	O	X	X	(n/a)	
		onkeydown	O	X	X	O	X	X	(n/a)	
		onkeyup	O	X	X	O	X	X	(n/a)	
		xml:lang	X	X	X	O	X	X	(n/a)	
		xmlns	X	X	X	O	X	X	(n/a)	
Scripts										
The SCRIPT element	SCRIPT		O	X	X	O	X	O		
		charset	O	X	X	O	X	O	(none)	
		type	O	X	X	O	X	O	(none)	
		src	O	X	X	O	X	O	(none)	
		defer	O	X	X	O	X	O	(none)	
The NOSCRIPT element	NOSCRIPT		O	X	X	O	X	O		

Items	Elements	Attributes	W3C HTML 4.01	Compact HTML	XHTML Basic1.0	XHTML 1.1	XHTML MobileProfile	NF3 for iR Series	Default Values(the value applied when the attribute isn't specified)	NF3 for iR Series Remarks
Layer										
The LAYER element	LAYER		X	X	X	X	X	X		Browser vendor extension
The ILAYER element	ILAYER		X	X	X	X	X	X		Browser vendor extension
The NOLAYER element	NOLAYER		X	X	X	X	X	X		Browser vendor extension
Security										
Key Generator	KEYGEN		X	X	X	X	X	X		Browser vendor extension

Chapter 2

CSS

O: Supported

A: Optional, not requires implementation

X: Not Supported

** : The display might be different according to the installed font.

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

(none) Cannot describe as A initial (default) value of the attribute. the result is dependent on the situation, or existence of the attribute matters, or depends on the image size, or the attribute is required. (* indicates "common attribute")

(n/a) The attribute is not supported.

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
Selector Patterns									
*			X	O	O	O	O		
E			O	O	O	O	O		
E F			O	O	O	O	O		
E > F			X	O	X	X	O		
E:first-child			X	O	X	X	O		
E:link			O	O	O	O	O		
E:visited			O	O	O	A	O		
E:active			O	O	O	A	O		An event occurs after mouseup.
E:hover			X	O	X	X	X		Graphic System dependent
E:focus			X	O	O	A	O		
E:lang(c)			X	O	X	X	X		
E + F			X	O	X	X	O		
E[foo]			X	O	X	X	O		
E[foo="warning"]			X	O	X	X	O		
E[foo!="warning"]			X	O	X	X	O		
E[lang="en"]			X	O	X	X	O		
Div.warning			O	O	O	O	O		
E#myid			O	O	O	O	O		
E:first-letter			O	O	-	X	X		
E:first-line			O	O	-	X	X		
E:before			X	O	-	X	X		Resource required and rarely used.
E:after			X	O	-	X	X		Resource required and rarely used.
E, F			O	O		O	O		
Boxes									
margin-top		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	auto		O	O	O	O	O		
	inherit		O	O	O	O	O		
margin-right		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	auto		O	O	O	O	O		
	inherit		O	O	O	O	O		
margin-bottom		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	auto		O	O	O	O	O		
	inherit		O	O	O	O	O		
margin-left		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	auto		O	O	O	O	O		
	inherit		O	O	O	O	O		
margin		visual	O	O	O	A	O	(see individual properties)	If margin attribute is specified in div tags within td tags, display is executed without leaving a margin on the top and bottom.
	<margin-width>(1,4)		O	O	O	A	O		
	inherit		O	O	O	A	O		
padding-top		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	inherit		O	O	O	O	O		
padding-right		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
	<percentage>		O	O	O	O	O		
	inherit		O	O	O	O	O		
padding-bottom		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	inherit		O	O	O	O	O		
padding-left		visual	O	O	O	O	O	0	
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	inherit		O	O	O	O	O		
padding		visual	O	O	O	A	O	(see individual properties)	
	<padding-width>{1,4}		O	O	O	A	O		"%" not Supported
	inherit		O	O	O	A	O		
border-top-width		visual	O	O	O	O	O	medium	
	thin		O	O	O	O	O		
	medium		O	O	O	O	O		
	thick		O	O	O	O	O		
	<length>		O	O	O	A	O		
	inherit		O	O	O	O	O		
border-right-width		visual	O	O	O	O	O	medium	
	thin		O	O	O	O	O		
	medium		O	O	O	O	O		
	thick		O	O	O	O	O		
	<length>		O	O	O	A	O		
	inherit		O	O	O	O	O		
border-bottom-width		visual	O	O	O	O	O	medium	
	thin		O	O	O	O	O		
	medium		O	O	O	O	O		
	thick		O	O	O	O	O		
	<length>		O	O	O	A	O		
	inherit		O	O	O	O	O		
border-left-width		visual	O	O	O	O	O	medium	
	thin		O	O	O	O	O		
	medium		O	O	O	O	O		
	thick		O	O	O	O	O		
	<length>		O	O	O	A	O		
	inherit		O	O	O	O	O		
border-width		visual	O	O	O	A	O	(see individual properties)	
	<border-width>{1,4}		O	O	O	A	O		
	inherit		O	O	O	A	O		
border-top-color		visual	X	O	O	O	O	(the value of the 'color'	
	<color>		X	O	O	O	O		
	transparent		X	X	X	X	O		NF3 specific.
	inherit		X	O	O	O	O		
border-right-color		visual	X	O	O	O	O	(the value of the 'color'	
	<color>		X	O	O	O	O		
	transparent		X	X	X	X	O		NF3 specific.
	inherit		X	O	O	O	O		
border-bottom-color		visual	X	O	O	O	O	(the value of the 'color'	
	<color>		X	O	O	O	O		
	transparent		X	X	X	X	O		NF3 specific.
	inherit		X	O	O	O	O		
border-left-color		visual	X	O	O	O	O	(the value of the 'color'	
	<color>		X	O	O	O	O		
	transparent		X	X	X	X	O		NF3 specific.
	inherit		X	O	O	O	O		
border-color		visual	O	O	O	O	O	(see individual properties)	

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
	<color>{1,4}		O	O	O	O	O		
	transparent		O	O	O	X	O		
	inherit		O	O	O	O	O		
border-top-style		visual	X	O	O	O	O	none	
	none		X	O	O	O	O		
	hidden		X	O	O	O	O		
	dotted		X	O	O	A	X		Graphic System dependent
	dashed		X	O	O	A	X		Graphic System dependent
	solid		X	O	O	O	O		
	double		X	O	O	A	X		
	groove		X	O	O	A	X		Graphic System dependent
	ridge		X	O	O	A	X		Graphic System dependent
	inset		X	O	O	A	O		
	outset		X	O	O	A	O		
	inherit		X	O	O	O	O		
border-right-style		visual	X	O	O	O	O	none	
	none		X	O	O	O	O		
	hidden		X	O	O	O	O		
	dotted		X	O	O	A	X		Graphic System dependent
	dashed		X	O	O	A	X		Graphic System dependent
	solid		X	O	O	O	O		
	double		X	O	O	A	X		
	groove		X	O	O	A	X		Graphic System dependent
	ridge		X	O	O	A	X		Graphic System dependent
	inset		X	O	O	A	O		
	outset		X	O	O	A	O		
	inherit		X	O	O	O	O		
border-bottom-style		visual	X	O	O	O	O	none	
	none		X	O	O	O	O		
	hidden		X	O	O	O	O		
	dotted		X	O	O	A	X		Graphic System dependent
	dashed		X	O	O	A	X		Graphic System dependent
	solid		X	O	O	O	O		
	double		X	O	O	A	X		
	groove		X	O	O	A	X		Graphic System dependent
	ridge		X	O	O	A	X		Graphic System dependent
	inset		X	O	O	A	O		
	outset		X	O	O	A	O		
	inherit		X	O	O	O	O		
border-left-style		visual	X	O	O	O	O	none	
	none		X	O	O	O	O		
	hidden		X	O	O	O	O		
	dotted		X	O	O	A	X		Graphic System dependent
	dashed		X	O	O	A	X		Graphic System dependent
	solid		X	O	O	O	O		
	double		X	O	O	A	X		
	groove		X	O	O	A	X		Graphic System dependent
	ridge		X	O	O	A	X		Graphic System dependent
	inset		X	O	O	A	O		
	outset		X	O	O	A	O		
	inherit		X	O	O	O	O		
border-style		visual	O	O	O	A	O	(see individual properties)	
	<border-style>{1,4}		O	O	O	A	O		
	inherit		O	O	O	A	O		
border-top		visual	O	O	O	O	O	(see individual properties)	
	'border-top-width' 'border-top-style' 'border-top-color'		O	O	O	O	O		
	inherit		O	O	O	O	O		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
border-right		visual	O	O	O	O	O	(see individual properties)	
	'border-right-width' 'border-right-style' 'border-right-color'		O	O	O	O	O		
	inherit		O	O	O	O	O		
border-bottom		visual	O	O	O	O	O	(see individual properties)	
	'border-bottom-width' 'border-bottom-style' 'border-bottom-color'		O	O	O	O	O		
	inherit		O	O	O	O	O		
border-left		visual	O	O	O	O	O	(see individual properties)	
	'border-left-width' 'border-left-style' 'border-left-color'		O	O	O	O	O		
	inherit		O	O	O	O	O		
border		visual	O	O	O	O	O	(see individual properties)	
	'border-top-width' 'border-top-style' 'border-top-color'		O	O	O	O	O		
	inherit		O	O	O	O	O		
Visual formatting model									
display		all	O	O	O	A	O	inline	
		block	O	O	O	O	O		
		inline	O	O	O	O	O		
		list-item	O	O	O	O	X		Resource required and rarely used.
		marker	X	O	O	X	X		Resource required and rarely used.
		none	O	O	O	O	O		
		run-in	X	O	O	X	X		Resource required and rarely used.
		compact	X	O	O	X	X		Resource required and rarely used.
		table	X	O	O	X	X		Resource required and rarely used.
		inline-table	X	O	O	X	X		Resource required and rarely used.
		table-row-group	X	O	O	X	X		Resource required and rarely used.
		table-column	X	O	O	X	X		Resource required and rarely used.
		table-column-group	X	O	O	X	X		Resource required and rarely used.
		table-header-group	X	O	O	X	X		Resource required and rarely used.
		table-footer-group	X	O	O	X	X		Resource required and rarely used.
		table-row	X	O	O	X	X		Resource required and rarely used.
		table-cell	X	O	O	X	X		Resource required and rarely used.
	table-caption	X	O	O	X	X		Resource required and rarely used.	
	inherit	O	O	O	O	O			
position		visual	X	O	X	X	O	static	
		static	X	O	X	X	O		
		relative	X	O	X	X	X		Resource required and rarely used.
		absolute	X	O	X	X	O		marquee element is not supported. HR element is not supported. TD element is not supported. BODY element is not supported.
		fixed	X	O	X	X	O		
	inherit	X	O	X	X	O			
top		visual	X	O	X	X	O	auto	
		<length>	X	O	X	X	O		
		<percentage>	X	O	X	X	O		
		auto	X	O	X	X	O		
		inherit	X	O	X	X	O		
right		visual	X	O	X	X	X	(n/a)	
		<length>	X	O	X	X	X		
		<percentage>	X	O	X	X	X		
		auto	X	O	X	X	X		
		inherit	X	O	X	X	X		
bottom		visual	X	O	X	X	X	(n/a)	
		<length>	X	O	X	X	X		
		<percentage>	X	O	X	X	X		
		auto	X	O	X	X	X		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks	
left	inherit		X	O	X	X	X			
		visual	X	O	X	X	O	auto		
	<length>		X	O	X	X	O			
	<percentage>		X	O	X	X	O			
	auto		X	O	X	X	O			
float	inherit		X	O	X	X	O			
		visual	O	O	O	O	O	none	marquee attribute is not supported.	
	left		O	O	O	O	O			
	right		O	O	O	O	O			
	none		O	O	O	O	O			
clear	inherit		O	O	O	O	O			
		visual	O	O	O	O	O	none		
	none		O	O	O	O	O			
	left		O	O	O	O	O			
	right		O	O	O	O	O			
z-index	both		O	O	O	O	O			
	inherit		O	O	O	O	O			
		visual	X	O	X	X	O	auto	Overlap control is not supported.	
	auto		X	O	X	X	O			
	<integer>		X	O	X	X	O			
direction	inherit		X	O	X	X	O			
		visual	X	O	X	X	X	(n/a)		
	ltr		X	O	X	X	X			
	rtl		X	O	X	X	X			
unicode-bidi	inherit		X	O	X	X	X			
		visual	X	O	X	X	X	(n/a)	Resource required	
	normal		X	O	X	X	X		Resource required	
	embed		X	O	X	X	X		Resource required	
	bidi-override		X	O	X	X	X		Resource required	
Visual formatting model details	inherit		X	O	X	X	X		Resource required	
	width		visual	O	O	O	O	O	auto	
		<length>		O	O	O	O	O		
		<percentage>		O	O	O	O	O		
		auto		O	O	O	O	O		
inherit			O	O	O	O	O			
min-width		visual	X	O	X	X	X	(n/a)		
	<length>		X	O	X	X	X		Resource required	
	<percentage>		X	O	X	X	X		Resource required	
	inherit		X	O	X	X	X		Resource required	
max-width		visual	X	O	X	X	X	(n/a)		
	<length>		X	O	X	X	X		Resource required	
	<percentage>		X	O	X	X	X		Resource required	
	none		X	O	X	X	X		Resource required	
	inherit		X	O	X	X	X		Resource required	
height		visual	O	O	O	O	O	auto		
	<length>		O	O	O	O	O			
	<percentage>		O	O	O	O	O			
	auto		O	O	O	O	O			
	inherit		O	O	O	O	O			
min-height		visual	X	O	X	X	X	(n/a)		
	<length>		X	O	X	X	X		Resource required	
	<percentage>		X	O	X	X	X		Resource required	
	inherit		X	O	X	X	X			
max-height		visual	X	O	X	X	X	(n/a)		
	<length>		X	O	X	X	X		Resource required	
	<percentage>		X	O	X	X	X		Resource required	

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
	none		X	O	X	X	X		Resource required
	inherit		X	O	X	X	X		Resource required
line-height		visual	O	O	X	X	O	normal	
	normal		O	O	X	X	O		
	number		O	O	X	X	O		
	<length>		O	O	X	X	O		
	<percentage>		O	O	X	X	O		
	inherit		O	O	X	X	O		
vertical-align		visual	O	O	O	O	O	baseline	
	baseline		O	O	O	O	O		
	middle		O	O	O	O	O		
	sub		O	O	O	O	O		
	super		O	O	O	O	O		
	text-top		O	O	O	X	O		
	text-bottom		O	O	O	X	O		
	<percentage>		O	O	O	X	O		
	<length>		O	O	O	X	O		
	top		O	O	O	O	O		
	bottom		O	O	O	O	O		
	inherit		O	O	O	O	O		
Visual effects									
overflow		visual	X	O	X	X	O	visible	Graphic System dependent
	visible		X	O	X	X	O		
	hidden		X	O	X	X	O		
	scroll		X	O	X	X	X		Graphic System dependent
	auto		X	O	X	X	X		Graphic System dependent
	inherit		X	O	X	X	O		
clip		visual	X	O	X	X	O	auto	Resource required and rarely used.
	auto		X	O	X	X	O		
	<shape>		X	O	X	X	X		Resource required and rarely used.
	inherit		X	O	X	X	X		Resource required and rarely used.
visibility		visual	X	O	O	O	O	inherit	
	visible		X	O	O	O	O		
	hidden		X	O	O	O	O		
	collapse		X	O	O	A	X		Resource required and rarely used.
	inherit		X	O	O	O	O		
Generated content, automatic numbering, and lists									
content			X	O	X	X	X	(n/a)	Resource required and rarely used.
	[<string> <uri> <counter> open-quote close-quote no-open-quote no-close-quote attr(X)]+	all	X	O	X	X	X		Resource required and rarely used.
	inherit		X	O	X	X	X		Resource required and rarely used.
quotes		visual	X	O	X	X	X	(n/a)	Resource required and rarely used.
	[<string> <string>]+		X	O	X	X	X		Resource required and rarely used.
	none		X	O	X	X	X		Resource required and rarely used.
	inherit		X	O	X	X	X		Resource required and rarely used.
counter-reset			X	O	X	O	X	(n/a)	Resource required and rarely used.
	[<identifier> <integer>?]+	all	X	O	X	O	X		Resource required and rarely used.
	none		X	O	X	O	X		Resource required and rarely used.
	inherit		X	O	X	O	X		Resource required and rarely used.
counter-increment			X	O	X	O	X	(n/a)	Resource required and rarely used.
	[<identifier> <integer>?]+	all	X	O	X	O	X		Resource required and rarely used.
	none		X	O	X	O	X		Resource required and rarely used.
	inherit		X	O	X	O	X		Resource required and rarely used.
marker-offset		visual	X	O	X	X	X	(n/a)	
	<length>		X	O	X	X	X		
	auto		X	O	X	X	X		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
	inherit		X	O	X	X	X		
list-style-type	visual	visual	O	O	O	O	O	disc	
	disc		O	O	O	O	O		
	circle		O	O	O	O	O		
	square		O	O	O	O	O		
	decimal		O	O	O	O	O		
	decimal-leading-zero		O	O	O	X	O		
	lower-roman		O	O	O	O	O		
	upper-roman		O	O	O	O	O		
	lower-greek		O	O	O	X	X		Resource required and rarely used.
	lower-alpha		O	O	O	O	O		
	lower-latin		O	O	O	X	O		
	upper-alpha		O	O	O	O	O		
	upper-latin		O	O	O	X	O		
	hebrew		O	O	O	X	X		Resource required and rarely used.
	armenian		O	O	O	X	X		Resource required and rarely used.
	georgian		O	O	O	X	X		Resource required and rarely used.
	ckj-ideographic		O	O	O	X	X		Resource required and rarely used.
	hiragana		O	O	O	X	X		Resource required and rarely used.
	katakana		O	O	O	X	X		Resource required and rarely used.
	hiragana-iroha		O	O	O	X	X		Resource required and rarely used.
	katakana-iroha		O	O	O	X	X		Resource required and rarely used.
	none		O	O	O	O	O		
	inherit		O	O	O	O	O		
list-style-image	visual	visual	O	O	O	O	O	none	
	<uri>		O	O	O	O	O		
	none		O	O	O	O	O		
	inherit		O	O	O	O	O		
list-style-position	visual	visual	O	O	O	O	O	outside	
	inside		O	O	O	O	O		
	outside		O	O	O	O	O		
	inherit		O	O	O	O	O		
list-style	visual	visual	O	O	O	A	O	(see individual properties)	
	'list-style-type' 'list-style-position' 'list-style-image'		O	O	O	A	O		
	inherit		O	O	O	A	O		
Paged media									
size	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
marks	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
page-break-before	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
page-break-after	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
page-break-inside	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
page	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
orphans	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
widows	(omitted)	visual, paged	X	O	X	X	X		paged media is not supported
Colors and Backgrounds									
color		visual	O	O	O	O	O	black	
	<color>		O	O	O	O	O		
	inherit		O	O	O	O	O		
background-color	visual	visual	O	O	O	O	O	transparent	
	<color>		O	O	O	O	O		
	transparent		O	O	O	O	O		
	inherit		O	O	O	O	O		
background-image	visual	visual	O	O	O	O	O	none	
	<uri>		O	O	O	O	O		
	none		O	O	O	O	O		
	inherit		O	O	O	O	O		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
background-repeat		visual	O	O	O	O	O	repeat	background-repeat specified in the THEAD attribute is not supported.
	repeat		O	O	O	O	O		
	repeat-x		O	O	O	O	O		
	repeat-y		O	O	O	O	O		
	no-repeat		O	O	O	O	O		
	inherit		O	O	O	O	O		
background-attachment		visual	O	O	O	O	O	scroll	
	scroll		O	O	O	O	O		
	fixed		O	O	O	O	O		
	inherit		O	O	O	O	O		
background-position		visual	O	O	O	O	O	0% 0%	
	<percentage>(1,2)		O	O	O	A	O		
	<length>(1,2)		O	O	O	A	O		
	[top center bottom] [left center right]		O	O	O	O	O		
	inherit		O	O	O	O	O		
background		visual	O	O	O	O	O	(see individual properties)	
	'background-color' 'background-image' 'background-repeat' 'background-attachment' 'background-position'		O	O	O	O	O		
	inherit		O	O	O	O	O		
Fonts									
font-family			O	O	O	O	O	(according to preference)	
	[[<family-name> <generic-family>],]* [<family-name> <generic-family>]	visual	O	O	O	O	**		Font System dependent
	inherit		O	O	O	O	O		
font-style		visual	O	O	O	O	O	normal	
	normal		O	O	O	O	O		
	italic		O	O	O	O	**		Font System dependent
	oblique		O	O	O	O	**		Font System dependent
	inherit		O	O	O	O	O		
font-variant		visual	O	O	O	O	X	(n/a)	Resource required and rarely used.
	normal		O	O	O	O	O		
	small-caps		O	O	O	O	X		Resource required and rarely used.
	inherit		O	O	O	O	X		Resource required and rarely used.
font-weight		visual	O	O	O	O	O	normal	
	normal		O	O	O	O	O		
	bold		O	O	O	O	**		Font System dependent
	bolder		O	O	O	O	**		Font System dependent
	lighter		O	O	O	O	**		Font System dependent
	100		O	O	O	O	**		Font System dependent
	200		O	O	O	O	**		Font System dependent
	300		O	O	O	O	**		Font System dependent
	400		O	O	O	O	**		Font System dependent
	500		O	O	O	O	**		Font System dependent
	600		O	O	O	O	**		Font System dependent
	700		O	O	O	O	**		Font System dependent
	800		O	O	O	O	**		Font System dependent
	900		O	O	O	O	**		Font System dependent
	inherit		O	O	O	O	O		
font-stretch			X	O	X	X	X	(n/a)	Font System dependent
	normal	visual	X	O	X	X	X		Font System dependent
	wider		X	O	X	X	X		Font System dependent
	narrower		X	O	X	X	X		Font System dependent
	ultra-condensed		X	O	X	X	X		Font System dependent
	extra-condensed		X	O	X	X	X		Font System dependent
	condensed		X	O	X	X	X		Font System dependent

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
	semi-condensed		X	O	X	X	X		Font System dependent
	semi-expanded		X	O	X	X	X		Font System dependent
	expanded		X	O	X	X	X		Font System dependent
	extra-expanded		X	O	X	X	X		Font System dependent
	ultra-expanded		X	O	X	X	X		Font System dependent
	inherit		X	O	X	X	X		
font-size			O	O	O	O	O	medium	
	<absolute-size>	visual	O	O	O	O	O		
	<relative-size>		O	O	O	O	O		
	<length>		O	O	O	A	**		Font System dependent
	<percentage>		O	O	O	A	**		Font System dependent
	inherit		O	O	O	O	O		
font-size-adjust			X	O	X	X	X	(n/a)	Font System dependent
	number	visual	X	O	X	X	X		Font System dependent
	none		X	O	X	X	X		Font System dependent
	inherit		X	O	X	X	X		Font System dependent
font			O	O	O	O	O	(see individual properties)	
	['font-style' 'font-variant' 'font-weight']?'font-size' [/ 'line-height']? 'font-family'	visual	O	O	O	O	**		Font System dependent
	caption		O	O	O	O	**		Font System dependent
	icon		O	O	O	O	X		
	menu		O	O	O	O	X		
	message-box		O	O	O	O	X		
	small-caption		O	O	O	O	X		
	status-bar		O	O	O	O	X		
	inherit		O	O	O	O	O		
Text									
text-indent		visual	O	O	O	O	O	0	text-indent specified in the TABLE attribute, CAPTION attribute, THEAD attribute, and TD attribute is not supported.
	<length>		O	O	O	O	O		
	<percentage>		O	O	O	O	O		
	inherit		O	O	O	O	O		
text-align		visual	O	O	O	O	O	left	
	left		O	O	O	O	O		
	right		O	O	O	O	O		
	center		O	O	O	O	O		
	justify		O	O	O	O	X		Resource required and rarely used.
	<string>		O	O	O	X	X		
	inherit		O	O	O	O	O		
text-decoration		visual	O	O	O	O	O	none	
	underline overline line-through blink		O	O	O	A	O		
	none		O	O	O	O	O		
	inherit		O	O	O	O	O		
text-shadow		visual	X	O	X	X	X	(n/a)	Font System dependent
	[<color> <length> <length> <length>? ,]*		X	O	X	X	X		Font System dependent
	[<color> <length> <length> <length>?]		X	O	X	X	X		Font System dependent
	none		X	O	X	X	X		Font System dependent
	inherit		X	O	X	X	X		Font System dependent
letter-spacing		visual	O	O	X	X	X	(n/a)	
	<length>		O	O	X	X	X		
	normal		O	O	X	X	X		
	inherit		O	O	X	X	X		
word-spacing		visual	O	O	X	X	X	(n/a)	
	<length>		O	O	X	X	X		
	normal		O	O	X	X	X		

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
text-transform	inherit		O	O	X	X	X		
	visual		O	O	O	O	X	(n/a)	Resource required and rarely used.
	capitalize		O	O	O	O	X		Resource required and rarely used.
	uppercase		O	O	O	O	X		Resource required and rarely used.
	lowercase		O	O	O	O	X		Resource required and rarely used.
	none		O	O	O	O	X		Resource required and rarely used.
white-space	inherit		O	O	O	O	X		Resource required and rarely used
	visual		O	O	O	O	O	normal	
	normal		O	O	O	O	O		
	pre		O	O	O	O	X		
	nowrap		O	O	O	O	O		
inherit		O	O	O	O	O			
Tables									
caption-side	visual		X	O	X	X	O	top	
	top		X	O	X	X	O		
	bottom		X	O	X	X	O		
	left		X	O	X	X	X		Resource required and rarely used.
	right		X	O	X	X	X		Resource required and rarely used.
	inherit		X	O	X	X	O		
table-layout	visual		X	O	X	X	X	(n/a)	Resource required and rarely used.
	auto		X	O	X	X	X		Resource required and rarely used.
	fixed		X	O	X	X	X		Resource required and rarely used.
	inherit		X	O	X	X	X		Resource required and rarely used.
border-collapse	visual		X	O	X	X	O	separate	
	collapse		X	O	X	X	O		
	separate		X	O	X	X	O		
	inherit		X	O	X	X	O		
border-spacing	visual		X	O	X	X	O	0	Resource required and rarely used.
	<length> <length>?		X	O	X	X	O		
	inherit		X	O	X	X	X		Resource required and rarely used.
empty-cells	visual		X	O	X	X	O	show	
	show		X	O	X	X	X		Resource required and rarely used.
	hide		X	O	X	X	O		
	inherit		X	O	X	X	O		
speak-header	(omitted)	aural	X	O	X	X	X		aural media is not supported
User Interface (Interactive)									
cursor	visual, interactive		X	O	X	X	X	(n/a)	Graphic System dependent
	[<uri>.* [auto crosshair default pointer move e-resize ne-resize nw-resize n-resize se-resize sw-resize s-resize w-resize text wait help]		X	O	X	X	X		Graphic System dependent
	inherit		X	O	X	X	X		Graphic System dependent
outline	visual, interactive		X	O	X	X	X	(n/a)	Resource required
	outline-color' 'outline-style' 'outline-width'		X	O	X	X	X		Resource required
	inherit		X	O	X	X	X		Resource required
outline-width	visual, interactive		X	O	X	X	X	(n/a)	Resource required
	<border-width>		X	O	X	X	X		Resource required
	inherit		X	O	X	X	X		Resource required
outline-style	visual, interactive		X	O	X	X	X	(n/a)	Resource required
	<border-style>		X	O	X	X	X		Resource required
	inherit		X	O	X	X	X		Resource required
outline-color	visual, interactive		X	O	X	X	X	(n/a)	Resource required
	<color>		X	O	X	X	X		Resource required
	invert		X	O	X	X	X		Resource required
	inherit		X	O	X	X	X		Resource required
Aural style sheets									
volume	(omitted)	aural	X	O	X	X	X		aural media is not supported

Properties	Values	Media groups	CSS1	CSS2	CSS Mobile Profile 1.0	WAP CSS Specification	NF3 for iR Series	NF3 for iR Series default value	NF3 for iR Series Remarks
speak	(omitted)	aural	X	O	X	X	X		aural media is not supported
pause-before	(omitted)	aural	X	O	X	X	X		aural media is not supported
pause-after	(omitted)	aural	X	O	X	X	X		aural media is not supported
pause	(omitted)	aural	X	O	X	X	X		aural media is not supported
cue-before	(omitted)	aural	X	O	X	X	X		aural media is not supported
cue-after	(omitted)	aural	X	O	X	X	X		aural media is not supported
cue	(omitted)	aural	X	O	X	X	X		aural media is not supported
play-during	(omitted)	aural	X	O	X	X	X		aural media is not supported
azimuth	(omitted)	aural	X	O	X	X	X		aural media is not supported
elevation	(omitted)	aural	X	O	X	X	X		aural media is not supported
speech-rate	(omitted)	aural	X	O	X	X	X		aural media is not supported
voice-family	(omitted)	aural	X	O	X	X	X		aural media is not supported
pitch	(omitted)	aural	X	O	X	X	X		aural media is not supported
pitch-range	(omitted)	aural	X	O	X	X	X		aural media is not supported
stress	(omitted)	aural	X	O	X	X	X		aural media is not supported
richness	(omitted)	aural	X	O	X	X	X		aural media is not supported
speak-punctuation	(omitted)	aural	X	O	X	X	X		aural media is not supported
speak-numeral	(omitted)	aural	X	O	X	X	X		aural media is not supported

Chapter 3

ECMAScript Properties/Methods

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
Global	(Value Properties)					
	NaN	O	O	O	O	
	Infinity	O	O	O	O	
	undefined	O	O	O	O	
	(Functions Properties)					
	eval(x)	O	O	O	O	
	parseInt(string [, radix])	O	O	O	O	
	parseFloat(string)	O	O	O	O	
	isNaN(number)	O	O	O	O	
	isFinite(number)	O	O	O	O	
	(URI Handling Function Properties)					
	decodeURI(encodedURI)	O	X	X	O	
	decodeURIComponent(edcodedURIComponent)	O	X	X	O	
	encodeURI(uri)	O	X	X	O	
	encodeURIComponent(uriComponent)	O	X	X	O	
	taint([dataElementName])	X	X	X	X	
	untaint([dataElementName])	X	X	X	X	
	escape(string)	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	unescape(string)	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	Objects	(as a Function)				
Object(value)		O	O	O	O	
(Constructor)						
new Object([value])		O	O	O	O	
(Properties of the Object Constructor)						
length		O	O	O	O	
prototype		O	O	O	O	
(Properties of the Object Prototype Object)						
constructor		O	O	O	O	
toString()		O	O	O	O	
toLocaleString()		O	X	X	O	
valueOf()		O	O	O	O	
hasOwnProperty(V)		O	X	X	O	
isPrototypeOf(V)		O	X	X	O	
propertyIsEnumerable(V)		O	X	X	O	
eval(string)		X	O	X	X	
toSource()		X	O	O	X	
unwatch(prop)		X	O	O	X	
watch(prop, handler)		X	O	O	X	

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks	
Function	(as a Function)						
	Function([p1, p2, ... , pN,] body)	O	O	O	O		
	(Constructor)						
	new Function([p1, p2, ... , pN,] body)	O	O	O	O		
	(Properties of the Function Constructor)						
	length	O	O	O	O		
	prototype	O	O	O	O		
	(Properties of the Function Prototype Object)						
	constructor	O	O	O	O		
	toString()	O	O	O	O		
	apply(thisArg [, argArray])	O	O	O	O		
	call(thisArg [, arg1, arg2, ... , argN])	O	O	O	O		
	toSource()	X	O	O	X		
	(Properties of Function Instances)						
	length	O	O	O	O		
	prototype	O	O	O	O		
	arity	X	O	O	X		
	Arguments	(Properties)					
		callee	O	O	O	O	
		caller	X	O	O	X	
length		O	O	O	O		
Array	(as a Function)						
	Array([item1, item2, ... , itemN])	O	O	O	O		
	(Constructors)						
	new Array([item0, item1, ... , itemN])	O	O	O	O		
	new Array(len)	O	O	O	O		
	(Properties of the Array Constructor)						
	length	O	O	O	O		
	prototype	O	O	O	O		
	(Properties of the Array Prototype Object)						
	constructor	O	O	O	O		
	toString()	O	O	O	O		
	toLocaleString()	O	X	X	O		
	concat([item1, item2, ... , itemN])	O	O	O	O		
	join(separator)	O	O	O	O		
	pop()	O	O	O	O		
	push([item1, item2, ... , itemN])	O	O	O	O		
	reverse()	O	O	O	O		
	shift()	O	O	O	O		
	slice(start [, end])	O	O	O	O		
	sort(comparefn)	O	O	O	O		
	splice(start, deleteCount [, item1, item2, ... , itemN])	O	O	O	O		
	unshift([item1, item2, ... , itemN])	O	O	O	O		
	toSource()	X	O	O	X		
	(Properties of Array Instances)						

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
	length	O	O	O	O	
	index	O	O	O	O	For a return value of RegExp.prototype.exec() etc.
	input	O	O	O	O	For a return value of RegExp.prototype.exec() etc.
String	(as a Function)					
	String([value])	O	O	O	O	
	(Constructor)					
	new String([value])	O	O	O	O	
	(Properties of the String Constructor)					
	length	O	O	O	O	
	prototype	O	O	O	O	
	fromCharCode([code0, code1, ..., codeN])	O	O	O	O	
	(Properties of the String Prototype Object)					
	constructor	O	O	O	O	
	toString()	O	O	O	O	
	valueOf()	O	O	O	O	
	charAt(pos)	O	O	O	O	
	charCodeAt(pos)	O	O	O	O	
	concat([item1, item2, ..., itemN])	O	O	O	O	
	indexOf(pattern [, pos])	O	O	O	O	
	lastIndexOf(pattern [, pos])	O	O	O	O	
	localeCompare(that)	O	X	X	O	
	match(regex)	O	O	O	O	
	replace(searchValue, replaceValue)	O	O	O	O	
	search(regex)	O	O	O	O	
	slice(start [, end])	O	O	O	O	
	split(separator [, lim])	O	O	O	O	
	substring(start, end)	O	O	O	O	
	substr(start [, length])	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	toLowerCase()	O	O	O	O	
	toLocaleLowerCase()	O	X	X	O	
	toUpperCase()	O	O	O	O	
	toLocaleUpperCase()	O	X	X	O	
	anchor(string)	X	O	O	O	A Netscape extension
	link(string)	X	O	O	O	A Netscape extension
	fontcolor(string)	X	O	O	O	A Netscape extension
	fontsize(string)	X	O	O	O	A Netscape extension
	big()	X	O	O	O	A Netscape extension
	blink()	X	O	O	O	A Netscape extension
	bold()	X	O	O	O	A Netscape extension
	fixed()	X	O	O	O	A Netscape extension
	italics()	X	O	O	O	A Netscape extension
	small()	X	O	O	O	A Netscape extension
	strike()	X	O	O	O	A Netscape extension
sub()	X	O	O	O	A Netscape extension	
sup()	X	O	O	O	A Netscape extension	
toSource()	X	O	O	X		
(Properties of String Instances)						

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
Boolean	string.length	O	O	O	O	
	(as a Function)					
	Boolean(value)	O	O	O	O	
	(Constructor)					
	new Boolean(value)	O	O	O	O	
	(Properties of the Boolean Constructor)					
	length	O	O	O	O	
	prototype	O	O	O	O	
	(Properties of the Boolean Prototype Object)					
	constructor	O	O	O	O	
	toString()	O	O	O	O	
	valueOf()	O	O	O	O	
	toSource()	X	O	O	X	
	Number	(as a Function)				
Number([value])		O	O	O	O	
(Constructor)						
new Number([value])		O	O	O	O	
(Properties of the Number Constructor)						
length		O	O	O	O	
prototype		O	O	O	O	
MAX_VALUE		O	O	O	O	
MIN_VALUE		O	O	O	O	
NaN		O	O	O	O	
NEGATIVE_INFINITY		O	O	O	O	
POSITIVE_INFINITY		O	O	O	O	
(Properties of the Number Prototype Object)						
constructor		O	O	O	O	
toString([radix])		O	O	O	O	
toLocaleString()		O	X	X	O	
valueOf()		O	O	O	O	
toFixed(fractionDigits)		O	X	X	O	Added for JavaScript 1.5
toExponential(fractionDigits)		O	X	X	O	Added for JavaScript 1.5
toPrecision(precision)		O	X	X	O	Added for JavaScript 1.5
toSource()		X	O	O	X	

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks	
Math	(Value Properties)						
	E	O	O	O	O		
	LN10	O	O	O	O		
	LN2	O	O	O	O		
	LOG2E	O	O	O	O		
	LOG10E	O	O	O	O		
	PI	O	O	O	O		
	SQRT1_2	O	O	O	O		
	SQRT2	O	O	O	O		
	(Function Properties)						
	abs(x)	O	O	O	O		
	acos(x)	O	O	O	O		
	asin(x)	O	O	O	O		
	atan(x)	O	O	O	O		
	atan2(y, x)	O	O	O	O		
	ceil(x)	O	O	O	O		
	cos(x)	O	O	O	O		
	exp(x)	O	O	O	O		
	floor(x)	O	O	O	O		
	log(x)	O	O	O	O		
	max([value1, value2, ... , valueN])	O	O	O	O		
	min([value1, value2, ... , valueN])	O	O	O	O		
	pow(x, y)	O	O	O	O		
	random()	O	O	O	O		
	round(x)	O	O	O	O		
	sin(x)	O	O	O	O		
	sqrt(x)	O	O	O	O		
	tan(x)	O	O	O	O		
	Date	(as a Function)					
		Date (year, month, date, hours, minutes, seconds, ms)	O	O	O	O	
(Constructors)							
new Date(year, month [, date, hours, minutes, seconds, ms])		O	O	O	O		
new Date()		O	O	O	O		
new Date(milliseconds)		O	O	O	O		
new Date(dateString)		O	O	O	O		
(Properties of the Date Constructor)							
length		O	O	O	O		
prototype		O	O	O	O		
parse(string)		O	O	O	O		
UTC(year, month [, date, hours, minutes, seconds, ms])	O	O	O	O			

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
	(Properties of the Date Prototype Object)					
	constructor	O	O	O	O	
	toString()	O	O	O	O	
	toDateString()	O	X	X	O	
	toTimeString()	O	X	X	O	
	toLocaleString()	O	O	O	O	
	toLocaleDateString()	O	X	X	O	
	toLocaleTimeString()	O	X	X	O	
	valueOf()	O	O	O	O	
	getTime()	O	O	O	O	
	getFullYear()	O	O	O	O	
	getUTCFullYear()	O	O	O	O	
	getMonth()	O	O	O	O	
	getUTCMonth()	O	O	O	O	
	getDate()	O	O	O	O	
	getUTCDate()	O	O	O	O	
	getDay()	O	O	O	O	
	getUTCDay()	O	O	O	O	
	getHours()	O	O	O	O	
	getUTCHours()	O	O	O	O	
	getMinutes()	O	O	O	O	
	getUTCMinutes()	O	O	O	O	
	getSeconds()	O	O	O	O	
	getUTCSeconds()	O	O	O	O	
	getMilliseconds()	O	O	O	O	
	getUTCMilliseconds()	O	O	O	O	
	getTimezoneOffset()	O	O	O	O	
	setTime(time)	O	O	O	O	
	setMilliseconds(ms)	O	O	O	O	
	setUTCMilliseconds(ms)	O	O	O	O	
	setSeconds(sec [, ms])	O	O	O	O	
	setUTCSeconds(sec [, ms])	O	O	O	O	
	setMinutes(minute [, sec, ms])	O	O	O	O	
	setUTCMinutes(minute [, sec, ms])	O	O	O	O	
	setHours(hour [, minute, sec, ms])	O	O	O	O	
	setUTCHours(hour [, minute, sec, ms])	O	O	O	O	
	setDate(date)	O	O	O	O	
	setUTCDate(date)	O	O	O	O	
	setMonth(month [, date])	O	O	O	O	
	setUTCMonth(month [, date])	O	O	O	O	
	setFullYear(year [, month, date])	O	O	O	O	
	setUTCFullYear(year [, month, date])	O	O	O	O	
	toUTCString()	O	O	O	O	
	toGMTString()	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	getFullYear()	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	setYear(year)	O	O	O	O	Described in appendix of ECMA-262 3rd Spec.
	toSource()	X	O	O	X	

Objects	Constructors/Properties/Methods	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
RegExp	(as a Function)					
	RegExp(pattern [, flags])	O	O	O	O	
	(Constructor)					
	new RegExp(pattern [, flags])	O	O	O	O	
	(Properties of the RegExp Constructor)					
	length	O	O	O	O	
	prototype	O	O	O	O	
	\$1...\$9	X	O	O	X	
	input(also \$_)	X	O	O	X	
	lastMatch(also \$\$)	X	O	O	X	
	lastParen(also \$+)	X	O	O	X	
	leftContext(also \$')	X	O	O	X	
	rightContext(also \$')	X	O	O	X	
	multiline(also \$*)	X	O	O	X	
	(Properties of the RegExp Prototype Object)					
	constructor	O	O	O	O	
	exec([string])	O	O	O	O	
	test([string])	O	O	O	O	
	toString()	O	O	O	O	
	compile(pattern [, flags])	X	O	O	X	
	toSource()	X	O	O	X	
	valueOf()	O	O	O	O	
	(Properties of RegExp Instances)					
	source	O	O	O	O	
	global	O	O	O	O	
	ignoreCase	O	O	O	O	
	multiline	O	X	X	O	
lastIndex	O	O	O	O		
Error	(as a Function)					
	Error(message)	O	X	X	O	Added for JavaScript 1.5
	(Constructor)					
	new Error(message)	O	X	X	O	Added for JavaScript 1.5
	(Properties of the Error Constructor)					
	length	O	X	X	O	Added for JavaScript 1.5
	prototype	O	X	X	O	Added for JavaScript 1.5
	(Properties of the Error Prototype Object)					
	constructor	O	X	X	O	Added for JavaScript 1.5
	name	O	X	X	O	Added for JavaScript 1.5
message	O	X	X	O	Added for JavaScript 1.5	
toString()	O	X	X	O		
EvalError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5
RangeError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5
ReferenceError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5
SyntaxError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5
TypeError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5
URIError	The same as "Error Object"	O	X	X	O	Added for JavaScript 1.5

Chapter 4

ECMAScript Statements

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Statements	Syntax	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
Variable Statement	var varname [= value] [..., varname [= value]]	O	O	O	O	
Empty Statement	;	O	O	O	O	
if Statement	if (condition) { statements1 } [else { statements2 }]	O	O	O	O	
Iteration Statements	do statements while (condition);	O	O	O	O	If the loop timer reaches the limit, it stops executing the script (to avoid an infinite loop). The default limit is 1,000,000.
	while (condition) { statements }	O	O	O	O	If the loop timer reaches the limit, it stops executing the script (to avoid an infinite loop). The default limit is 1,000,000.
	for ([initial-expression]; [condition]; [increment-expression]) { statements }	O	O	O	O	If the loop timer reaches the limit, it stops executing the script (to avoid an infinite loop). The default limit is 1,000,000.
	for (variable in object) { statements }	O	O	O	O	If the loop timer reaches the limit, it stops executing the script (to avoid an infinite loop). The default limit is 1,000,000.
continue Statement	continue [label]	O	O	O	O	
break Statement	break [label]	O	O	O	O	
return Statement	return expression	O	O	O	O	
with Statement	with (object) { statements }	O	O	O	O	
label Statement	label : statements	O	O	O	O	

Statements	Syntax	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.?)	NF3 for iR Series	NF3 for iR Series Remarks
switch Statement	switch (expression) { case label : statements; break; case label : statements; break; ... default : statements; }	O	O	O	O	
throw Statement	throw expression	O	X	O	O	
try Statement	try { statements } [catch (catchID) { statements }] [finally { statements }]	O	X	O	O	
function Statement	function name([param][,param] [..., param]) { statements }	O	O	O	O	
Comments	// comment text /* multiple line comment text */	O	O	O	O	
export Statement	export name1, name2, ..., nameN export *	X	O	O	X	
import Statement	import objectName. name1, objectName. name2,...,objectName. nameN import objectName.*	X	O	O	X	

Chapter 5

ECMAScript Operators

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Operators	Syntax	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.7)	NF3 for iR Series	NF3 for iR Series Remarks
Arithmetic Operators	x ++	O	O	O	O	
	++ x	O	O	O	O	
	+ x	O	O	O	O	
	x --	O	O	O	O	
	-- x	O	O	O	O	
	- x	O	O	O	O	
	x + y	O	O	O	O	
	x - y	O	O	O	O	
	x * y	O	O	O	O	
	x / y	O	O	O	O	
Comparison Operators	x % y	O	O	O	O	
	x == y	O	O	O	O	
	x != y	O	O	O	O	
	x === y	O	O	O	O	
	x !== y	O	O	O	O	
	x > y	O	O	O	O	
	x >= y	O	O	O	O	
	x < y	O	O	O	O	
Bitwise Operators	x <= y	O	O	O	O	
	x & y	O	O	O	O	
	x y	O	O	O	O	
	x ^ y	O	O	O	O	
	~ x	O	O	O	O	
	x << y	O	O	O	O	
	x >> y	O	O	O	O	
Logical Operators	x >>> y	O	O	O	O	
	expr1 && expr2	O	O	O	O	
	expr1 expr2	O	O	O	O	
	! expr	O	O	O	O	

Operators	Syntax	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.7)	NF3 for iR Series	NF3 for iR Series Remarks
Assignment Operators	x = y	O	O	O	O	
	x += y	O	O	O	O	
	x -= y	O	O	O	O	
	x *= y	O	O	O	O	
	x /= y	O	O	O	O	
	x %= y	O	O	O	O	
	x <<= y	O	O	O	O	
	x >>= y	O	O	O	O	
	x >>>= y	O	O	O	O	
	x &= y	O	O	O	O	
	x ^= y	O	O	O	O	
	x = y	O	O	O	O	
	String Operators	string + string	O	O	O	O
string += string		O	O	O	O	
Conditional Operator	condition ? expr1 : expr2	O	O	O	O	
Comma Operator	expr1, expr2	O	O	O	O	
delete Operators	delete objectName	O	O	O	O	
	delete objectName. property	O	O	O	O	
	delete objectName[index]	O	O	O	O	
	delete property	O	O	O	O	
new Operator	objectName = new objectType (param1 [, param2] ...[, paramN])	O	O	O	O	
typeof Operators	typeof operand	O	O	O	O	
	typeof (operand)	O	O	O	O	
void Operators	void (expression)	O	O	O	O	
	void expression	O	O	O	O	
instanceof Operator	objectName instanceof objectType	O	X	O	O	
in Operator	propNameOrNumber in objectName	O	X	O	O	
this keyword	this[. propertyName]	O	O	O	O	
Others	[]	O	O	O	O	
	()	O	O	O	O	
	.	O	O	O	O	

Chapter 6

ECMAScript Types and Literals

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Types	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.x)	NF3 for iR Series	NF3 for iR Series Remarks
Undefined Type	O	O	O	O	
Null Type	O	O	O	O	
Boolean Type	O	O	O	O	
Number Type	O	O	O	O	
String Type	O	O	O	O	
Object Type	O	O	O	O	

Literals	ECMA-262 3rd Edition	JavaScript 1.3 (Netscape 4.06)	JavaScript 1.4 (Netscape 4.x)	NF3 for iR Series	NF3 for iR Series Remarks
Boolean values	O	O	O	O	
Numbers	O	O	O	O	
Strings	O	O	O	O	
Array	O	O	O	O	
Object	O	O	O	O	
null	O	O	O	O	

Chapter 7

DOM0 ECMAScript Binding

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Objects	Attributes/Methods/Event Handlers/Constructors	Types	Read only	JavaScript 1.3 (NetScape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
Navigator	(Attributes)						
	appName	DOMString	O	O	O		
	appVersion	DOMString	O	O	O		
	language	DOMString	O	O	O		
	mimeTypes	MimeTypeArray	O	O	O		
	platform	DOMString	O	O	O		
	oscpu	DOMString	O	X	X	Resource required and rarely used	
	vendor	DOMString	O	X	X	Resource required and rarely used	
	vendorSub	DOMString	O	X	X	Resource required and rarely used	
	product	DOMString	O	X	X	Resource required and rarely used	
	productSub	DOMString	O	X	X	Resource required and rarely used	
	plugins	PluginArray	O	O	O		
	securityPolicy	DOMString	O	X	X	Resource required and rarely used	
	userAgent	DOMString	O	O	O		
	cookieEnabled	boolean	O	X	X	Resource required and rarely used	
	(Methods)						
	javaEnabled()	boolean	-	O	X	Resource required and rarely used	
preference(in DOMString prefName [, in DOMString setValue])	boolean/long	-	O	X	Resource required and rarely used		
savePreferences()	void	-	O	X	Resource required and rarely used		
taintEnabled()	boolean	-	X	X	Resource required and rarely used		
MimeTypeArray	(Attributes)						
	length	unsigned long	O	O	O		
	[index]	MimeType	O	O	O		
	["name"]	MimeType	O	O	O		
	.name	MimeType	O	X	O		
MimeType	(Attributes)						
	description	DOMString	O	O	O		
	enabledPlugin	Plugin	O	O	O		
	suffixes	DOMString	O	O	O		
PluginArray	(Attributes)						
	length	unsigned long	O	O	O		
	(Methods)						
	refresh(in boolean reload)	void	-	O	O		
	[index]	Plugin	O	O	O		
	["name"]	Plugin	O	O	O		
Plugin	(Attributes)						
	description	DOMString	O	O	O		
	filename	DOMString	O	O	O		
	length	unsigned long	O	O	O		
	name	DOMString	O	O	O		
Screen	(Attributes)						
	availHeight	long	O	O	O		
	availLeft	long	O	O	X	Less meaning for mobile browser	
	availTop	long	O	O	X	Less meaning for mobile browser	
	availWidth	long	O	O	O		
	colorDepth	long	O	O	O		
	height	long	O	O	O		
	pixelDepth	long	O	O	O		
	width	long	O	O	O		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	Read only	JavaScript 1.3 (NetScape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	
WindowCollection	(Attributes)							
	length	unsigned long	O	O	O			
	[index]	Window	X	O	O			
	["name"]	Window	X	O	O			
	.name	Window	X	X	O			
Window	(Attributes)							
	closed	boolean	O	O	O			
	crypto	Crypto	O	O	X			
	defaultStatus	DOMString	X	O	X	Resource required and rarely used		
	document	HTMLDocument	O	O	O			
	frames	WindowCollection	O	O	O			
	history	History	O	O	O			
	innerHeight	long	X	O	O	No support for rewriting innerHeight		
	innerWidth	long	X	O	O			
	length	unsigned long	O	O	O			
	location	Location	X	O	O		setlocation to new URL	
	locationbar	Bar	O	O	X	Less meaning for mobile browser		
	menubar	Bar	O	O	X	Less meaning for mobile browser		
	name	DOMString	X	O	O		name is changed	
	navigator	Navigator	O	X	O			
	offscreenBuffering	boolean	X	O	X	Resource required and rarely used		
	opener	Window	X	O	O			
	outerHeight	long	X	O	X	Less meaning for mobile browser		
	outerWidth	long	X	O	X	Less meaning for mobile browser		
	pageXOffset	long	O	O	X	Less meaning for mobile browser		
	pageYOffset	long	O	O	X	Less meaning for mobile browser		
	parent	Window	O	O	O			
	personalbar	Bar	O	O	X	Less meaning for mobile browser		
	screen	Screen	O	X	X	Less meaning for mobile browser		
	screenX	long	X	O	X	Less meaning for mobile browser		
	screenY	long	X	O	X	Less meaning for mobile browser		
	scrollbars	Bar	O	O	X	Less meaning for mobile browser		
	self	Window	O	O	O			
	status	DOMString	X	O	X			
	statusbar	Bar	O	O	X	Less meaning for mobile browser		
	toolbar	Bar	O	O	O			
	top	Window	O	O	O			
	window	Window	O	O	O			
		(Methods)						
		alert(in DOMString message)	void	-	O	O		
		atob(encodedData)		-	O	X		
		back()	void	-	O	O		
		blur()	void	-	O	X		
		btoa(stringToEncode)		-	O	X		
		captureEvents(eventType1 [, eventTypeN...])	void	-	O	X		
		clearInterval(in long intervalID)	void	-	O	O		
		clearTimeout(in long timeoutID)	void	-	O	O		
		close()	void	-	O	X		
		confirm(in DOMString message)	boolean	-	O	O		
		disableExternalCapture()	void	-	O	X		
		enableExternalCapture()	void	-	O	X		
		find(in DOMString string, in boolean caseSensitive, in boolean backward)	boolean	-	O	X		
	focus()	void	-	O	X			
	forward()	void	-	O	O			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	Read only	JavaScript 1.3 (NetScape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
	handleEvent(event)	void	-	O	X		
	home()	void	-	O	O		
	moveBy(in long horizontal, in long vertical)	void	-	O	X		
	moveTo(in long x-coordinate, in long y-coordinate)	void	-	O	X		
	open(in DOMString URL, in DOMString windowName, in DOMString windowFeatures)	Window	-	O	X		
	print()	void	-	O	X		
	prompt(in DOMString message, in DOMString inputDefault / in DOMString message, in long inputDefault)	DOMString	-	O	O		
	releaseEvents(eventType1 [, eventTypeN...])	void	-	O	X		
	resizeBy(in long horizontal, in long vertical)	void	-	O	X		
	resizeTo(in long outerWidth, in long outerHeight)	void	-	O	X		
	routeEvent(event)	void	-	O	X		
	scroll(in long x-coordinate, in long y-coordinate)	void	-	O	O		
	scrollBy(in long horizontal, in long vertical)	void	-	O	O		
	scrollTo (in long x-coordinate, in long y-coordinate)	void	-	O	O		
	setHotKeys(in boolean setting)		-	O	X		
	setInterval(in DOMString expression, in long msec, in Function function, in long msec, in arg1, argN)	long	-	O	O		
	setResizable(in boolean setting)		-	O	X		
	setTimeout(in DOMString expression, in long msec, in Function function, in long msec, in arg1, argN)	long	-	O	O		
	setZOptions(windowPosition)		-	O	X		
	stop()	void	-	O	O		
	(Event Handlers)						
	onblur	n/a	-	O	O	Less meaning for mobile browser	event handler is replaced
	ondragdrop	n/a	-	O	X	Less meaning for mobile browser	
	onerror	n/a	-	O	X	Resource required and rarely used	
	onfocus	n/a	-	O	O	As for each support, refer to each element	event handler is replaced
	onload	n/a	-	O	O	As for each support, refer to each element	event handler is replaced
	onmove	n/a	-	O	X	Less meaning for mobile browser	
	onresize	n/a	-	O	X	Less meaning for mobile browser	
	onunload	n/a	-	O	O	As for each support, refer to each element	event handler is replaced
	onabort	n/a	-	X	X	Resource required and rarely used	
	onchange	n/a	-	X	O	As for each support, refer to each element	
	onclick	n/a	-	X	O	As for each support, refer to each element	
	onclose	n/a	-	X	X	Resource required and rarely used	
	onkeydown	n/a	-	X	O	As for each support, refer to each element	
	onkeypress	n/a	-	X	O	As for each support, refer to each element	
	onkeyup	n/a	-	X	X	Resource required and rarely used	
	onmousedown	n/a	-	X	O	As for each support, refer to each element	
	onmousemove	n/a	-	X	X	As for each support, refer to each element	
	onmouseout	n/a	-	X	O	As for each support, refer to each element	
	onmouseover	n/a	-	X	O	As for each support, refer to each element	
	onmouseup	n/a	-	X	O	As for each support, refer to each element	
	onpaint	n/a	-	X	X	Resource required and rarely used	
	onreset	n/a	-	X	X	Resource required and rarely used	
	onscroll	n/a	-	X	X	Resource required and rarely used	
	onselect	n/a	-	X	X	Resource required and rarely used	
	onsubmit	n/a	-	X	X	Resource required and rarely used	
	(Constructor)						
	new window()	n/a	-	O	X		
History	(Attributes)						
	current	DOMString	O	O	X	Does not support for security reason	
	length	unsigned long	O	O	O		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	Read only	JavaScript 1.3 (NetScape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
	next	DOMString	O	O	X	Does not support for security reason	
	previous	DOMString	O	O	X	Does not support for security reason	
	(Methods)						
	back()	void	-	O	O		
	forward()	void	-	O	O		
	go(in long delta / in DOMString location)	void	-	O	O		
location	(Attributes)						
	hash	DOMString	X	O	O		setlocation to new URL
	host	DOMString	X	O	O		setlocation to new URL
	hostname	DOMString	X	O	O		setlocation to new URL
	href	DOMString	X	O	O		setlocation to new URL
	pathname	DOMString	X	O	O		setlocation to new URL
	port	DOMString	X	O	O		setlocation to new URL
	protocol	DOMString	X	O	O		setlocation to new URL
	search	DOMString	X	O	O		setlocation to new URL
	(Methods)						
	reload((in boolean forceGet))	void	-	O	O		
	replace(in DOMString URL)	void	-	O	O		
	toString()	DOMString	-	X	O		
Bar	(Methods)						
	visible	boolean	O	X	X	Less meaning for mobile browser	
Crypto	(Methods)						
	random(numberOfBytes)	DOMString	-	O	X	Resource required and rarely used	
	signText(text, selectionStyle [, authority1 [, authorityN...]])	DOMString	-	O	X		

Chapter 8

DOM Core Level1,2

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

Objects	Attributes/Methods	Exception	Types	DOM1	Read only	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
DOMException	(Attributes) code		unsigned short	O	X	X	Resource required and rarely used	
DOMImplementation	(Methods) hasFeature (in DOMString feature, in DOMString version)		boolean	O	-	O		
	createDocumentType	raises (DOMException)	DocumentType	X	-	X	DOM2	
	createDocument	raises (DOMException)	Document	X	-	X	DOM2	
DocumentFragment				O	-	X	Resource required and rarely used	
Document	(Attributes) doctype implementation documentElement		DocumentType DOMImplementation Element	O O O	O O O	X O O		
	(Methods) createElement(in DOMString tagName)	raises (DOMException)	Element	O	-	X	Dynamic document tree manipulation requires resource	
	createDocumentFragment()		DocumentFragment	O	-	X	Dynamic document tree manipulation requires resource	
	createTextNode(in DOMString data)		Text	O	-	X	Dynamic document tree manipulation requires resource	
	createComment(in DOMString data)		Comment	O	-	X	Dynamic document tree manipulation requires resource	
	createCDATASection(in DOMString data)	raises (DOMException)	CDATASection	O	-	X	Dynamic document tree manipulation requires resource	
	createProcessingInstruction (in DOMString target, in DOMString data)	raises (DOMException)	ProcessingInstruction	O	-	X	Dynamic document tree manipulation requires resource	
	createAttribute(in DOMString name)	raises (DOMException)	Attr	O	-	X	Dynamic document tree manipulation requires resource	
	createEntityReference (in DOMString name)	raises (DOMException)	EntityReference	O	-	X	Dynamic document tree manipulation requires resource	
	getElementsByTagName (in DOMString tagname)		NodeList	O	-	O		
	importNode (in Node importedNode, in boolean deep)	raises (DOMException)	Node	X	-	X	DOM2	
	createElementNS (in DOMString namespaceURI, in DOMString qualifiedName)	raises (DOMException)	Element	X	-	X	DOM2	
	createAttributeNS (in DOMString namespaceURI, in DOMString qualifiedName)	raises (DOMException)	Attr	X	-	X	DOM2	
	getElementsByTagNameNS (in DOMString namespaceURI, in DOMString localName)		NodeList	X	-	X	DOM2	
	getElementById(in DOMString elementId)		Element	X	-	O	DOM2	

Objects	Attributes/Methods	Exception	Types	DOM1	Read only	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
Node	(Attributes)							
	nodeName		DOMString	O	O	O	CDATA section is handled as a normal text without creating a node.	
	nodeValue	raises(DOMException) on setting raises(DOMException) on retrieval	DOMString	O	X	O	Implementation of overwriting "node.nodeValue" is limited to text node.	no support
	nodeType		unsigned short	O	O	O		
	parentNode		Node	O	O	O		
	childNodes		NodeList	O	O	O	Comment is not recognized as a node, but splits a Text node.	
	firstChild		Node	O	O	O	Even in the case of whitespace only, it is interpreted as a Text node.	
	lastChild		Node	O	O	O	How to handle white spaces and CR depends on browser.	
	previousSibling		Node	O	O	O	How to handle white spaces and CR depends on browser.	
	nextSibling		Node	O	O	O	How to handle white spaces and CR depends on browser.	
	attributes		NamedNodeMap	O	O	O	How to handle white spaces and CR depends on browser.	
	ownerDocument		Document	X	O	O		
	(Methods)							
	insertBefore(in Node newChild, in Node refChild)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	replaceChild(in Node newChild, in Node oldChild)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	removeChild(in Node oldChild)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	appendChild(in Node newChild)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	hasChildNodes()		boolean	O	-	O		
	cloneNode(in boolean deep)		Node	O	-	X	Dynamic document tree manipulation requires resource	
	normalize()		void	X	-	X	DOM2	
	isSupported(in DOMString feature, in DOMString version)		boolean	X	-	X	DOM2	
	namespaceURI		DOMString	X	-	X	DOM2	
	prefix	raises(DOMException) on setting	DOMString	X	-	X	DOM2	
	localName		DOMString	X	-	X	DOM2	
	hasAttributes()		boolean	X	-	X	DOM2	

Objects	Attributes/Methods	Exception	Types	DOM1	Read only	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
NodeList	(Attributes)							
	length		unsigned long	O	O	O	Tags not relating to rendering create no node objects, to save memory.	
	(Methods)							
NamedNodeMap	item(in unsigned long index)		Node	O	-	O	Tags not relating to rendering create no node objects, to save memory.	
	(Attributes)							
	length		unsigned long	O	O	O		
	(Methods)							
	getNamedItem(in DOMString name)		Node	O	-	O		
	setNamedItem(in Node arg)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	removeNamedItem(in DOMString name)	raises (DOMException)	Node	O	-	X	Dynamic document tree manipulation requires resource	
	item(in unsigned long index)		Node	O	-	O		
	getNamedItemNS(in DOMString namespaceURI, in DOMString localName)		Node	X	-	X	DOM2	
setNamedItemNS(in Node arg)	raises(DOMException)	Node	X	-	X	DOM2		
removeNamedItemNS(in DOMString namespaceURI, in DOMString localName)	raises(DOMException)	Node	X	-	X	DOM2		
CharacterData	(Attributes)							
	data	raises(DOMException) on setting raises(DOMException) on retrieval	DOMString	O	X	O		
	length		unsigned long	O	O	O		
	(Methods)							
	substringData(in unsigned long offset, in unsigned long count)	raises (DOMException)	DOMString	O	-	O		
	appendData(in DOMString arg)	raises (DOMException)	void	O	-	X	Dynamic document tree manipulation requires resource	
	insertData(in unsigned long offset, in DOMString arg)	raises (DOMException)	void	O	-	X	Dynamic document tree manipulation requires resource	
	deleteData(in unsigned long offset, in unsigned long count)	raises (DOMException)	void	O	-	X	Dynamic document tree manipulation requires resource	
replaceData(in unsigned long offset, in unsigned long count, in DOMString arg)	raises (DOMException)	void	O	-	X	Dynamic document tree manipulation requires resource		
Attr	(Attributes)							
	name		DOMString	O	O	O		
	specified		boolean	O	O	O		
	value		DOMString	O	X	O		no support
	ownerElement		ownerElement	X	O	X	DOM2	

Objects	Attributes/Methods	Exception	Types	DOM1	Read only	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
Element	(Attributes)							
	tagName		DOMString	O	O	O		
	(Methods)							
	getAttribute(in DOMString name)		DOMString	O	-	O		
	setAttribute (in DOMString name, in DOMString value)	raises (DOMException)	void	O	-	O		
	removeAttribute (in DOMString name)	raises (DOMException)	void	O	-	X	Dynamic document tree manipulation requires resource	
	getAttributeNode (in DOMString name)		Attr	O	-	O		
	setAttributeNode (in Attr newAttr)	raises (DOMException)	Attr	O	-	X	Dynamic document tree manipulation requires resource	
	removeAttributeNode (in Attr oldAttr)	raises (DOMException)	Attr	O	-	X	Dynamic document tree manipulation requires resource	
	getElementsByTagName (in DOMString name)		NodeList	O	-	O		
	normalize()		void	O	-	X	Dynamic document tree manipulation requires resource	
	getAttributeNS (namespaceURI, localName);		DOMString	X	-	X	DOM2	
	setAttributeNS (namespaceURI,qualifiedName)	raises (DOMException)	void	X	-	X	DOM2	
	removeAttributeNS (namespaceURI,localName)	raises (DOMException)	void	X	-	X	DOM2	
	getAttributeNodeNS (namespaceURI,localName)		Attr	X	-	X	DOM2	
	setAttributeNodeNS(newAttr)	raises (DOMException)	Attr	X	-	X	DOM2	
	getElementsByTagNameNS (namespaceURI,localName)		NodeList	X	-	X	DOM2	
	hasAttribute(name)		boolean	X	-	X	DOM2	
hasAttributeNS (namespaceURI,localName)		boolean	X	-	X	DOM2		

Objects	Attributes/Methods	Exception	Types	DOM1	Read only	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value
Text	(Methods)							
	splitText(in unsigned long offset)	raises (DOMException)	Text	O	-	X	Dynamic document tree manipulation requires resource	
Comment				O	-	X	Resource required and rarely used	
CDATASection				O	-	X	Resource required and rarely used	
DocumentType	(Attributes)							
	name		DOMString	O	O	X	Resource required and rarely used	
	entities		NamedNodeMap	O	O	X	Resource required and rarely used	
	notations		NamedNodeMap	O	O	X	Resource required and rarely used	
	publicId		DOMString	X	O	X	DOM2	
	systemId		DOMString	X	O	X	DOM2	
Notation	internalSubset		DOMString	X	O	X	DOM2	
	(Attributes)							
	publicId		DOMString	O	O	X	Resource required and rarely used	
Entity	systemId		DOMString	O	O	X	Resource required and rarely used	
	(Attributes)							
	notationName		DOMString	O	O	X	Resource required and rarely used	
	publicId		DOMString	O	O	X	Resource required and rarely used	
EntityReference				O	-	X	Resource required and rarely used	
ProcessingInstruction	(Attributes)							
	target		DOMString	O	O	X	Resource required and rarely used	
	data	raises (DOMException) on setting	DOMString	O	X	X	Resource required and rarely used	

Chapter 9

DOM Event Level2

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

* For "img" element, dynamic changes of "width", "height", and "attribute" are not supported.

createElement('option') is not supported.

In NF3 specification, an external sheet is not included as a member of styleSheets.

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement	
Event	(Attributes)									
	data	string	X	X	O	X	JavaScript extension			
	height		X	X	O	X	JavaScript extension			
	layerX	integer	X	X	O	X	JavaScript extension			
	layerY	integer	X	X	O	X	JavaScript extension			
	modifiers	integer	X	X	O	X	JavaScript extension			
	pageX	integer	X	X	O	X	JavaScript extension			
	pageY	integer	X	X	O	X	JavaScript extension			
	screenX	integer	X	O	O	O	Attribute value cannot be retrieved in Script.			
	screenY	integer	X	O	O	O	DOM2			
	target		X	O	O	O	DOM2			
	srcElement		X	O	X	O	Internet Explorer extension			
	type	string	X	O	O	O	DOM2			
	which	integer	X	X	O	X	JavaScript extension			
	width		X	X	O	X	JavaScript extension			
	x	integer	X	X	O	X	JavaScript extension			
	y	integer	X	X	O	X	JavaScript extension			
	currentNode	Node	X	O	X	O	DOM2			
	eventPhase	unsigned short	X	O	X	O	DOM2			
	bubbles	boolean	X	O	O	O	DOM2			
	cancelable	boolean	X	O	O	O	DOM2			
	timeStamp	DOMTimeStamp	X	O	X	X	DOM2			
	EventException	(Methods)								
		initEvent	void	X	-	X	X	DOM2		
preventDefault		void	X	-	X	O	DOM2			
stopPropagation		void	X	-	X	O	DOM2			
UIEvent: Event	(Attributes)									
	code	unsigned short	X	X	X	X	DOM2			
	view		X	O	O	O	DOM2			
	detail		X	O	X	X	DOM2			
	clientX		X	O	O	O	Attribute value cannot be retrieved in Script.			
	clientY		X	O	O	O	DOM2			
UIEvent: Event	(Methods)									
	initUIEvent		X	-	X	X	Browser vendor extension			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
MouseEvent:UIEvent	(Attributes)								
	screenX		X	O	O	O	DOM2. Same value as clientX.		
	screenY		X	O	O	O	DOM2. Same value as clientY.		
	clientX		X	O	X	O	DOM2		
	clientY		X	O	X	O	DOM2		
	ctrlKey		X	O	X	X	DOM2		
	shiftKey		X	O	X	X	DOM2		
	altKey		X	O	X	X	DOM2		
	metaKey		X	O	X	X	DOM2		
	button		X	O	X	X	DOM2		
	relatedTarget		X	O	X	X	DOM2		
	pageX		X	-	O	O	DOM2		
	pageY		X	-	O	O	DOM2		
	x		X	-	O	O			
	y		X	-	O	O			
	data		X	-	O	X			
	width		X	-	O	X			
	height		X	-	O	X			
	modifiers		X	-	O	X			
	which		X	-	O	X			
	(Methods)								
initMouseEvent	void		X	-	-	X	DOM2		
KeyEvent:UIEvent	(Attributes)								
	keyCode		X	-	X	X	DOM2		
	charCode		X	-	X	X	DOM2		
	shiftKey		X	-	X	X	DOM2		
	ctrlKey		X	-	X	X	DOM2		
	metaKey		X	-	X	X	DOM2		
altKey		X	-	X	X	DOM2			

Chapter 10

DOM HTML Level1,2

O: Supported

X: Not Supported

This document describes whether each feature is supported or not supported.

In the Canon machine, the one that the display and the operation of NF3 change is reflected about the difference.

The display and operation might be different according to the Canon machine that uses it.

For detailed specification on each feature, refer to corresponding document.

NF3 specific means that the feature is not supported by W3C

specifications but NF3 supports it because;

(1) To make content more attractive

(2) To avoid unnecessary source code edit or branch.

* For "img" element, dynamic changes of "width", "height", and "attribute" are not supported.

createElement('option') is not supported.

In NF3 specification, an external sheet is not included as a member of styleSheets.

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
HTMLDOMImplementation	(Methods)								
	createHTMLDocument	DOMString	X	-	X	X	DOM2		
HTMLCollection	(Attributes)								
	length	unsigned long	O	O	X	O			
	(Methods)								
	item(in unsigned long index)	Node	O	-	X	O			
	namedItem (in DOMString name)	Node	O	-	X	O			
	.								
	[index]	HTMLElement	X	X	X	O		no support	
["name"]	HTMLElement	X	X	X	O		no support		
.name	HTMLElement	X	X	X	O		no support		
HTMLDocument	(Attributes)								
	title	DOMString	O	X	O	O		change document title	
	referrer	DOMString	O	O	O	O			
	domain	DOMString	O	O	O	O			
	URL	DOMString	O	O	O	O			
	body	HTMLElement	O	X	X	O		no support	
	images	HTMLCollection	O	O	O	O			
	applets	HTMLCollection	O	O	O	O			
	links	HTMLCollection	O	O	O	O			
	forms	HTMLCollection	O	O	O	O			
	anchors	HTMLCollection	O	O	O	O			
	cookie	DOMString	O	X	O	O		change document cookie	
	alinkColor		X	X	O	O		no support	
	bgColor		X	X	O	O		change document background color	
	fgColor		X	X	O	O		change document foreground color	
	linkColor		X	X	O	O		no support	
	vlinkColor		X	X	O	O		no support	
	classes		X	X	O	X	JavaScript extension		
	embeds		X	O	O	O	Attribute value cannot be retrieved in Script.		
	formName		X	X	O	X	JavaScript extension		
	height		X	X	O	X		no support	
	width		X	X	O	O		no support	
	ids		X	X	O	O			
	lastModified		X	O	O	O			
	layers		X	X	O	X	JavaScript extension		
	plugins		X	O	O	O			
	all	HTMLCollection	X	O	X	O	In retrieving an object, nf3 always retrieves the top object.		
	location	Location	X	X	O	O		setlocation to new URL	
	styleSheets	styleSheetList	X	O	O	O			
	tags		X	X	O	X	JavaScript extension		
(Methods)									
open()	void	O	-	O	O				
close()	void	O	-	O	O				
write(in DOMString text)	void	O	-	O	O				
writeln(in DOMString text)	void	O	-	O	O				
getElementsByName (in DOMString elementName)	NodeList	O	-	X	O				
captureEvents(eventType)	void	X	-	O	X	JavaScript extension			
releaseEvents(eventType)	void	X	-	O	X	JavaScript extension			
routeEvent(event)	void	X	-	O	X	JavaScript extension			
getSelection()		X	-	O	X	JavaScript extension			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	handleEvent(event)	void	X	-	O	X	JavaScript extension		
	contextual(context1, ...[contextN,] affectedStyle)		X	-	O	X	JavaScript extension		
	(Event Handlers)								
	onclick	-	X	X	O	O		event handler is replaced	
	ondblclick	-	X	X	O	X	Less meaning for mobile browser		
	onkeydown	-	X	X	O	X	Less meaning for mobile browser		
	onKeyPress	-	X	X	O	X	Less meaning for mobile browser		
	onkeyup	-	X	X	O	X	Less meaning for mobile browser		
	onmousedown	-	X	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup	-	X	X	O	O		event handler is replaced	
HTMLElement	(Attributes)								
	id	DOMString	O	X	X	O		no support	
	title	DOMString	O	X	X	O		no support	
	lang	DOMString	O	X	X	O		no support	
	dir	DOMString	O	X	X	O		no support	
	style	CSS2Properties	O	O	O	O			
	className	DOMString	O	X	X	O		no support	
HTMLHtmlElement	(Attributes)								
	version	DOMString	O	X	X	O		no support	
HTMLHeadElement	(Attributes)								
	profile	DOMString	O	X	X	O		no support	
HTMMLinkElement	(Attributes)								
	disabled	boolean	O	X	X	O		no support	
	charset	DOMString	O	X	X	O		no support	
	hash		X	X	O	X	JavaScript extension		
	hreflang	DOMString	O	X	X	O		no support	
	media	DOMString	O	X	X	O		no support	
	rel	DOMString	O	X	X	O		no support	
	rev	DOMString	O	X	X	O		no support	
	target	DOMString	O	X	O	O		no support	
	type	DOMString	X	X	X	O	JavaScript extension		
	host		X	X	O	X	JavaScript extension		
	hostname		X	X	O	X	JavaScript extension		
	href	DOMString	O	X	O	O		no support	
	x		X	O	O	X	JavaScript extension		
	y		X	O	O	X	JavaScript extension		
	pathname		X	X	O	X	JavaScript extension		
	port		X	X	O	X	JavaScript extension		
	protocol		X	X	O	X	JavaScript extension		
	search		X	X	O	X	JavaScript extension		
	text		X	X	O	X	JavaScript extension		
	(Methods)								
	handleEvent(event)		X	-	O	X			
	(Event Handlers)								
	onClick	-	X	X	O	X		event handler is replaced	
	onDbClick	-	X	X	O	X	Less meaning for mobile browser		
	onKeyDown	-	X	X	O	X	Less meaning for mobile browser		
	onKeyPress	-	X	X	O	X	Less meaning for mobile browser		
	onKeyUp	-	X	X	O	X	Less meaning for mobile browser		
	onMouseDown	-	X	X	O	X		event handler is replaced	
	onMouseOut	-	X	X	O	X		event handler is replaced	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onMouseOver	-	X	X	O	X		event handler is replaced	
	onMouseUp	-	X	X	O	X		event handler is replaced	
HTMLTitleElement	(Attributes)								
	text	DOMString	O	X	X	O		no support	
HTMLMetaElement	(Attributes)								
	content	DOMString	O	X	X	O		no support	
	httpEquiv	DOMString	O	X	X	O		no support	
	name	DOMString	O	X	X	O		no support	
	scheme	DOMString	O	X	X	O		no support	
HTMLBaseElement	(Attributes)								
	href	DOMString	O	X	X	O		no support	
	target	DOMString	O	X	X	O		no support	
HTMLIsIndexElement	(Attributes)								
	form	HTMLFormElement	O	O	X	O			
	prompt	DOMString	O	X	X	O		no support	
HTMLStyleElement	(Attributes)								
	disabled	boolean	O	X	X	O	Resource required and rarely used		
	media	DOMString	O	X	X	O			
	type	DOMString	O	X	X	O			
	align		X	X	O	X	Resource required and rarely used		
	backgroundColor		X	X	O	X	Resource required and rarely used		
	backgroundImage		X	X	O	X	Resource required and rarely used		
	borderBottomWidth		X	X	O	X	Resource required and rarely used		
	borderColor		X	X	O	X	Resource required and rarely used		
	borderLeftWidth		X	X	O	X	Resource required and rarely used		
	borderRightWidth		X	X	O	X	Resource required and rarely used		
	borderStyle		X	X	O	X	Resource required and rarely used		
	borderTopWidth		X	X	O	X	Resource required and rarely used		
	clear	string	X	X	O	X	Resource required and rarely used		
	color		X	X	O	X	Resource required and rarely used		
	display		X	X	O	X	Resource required and rarely used		
	fontFamily	string	X	X	O	X	Resource required and rarely used		
	fontSize	string	X	X	O	X	Resource required and rarely used		
	fontStyle	string	X	X	O	X	Resource required and rarely used		
	fontWeight		X	X	O	X	Resource required and rarely used		
	lineHeight		X	X	O	X	Resource required and rarely used		
	listStyleType	string	X	X	O	X	Resource required and rarely used		
	marginBottom		X	X	O	X	Resource required and rarely used		
	marginLeft		X	X	O	X	Resource required and rarely used		
	marginRight		X	X	O	X	Resource required and rarely used		
	marginTop		X	X	O	X	Resource required and rarely used		
	paddingBottom		X	X	O	X	Resource required and rarely used		
	paddingLeft		X	X	O	X	Resource required and rarely used		
	paddingRight		X	X	O	X	Resource required and rarely used		
	paddingTop		X	X	O	X	Resource required and rarely used		
	textAlign	string	X	X	O	X	Resource required and rarely used		
	textDecoration	string	X	X	O	X	Resource required and rarely used		
	textIndent	string	X	X	O	X	Resource required and rarely used		
	textTransform		X	X	O	X	Resource required and rarely used		
	whiteSpace		X	X	O	X	Resource required and rarely used		
	width	string	X	X	O	X	Resource required and rarely used		
	(Methods)								
	borderWidths		X	-	O	X	Resource required and rarely used		
	margins		X	-	O	X	Resource required and rarely used		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement	
	padding		X	-	O	X	Resource required and rarely used			
HTMLBodyElement	(Attributes)									
	aLink	DOMString	O	X	X	O		no support		
	background	DOMString	O	X	X	O		change background color		
	bgColor	DOMString	O	X	X	O		change background color		
	link	DOMString	O	X	X	O		no support		
	text	DOMString	O	X	X	O		change foreground color		
	vLink	DOMString	O	X	X	O		no support		
	clientWidth	long	X	X	O	O		no support		
	clientHeight	long	X	X	O	O		no support		
	(Event Handlers)									
	onclick			O	X	O	O		event handler is replaced	
	ondblclick			O	X	O	X	Less meaning for mobile browser		
	onkeydown			O	X	O	X	Less meaning for mobile browser		
	onkeypress			O	X	O	X	Less meaning for mobile browser		
	onkeyup			O	X	O	X	Less meaning for mobile browser		
	onmousedown			O	X	O	O		event handler is replaced	
	onmousemove			O	X	O	X		event handler is replaced	
	onmouseout			O	X	O	O		event handler is replaced	
	onmouseover			O	X	O	O		event handler is replaced	
	onmouseup			O	X	O	O		event handler is replaced	
	onload			O	X	O	O		no support	
	onunload			O	X	O	O		event handler is replaced	
	HTMLFormElement	(Attributes)								
		acceptCharset	DOMString	O	X	X	O		no support	
action		DOMString	O	X	O	O		no support		
elements		HTMLCollection	O	O	O	O				
encoding		string	X	X	O	X	JavaScript extension			
enctype		DOMString	O	X	X	O		no support		
length		long	O	O	O	O				
method		DOMString	O	X	O	O		no support		
name		DOMString	O	X	O	O		no support		
target		DOMString	O	X	O	O		no support		
(Methods)										
handleEvent(event)		void		X	-	O	X			
reset()		void		O	-	O	O			
submit()		void		O	-	O	O			
(Event Handlers)										
onReset		-		X	X	O	O		event handler is replaced	
onSubmit		-		X	X	O	O		event handler is replaced	
onclick				O	X	O	O		event handler is replaced	
ondblclick				O	X	O	X	Less meaning for mobile browser		
onkeydown				O	X	O	X	Less meaning for mobile browser		
onkeypress				O	X	O	X	Less meaning for mobile browser		
onkeyup				O	X	O	X	Less meaning for mobile browser		
onmousedown				O	X	O	O		event handler is replaced	
onmousemove				O	X	O	X		event handler is replaced	
onmouseout			O	X	O	O		event handler is replaced		
onmouseover			O	X	O	O		event handler is replaced		
onmouseup			O	X	O	O		event handler is replaced		
HTMLSelectElement	(Attributes)									
	disabled	boolean	O	X	X	O		change state to disable		
	form	HTMLFormElement	O	O	O	O				
	length	long	O	X	O	O				

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement	
	multiple	boolean	O	X	X	O		no support		
	name	DOMString	O	X	O	O		no support		
	options	HTMLCollection	O	O	O	O				
	selectedIndex	long	O	X	O	O		change selected index		
	size	long	O	X	X	O		no support		
	tabIndex	long	O	X	X	O		no support		
	type	DOMString	O	O	O	O				
	value	DOMString	O	X	X	O		change value		
	(Methods)									
	add(in HTMLElement element, in HTMLElement before)	void		O	-	X	O			
	blur()	void		O	-	O	O			
	focus()	void		O	-	O	O			
	handleEvent(event)			X	-	O	X	JavaScript extension		
	remove(in long index)	void		O	-	X	O			
	(Event Handlers)									
	onBlur	-		X	X	O	O		event handler is replaced	
	onChange	-		X	X	O	O		event handler is replaced	
	onFocus	-		X	X	O	O		event handler is replaced	
	onclick			O	X	O	O		event handler is replaced	
	ondblclick			O	X	O	X	Less meaning for mobile browser		
	onkeydown			O	X	O	X	Less meaning for mobile browser		
	onkeypress			O	X	O	X	Less meaning for mobile browser		
	onkeyup			O	X	O	X	Less meaning for mobile browser		
	onmousedown			O	X	O	O		event handler is replaced	
	onmousemove			O	X	O	X		event handler is replaced	
	onmouseout			O	X	O	O		event handler is replaced	
	onmouseover			O	X	O	O		event handler is replaced	
	onmouseup			O	X	O	X		event handler is replaced	
	(Attributes)									
	disabled	boolean		O	X	X	O		no support	
	label	DOMString		O	X	X	O		no support	
	(Event Handlers)									
	onclick			O	X	O	O		event handler is replaced	
ondblclick			O	X	O	X	Less meaning for mobile browser			
onkeydown			O	X	O	X	Less meaning for mobile browser			
onkeypress			O	X	O	X	Less meaning for mobile browser			
onkeyup			O	X	O	X	Less meaning for mobile browser			
onmousedown			O	X	O	O		event handler is replaced		
onmousemove			O	X	O	X		event handler is replaced		
onmouseout			O	X	O	O		event handler is replaced		
onmouseover			O	X	O	O		event handler is replaced		
onmouseup			O	X	O	O		event handler is replaced		
(Attributes)										
defaultSelected	boolean		O	X	O	O		no support		
disabled	boolean		O	X	X	O		no support		
form	HTMLFormElement		O	O	X	O				
index	long		O	O	O	O				
label	DOMString		O	X	X	O		no support		
length			X	O	O	O				
selected	boolean		O	X	O	O				
text	DOMString		O	O	O	O				
value	DOMString		O	X	O	O		change value		
(Constructor)										

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	new Option([text[, value[, defaultSelected[, selected]]]])		X	-	O	X			
	(Event Handlers)								
	onclick		O	X	O	X			
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLInputElement	(Attributes)								
	defaultValue	DOMString	O	X	O	O		change default value	password, text
	defaultChecked	boolean	O	X	O	O		change default checked	checkbox, radio
	form	HTMLFormElement	O	O	O	O			checkbox, file, hidden, password, radio, reset, submit, text
	accept	DOMString	O	X	X	O		no support	
	accessKey	DOMString	O	X	X	O		no support	
	align	DOMString	O	X	X	O		no support	
	alt	DOMString	O	X	X	O		no support	
	checked	boolean	O	X	O	O		change checked status	checkbox, radio
	disabled	boolean	O	X	X	O		change disabled status	
	maxLength	long	O	X	X	O		change maxlength	
	name	DOMString	O	X	O	O		no support	checkbox, file, hidden, password, radio, reset, submit, text
	readOnly	boolean	O	X	X	O		change readonly/write	
	size	unsigned long	O	X	X	O		no support	
	src	DOMString	O	X	X	O		no support	
	tabIndex	long	O	X	X	O		no support	
	type	DOMString	O	X	O	O		no support	
	useMap	DOMString	O	X	X	O		no support	
	value	DOMString	O	X	O	O		change value	side effect in changing the value of a checkbox and a radiobutton is not supported.
	length		X		X	X	Browser vendor extension		radio
	(Methods)								
	blur()	void	O	-	O	O			checkbox, file, password, radio, reset, submit, text
	focus()	void	O	-	O	O			checkbox, file, password, radio, reset, submit, text
	select()	void	O	-	O	X	Less meaning for mobile browser		file, password, text v2.6: "file" not supported
	click()	void	O	-	O	O			checkbox, radio, reset, submit
	handleEvent(event)	void	X	-	O	X	Resource required and rarely used		checkbox, file, password, radio, reset, submit, text
	(Event Handlers)								
	onBlur	-	X	X	O	O		event handler is replaced	checkbox, file, password, radio, reset, submit, text
	onChange	-	X	X	O	O		event handler is replaced	file, text
	onClick	-	X	X	O	O		event handler is replaced	checkbox, radio, reset, submit
	onFocus	-	X	X	O	O		event handler is replaced	checkbox, file, password, radio, reset, submit, text

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onKeyDown	-	X	X	X	X			password, text
	onKeyPress	-	X	X	X	X			password, text
	onKeyUp	-	X	X	X	X	Less meaning for mobile browser		
	onMouseDown	-	X	X	X	O		event handler is replaced	checkbox, radio, reset, submit
	onMouseUp	-	X	X	X	O		event handler is replaced	checkbox, radio, reset, submit
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	X		event handler is replaced	
	onmouseover		O	X	O	X		event handler is replaced	
	onSelect	-	X	X	O	X	Less meaning for mobile browser		text
HTMLTextAreaElement	(Attributes)								
	accessKey	DOMString	O	X	X	O		no support	
	cols	long	O	X	X	O		no support	
	defaultValue	DOMString	O	X	O	O		change default value	
	disabled	boolean	O	X	X	O		change state to disable	
	form	HTMLFormElement	O	O	O	O			
	readOnly	boolean	O	X	X	O		change state to readonly/write	
	rows	long	O	X	X	O		no support	
	name	DOMString	O	X	O	O		no support	
	tabIndex	long	O	X	X	O		no support	
	type	DOMString	O	O	O	O			
	value	DOMString	O	X	O	O		change value	
	(Methods)								
	blur()	void	O	-	O	O			
	focus()	void	O	-	O	O			
	handleEvent(event)	void	X	-	O	X	JavaScript extension		
	select()	void	O	-	O	X	Less meaning for mobile browser		
	(Event Handlers)								
	onBlur	-	X	X	O	O		event handler is replaced	
	onChange	-	X	X	O	O		event handler is replaced	
	onFocus	-	X	X	O	O		event handler is replaced	
	onKeyDown	-	X	X	O	X	Less meaning for mobile browser		
	onKeyPress	-	X	X	O	X	Less meaning for mobile browser		
	onKeyUp	-	X	X	O	X	Less meaning for mobile browser		
	onSelect	-	X	X	O	X	Less meaning for mobile browser		
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X			
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	X		event handler is replaced	
onmouseover		O	X	O	X		event handler is replaced		
onmouseup		O	X	O	X		event handler is replaced		
HTMLButtonElement	(Attributes)								
	accessKey	DOMString	O	X	X	O		no support	
	disabled	boolean	O	X	X	O		no support	
	form	HTMLFormElement	O	O	O	O			
	name	DOMString	O	X	O	O		no support	
	tabIndex	long	O	X	X	O		no support	
	type	DOMString	O	O	O	O			
	value	DOMString	O	X	O	O		no support	
	(Methods)								
	blur()	void	X	-	O	O			
click()		X	-	O	O				
focus()	void	X	-	O	O				

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	handleEvent(event)		X	-	O	X	JavaScript extension		
	(Event Handlers)								
	onBlur	-	X	X	O	O		event handler is replaced	
	onClick	-	X	X	O	O		event handler is replaced	
	onFocus	-	X	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onMouseDown	-	X	X	O	O		event handler is replaced	
	onMouseUp	-	X	X	O	O		event handler is replaced	
	HTMLLabelElement	(Attributes)							
form		HTMLFormElement	O	O	X	O			
accessKey		DOMString	O	X	X	O		no support	
htmlFor		DOMString	O	X	X	O		no support	
(Event Handlers)									
onclick			O	X	O	X	Resource required and rarely used		
ondblclick			O	X	O	X	Less meaning for mobile browser		
onkeydown			O	X	O	X	Less meaning for mobile browser		
onkeypress			O	X	O	X	Less meaning for mobile browser		
onkeyup			O	X	O	X	Less meaning for mobile browser		
onmousedown			O	X	O	X	Resource required and rarely used		
onmousemove			O	X	O	X	Resource required and rarely used		
onmouseout			O	X	O	X	Resource required and rarely used		
onmouseover			O	X	O	X	Resource required and rarely used		
onmouseup			O	X	O	X	Resource required and rarely used		
onfocus			O	X	O	X	Resource required and rarely used		
onblur			O	X	O	X	Resource required and rarely used		
HTMLFieldSetElement	(Attributes)								
	form	HTMLFormElement	O	O	X	O			
	(Event Handlers)								
	onclick		O	X	O	X		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	X		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	X		event handler is replaced	
	onmouseover		O	X	O	X		event handler is replaced	
	onmouseup		O	X	O	X		event handler is replaced	
HTMLLegendElement	(Attributes)								
	form	HTMLFormElement	O	O	X	O			
	accessKey	DOMString	O	X	X	O		no support	
	align	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	X		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onmousedown		O	X	O	X		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	X		event handler is replaced	
	onmouseover		O	X	O	X		event handler is replaced	
	onmouseup		O	X	O	X		event handler is replaced	
HTMLUListElement	(Attributes)								
	compact	boolean	O	X	X	O		no support	
	type	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
onmouseup		O	X	O	O		event handler is replaced		
HTMLListElement	(Attributes)								
	compact	boolean	O	X	X	O		no support	
	start	long	O	X	X	O		no support	
	type	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
onmouseover		O	X	O	O		event handler is replaced		
onmouseup		O	X	O	O		event handler is replaced		
HTMLDListElement	(Attributes)								
	compact	boolean	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
onmouseout		O	X	O	O		event handler is replaced		
onmouseover		O	X	O	O		event handler is replaced		
onmouseup		O	X	O	O		event handler is replaced		
HTMLDirectoryElement	(Attributes)								
	compact	boolean	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
onkeydown		O	X	O	X	Less meaning for mobile browser			
onkeypress		O	X	O	X	Less meaning for mobile browser			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLMenuElement	(Attributes)								
	compact	boolean	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLLIElement	(Attributes)								
	type	DOMString	O	X	X	O		no support	
	value	long	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLBlockquoteElement	(Attributes)								
	cite	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLDivElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLParagraphElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLHeadingElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLQuoteElement	(Attributes)								
	cite	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLPreElement	(Attributes)								
	width	long	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
onmousemove		O	X	O	X		event handler is replaced		

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLBRElement	(Attributes)								
	clear	DOMString	O	X	X	O		no support	
HTMLBaseFontElement	(Attributes)								
	color	DOMString	O	X	X	O		no support	
	face	DOMString	O	X	X	O		no support	
	size	DOMString	O	X	X	O		no support	
HTMLFontElement	(Attributes)								
	color	DOMString	O	X	X	O		no support	
	face	DOMString	O	X	X	O		no support	
	size	DOMString	O	X	X	O		no support	
HTMLHRElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	noShade	boolean	O	X	X	O		no support	
	size	DOMString	O	X	X	O		no support	
	width	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	X		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	X		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	X		event handler is replaced	
	onmouseover		O	X	O	X		event handler is replaced	
	onmouseup		O	X	O	X		event handler is replaced	
HTMLModElement	(Attributes)								
	cite	DOMString	O	X	X	O		no support	
	dateTime	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLAnchorElement	(Attributes)								
	accessKey	DOMString	O	X	X	O		no support	
	charset	DOMString	O	X	X	O		no support	
	coords	DOMString	O	X	X	O		no support	
	href	DOMString	O	X	X	O		no support	
	hreflang	DOMString	O	X	X	O		no support	
	name	DOMString	O	X	O	O		no support	
	rel	DOMString	O	X	X	O		no support	
	rev	DOMString	O	X	X	O		no support	
	shape	DOMString	O	X	X	O		no support	
	tabIndex	long	O	X	X	O		no support	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement	
	target	DOMString	O	X	X	O		no support		
	text		X	O	O	X	JavaScript extension			
	type	DOMString	O	X	X	O		no support		
	x		X	O	O	X				
	y		X	O	O	X				
	hash	DOMString	X	X	O	O		no support		
	host	DOMString	X	X	O	O		no support		
	hostname	DOMString	X	X	O	O		no support		
	pathname	DOMString	X	X	O	O		no support		
	port	DOMString	X	X	O	O		no support		
	protocol	DOMString	X	X	O	O		no support		
	search	DOMString	X	X	O	O		no support		
	(Methods)									
	blur()	void		O	-	X	O			
	focus()	void		O	-	X	O			
	click()	void		-	-	X	O			
	(Event Handlers)									
	onclick			O	X	O	O		event handler is replaced	
	ondblclick			O	X	O	X	Less meaning for mobile browser		
	onkeydown			O	X	O	X	Less meaning for mobile browser		
	onkeypress			O	X	O	X	Less meaning for mobile browser		
	onkeyup			O	X	O	X	Less meaning for mobile browser		
	onmousedown			O	X	O	O		event handler is replaced	
	onmousemove			O	X	O	X		event handler is replaced	
	onmouseout			O	X	O	O		event handler is replaced	
	onmouseover			O	X	O	O		event handler is replaced	
	onmouseup			O	X	O	O		event handler is replaced	
	onfocus			O	X	O	O		event handler is replaced	
	onblur			O	X	O	O		event handler is replaced	
	(Attributes)									
align	DOMString		O	X	X	O		no support		
alt	DOMString		O	X	X	O		no support		
border	long		O	X	O	O		no support		
complete	boolean		X	O	O	O				
height	long		O	X	O	O	For "img" element, dynamic changes of "width", "height", and "attribute" are not supported.	no support		
hspace	long		O	X	O	O		no support		
isMap	boolean		O	X	X	O		no support		
longDesc	DOMString		O	X	X	O		no support		
name	DOMString		O	X	O	O		no support		
src	DOMString		O	X	O	O		image is changed to new URL		
useMap	DOMString		O	X	X	O		no support		
vspace	long		O	X	O	O		no support		
width	long		O	X	O	O	For "img" element, dynamic changes of "width", "height", and "attribute" are not supported.	no support		
(Methods)										
handleEvent(event)			X	-	O	X				
(Event Handlers)										
onAbort	-		X	X	O	X	Resource required and rarely used			
onclick			O	X	O	O		event handler is replaced		
ondblclick			O	X	O	X	Less meaning for mobile browser			
onError	-		X	X	O	X	Resource required and rarely used			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onKeyDown	-	X	X	O	X	Less meaning for mobile browser		
	onKeyPress	-	X	X	O	X	Less meaning for mobile browser		
	onKeyUp	-	X	X	O	X	Less meaning for mobile browser		
	onLoad	-	X	X	O	O			
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
	(Constructor)								
	new Image([width,] [height])		X	-	O	O			
HTMLObjectElement	(Attributes)								
	code	DOMString	O	X	X	O		no support	
	align	DOMString	O	X	X	O		no support	
	archive	DOMString	O	X	X	O		no support	
	border	DOMString	O	X	X	O		no support	
	codeBase	DOMString	O	X	X	O		no support	
	codeType	DOMString	O	X	X	O		no support	
	data	DOMString	O	X	X	O	Overwriting properties is not supported.	no support	
	declare	boolean	O	X	X	O		no support	
	height	DOMString	O	X	X	O		no support	
	hspace	DOMString	O	X	X	O		no support	
	name	DOMString	O	X	X	O		no support	
	standby	DOMString	O	X	X	O		no support	
	tabIndex	long	O	X	X	O		no support	
	type	DOMString	O	X	X	O		no support	
	useMap	DOMString	O	X	X	O		no support	
	vspace	DOMString	O	X	X	O		no support	
	width	DOMString	O	X	X	O		no support	
	contentDocument	Document	X	O	X	X		DOM2	
	(Event Handlers)								
	onclick		O	X	O	X	Resource required and rarely used		
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	X	Resource required and rarely used		
	onmousemove		O	X	O	X	Resource required and rarely used		
	onmouseout		O	X	O	X	Resource required and rarely used		
	onmouseover		O	X	O	X	Resource required and rarely used		
	onmouseup		O	X	O	X	Resource required and rarely used		
HTMLParamElement	(Attributes)								
	name	DOMString	O	X	X	O		no support	
	type	DOMString	O	X	X	O		no support	
	value	DOMString	O	X	X	O		no support	
	valueType	DOMString	O	X	X	O		no support	
HTMLAppletElement	(Attributes)								
	align	DOMString	O	X	X	X			
	alt	DOMString	O	X	X	X			
	archive	DOMString	O	X	X	X			
	code	DOMString	O	X	X	X			
	codeBase	DOMString	O	X	X	X			
	height	DOMString	O	X	X	X			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	hspace	DOMString	O	X	X	X			
	name	DOMString	O	X	X	X			
	object	DOMString	O	X	X	X			
	vspace	DOMString	O	X	X	X			
	width	DOMString	O	X	X	X			
	all public attributes of the Java applet		X	X	O	X	Difficult to implement		
	(Methods)								
all public methods of the Java applet		X	-	O	X	Difficult to implement			
HTMLMapElement	(Attributes)								
	areas	HTMLCollection	O	O	X	O			
	name	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLAreaElement	(Attributes)								
	accessKey	DOMString	O	X	X	O		no support	
	alt	DOMString	O	X	X	O		no support	
	coords	DOMString	O	X	X	O		no support	
	href	DOMString	O	X	O	O		no support	
	noHref	boolean	O	X	X	O		no support	
	shape	DOMString	O	X	X	O		no support	
	tabIndex	long	O	X	X	O		no support	
	target	DOMString	O	X	O	O		no support	
	the same as link								
	(Methods)								
	the same as link		X		O	O			
	(Event Handlers)								
	onblur		O	X	O	O		event handler is replaced	
	onclick		O	X	O	O		event handler is replaced	
	onDbClick	-	X	X	O	X	Less meaning for mobile browser		
	onfocus		O	X	O	O		event handler is replaced	
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
onmousemove		O	X	O	X		event handler is replaced		
onmouseup		O	X	O	O		event handler is replaced		
onMouseOut	-	X	X	O	O		event handler is replaced		
onMouseOver	-	X	X	O	O		event handler is replaced		
HTMLScriptElement	(Attributes)								
	text	DOMString	O	X	X	O	Overwriting properties is not supported.	no support	
	htmlFor	DOMString	O	X	X	X		no support	
	event	DOMString	O	X	X	X		no support	
	charset	DOMString	O	X	X	O		no support	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	defer	boolean	O	X	X	O		no support	
	src	DOMString	O	X	X	O		no support	
	type	DOMString	O	X	X	O		no support	
HTMLTableElement	(Attributes)								
	caption	HTMLTableCaptionElement	O	X	X	O		no support	
	tHead	HTMLTableSectionElement	O	X	X	O		no support	
	tFoot	HTMLTableSectionElement	O	X	X	O		no support	
	rows	HTMLCollection	O	O	X	O			
	tBodies	HTMLCollection	O	O	X	O			
	align	DOMString	O	X	X	O		no support	
	bgColor	DOMString	O	X	X	O		no support	
	border	DOMString	O	X	X	O		no support	
	cellPadding	DOMString	O	X	X	O		no support	
	cellSpacing	DOMString	O	X	X	O		no support	
	frame	DOMString	O	X	X	O		no support	
	rules	DOMString	O	X	X	O		no support	
	summary	DOMString	O	X	X	O		no support	
	width	DOMString	O	X	X	O		no support	
	(Methods)								
	createTHead()	HTMLTableSectionElement	O	-	X	X		Dynamic document tree manipulation requires resource	
	deleteTHead()	void	O	-	X	X		Dynamic document tree manipulation requires resource	
	createTFoot()	HTMLTableSectionElement	O	-	X	X		Dynamic document tree manipulation requires resource	
	deleteTFoot()	void	O	-	X	X		Dynamic document tree manipulation requires resource	
	createCaption()	HTMLTableCaptionElement	O	-	X	X		Dynamic document tree manipulation requires resource	
	deleteCaption()	void	O	-	X	X		Dynamic document tree manipulation requires resource	
	insertRow(in long index)	HTMLTableSectionElement	O	-	X	X		Dynamic document tree manipulation requires resource	
	deleteRow(in long index)	void	O	-	X	X		Dynamic document tree manipulation requires resource	
	(Event Handlers)								
	onclick		O	X	O	O			event handler is replaced
	ondblclick		O	X	O	X		Less meaning for mobile browser	
	onkeydown		O	X	O	X		Less meaning for mobile browser	
	onkeypress		O	X	O	X		Less meaning for mobile browser	
	onkeyup		O	X	O	X		Less meaning for mobile browser	
onmousedown		O	X	O	O			event handler is replaced	
onmousemove		O	X	O	X			event handler is replaced	
onmouseout		O	X	O	O			event handler is replaced	
onmouseover		O	X	O	O			event handler is replaced	
onmouseup		O	X	O	O			event handler is replaced	
HTMLTableCaptionElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X		Less meaning for mobile browser	
	onkeydown		O	X	O	X		Less meaning for mobile browser	
	onkeypress		O	X	O	X		Less meaning for mobile browser	
	onkeyup		O	X	O	X		Less meaning for mobile browser	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
HTMLTableColElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	ch	DOMString	O	X	X	O		no support	
	chOff	DOMString	O	X	X	O		no support	
	span	long	O	X	X	O		no support	
	vAlign	DOMString	O	X	X	O		no support	
	width	DOMString	O	X	X	O		no support	
	(Event Handlers)								
	onclick			O	X	O	O		event handler is replaced
	ondblclick			O	X	O	X	Less meaning for mobile browser	
	onkeydown			O	X	O	X	Less meaning for mobile browser	
	onkeypress			O	X	O	X	Less meaning for mobile browser	
	onkeyup			O	X	O	X	Less meaning for mobile browser	
	onmousedown			O	X	O	X		event handler is replaced
	onmousemove			O	X	O	X		event handler is replaced
	onmouseout			O	X	O	X		event handler is replaced
	onmouseover			O	X	O	X		event handler is replaced
onmouseup			O	X	O	X		event handler is replaced	
HTMLTableSectionElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	ch	DOMString	O	X	X	O		no support	
	chOff	DOMString	O	X	X	O		no support	
	vAlign	DOMString	O	X	X	O		no support	
	rows	HTMLCollection	O	O	X	O			
	(Methods)								
	insertRow(in long index)	HTMLElement		O	-	X	X	Dynamic document tree manipulation requires resource	
	deleteRow(in long index)	void		O	-	X	X	Dynamic document tree manipulation requires resource	
	(Event Handlers)								
	onclick			O	X	O	O		event handler is replaced
	ondblclick			O	X	O	X	Less meaning for mobile browser	
	onkeydown			O	X	O	X	Less meaning for mobile browser	
	onkeypress			O	X	O	X	Less meaning for mobile browser	
	onkeyup			O	X	O	X	Less meaning for mobile browser	
	onmousedown			O	X	O	O		event handler is replaced
	onmousemove			O	X	O	X		event handler is replaced
onmouseout			O	X	O	O		event handler is replaced	
onmouseover			O	X	O	O		event handler is replaced	
onmouseup			O	X	O	O		event handler is replaced	
HTMLTableRowElement	(Attributes)								
	rowIndex	long	O	O	X	O			
	sectionRowIndex	long	O	O	X	O			
	cells	HTMLCollection	O	O	X	O			
	align	DOMString	O	X	X	O		no support	
	bgColor	DOMString	O	X	X	O		no support	
	ch	DOMString	O	X	X	O		no support	
	chOff	DOMString	O	X	X	O		no support	
	vAlign	DOMString	O	X	X	O		no support	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	(Methods)								
	insertCell(in long index)	HTMLElement	O	-	X	X	Dynamic document tree manipulation requires resource		
	deleteCell(in long index)	void	O	-	X	X	Dynamic document tree manipulation requires resource		
	(Event Handlers)								
	onclick		O	X	O	O		event handler is replaced	
	ondblclick		O	X	O	X	Less meaning for mobile browser		
	onkeydown		O	X	O	X	Less meaning for mobile browser		
	onkeypress		O	X	O	X	Less meaning for mobile browser		
	onkeyup		O	X	O	X	Less meaning for mobile browser		
	onmousedown		O	X	O	O		event handler is replaced	
	onmousemove		O	X	O	X		event handler is replaced	
	onmouseout		O	X	O	O		event handler is replaced	
	onmouseover		O	X	O	O		event handler is replaced	
	onmouseup		O	X	O	O		event handler is replaced	
	HTMLTableCellElement	(Attributes)							
cellIndex		long	O	O	X	O			
abbr		DOMString	O	X	X	O		no support	
align		DOMString	O	X	X	O		no support	
axis		DOMString	O	X	X	O		no support	
bgColor		DOMString	O	X	X	O		no support	
ch		DOMString	O	X	X	O		no support	
chOff		DOMString	O	X	X	O		no support	
colSpan		long	O	X	X	O		no support	
headers		DOMString	O	X	X	O		no support	
height		DOMString	O	X	X	O		no support	
noWrap		boolean	O	X	X	O		no support	
rowSpan		long	O	X	X	O		no support	
scope		DOMString	O	X	X	O		no support	
vAlign		DOMString	O	X	X	O		no support	
width		DOMString	O	X	X	O		no support	
(Event Handlers)									
onclick			O	X	O	O		event handler is replaced	
ondblclick			O	X	O	X	Less meaning for mobile browser		
onkeydown			O	X	O	X	Less meaning for mobile browser		
onkeypress			O	X	O	X	Less meaning for mobile browser		
onkeyup			O	X	O	X	Less meaning for mobile browser		
onmousedown			O	X	O	O		event handler is replaced	
onmousemove			O	X	O	X		event handler is replaced	
onmouseout		O	X	O	O		event handler is replaced		
onmouseover		O	X	O	O		event handler is replaced		
onmouseup		O	X	O	O		event handler is replaced		
HTMLFrameSetElement	(Attributes)						In the case of frameborder=0, border specified in frame switches display/nondisplay.		
	cols	DOMString	O	X	X	O	Overwriting properties is not	no support	
	rows	DOMString	O	X	X	O	Overwriting properties is not	no support	
	(Event Handlers)								
	onload		O	X	O	O		no support	
onunload		O	X	O	O		event handler is replaced		
HTMLFrameElement	(Attributes)								
	frameBorder	DOMString	O	X	X	O	Overwriting properties is not	no support	
	longDesc	DOMString	O	X	X	O	Overwriting properties is not	no support	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	marginHeight	DOMString	O	X	X	O	Overwriting properties is not	no support	
	marginWidth	DOMString	O	X	X	O	Overwriting properties is not	no support	
	name	DOMString	O	X	O	O	Overwriting properties is not	no support	
	noResize	boolean	O	X	X	O	Overwriting properties is not	no support	
	scrolling	DOMString	O	X	X	O	Overwriting properties is not	no support	
	src	DOMString	O	X	X	O	Overwriting properties is not	no support	
	contentDocument	Document	X	O	-	X	DOM2		
	(Methods)								
	the same as window			X	-	O			
HTMLIFrameElement	(Attributes)								
	align	DOMString	O	X	X	O		no support	
	frameBorder	DOMString	O	X	X	O		no support	
	height	DOMString	O	X	X	O		no support	
	longDesc	DOMString	O	X	X	O		no support	
	marginHeight	DOMString	O	X	X	O		no support	
	marginWidth	DOMString	O	X	X	O		no support	
	name	DOMString	O	X	X	O		no support	
	scrolling	DOMString	O	X	X	O		no support	
	src	DOMString	O	X	X	O		no support	
	width	DOMString	O	X	X	O		no support	
	contentDocument	Document	X	O	-	X			
	Layer(layers)	(Attributes)							
above			X	O	O	X	JavaScript extension		
background			X	X	O	X	JavaScript extension		
below			X	O	O	X	JavaScript extension		
bgColor			X	X	O	X	JavaScript extension		
clip.bottom		integer	X	X	O	X	JavaScript extension		
clip.height		integer	X	X	O	X	JavaScript extension		
clip.left		integer	X	X	O	X	JavaScript extension		
clip.right		integer	X	X	O	X	JavaScript extension		
clip.top		integer	X	X	O	X	JavaScript extension		
clip.width		integer	X	X	O	X	JavaScript extension		
document			X	O	O	X	JavaScript extension		
hidden		boolean	X		X	X	JavaScript extension		
id			X		X	X	JavaScript extension		
left		integer	X	O	O	X	JavaScript extension		
name			X	O	O	X	JavaScript extension		
pageX		integer	X	X	O	X	JavaScript extension		
pageY		integer	X	X	O	X	JavaScript extension		
parentLayer			X	O	O	X	JavaScript extension		
siblingAbove			X	O	O	X	JavaScript extension		
siblingBelow			X	O	O	X	JavaScript extension		
src		string	X	X	O	X	JavaScript extension		
top		integer	X	X	O	X	JavaScript extension		
visibility		string	X	X	O	X	JavaScript extension		
window			X	O	O	X	JavaScript extension		
x			X	X	O	X	JavaScript extension		
y			X	X	O	X	JavaScript extension		
zIndex		integer	X	X	O	X	JavaScript extension		
(Methods)									
captureEvents(eventType)		void	X	-	O	X	JavaScript extension		
handleEvent(event)	void	X	-	O	X	JavaScript extension			
load(sourcestrng, width)	boolean	X	-	O	X	JavaScript extension			
moveAbove(aLayer)	void	X	-	O	X	JavaScript extension			

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series	Remarks	Side effect of change property value	supplement
	moveBelow(aLayer)	void	X	-	O	X		JavaScript extension		
	moveBy(horizontal, vertical)	void	X	-	O	X		JavaScript extension		
	moveTo(x-coordinate, y-coordinate)	void	X	-	O	X		JavaScript extension		
	moveToAbsolute(x, y)	void	X	-	O	X		JavaScript extension		
	releaseEvents(eventType)	void	X	-	O	X		JavaScript extension		
	resizeBy(width, height)	void	X	-	O	X		JavaScript extension		
	resizeTo(width, height)	void	X	-	O	X		JavaScript extension		
	routeEvent(event)	void	X	-	O	X		JavaScript extension		
	(Event Handlers)									
	onBlur	-	X	X	O	X		JavaScript extension		
	onFocus	-	X	X	O	X		JavaScript extension		
	onLoad	-	X	X	O	X		JavaScript extension		
	onMouseOut	-	X	X	O	X		JavaScript extension		
	onMouseOver	-	X	X	O	X		JavaScript extension		
CSS2Propeties	(Attributes)									
	border	DOMString	O	X	X	O			style is changed and relayout	
	border-color	DOMString	O	X	X	O		side effect of style.borderColor used in table element also influences drawing inside a cell. The result is notified in hexadecimal.	style is changed and relayout	
	border-style	DOMString	O	X	X	O			style is changed and relayout	
	border-top	DOMString	O	X	X	O			style is changed and relayout	
	border-right	DOMString	O	X	X	O			style is changed and relayout	
	border-bottom	DOMString	O	X	X	O			style is changed and relayout	
	border-left	DOMString	O	X	X	O			style is changed and relayout	
	border-top-color	DOMString	O	X	X	O			style is changed and relayout	
	border-right-color	DOMString	O	X	X	O			style is changed and relayout	
	border-bottom-color	DOMString	O	X	X	O			style is changed and relayout	
	border-left-color	DOMString	O	X	X	O			style is changed and relayout	
	border-top-style	DOMString	O	X	X	O			style is changed and relayout	
	border-right-style	DOMString	O	X	X	O			style is changed and relayout	
	border-bottom-style	DOMString	O	X	X	O			style is changed and relayout	
	border-left-style	DOMString	O	X	X	O			style is changed and relayout	
	border-top-width	DOMString	O	X	X	O			style is changed and relayout	
	border-right-width	DOMString	O	X	X	O			style is changed and relayout	
	border-bottom-width	DOMString	O	X	X	O			style is changed and relayout	
	border-left-width	DOMString	O	X	X	O			style is changed and relayout	
	border-width	DOMString	O	X	X	O		If a value is referred to in script, the result is notified in values in px.	style is changed and relayout	
	margin	DOMString	O	X	X	O			style is changed and relayout	
	margin-top	DOMString	O	X	X	O			style is changed and relayout	
	margin-right	DOMString	O	X	X	O			style is changed and relayout	
	margin-bottom	DOMString	O	X	X	O			style is changed and relayout	
	margin-left	DOMString	O	X	X	O			style is changed and relayout	
	padding	DOMString	O	X	X	O			style is changed and relayout	
	padding-top	DOMString	O	X	X	O			style is changed and relayout	
	padding-right	DOMString	O	X	X	O			style is changed and relayout	
	padding-bottom	DOMString	O	X	X	O			style is changed and relayout	
	padding-left	DOMString	O	X	X	O			style is changed and relayout	
	clear	DOMString	O	X	X	O			style is changed and relayout	
	float	DOMString	O	X	X	O			no support	
	height	DOMString	O	X	X	O			style is changed and relayout	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series Remarks	Side effect of change property value	supplement
	width	DOMString	O	X	X	O		style is changed and layout	
	max-width	DOMString	O	X	X	X			
	min-height	DOMString	O	X	X	X			
	max-height	DOMString	O	X	X	X			
	min-width	DOMString	O	X	X	X			
	bottom	DOMString	O	X	X	X			
	clip	DOMString	O	X	X	X	Resource required and rarely used		
	left	DOMString	O	X	X	O		style is changed and layout	
	overflow	DOMString	O	X	X	X	Resource required and rarely used		
	position	DOMString	O	X	X	O		no support	
	right	DOMString	O	X	X	X			
	top	DOMString	O	X	X	O		style is changed and layout	
	visibility	DOMString	O	X	X	O		style is changed and layout	
	z-index	DOMString	O	X	X	O		style is changed and layout	
	content	DOMString	O	X	X	X	Resource required and rarely used		
	counter-increment	DOMString	O	X	X	X	Resource required and rarely used		
	counter-reset	DOMString	O	X	X	X	Resource required and rarely used		
	quotes	DOMString	O	X	X	X	Resource required and rarely used		
	background	DOMString	O	X	X	O		style is changed and layout	
	background-attachment	DOMString	O	X	X	O		style is changed and layout	
	background-color	DOMString	O	X	X	O		style is changed and layout	
	background-image	DOMString	O	X	X	O		style is changed and layout	
	background-position	DOMString	O	X	X	O		style is changed and layout	
	background-repeat	DOMString	O	X	X	O		style is changed and layout	
	color	DOMString	O	X	X	O		style is changed and layout	
	font	DOMString	O	X	X	O		style is changed and layout	
	font-family	DOMString	O	X	X	O		style is changed and layout	
	font-size	DOMString	O	X	X	O		style is changed and layout	
	font-size-adjust	DOMString	O	X	X	X	Resource required and rarely used		
	font-stretch	DOMString	O	X	X	X	Resource required and rarely used		
	font-style	DOMString	O	X	X	O		style is changed and layout	
	font-variant	DOMString	O	X	X	X	Resource required and rarely used		
	font-weight	DOMString	O	X	X	O		style is changed and layout	
	line-height	DOMString	O	X	X	O		style is changed and layout	
	letter-spacing	DOMString	O	X	X	X			
	text-align	DOMString	O	X	X	O		style is changed and layout	
	text-decoration	DOMString	O	X	X	O		style is changed and layout	
	text-indent	DOMString	O	X	X	O		style is changed and layout	
	text-shadow	DOMString	O	X	X	X	Resource required and rarely used		
	text-transform	DOMString	O	X	X	X	Resource required and rarely used		
	vertical-align	DOMString	O	X	X	O		style is changed and layout	
	word-spacing	DOMString	O	X	X	X			
	border-collapse	DOMString	O	X	X	X	Resource required and rarely used		
	border-spacing	DOMString	O	X	X	X	Resource required and rarely used		
	caption-side	DOMString	O	X	X	X	Resource required and rarely used		
	empty-cells	DOMString	O	X	X	X	Resource required and rarely used		
	table-layout	DOMString	O	X	X	X	Resource required and rarely used		
	cursor	DOMString	O	X	X	X	Resource required and rarely used		
	outline	DOMString	O	X	X	X	Resource required and rarely used		
	outline-color	DOMString	O	X	X	X	Resource required and rarely used		
	outline-style	DOMString	O	X	X	X	Resource required and rarely used		
	outline-width	DOMString	O	X	X	X	Resource required and rarely used		
	direction	DOMString	O	X	X	X			
	display	DOMString	O	X	X	O		no support	

Objects	Attributes/Methods/Event Handlers/Constructors	Types	DOM1	Read only	JavaScript 1.3 (Netscape 4.06)	NF3 for iR Series	NF3 for iR Series	Remarks	Side effect of change property value	supplement
	list-style	DOMString	O	X	X	O			style is changed and layout	
	list-style-image	DOMString	O	X	X	O			style is changed and layout	
	list-style-position	DOMString	O	X	X	O			style is changed and layout	
	list-style-type	DOMString	O	X	X	O			style is changed and layout	
	marker-offset	DOMString	O	X	X	X				
	unicode-bidi	DOMString	O	X	X	X		Resource required and rarely used		
	white-space	DOMString	O	X	X	O			style is changed and layout	
	azimuth	DOMString	O	X	X	X		Resource required and rarely used		
	cue	DOMString	O	X	X	X		Resource required and rarely used		
	cue-before	DOMString	O	X	X	X		Resource required and rarely used		
	cue-after	DOMString	O	X	X	X		Resource required and rarely used		
	elevation	DOMString	O	X	X	X		Resource required and rarely used		
	pause	DOMString	O	X	X	X		Resource required and rarely used		
	pause-before	DOMString	O	X	X	X		Resource required and rarely used		
	pause-after	DOMString	O	X	X	X		Resource required and rarely used		
	pitch	DOMString	O	X	X	X		Resource required and rarely used		
	pitch-range	DOMString	O	X	X	X		Resource required and rarely used		
	play-during	DOMString	O	X	X	X		Resource required and rarely used		
	richness	DOMString	O	X	X	X		Resource required and rarely used		
	speak	DOMString	O	X	X	X		Resource required and rarely used		
	speak-header	DOMString	O	X	X	X		Resource required and rarely used		
	speak-numeral	DOMString	O	X	X	X		Resource required and rarely used		
	speak-punctuation	DOMString	O	X	X	X		Resource required and rarely used		
	speech-rate	DOMString	O	X	X	X		Resource required and rarely used		
	stress	DOMString	O	X	X	X		Resource required and rarely used		
	voice-family	DOMString	O	X	X	X		Resource required and rarely used		
	volume	DOMString	O	X	X	X		Resource required and rarely used		
	marks	DOMString	O	X	X	X		Resource required and rarely used		
	orphans	DOMString	O	X	X	X		Resource required and rarely used		
	page	DOMString	O	X	X	X		Resource required and rarely used		
	page-break-before	DOMString	O	X	X	X		Resource required and rarely used		
	page-break-after	DOMString	O	X	X	X		Resource required and rarely used		
	page-break-inside	DOMString	O	X	X	X		Resource required and rarely used		
	size	DOMString	O	X	X	X		Resource required and rarely used		
	widows	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-marquee	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-marquee-style	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-marquee-loop	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-marquee-dir	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-marquee-speed	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-accesskey	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-input-format	DOMString	O	X	X	X		Resource required and rarely used		
	-wap-input-required	DOMString	O	X	X	X		Resource required and rarely used		

NF3 for iR Series Web Access Software Function Specification Element/Attribute

- * NetFront is a trademark or registered trademark of ACCESS CO., LTD. in Japan and other countries.
 - * ACCESS is a registered trademark of ACCESS CO., LTD. in Japan.
 - * This software is based in part on the work of the Independent JPEG Group.
 - * This software is licensed under U.S. Patent No. 4,558,302 and foreign counterparts.
 - * Java, all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.
 - * Microsoft, Windows, Windows NT and Internet Explorer are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
 - * RSA and RC4 are trademarks or registered trademarks of RSA Security, Inc.
 - * Netscape is a registered trademark of Netscape Communications Corporation in the U.S. and other countries.
 - * i-mode is a trademark or registered trademark of NTT DoCoMo, Inc. within Japan and other countries.
 - * Canon and imageRUNNER are registered trademarks of Canon Inc.
-

- * All other trademarks, logos and trade names mentioned in the document are the property of their respective owners.
- * No one may delete or in any manner alter the copyright, trademark or other proprietary right notices of ACCESS CO., LTD. or any other third party appearing on or within this product; and no one may add any mark or indication to this product which is similar to, or may be confused with, the copyright or other proprietary marks or notices of ACCESS CO., LTD. or any third party.

Revision History

Rev.	Date	Note
1.0	2005/11/1	Initial release.