

Canon

imageCLASS MF4890dw | imageCLASS MF4880dw | imageCLASS MF4770n

Revolutionizing Today's Workspace

Multifunction Laser Printers

- Print and Copy at blazing speeds –
up to 26 ppm¹ [MF4880dw/MF4890dw];
up to 24 ppm¹ [MF4770n]
- **Duplex Versatility** –
two-sided printing [MF4880dw/MF4890dw];
copying, scanning, and PC faxing [MF4890dw]
- **Wireless Connectivity** - print from almost
anywhere in your home or office³
[MF4880dw/MF4890dw]
- Single touch **Quiet Mode** button reduces
the operational noise of the machine¹³
- **Simple Solution Keys** make scanning effortless
and give the ability to use more eco-friendly
copying options
- 33.6 Kbps **Super G3 Fax⁹**
- User-friendly **5-line LCD** and **tiltable control
panel** for easy navigation
- **Single Cartridge System** for easy supplies
replenishment



MF4890dw shown



FEATURES	imageCLASS MF4770n	imageCLASS MF4880dw	imageCLASS MF4890dw
BASIC SPECIFICATIONS			
Functions	Print/Copy/Scan/Fax/PC Fax		
Print Speeds (default print mode: 2-sided)	Up to 24 ppm (1-sided, plain paper letter) ¹	Up to 16 ppm ¹ (2-sided, plain paper letter) Up to 26 ppm ¹ (1-sided, plain paper letter)	
Connectivity	USB 2.0 Hi-Speed ² , 10/100 Base-T Ethernet	USB 2.0 Hi-Speed ² , 10/100 Base-T Ethernet, 802.11 b/g/n Wireless ³	
Operating Systems	Windows [®] 7, Windows Server [®] 2008 R2, Windows Server [®] 2008, Windows Vista [®] , Windows Server 2003, Windows XP, Mac OS X 10.5.8 & up <i>Drivers available for download from www.usa.canon.com</i>		
Paper Handling	Simplex Automatic Document Feeder: 35-sheets ⁴		Duplex Automatic Document Feeder: 50-sheets ⁴
	Standard Cassette: 250-sheet ⁴ ; 16-43 lb. bond; Letter, Legal, A4, A5, B5, Statement, Executive		
	Multipurpose Tray: 1-sheet ⁴ ; 16-43 lb. bond		
	Platen Size: Up to 8.5" x 11"		
	ADF Size: 5.8" x 4.1" to 8.5" x 14"		ADF Size: 5.5" x 5" to 8.5" x 14"
Duplex	N/A	Print	All Mode (Print, Copy, Scan, Fax)
Duty Cycle	Up to 8,000 pages per month	Up to 10,000 pages per month	
Security	IP Filtering, MAC Address Filtering		
PRINTER SPECIFICATIONS			
First Print Time	Approximately 5.8 seconds (letter) ⁵		
Printer Language	UFR II LT (Host-based)		
Print Resolution	Up to 600 x 600 dpi (1200 x 600 dpi quality)		
Print Features	Print Modes (Watermark, Toner Saver, Page Composer)		
Print Memory	128 MB (Shared with Copy Memory)		
COPIER SPECIFICATIONS			
First Copy Time	Approximately 8.7 seconds ⁶		
Copy Resolution	Up to 600 x 600 dpi		
Halftones	256 levels		
Maximum # of Copies	99 copies		
Copy Features	Reduction/Enlargement 25%-400%, Collate, 2 on 1, 4 on 1, ID Card Copy, Copy Modes (Text, Photo, Text/Photo, Text/Photo+)		
SCANNER SPECIFICATIONS			
Scan Type	Color Contact Image Sensor (CIS); 24-bit color depth; TWAIN & WIA compatible		
Scan Speed	Black/Color: Up to 21 ipm/3.9 ipm ⁷		Black/Color: Up to 23 ipm/3.9 ipm ⁷ (1-sided) Black/Color: Up to 8 ipm/2.6 ipm ⁷ (2-sided)
Scan Resolution	Up to 600 x 600 dpi (optical); Up to 9600 x 9600 (interpolated)		
Output File Formats	Hi-Compression PDF (Windows only), Searchable PDF (Windows only), PDF, JPEG, TIFF, BMP, PNG ⁸		
Scan Features	Rotate, Push (Scan to PC) & Pull Scan		
FAX SPECIFICATIONS			
Modem Speed	Up to 33.6 Kbps (Super G3) ⁹		
Fax Resolution	Up to 200 x 400 dpi (super fine)		
Fax Memory	Up to 256 sheets ¹⁰		
Speed Dialing	4 one-touch speed dials; 100 coded dials		
Group Dialing	103 destinations		
Sequential Broadcasting	114 destinations		
PC Fax	Yes (sending only)		
Fax Forwarding	Yes (FAX -> FAX)		
Fax Features	Fax/Telephone Auto Switch, Remote RX, Dual Access, Distinctive Ring Pattern Detection, Error Correction Mode, Auto Redial, Activity Result & Management Reports		

Features and specifications are subject to change without notice.

GENERAL SPECIFICATIONS

Dimensions: MF4770n/MF4880dw:

15.4" (W) x 14.3" (D) x 14.2" (H)

MF4890dw:

15.4" (W) x 14.5" (D) x 14.2" (H)

Weight: MF4770n:

25.1 lbs. (w/o CRG); 26.2 lbs. (w/ CRG)

MF4880dw:

26.7 lbs. (w/o CRG); 28 lbs. (w/ CRG)

MF4890dw:

28.2 lbs. (w/o CRG); 29.5 lbs. (w/ CRG)

Package Weight: MF4770n: Approx. 35.7 lbs.

MF4880dw: Approx. 37.0 lbs.

MF4890dw: Approx. 38.8 lbs.

Warranty: 1 year limited exchange/carry-in¹¹ (Extended warranty available)

ENVIRONMENTAL SPECIFICATIONS

MF4770n:

Typical Energy Consumption (TEC): 0.7kWh

Power Consumption:

During Operation: Approx. 520W

Standby: Approx. 4.5W

Energy Saver: Approx. 1.3W

MF4880dw/MF4890dw:

Typical Energy Consumption (TEC): 0.8kWh

Power Consumption:

During Operation: Approx. 520W

Standby: Approx. 5W

Energy Saver: Approx. 2.1W

Noise Level¹²

During Operation: 6.6 B or less (sound power)

51 dB or less (sound pressure)

During Standby: 4.3 B or less (sound power)

Inaudible (sound pressure)

WHAT COMES IN THE BOX

Power Cord (USB not included), Phone Cable, Starter Cartridge 128, Canon Drivers, MF Toolbox (scan application), Document Management & OCR Software

ORDERING INFORMATION

ImageCLASS MF4770n Item #6371B030AA
ImageCLASS MF4880dw Item #6371B010AA
ImageCLASS MF4890dw Item #6371B006AA

Virtual CarePAK (2 Year Exchange/Carry-in CarePAK)

ImageCLASS MF4770n Item #6521A107AA
ImageCLASS MF4880dw Item #6521A106AA
ImageCLASS MF4890dw Item #6521A105AA

E-CarePAK (2 Year Exchange/Carry-in CarePAK) Item #5707B020AA

Replacement Consumable:
Cartridge 128 (yields approx. 2,100 sheets ISO/IEC) Item #3500B001AA

1) Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type and orientation of paper. 2) USB 2.0 Hi-Speed requires Windows[®] 7, Windows Vista[®], Windows XP/2000 or Mac OS X operating systems. For Windows 98, Me and Mac OS X v. 10.2 to 10.2.6 operating systems, the printer/scanner will operate at USB 1.1 specifications. 3) Wireless performance may vary based on terrain and distance between the printer and wireless network clients. 4) Based on 20 lb. bond paper. 5) May vary depending on the output environment. 6) Letter size, after being restored from energy saver mode. 7) Based on letter-size scanning at 300 x 300 dpi. 8) PNG supports Mac OS only. 9) The Public Switched Telephone Network currently supports fax modem speeds of 28.8 Kbps or lower, depending on telephone line conditions. Sending and receiving fax machines need to conform to ITU-T v.34 guidelines. 10) Based on ITU-T #1 Chart (standard mode). 11) Warranty program is subject to certain conditions and restrictions. See the warranty card for details. 12) Declared noise emission in accordance with ISO 9296. 13) Quiet Mode may affect processing speed and may not lower all sound. Quiet Mode is only compatible with certain paper sizes or types. Special Mode has higher priority than Quiet Mode.



©2012 Canon U.S.A., Inc. Canon, imageCLASS and the Super G3 logo are registered trademarks of Canon Inc. in the United States and may be registered trademarks or trademarks in other countries. imageANYWARE is a trademark of Canon U.S.A., Inc. Microsoft, Windows, the Windows logo and Windows 7 are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and other countries. Wi-Fi is a registered trademark of the Wi-Fi Alliance. The 'Wi-Fi CERTIFIED' logo is a certification mark of the Wi-Fi Alliance. All other product and brand names are trademarks of their respective owners. Specifications are subject to change without notice. As an ENERGY STAR partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. The limited warranty given by Canon U.S.A., Inc. is for Canon imageCLASS D4000 Series models purchased and used in the United States.

Canon
imageANYWARE