

EOS REBEL

COMPARISON CHART

		 EOS Rebel T7i	 EOS Rebel T6s EOS Rebel T6i	 EOS Rebel T5i	 EOS Rebel T6	 EOS Rebel T5	 EOS Rebel SL2
Image Sensor	Size	Approx. 24.2 megapixels			Approx. 18.0 megapixels		Approx. 24.2 megapixels
	Type	APS-C CMOS Sensor					
ISO Range	Stills	ISO 100–25600, H: 51200	ISO 100–12800, H: 25600		ISO 100–6400, H: 12800		ISO 100–25600, H: 51200
	Videos	ISO 100–12800, H: 25600	ISO 100–6400, H: 12800		ISO 100–6400		ISO 100–12800, H: 25600
Image Processor							
Continuous Shooting		Up to 6.0 fps	Up to 5.0 fps		Up to 3.0 fps		Up to 5.0 fps
Maximum Shutter Speed Range		BULB, 30–1/4000 sec.					
Number of Focusing Points*		Max. 45 cross-type AF points	Max. 19 cross-type AF points	All 9 cross-type AF points	9 AF points		
Live View Autofocus		Dual Pixel AF CMOS	Hybrid AF III CMOS	Hybrid AF CMOS	Contrast AF		Dual Pixel AF CMOS
Video Recording	Video Recording Size	1920 x 1080 (Full HD): 60p, 30p, 24p; 1280 x 720 (HD): 60p, 30p; 640 x 480 (SD): 30p	1920 x 1080 (Full HD): 30p, 24p; 1280 x 720 (HD): 60p, 30p; 640 x 480 (SD): 30p	1920 x 1080 (Full HD): 30p, 24p; 1280 x 720 (HD): 60p; 640 x 480 (SD): 30p			1920 x 1080 (Full HD): 60p, 30p, 24p; 1280 x 720 (HD): 60p, 30p; 640 x 480 (SD): 30p
	MP4 Recording	Yes		-		Yes	
	Special Features	HDR Video, Time-lapse Video	HDR Video (T6s only)		-		HDR Video, Time-lapse Video
	Built-in Microphones	Stereo			Monaural		Stereo
LCD Size/Type		Vari-angle Touch Screen 3.0-inch Clear View LCD monitor II			3.0-inch LCD monitor		Vari-angle Touch Screen 3.0-inch Clear View LCD monitor II
Built-in Wireless Connectivity				-		-	
Recording Media		SD / SDHC / SDXC Memory Cards (UHS-I compatible)					
Connectivity		USB 2.0 Hi-Speed (PictBridge compatible); AV Output (NTSC, MP4, Stereo Audio); Micro-HDMI Connector, SD Memory Card Slot			USB 2.0 Hi-Speed (PictBridge compatible); AV Output (NTSC, MOV, Stereo Audio); Micro-HDMI Connector, SD Memory Card Slot		USB 2.0 Hi-Speed, AV Output (NTSC, MP4, Stereo Audio); Micro-HDMI Connector, SD Memory Card Slot
Additional Features		Built-in Flash / Hot Shoe					
Dimensions (W x H x D)		Approx. 5.16 x 3.93 x 3.00 in./ 131.0 x 99.9 x 76.2mm	T6s: Approx. 5.20 x 3.98 x 3.07 in./ 131.9 x 100.9 x 77.8mm T6i: Approx. 5.20 x 3.97 x 3.07 in./ 131.9 x 100.7 x 77.8mm	Approx. 5.2 x 3.9 x 3.1 in./ 133.1 x 99.8 x 78.8mm	Approx. 5.08 x 3.99 x 3.06 in./ 129.0 x 101.3 x 77.6mm	Approx. 5.10 x 3.93 x 3.07 in./ 129.6 x 99.7 x 77.9 mm	Approx. 4.82 x 3.65 x 2.75 in./ 122.4 x 92.6 x 69.8mm
Weight (CIPA standard^^)		Approx. 18.77 oz. / 532g	T6s: Approx. 19.93 oz. / 565g T6i: Approx. 19.58 oz. / 555g	Approx. 20.5 oz. / 580g	Approx. 17.11 oz. / 485g	Approx. 16.93 oz. / 480g	Approx. 15.98 oz. / 453g

Not responsible for typographical errors. Products not shown to scale. * The number of AF points, cross-type AF points and Dual cross-type AF points vary depending on the lens used. ** Compatible with iOS® versions 8.4/9.3/10.2, Android™ smartphone and tablet versions 4.1/4.2/4.3/4.4/5.0/5.1/6.0/7.0/7.1. Data charges may apply with the download of the free Canon Camera Connect app. This app helps enable you to upload images to social media services. Please note that image files may contain personally identifiable information that may implicate privacy laws. Canon disclaims and has no responsibility for your use of such images. Canon does not obtain, collect or use such images or any information included in such images through this app. *** Compatible with Android™ smartphone and tablet versions 4.1/4.2/4.3/4.4/5.0/5.1/6.0/7.0/7.1. ^ Compatible with select smartphone and tablet devices (Android™ version 5.0 or later and the following iOS® devices: iPhone 4s or later, iPad 3rd gen. or later, iPod Touch 5th gen. or later) equipped with Bluetooth™ version 4.0 or later and the Camera Connect App Ver. 2.0.40. This application is not guaranteed to operate on all listed devices, even if minimum requirements are met. ^^ CIPA Standard-including the battery and memory card.