



MACRO TWIN LITE MT-26EX-RT

Specifications

Main Unit Spec																							
Flash																							
Type	E-TTL II/E-TTL autoflash, Twin flash for close-distance photography																						
Guide Number	Both-sides firing: 85.3/26 Single-side firing: 65.3/19.9 (ISO 100, in feet/meters) • Flash output for quick flash is approx. 1/2 to 1/6 of full output (depending on the charge status).																						
Flash Duration	<table border="1"> <thead> <tr> <th>Flash Output</th> <th>Firing Duration (Approx., sec.)</th> </tr> </thead> <tbody> <tr> <td>1/1 (Full)</td> <td>1/1300</td> </tr> <tr> <td>1/2</td> <td>1/1900</td> </tr> <tr> <td>1/4</td> <td>1/3700</td> </tr> <tr> <td>1/8</td> <td>1/8700</td> </tr> <tr> <td>1/16</td> <td>1/13000</td> </tr> <tr> <td>1/32</td> <td>1/23000</td> </tr> <tr> <td>1/64</td> <td>1/34000</td> </tr> <tr> <td>1/128</td> <td>1/42000</td> </tr> <tr> <td>1/256</td> <td>1/58000</td> </tr> <tr> <td>1/512</td> <td>1/67000</td> </tr> </tbody> </table>	Flash Output	Firing Duration (Approx., sec.)	1/1 (Full)	1/1300	1/2	1/1900	1/4	1/3700	1/8	1/8700	1/16	1/13000	1/32	1/23000	1/64	1/34000	1/128	1/42000	1/256	1/58000	1/512	1/67000
Flash Output	Firing Duration (Approx., sec.)																						
1/1 (Full)	1/1300																						
1/2	1/1900																						
1/4	1/3700																						
1/8	1/8700																						
1/16	1/13000																						
1/32	1/23000																						
1/64	1/34000																						
1/128	1/42000																						
1/256	1/58000																						
1/512	1/67000																						
Flash Control System	8:1 - 1:1 - 1:8; 1/2-stop increments																						
Exposure Control Modes	(1) Both-sides firing (2) Single-side firing																						
Custom Functions	8 Custom Functions																						
General																							
Power Source	Four size-AA/LR6 alkaline batteries • Size-AA/HR6 Ni-MH batteries also usable.																						
External Power Source	Compact Battery Pack CP-E4N • Compact Battery Pack CP-E3 or CP-E4 can also be used.																						
Dimensions (W x H x D)	Flash head unit (including mount ring): Approx. 9.14 x 3.59 x 1.93 in. / 232.2 x 91.1 x 49.1mm Control unit: Approx. 2.74 x 4.43 x 3.54 in. / 69.5 x 112.5 x 90.0mm																						
Weight	Approx. 20.1 oz. / 570g Includes flash unit and control unit, excluding batteries.																						