



RF600mm F4 L IS USM

Specifications

Lens	
Focal Length	600mm
Maximum and Minimum Aperture	F4-32
Lens Mount Type	RF Mount (Canon RF mount; Exclusively for Canon EOS R-series cameras)
Minimum Focusing Distance	13.78 ft. /4.2m
Maximum Magnification	0.15x
Angle of View	Diagonal: 04°10'
Lens Construction	17 elements in 13 groups
Special Elements	Two Fluorite, One Super UD
Lens Coating	Super Spectra, Fluorine (front & rear elements), ASC
Filter Size Diameter	Ø52 mm (Drop-in filter — Drop-in Screw-type Filter Holder 52 [WIII] included, with 52mm clear Protect Filter)
Aperture Blades	9
Dust/Water Resistance	Supported (Rubber ring on lens mount, focus/playback rings, switch panel and switches)
IS Mode Selection	Provided: mode 1, 2, 3
Optical Image Stabilization	CIPA standard: 5.5 stops (using an EOS R / EOS R5)
Maximum Outer Diameter x Length	Approx. 6.6 in x 18.6 in. / 168mm x 472mm
Weight	Approx. 6.8 lbs. / 3090g
Accessories	
Lens hood	Long: ET-160 (WIII) (Bundled) Short: ET-160B (Sold separately)
Lens Cap	E-185C (soft type) (bundled)
Dust Cap	Lens Dust Cap RF (Bundled)
Lens Case	LS600 Soft Case (Bundled)
Drop-in Filters	Canon Drop-in Circular Polarizing Filter 52 (WIII) Canon Drop-in Gelatin Filter Holder 52 (WIII)