

PRODUCT SPECIFICATIONS



Main Unit

Type

Color Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store
 Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory

4.0 GB RAM

Hard Disk Drive

Standard: 250 GB
 Maximum: 1 TB

Mirroring Hard Disk Drive

Optional (250 GB, 1 TB)
 Method: Raid1

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
 Wireless LAN (IEEE 802.11 b/g/n)

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),
 USB 2.0 x1 (Device)
 Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets
 Maximum: 6,350 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet
 Stack Bypass

Optional: Dual 550-sheet Paper Cassettes
 (CASSETTE FEEDING UNIT-AM1),
 2,450-sheet High-Capacity Paper Cassette
 (HIGH CAPACITY CASSETTE FEEDING
 UNIT-A1), 2,700-sheet Paper Deck
 (PAPER DECK UNIT-F1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets
 Maximum: 3,450 Sheets
 (with External Finisher and Copy Tray)

Finishing Capabilities

Standard: Collate, Group
 With Inner
 Finisher: Collate, Group, Offset, Staple, Hole Punch,
 Staple-Free Staple, Staple On Demand
 With External
 Finishers: Collate, Group, Offset, Staple, Booklet, Hole
 Punch, Staple-Free Staple, Staple On Demand

Supported Media Types

Paper
 Cassette 1: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond,
 Transparency, Envelope
 Paper
 Cassette 2: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Letterhead, Bond,
 Transparency, Tab, Envelope
 Stack Bypass: Thin, Plain, Recycled, Color, Heavy,
 Pre-punched, Labels, Letterhead,
 Bond, Coated, Transparency, Tab,
 Tracing,¹ Envelope

Supported Media Sizes

Paper
 Cassette 1: Letter, Executive, Statement-R, Envelope
 [No.10 (COM10), DL, ISO-C5], Custom Size
 (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")
 Paper
 Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
 Executive, Statement-R, Envelope [No.10
 (COM10), Monarch, DL, ISO-C5], Custom Size
 (3-7/8" x 7-1/8" to 12" x 18")
 Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,
 Executive, Statement, Statement-R,
 Envelope [No.10 (COM10), Monarch,
 DL, ISO-C5], Envelope Custom Size
 (3-7/8" x 3-7/8" to 12-5/8" x 18"),
 Custom Size (3-7/8" x 5-1/2" to
 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to
 12-5/8" x 18")

Supported Media Weights

Cassettes:	14 lb. Bond to 140 lb. Index (52 to 256 g/m ²)
Stack Bypass:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m ²)
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m ²)

Warm-up Time

From Power On:	10 Seconds ²
From Sleep Mode:	10 Seconds

Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)³

Installation Space (W x D)

Basic:	Stack Bypass + Cassette Drawers open: 37-1/8" x 46-3/8" (943 mm x 1,176 mm) ³
--------	---

Weight

Approx. 313.1 lb. (142 kg)⁴

Print Specifications

Print Speed (BW and Color)

C5560i II:	Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")
C5550i II:	Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")
C5540i II:	Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")
C5535i II:	Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR II, PCL®6, Adobe® PS® 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁵

Supported File Types

PDF, TIFF, JPEG, EPS,⁶ XPS

Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts:	93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese), ⁷ Barcode Fonts ⁸
PS fonts:	136 Roman

Operating System⁹

UFR II:	Windows Vista®/Server 2008/Windows® 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.7 or later)
PCL:	Windows Vista/Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016
PS:	Windows Vista/Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.7 or later)

Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing

Copy Specifications

Copy Speed (BW and Color)

C5560i II:	Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")
C5550i II:	Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")
C5540i II:	Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")
C5535i II:	Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

First-Copy-Out Time (Letter)

C5560i II:	As fast as 2.9 seconds (BW)/4.5 seconds (Color)
C5550i II:	As fast as 3.5 seconds (BW)/5.2 seconds (Color)
C5540i II:	As fast as 4.1 seconds (BW)/6.1 seconds (Color)
C5535i II:	As fast as 4.9 seconds (BW)/7.4 seconds (Color)

Copy Resolution (dpi)

Reading:	600 x 600
Printing:	1200 x 1200

Multiple Copies

Up to 9,999 Copies

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on I, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original:	13 lb. Bond to 58 lb. Cover (50 to 157 g/m ²)
CL Original:	17 lb. Bond to 58 lb. Cover (64 to 157 g/m ²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

Pull Scan

Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows Vista/7/8.1/10
Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning (BW):
80 ipm (300 dpi)/80 ipm (600 dpi)
Single-sided Scanning (Color):
80 ipm (300 dpi)/60 ipm (600 dpi)
Double-sided Scanning (BW):
160 ipm (300 dpi)/150 ipm (600 dpi)
Double-sided Scanning (Color):
160 ipm (300 dpi)/80 ipm (600 dpi)

Send Specifications

Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File:	FTP, SMB, WebDAV
E-mail/I-Fax:	SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard:	TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint®, Word, Digital Signature (PDF/XPS))
Optional:	PDF (Trace & Smooth)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

Fax Specifications

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (1 TB HDD)

Advanced Box Features

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media

Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express,^{10,11} User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Document

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration
Optional: User Signatures, Document Scan Locking

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (no condensation)

Power Requirements

C5560i/C5550i II: 120-127V AC 60 Hz, 11.5 A

C5540i/C5535i II: 120-127V AC, 60 Hz, 10 A

Plug (Main Unit)

C5560i II/C5550i II: NEMA 5-20P

C5540i II/C5535i II: NEMA 5-15P

Power Consumption

Maximum: Approx. 1.8 kW

Standby: Approx. 66.2 W

Sleep Mode: Approx. 0.8 W¹²

Typical Electricity Consumption (TEC) Rating:

C5560i II: 3.2 kWh

C5550i II: 2.5 kWh

C5540i II: 2.0 kWh

C5535i II: 1.6 kWh

Standards

ENERGY STAR® Certified

Rated EPEAT® Gold¹³

RoHS Compliant

Consumables

Toner

GPR-55 Toner¹⁴

Toner Yield (Estimated @ 6% Coverage)

Black: 69,000 Images

Color (C,M,Y):¹⁴ 60,000 Images

Fiery Print Controller Specifications (Optional)

ColorPASS-GX500 (External)

(iR ADV C5560i II/iR ADV C5550i II only)

System

Fiery FS200 Pro

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

Adobe PS 3, PCL5 (Driverless)

Memory

4 GB

Hard Disk Drive

1 TB

Processor

Intel Core i5-4570S 2.9 GHz up to 3.6 GHz w/Turbo

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 10 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64bit only)/Windows Server 2012 R2 (64bit only)/MAC OS (10.7, 10.8, 10.9, 10.10, 10.11)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 6 (Front x 2, Rear x 4), USB2.0 x 2 (Front x 2)

Network Protocols

TCP/IP (LPR/Port 9100/SNMP/IPP/HTTP/HTTPS/FTP/SMB)/DNS

Direct Print

PDF1.7(APPE3), EPS, TIFF6, JDF1.4/JMF

VDP

FreeForm2.1, PDF/VT-2, PPML3, VPS

Fiery Print Controller Standard Features

FIERY HOT FOLDERS/Virtual Printers/Unity Display (Monitor required)/FIERY JDF/FIERY COMMAND WORKSTATION 5/Paper Catalog/FIERY SPOT-ON/FIERY REMOTE SCAN

Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND COMPOSE, Graphic Arts Package Premium Web Activate/Removable HDD Kit-B1/Integration Interface and Stand (19" display, keyboard and mouse)

Dimensions (W x D x H)

8-1/2" x 19" x 19-1/8" (215 mm x 483 mm x 485 mm)

imagePASS-P1 (Embedded)

System

Fiery FS200

Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

Standard Page Description Languages

PCL6, Adobe PS 3

Memory

2 GB

Hard Disk Drive

500 GB

Processor

Intel Celeron G1820 2.7 GHz

Fonts

PS: 138 Adobe PS Fonts

PCL: 113 PCL Fonts

Supported Operating Systems

Windows Vista (32 and 64 bit)/Windows 8 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 7 (32 and 64 bit)/Windows Server 2008 (32 and 64 bit)/Windows Server 2008 R2 (64 bit only)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/MAC OS (10.7 or higher)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB x 3.0 x 2 (Rear x 2), USB x 2.0 x 4 (Rear x 4)

Network Protocols

TCP/IP (LPR/Port 9100/IPP/SMB/FTP)/DNS

Fiery Print Controller Features

FIERY COMMAND WORKSTATION 5, PAPER CATALOG, FIERY SPOT ON, FIERY REMOTE SCAN

Fiery Print Controller Options

FIERY IMPOSE, FIERY COMPOSE, FIERY IMPOSE AND COMPOSE, Productivity package Web activate (Includes Fiery JDF), Hot Folders License

Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

Paper Supply Options

CASSETTE FEEDING UNIT-AM1

Paper Capacity: 550 Sheets x 2 Cassettes [20 lb. Bond (80 g/m2)]
 Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, and Custom Size [3-7/8" x 7-1/8" to 12" x 18" (98.0 x 182.0 to 304.8 x 457.2 mm)]
 Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m2)
 Power Source: From the Main Unit
 Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)
 Weight: Approx. 49.6 lb. (22.5 kg)

HIGH-CAPACITY CASSETTE FEEDING UNIT-A1

Paper Capacity: 2,450 sheets [20 lb. Bond (80 g/m2)]
 Paper Size: Letter
 Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m2)
 Power Source: From the Main Unit
 Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)
 Weight: 66.1 lb. (30 kg)

PAPER DECK UNIT-F1

Paper Capacity: 2,700 Sheets [20 lb. Bond (80 g/m2)]
 Paper Size: Letter
 Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m2)
 Power Source: From the Main Unit
 Dimensions (W x D x H): 15-3/4" x 24-7/8" x 17-3/8" (400 mm x 630 mm x 440 mm)
 Weight: 68.3 lb. (31 kg)

Output Options

INNER 2-WAY TRAY-J1

Number of Trays: 2
 Total Output Capacity: Upper Tray: 100 Sheets
 Lower Tray: 250 Sheets
 Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m2)
 Paper Size: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")
 Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")
 Dimensions (W x D x H): 16-7/8" x 16" x 3" (427 mm x 407 mm x 76 mm)
 Weight: Approx. 1.3 lb (0.6 kg)

INNER FINISHER-H1

Number of Trays: 2
 Top Tray Capacity: Letter/Statement/Statement-R/Executive (45 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (45 Sheets)
 Lower Tray Capacity: Letter/Statement/Statement-R/Executive (500 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (250 Sheets)
 Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m2)
 Acceptable Paper Weight: 14 lb. Bond to 140 lb. Cover (52 to 256 g/m2)
 Staple Position: Corner, Double
 Staple Capacity Corner Staple and Double Staple
 Letter/Executive: 50 Sheets (14 to 24 lb. Bond)
 11" x 17"/Legal/Letter-R: 30 Sheets (14 to 24 lb. Bond)
 Staple-Free Staple 11"x17"/Letter: 5 Sheets (14 to 17 lb. Bond)
 4 Sheets (17.3 to 21.7 lb. Bond)
 3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m2)]
 Power Source: From the Main Unit
 Dimensions (W x D x H): 29-1/4" x 29-1/4" x 8-7/8" (743 mm x 742 mm x 225 mm)
 Weight: Approx. 19 lb (8.6 kg)

STAPLE FINISHER-Y1 (External)

Number of Trays: 2
 Top Tray Capacity: Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
 Lower Tray Capacity: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)
 Paper Weight Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m2)
 Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m2)
 Staple Position: Corner, Double
 Staple Capacity Corner Staple and Double Staple
 Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m2)]
 11" x 17"/Legal/ 30 Sheets [24 lb. Bond (90 g/m2)]
 Letter-R: Staple-Free Staple: 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m²)]
 4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m²)]
 3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m²)]
 Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m²)]
 Power Source: From the Main Unit
 Dimensions (W x D x H): 25-1/8" x 24-1/2" x 45" (637 mm x 623 mm x 1142 mm)
 Weight: Approx. 68.3 lb (31 kg)

BOOKLET FINISHER-Y1 (External)

Number of Trays: 3
 Top Tray Capacity: Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
 Lower Tray Capacity: Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)
 Paper Weight Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m2)
 Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m2)
 Staple Position: Corner, Double
 Staple Capacity Corner Staple and Double Staple
 Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m2)]
 11" x 17"/Legal/ 30 Sheets [24 lb. Bond (90 g/m2)]
 Letter-R: Staple-Free Staple 11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond ((52 to 64 g/m2)]
 4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m2)]
 3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m2)]
 Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m2)]
 Booklet-Stitch Paper Size: 12" x 18", 11" x 17", Legal, Letter-R, Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]
 Booklet-Stitch Staple Capacity: 20 Sheets x 10 Sets [22 lb. Bond (81 g/m2)] (including one cover sheet up to 140 lb.)] Index (256 g/m2)
 Power Source: From the Main Unit/85.6 W
 Dimensions (W x D x H): 25-1/8" x 24-1/2" x 45" (637 mm x 623 mm x 1142 mm)
 Weight: Approx. 125.7 lb (57 kg)

INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable 14 lb. Bond to 110 lb. Cover
 Punch Paper (52 to 300 g/m2)
 Weight:

Acceptable Punch Paper Size Two Holes: 11" x 17", Legal, Letter, Letter-R, Executive
 Three Holes: 11" x 17", Letter, Executive
 Power Source: From the Main Unit

2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1)

Acceptable 14 lb. Bond to 110 lb. Cover
 Punch Paper (52 to 300 g/m2)
 Weight: Acceptable Punch Paper Size Two holes: 11" x 17", Legal, Letter, Letter-R, Executive
 Three holes: 11" x 17", Letter, Executive
 Power Source: From the Main Unit

Hardware Options

Card Readers

MiCARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

Others

CABINET TYPE-N
BUFFER PASS UNIT-L1
COPY TRAY-J2
UTILITY TRAY-B1
PLATEN COVER TYPE W
PRINTER COVER-J1
TAB FEEDING ATTACHMENT-F1
USB KEYBOARD

Security Options

Document Security

DOCUMENT SCAN LOCK KIT-B1
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON
CRITERIA CERTIFICATION¹⁵

Data Security

HDD MIRRORING KIT-J1
2.5"/250 GB HDD-N1
2.5"/1 TB HDD-P1
REMOVABLE HDD KIT-AL1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

Barcode Printing

BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller

imagePASS-P1
ColorPASS-GX500 (iR ADV C5560i II/iR ADV C5550i II only)
REMOVABLE HARD DISK DRIVE KIT-B1
FIERY IMPOSE
FIERY COMPOSE
FIERY IMPOSE AND COMPOSE

System Accessories

COPY CONTROL INTERFACE KIT-A1
CONNECTION KIT-A1 FOR BLUETOOTH LE
NFC KIT-C1
MEAP WEB CONNECTION KIT-G3¹⁶

Fax Accessories

SUPER G3 FAX BOARD-AS2
SUPER G3 2ND LINE FAX BOARD-AS2
SUPER G3 3RD/4TH LINE FAX BOARD-AS2
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1
BRAILLE LABEL KIT-F1

Staples

STAPLE-P1¹⁷
STAPLE CARTRIDGE-Y1¹⁸

¹ Some types of tracing paper cannot be used.

² Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

³ Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

⁴ Includes main unit, consumables, and Cassette Feeding Unit-AM1.

⁵ PDF print from Web sites is supported.

⁶ EPS can be printed directly only from the Remote User Interface.

⁷ Requires the optional PCL International Font Set-A1.

⁸ Requires the optional Barcode Printer Kit-D1.

⁹ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹⁰ No charge for this solution; however activation is required.

¹¹ Check for availability.

¹² 0.8 W sleep mode not available in all circumstances due to certain settings.

¹³ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

¹⁴ GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

¹⁵ Will launch at a later date.

¹⁶ No charge for this option; however it does need to be ordered.

¹⁷ Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.

¹⁸ Used for booklet finishing only. 3 cartridges per case. 2,000 staples per cartridge.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. II indicates that this model has been upgraded to new system software and includes additional security features as standard. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2018 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



0318R1-iRA5511xxSS-PDF-SP

