



XA75 XA70

| | | XA75 | XA70 |
|-----------------------------------|---|---|------|
| CMOS Sensor | Sensor Size | 1.0 inch | |
| | Effective Pixels | Approx. 8.29 million (total pixels: 13.40 million) | |
| Lens | Magnification, Focal Length | 15x optical zoom, 25.5 - 382.5 mm f/2.8-4.5 4K UHD (with Dynamic IS OFF/Standard IS ON) | |
| | ND Filter | 3 steps (switchable) | |
| | Image Stabilizer | Optical + electronic correction | |
| Focus | | Dual Pixel CMOS AF, Contrast AF | |
| Infrared camera supported | | YES | |
| LCD Monitor | | 3.5-inch (approx. 2.76 million dots), LCD, Capacitive touch panel | |
| EVF | | 0.36-inch (approx. 1.77 million dots), OLED, articulating | |
| Looks | | Standard, Wide DR (800%), Neutral, Monochrome | |
| Movie recording | XF-AVC (MXF) | 3840 x 2160 29.97p / 23.98p 1920 x 1080 59.94p / 59.94i / 29.97p / 23.98p | |
| | MP4 | 3840 x 2160 29.97p / 23.98p 1920 x 1080 59.94p / 29.97p / 23.98p 1280 x 720 59.94p | |
| | Audio | During MP4 recording: AAC 2ch, LPCM 4ch During XF-AVC recording: LPCM 4ch | |
| | Slow and Fast (S&F) Motion Recording | x0.4 and up (60 fps/Full HD 29.97p playback) | |
| | Color Sample/Bit Depth | 4:2:0 8 bit | |
| Recording Media | | SD card (UHS-I U3 support) x 2 slots | |
| Professional use terminals | SDI terminal | YES (3G-SDI) | NO |
| | XLR terminal | YES x2 | |
| Other terminals | | HDMI, separate headphone jack, UVC (USB Type-C), DC IN (USB Type-C), remote and MIC terminal (supports plug-in power) | |
| Detachable handle | | YES | |
| Wi-Fi | | NO | |
| Wired LAN | | NO | |

| | | XA75 | XA70 |
|--------------------------|--|---|---------------------------|
| Included battery | | BP-820 | |
| Power consumption | | Approx. 5.3W | |
| Dimensions | | Approx. 4.3 x 3.6 x 8.4 in. / 110 x 91 x 214 mm | |
| Weight | Body only | Approx. 2.2 lbs. / 990 g | Approx. 2.2 lbs. / 985 g |
| | Lens hood, mic holder unit, handle unit, BP-820 and memory card (1 pc) included | Approx. 3.2 lbs. / 1465 g | Approx. 3.2 lbs. / 1460 g |

| Recording Mode | [Main operation] SD Card recording | | | | SDI/HDMI output | | | | | | | |
|-----------------------|---|------------|--------------|-------------|------------------------|------------|--------------|-------------|--------|-----------|--------|--------|
| | Resolution | Frame rate | Color format | Color depth | Resolution | Frame rate | Color format | Color depth | | | | |
| XF-AVC | 3840x2160 | 29.97p | 4:2:0 | 8 bit | 1920x1080 | 29.97p | 4:2:2 | 8 bit | | | | |
| | | | | | | 59.94i | | | | | | |
| | | 1280x720 | | | 59.94p | | | | | | | |
| | | 1920x1080 | | | 23.98p | 23.98p | | | | | | |
| | 59.94i | | | | 59.94i | | | | | | | |
| | 1920x1080 | 59.94p | | | 59.94p | 59.94p | | | 59.94p | 1920x1080 | 59.94p | 59.94i |
| | | | | | | | | | | | 59.94i | |
| | | 59.94i | | | 59.94p | 59.94p | | | 59.94p | 1920x1080 | 29.97p | 59.94i |
| | | | 29.97p | | | | | | | | | |
| | | 23.98p | 23.98p | 23.98p | 23.98p | 23.98p | 1920x1080 | 23.98p | 59.94i | | | |
| | | | | | | | | 59.94i | | | | |
| | | | 59.94p | 59.94p | 59.94p | 59.94p | 1280x720 | 59.94p | 59.94p | | | |
| | | | | | | | | 59.94p | | | | |