

## Canon Accessibility Conformance Report

ITI VPAT® Version 2.4

### Name of Product:

Canon Inkjet Office All-In-One GX3000 Series, including :  
GX3010, GX3020, GX3040, GX3050, GX3060,  
GX3070, ,GX3072 GX3080, GX3090, GX3091 and GX3092.



**Product Description:** Multi-function Inkjet Printer

**Date:** October 14th, 2022

**Contact information:** [accessibility@cusa.canon.com](mailto:accessibility@cusa.canon.com) (USA)  
[IJ-accessibility@canon-europe.com](mailto:IJ-accessibility@canon-europe.com) (Europe)

### Notes:

Produce business-quality documents quickly with these ever-dependable, high volume refillable MegaTank printers.

**Evaluation Methods Used:** Inspection, measurement and testing are based on product knowledge and testing with consistent evaluation methods through our products. Softwares are tested with JAWS. (The testing was performed with JAWS 2021. An earlier version may not provide the same result.)

### Applicable Standards / Guidelines & Table of contents :

This report covers the degree of conformance for the following accessibility standard/guideline:

**US Section 508 standards (2017) with corrections (2018)**  
**EN 301 549 V3.2.1 (2021)**  
**WCAG 2.1 (2018)**  
**ISO/IEC 10779: 2020**

### The composition of evaluated product:

**Hardware Device**  
**Driver:** Printer Driver Software  
**Web Application:** Remote UI  
**Documents**

**Terms:** The terms used in the Conformance Level information are defined as follows:

**Supports:** The functionality of the product has at least one method that meets the criteria without known defects or meets with equivalent facilitation.

**Partially Supports:** Some functionality of the product does not meet the criteria.

**Supports through Equivalent Facilitation:** Some functionality of the product meet the intent of the Criteria through alternate way.

**Supports when combined with Compatible AT:** Some functionality of the product meet the criteria using assistive technology which is not a part of the product itself.

**Does Not Support:** Majority of functionality of the product does not meet the criteria.

**Not Applicable:** The criteria are not relevant to the product.

**Not Applicable – Fundamental Alteration Exception Applies:** The criteria are relevant to the product, but fundamentally impossible to meet the criteria, because of its conditions.

**\*Note 1:** To respect the WCAG, and avoid inconsistencies and confusion within this report, we follow the WCAG Understanding Conformance expressions through out the report. ie. if there is no target elements in the product, as eventually there is no underlying problem to be solved, it is expressed 'Supports' instead of 'Not Applicable', basically.

**Note 2:** 'Not Applicable' is limitedly applied to the case which the requirement presupposes the use of speech function provided by the equipment itself.

## US Section 508 Standards

### Chapter 3: Functional Performance Criteria

Criteria	Conformance Level	Remarks and Explanations
<p>302.1 Without Vision. Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that does not require user vision.</p>	<p>Partially Supports</p>	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. Speech output is not provided by the product itself. Some of the operable parts can not be discernible without vision. Keys on the operational panel are rather difficult to discern without vision. The stop key is tactilely distinguishable. The status indications on display cannot be distinguished by touch nor hearing.</p> <p><b>REMOTE UI*:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> Printer Driver can be operated with keyboard through hearing by using screen reader.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p> <p>*Access to Remote UI : Access to HTTP:XXX.XXX.XXX.XXX ( the IP address of your Canon device) to start its RemoteUI . Mainly the arrow-keys are used to move between the UI elements. For the Remote UI of this version, the child elements (lower hierarchy) follows after the parent elements serially.</p>
<p>302.2 With Limited Vision. Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that enables users to make use of limited vision.</p>	<p>Partially Supports</p>	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. The controls of key repeat and alarm volume cannot be operated easily without vision. Keys are rather difficult to discern without vision. Alphabetic keys and numeric keys are not provided. The stop key is tactilely distinguishable, among the existing keys. The scale of the ink capacity when refilling ink may be difficult to see because of the engraved mark. Other signs are easy to see. The status indications on display cannot be distinguished by touch nor hearing. Speech output is not provided by the product itself.</p> <p><b>REMOTE UI:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p>
<p>302.3 Without Perception of Color. Where a visual mode of operation is provided, ICT shall provide at least one visual mode of operation that does not require user perception of color.</p>	<p>Supports</p>	<p><b>HARDWARE:</b> The product has a monochrome display, which do not convey meaning by colour. All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.</p> <p><b>REMOTE UI:</b> There is information in text for the items which conveys meaning.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> Colour on display and on operable parts are not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>
<p>302.4 Without Hearing. Where an audible mode of operation is provided, ICT shall provide at least one mode of operation that does not require user hearing.</p>	<p>Supports</p>	<p>The product is basically operable without user hearing.</p> <p><b>HARDWARE:</b> The alarm volume is controllable.</p>

302.5 With Limited Hearing. Where an audible mode of operation is provided, ICT shall provide at least one mode of operation that enables users to make use of limited hearing.	Supports	The product is basically operable without user hearing.  HARDWARE: The alarm volume is controllable.
302.6 Without Speech. Where speech is used for input, control, or operation, ICT shall provide at least one mode of operation that does not require user speech.	Supports	The product does not require user speech.
302.7 With Limited Manipulation. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that does not require fine motor control or simultaneous manual operations.	Partially Supports	HARDWARE: There is no alternative in the operation part that requires pinching. The key repeat is controllable. <GX4000 Series> Bounce key function is not supported.  REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface.  PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
302.8 With Limited Reach and Strength. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that is operable with limited reach and limited strength.	Partially Supports	HARDWARE: There are places where the operating force for changing the paper size, but there is no alternative.  REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface.  PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
302.8 With Limited Reach and Strength. Where a manual mode of operation is provided, ICT shall provide at least one mode of operation that is operable with limited reach and limited strength.	Supports	HARDWARE: The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate pedestal which the user prepares.  REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface.  PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
302.9 With Limited Language, Cognitive, and Learning Abilities. ICT shall provide features making its use by individuals with limited cognitive, language, and learning abilities simpler and easier.	Partially Supports	HARDWARE: Speech output is not provided by the product itself. The status indications on display cannot be distinguished by touch nor hearing.  REMOTE UI: In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message can be confirmed only when the focus is on the status message.  PRINTER DRIVER: User can use the function that meets the purpose without interrupted by using accessibility feature.  DOCUMENTS: Components that have the same functionality are identified consistently.

#### Chapter 4: Hardware

Criteria	Conformance Level	Remarks and Explanations
402.1 General. (Closed Functionality ) ICT with closed functionality shall be operable without requiring the user to attach or install assistive technology other than personal headsets or other audio couplers, and shall conform to 402.	No response required according to ITI VPAT, as adviced on the original VPAT of ITI.	
402.2.1 Information Displayed On-Screen. Speech output shall be provided for all information displayed on-screen.	Does not support	Speech output is not provided by the product itself.
402.2.2 Transactional Outputs. Where transactional outputs are provided, the speech output shall audibly provide all information necessary to verify a transaction.	Not Applicable	Speech output is not provided by the product itself.

402.2.3 Speech Delivery Type and Coordination. Speech output shall be delivered through a mechanism that is readily available to all users, including, but not limited to, an industry standard connector or a telephone handset. Speech shall be recorded or digitized human, or synthesized. Speech output shall be coordinated with information displayed on the screen.	Not Applicable	Speech output is not provided by the product itself.
402.2.4 User Control. Speech output for any single function shall be automatically interrupted when a transaction is selected. Speech output shall be capable of being repeated and paused.	Not Applicable	Speech output is not provided by the product itself.
402.2.5 Braille Instructions. Where speech output is required by 402.2, braille instructions for initiating the speech mode of operation shall be provided. Braille shall be contracted and shall conform to 36 CFR part 1191, Appendix D, Section 703.3.1.	Not Applicable	Speech output is not provided by the product itself.
402.3.1 Private Listening. Where ICT provides private listening, it shall provide a mode of operation for controlling the volume. Where ICT delivers output by an audio transducer typically held up to the ear, a means for effective magnetic wireless coupling to hearing technologies shall be provided.	Not Applicable	Speech output is not provided by the product itself.
402.3.2 Non-private Listening. Where ICT provides non-private listening, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. A function shall be provided to automatically reset the volume to the default level after every use.	Not Applicable	Speech output is not provided by the product itself.
402.4 Characters on Display Screens.  At least one mode of characters displayed on the screen shall be in a sans serif font. Where ICT does not provide a screen enlargement feature, characters shall be 3/16 inch (4.8 mm) high minimum based on the uppercase letter "I". Characters shall contrast with their background with either light characters on a dark background or dark characters on a light background.	Partially Supports	The on-screen text size is about 2.5 mm, which doesn't meet the requirements, but the ample contrast makes it easy to see.
402.5 Characters on Variable Message Signs. Characters on variable message signs shall conform to section 703.7 Variable Message Signs of ICC A117.1:2009.	Supports	Variable message sign is not provided. The case without any target is stated "Supports", as explained in the Terms*.
403.1 Biometrics Where provided, biometrics shall not be the only means for user identification or control.	Supports	Biometric forms of user identification are not used. The case without any target is stated "Supports", as explained in the Terms*.
404.1 Preservation of Information Provided for Accessibility ICT that transmits or converts information or communication shall not remove non-proprietary information provided for accessibility or shall restore it upon delivery.	Supports	Functionality that transmits and converts information or communication is not provided. The case without any target is stated "Supports", as explained in the Terms*.
405.1 Privacy. The same degree of privacy of input and output shall be provided to all individuals. When speech output required by 402.2 is enabled, the screen shall not blank automatically.	Supports	Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Canon global privacy provides to all individuals the same degree of privacy. RemoteUI does not have function to make the PC display invisible.
406.1 Standard Connections Where data connections used for input and output are provided, at least one of each type of connection shall conform to industry standard non-proprietary formats.	Supports	This product provides connections that conform industry standards.
407.2 Contrast. Where provided, keys and controls shall contrast visually from background surfaces. Characters and symbols shall contrast visually from background surfaces with either light characters or symbols on a dark background or dark characters or symbols on a light background.	Partially Supports	The scale of the ink capacity when refilling ink may be difficult to see because of the engraved mark. Other signs are easy to see.
407.3.1 Tactilely Discernible. Input controls shall be operable by touch and tactilely discernible without activation.	Supports	The Start key and the Stop key tactilely distinguishable, among the existing keys.
407.3.2 Alphabetic Keys. Where provided, individual alphabetic keys shall be arranged in a QWERTY-based keyboard layout and the "F" and "J" keys shall be tactilely distinct from the other keys.	Supports	Alphabetic keys are not provided. The Start key and the Stop key tactilely distinguishable.

<p>407.3.3 Numeric Keys. Where provided, numeric keys shall be arranged in a 12-key ascending or descending keypad layout. The number five key shall be tactilely distinct from the other keys. Where the ICT provides an alphabetic overlay on numeric keys, the relationships between letters and digits shall conform to ITU-T Recommendation E.161</p>	Supports	Numeric keys are not provided. The Start key and the Stop key is tactilely distinguishable.
<p>407.4 Key Repeat. Where a keyboard with key repeat is provided, the delay before the key repeat feature is activated shall be fixed at, or adjustable to, 2 seconds minimum.</p>	Supports	This product has key repeat function, but this function can be disabled.
<p>407.5 Timed Response. Where a timed response is required, the user shall be alerted visually, as well as by touch or sound, and shall be given the opportunity to indicate that more time is needed.</p>	Supports	In the secure print function and multi-user, the screen locks when time passes. Screen lock function can be disabled.
<p>407.6 Operation. (General) At least one mode of operation shall be operable with one hand and shall not require tight grasping, pinching, or twisting of the wrist. The force required to activate operable parts shall be 5 pounds (22.2 N) maximum.</p>	Partially Supports	Some operations require pinching.
<p>407.7 Tickets, Fare Cards, and Keycards. Where tickets, fare cards, or keycards are provided, they shall have an orientation that is tactilely discernible if orientation is important to further use of the ticket, fare card, or keycard.</p>	Supports	This product does not require use of card. The case without any target is stated "Supports", as explained in the Terms*.
<p>407.8.1 Vertical Reference Plane. Operable parts shall be positioned for a side reach or a forward reach determined with respect to a vertical reference plane. The vertical reference plane shall be located in conformance to 407.8.2 or 407.8.3.</p>	Supports	The product is not intended to instale on a floor. It is possible to locate a vertical referene plane.
<p>407.8.1.1 Vertical Plane for Side Reach. Where a side reach is provided, the vertical reference plane shall be 48 inches (1220 mm) long minimum.</p>	Supports	The product is not intended to instale on a floor. It is possible to locate a vertical referene plane.
<p>407.8.1.2 Vertical Plane for Forward Reach. Where a forward reach is provided, the vertical reference plane shall be 30 inches (760 mm) long minimum.</p>	Supports	The product is not intended to instale on a floor. It is possible to locate a vertical referene plane.
<p>407.8.2 Side Reach. Operable parts of ICT providing a side reach shall conform to 407.8.2.1 or 407.8.2.2. The vertical reference plane shall be centered on the operable part and placed at the leading edge of the maximum protrusion of the ICT within the length of the vertical reference plane. Where a side reach requires a reach over a portion of the ICT, the height of that portion of the ICT shall be 34 inches (865 mm) maximum.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>407.8.2.1 Unobstructed Side Reach. Where the operable part is located 10 inches (255 mm) or less beyond the vertical reference plane, the operable part shall be 48 inches (1220 mm) high maximum and 15 inches (380 mm) high minimum above the floor.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>407.8.2.2 Obstructed side reach Where the operable part is located more than 10 inches (255 mm), but not more than 24 inches (610 mm), beyond the vertical reference plane, the height of the operable part shall be 46 inches (1170 mm) high maximum and 15 inches (380 mm) high minimum above the floor. The operable part shall not be located more than 24 inches (610 mm) beyond the vertical reference plane.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>407.8.3 Forward Reach. Operable parts of ICT providing a forward reach shall conform to 407.8.3.1 or 407.8.3.2. The vertical reference plane shall be centered, and intersect with, the operable part. Where a forward reach allows a reach over a portion of the ICT, the height of that portion of the ICT shall be 34 inches (865 mm) maximum.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>407.8.3.1 Unobstructed forward reach Where the operable part is located at the leading edge of the maximum protrusion within the length of the vertical reference plane of the ICT, the operable part shall be 48 inches (1220 mm) high maximum and 15 inches (380 mm) high minimum above the floor.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>407.8.3.2 Obstructed Forward Reach. Where the operable part is located beyond the leading edge of the maximum protrusion within the length of the vertical reference plane, the operable part shall conform to 407.12.3.2. The maximum allowable forward reach to an operable part shall be 25 inches (635 mm).</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.

407.8.3.2.1 Height. Where the operable part is located less than 20 inches (510 mm) beyond the vertical reference plane, the operable part shall be 48 inches (1220 mm) high maximum. Where the operable part is located 20 inches (510 mm) to 25 inches (635 mm) beyond the vertical	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
407.8.3.2.2 Knee and Toe Space. Knee and toe space under ICT shall be 27 inches (685 mm) high minimum, 25 inches (635 mm) deep maximum, and 30 inches (760 mm) wide minimum and shall be clear of obstructions.	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
408.2 Display Screens (General) Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be visible from a point located 40 inches (1015 mm) above the floor space where the display screen is viewed.	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
408.3 General. (Flashing) Where ICT emits lights in flashes, there shall be no more than three flashes in any one-second period.	Supports	There are no flashing lights that would affect the user.
409.1 Status Indicators. Status indicators, including all locking or toggle controls or keys (e.g., Caps Lock and Num Lock keys), shall be discernible visually and by touch or sound.	Does not support	The status indications on display cannot be distinguished by touch nor hearing.
410.1 Color Coding. Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.
411.1 Audible Signals. Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response.	Supports	All the informtion of audible signals or cues during operation are also given by the LED lights and other components visually .

## Chapter 5: Software

Criteria	Conformance Level	Remarks and Explanations
501.1 Scope. The requirements of Chapter 5 shall apply to software where required by 508 Chapter 2.  (E207.2 WCAG Conformance. User interface components, as well as the content of platforms and applications, shall conform to Level A and Level AA Success Criteria and Conformance Requirements in WCAG 2.0)	See WCAG section.	See WCAG section.
502.2.1 User Control of Accessibility Features. Platforms shall provide user control over platform features that are defined in the platform documentation as accessibility features.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver is not a platform. The case without any target is stated "Supports", as explained in the Terms*.
502.2.2 No Disruption of Accessibility Features. Software shall not disrupt platform features that are defined in the platform documentation as accessibility features.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).
502.3.1 Object Information. The object role, state(s), boundary, name, and description shall be programmatically determinable.	PRINTER DRIVER: Partially Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, information of some UI objects is not read.
502.3.2 Modification of Object Information. States and properties that can be set by the user shall be capable of being set programmatically, including through assistive technology.	PRINTER DRIVER: Partially Supports	PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting.

<p>502.3.3 Row, Column, and Headers. If an object is in a table, the occupied rows and columns, and any headers associated with those rows or columns, shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Does not Support</p>	<p>PRINTER DRIVER: Header cell and job data cells below the header are not read as set, and these are read in each row.</p>
<p>502.3.4 Values. Any current value(s), and any set or range of allowable values associated with an object, shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Supports when combined with Compatible AT</p>	<p>PRINTER DRIVER: The currently set value can be recognized programmatically for any UI object in the printer driver for which a value can be entered. However, for recognizing range of value, the use of assistive technology (e.g. JAWS) is needed.</p>
<p>502.3.5 Modification of Values. Values that can be set by the user shall be capable of being set programmatically, including through assistive technology.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: Values that can be set by the user are capable of being set through the program.</p>
<p>502.3.6 Label Relationships. Any relationship that a component has as a label for another component, or of being labeled by another component, shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. However, for recognizing some labels, the use of assistive technology (e.g. JAWS) is needed.</p>
<p>502.3.7 Hierarchical Relationships. Any hierarchical (parent-child) relationship that a component has as a container for, or being contained by, another component shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically.</p>
<p>502.3.8 Text The content of text objects, text attributes, and the boundary of text rendered to the screen, shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: In the printer driver, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically.</p>
<p>502.3.9 Modification of Text Text that can be set by the user shall be capable of being set programmatically, including through assistive technology.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: Texts that can be set by user are capable to be set programmatically through the program.</p>
<p>502.3.10 List of Actions A list of all actions that can be executed on an object shall be programmatically determinable.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers.</p>
<p>502.3.11 Actions on Objects. Applications shall allow assistive technology to programmatically execute available actions on objects.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers.</p>
<p>502.3.12 Focus Cursor. Applications shall expose information and mechanisms necessary to track focus, text insertion point, and selection attributes of user interface components.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver.</p>

502.3.13 Modification of Focus Cursor. Focus, text insertion point, and selection attributes that can be set by the user shall be capable of being set programmatically, including through the use of assistive Technology.	PRINTER DRIVER: Partially Supports	PRINTER DRIVER: Changes of focus, component attributes, and text insertion points can be recognized in the printer driver.
502.3.14 Event Notification. Notification of events relevant to user interactions, including but not limited to, changes in the component's state(s), value, name, description, or boundary, shall be available to assistive technology.	PRINTER DRIVER: Supports	PRINTER DRIVER: When changes of UI components occur, the printer driver can notify it programmatically.
502.4 Platform Accessibility Features. Platforms and platform software shall conform to the requirements in ANSI/HFES 200.2, Human Factors Engineering of Software User Interfaces — Part 2: Accessibility (incorporated by reference in Chapter 1) listed below:  Section 9.3.3 Enable sequential entry of multiple (chorded) keystrokes. 2. Section 9.3.4 Provide adjustment of delay before key acceptance. 3. Section 9.3.5 Provide adjustment of same-key double-strike acceptance. 4. Section 10.6.7 Allow users to choose visual alternative for audio output. 5. Section 10.6.8 Synchronize audio equivalents for visual events. 6. Section 10.6.9 Provide speech output services. 7. Section 10.7.1 Display any captions provided.	PRINTER DRIVER: Supports	PRINTER DRIVER: The product is not a platform. The case without any target is stated "Supports", as explained in the Terms*.
503.2 User Preferences. Applications shall permit user preferences from platform settings for color, contrast, font type, font size, and focus cursor.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).
503.3 Alternative User Interfaces. Where an application provides an alternative user interface that functions as assistive technology, the application shall use platform and other industry standard accessibility services.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver does not provide functionality relating to accessibility. The case without any target is stated "Supports", as explained in the Terms*.
503.4.1 Caption Controls. Where user controls are provided for volume adjustment, ICT shall provide user controls for the selection of captions at the same menu level as the user controls for volume or program selection.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver does not provide any video content with synchronized audio. The case without any target is stated "Supports", as explained in the Terms*.
503.4.2 Audio Description Controls. Where user controls are provided for program selection, ICT shall provide user controls for the selection of audio description at the same menu level as the user controls for volume or program selection.	PRINTER DRIVER: Supports	PRINTER DRIVER: The printer driver does not provide any video content with synchronized audio. The case without any target is stated "Supports", as explained in the Terms*.

## Chapter 6: Support Documentation and Services

Criteria	Conformance Level	Remarks and Explanations
602.2 Accessibility and Compatibility Features. Documentation shall list and explain how to use the accessibility and compatibility features required by Chapters 4 and 5. Documentation shall include accessibility features that are built-in and accessibility features that provide compatibility with assistive technology.	Supports	This VPAT lists and explains the features required by Section 508 Standard (2017) Chapters 4 and 5.
602.3 Electronic Support Documentation. Documentation in electronic format, including Web-based self-service support, shall conform to Level A and Level AA Success Criteria and Conformance Requirements in WCAG (incorporated by reference, see 702.10.1).	Supports	The WCAG is applied to the documentation. See WCAG section for the results.
602.4 Alternate Formats for Non-electronic Support Documentation. Where support documentation is only provided in non-electronic formats, alternate formats usable by individuals with disabilities shall be provided upon request.	Supports	Product support documentation will be provided upon request in electronic format.



<p>603.2 Information on Accessibility and Compatibility Features.  ICT support services shall include information on the accessibility and compatibility features required by 602.2.</p>	<p>Supports</p>	<p>Support services will provide information about functions related to accessibility by means according to user's requests.</p>
<p>603.3 Accommodation of Communication Needs.  Support services shall be provided directly to the user or through a referral to a point of contact. Such ICT support services shall accommodate the communication needs of individuals with disabilities.</p>	<p>Supports</p>	<p>Canon U.S.A., Inc. provides support services accommodating users with disabilities through 1(800) OKCANON (652-2666) assistance, TTY support at (866)251-3752. Canon otherwise available to U.S. federal government agencies through Federal Relay.</p>

**Chapter 4: Functional Performance Statements**

Criteria	Conformance Level	Remarks and Explanations
<p>4.2.1 Usage without vision Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that does not require vision. This is essential for users without vision and benefits many more users in different situations.</p>	<p>Partially Supports</p>	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. Speech output is not provided by the product itself. Some of the operable parts can not be discernible without vision. Keys on the operational panel are rather difficult to discern without vision. The stop key is tactilely distinguishable. The status indications on display cannot be distinguished by touch nor hearing.</p> <p><b>REMOTE UI*:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> Printer Driver can be operated with keyboard through hearing by using screen reader.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p> <p>*Access to Remote UI : Access to HTTP:XXX.XXX.XXX.XXX ( the IP address of your Canon device) to start its RemoteUI . Mainly the arrow-keys are used to move between the UI elements. For the Remote UI of this version, the child elements (lower hierarchy) follows after the parent elements serially.</p>
<p>4.2.2 Usage with limited vision Where ICT provides visual modes of operation, the ICT provides features that enable users to make better use of their limited vision. This is essential for users with limited vision and benefits many more users in different situations.</p>	<p>Partially Supports</p>	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. The controls of key repeat and alarm volume cannot be operated easily without vision. Keys are rather difficult to discern without vision. Alphabetic keys and numeric keys are not provided. The stop key is tactilely distinguishable, among the existing keys. The scale of the ink capacity when refilling ink may be difficult to see because of the engraved mark. Other signs are easy to see. The status indications on display cannot be distinguished by touch nor hearing. Speech output is not provided by the product itself.</p> <p><b>REMOTE UI:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p>
<p>4.2.3 Usage without perception of colour Where ICT provides visual modes of operation, the ICT provides a visual mode of operation that does not require user perception of colour. This is essential for users with limited colour perception and benefits many more users in different situations.</p>	<p>Supports</p>	<p><b>HARDWARE:</b> The product has a monochrome display, which do not convey meaning by colour. All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.</p> <p><b>REMOTE UI:</b> There is information in text for the items which conveys meaning.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> Colour on display and on operable parts are not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>
<p>4.2.4 Usage without hearing Where ICT provides auditory modes of operation, the ICT provides at least one mode of operation that does not require hearing. This is essential for users without hearing and benefits many more users in different situations.</p>	<p>Supports</p>	<p>The product is basically operable without user hearing.</p> <p><b>HARDWARE:</b> The alarm volume is controllable.</p>

<p>4.2.5 Usage with limited hearing Where ICT provides auditory modes of operation, the ICT provides enhanced audio features. This is essential for users with limited hearing and benefits many more users in different situations.</p>	<p>Supports</p>	<p>The product is basically operable without user hearing. HARDWARE: The alarm volume is controllable.</p>
<p>4.2.6 Usage with no or limited vocal capability Where ICT requires vocal input from users, the ICT provides at least one mode of operation that does not require them to generate vocal output. This is essential users with no or limited vocal capability and benefits many more users in different situations.</p>	<p>Supports</p>	<p>The product does not require user speech.</p>
<p>4.2.7 Usage with limited manipulation-or-strength Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.</p>	<p>Partially Supports</p>	<p>HARDWARE: There is no alternative in the operation part that requires pinching. The key repeat is controllable. &lt;GX4000 Series&gt; Bounce key function is not supported. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER &amp; DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.</p>
<p>4.2.7 Usage with limited manipulation-or-strength Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.</p>	<p>Partially Supports</p>	<p>HARDWARE: There are places where the operating force for changing the paper size, but there is no alternative. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER &amp; DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.</p>
<p>4.2.8 Usage with limited reach Where ICT products are free-standing or installed, all the elements required for operation will need to be within reach of all users. This is essential for users with limited reach and benefits many more users in different situations.</p>	<p>Supports</p>	<p>HARDWARE: The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate pedestal which the user prepares. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER &amp; DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.</p>
<p>4.2.9 Minimize photosensitive seizure triggers Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that minimizes the potential for triggering photosensitive seizures. This is essential for users with photosensitive seizure triggers.</p>	<p>Supports</p>	<p>The product does not have any component which may trigger photosensitive seizures.</p>
<p>4.2.10 Usage with limited cognition, language or learning The ICT provides features and/or presentation that makes it simpler and easier to understand, operate and use. This is essential for users with limited cognition, language or learning, and benefits many more users in different situations.</p>	<p>Partially Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself. The status indications on display cannot be distinguished by touch nor hearing. REMOTE UI: In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message can be confirmed only when the focus is on the status message. PRINTER DRIVER: User can use the function that meets the purpose without interrupted by using accessibility feature. DOCUMENTS: Components that have the same functionality are identified consistently.</p>
<p>4.2.11 Privacy Where ICT provides features for accessibility, the ICT maintains the privacy of users of these features at the same level as other users.</p>	<p>Supports</p>	<p>The product provides the the same level of privacy to the users with disabilities as the users without disabilities.</p>

**Chapter 5: Generic Requirements**

Criteria	Conformance Level	Remarks and Explanations
<p>5.1.2.2 Assistive technology Where ICT has closed functionality, that closed functionality shall be operable without requiring the user to attach, connect or install assistive technology and shall conform to the generic requirements of clauses 5.1.3 to 5.1.6 as applicable. Personal headsets and personal induction loops shall not be classed as assistive technology for the purpose of this clause.</p>		<p>See information in 5.1.3 through 5.1.6, as advised on the original VPAT of ITI.</p>
<p>5.1.3.1 Audio output of visual information Where visual information is needed to enable the use of those functions of ICT that are closed to assistive technologies for screen reading, ICT shall provide at least one mode of operation using non-visual access to enable the use of those functions.</p>	<p>HARDWARE: Does not support PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.  PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.1.3.2 Auditory output delivery including speech Where auditory output is provided as non-visual access to closed functionality, the auditory output shall be delivered: a) either directly by a mechanism included in or provided with the ICT; b) or by a personal headset that can be connected through a 3,5 mm audio jack, or an industry standard connection, without requiring the use of vision.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.  PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.1.3.3 Auditory output correlation Where auditory output is provided as non-visual access to closed functionality, and where information is displayed on the screen, the ICT should provide auditory information that allows the user to correlate the audio with the information displayed on the screen.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.  PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.  REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: The result for WCAG 1.3.1 is "Partially supports".)</p>
<p>5.1.3.4 Speech output user control Where speech output is provided as non-visual access to closed functionality, the speech output shall be capable of being interrupted and repeated when requested by the user, where permitted by security requirements.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.  PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.  REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: There is no interference with the accessibility function of OS.)</p>
<p>5.1.3.5 Speech output automatic interruption Where speech output is provided as non-visual access to closed functionality, the ICT shall interrupt current speech output when a user action occurs and when new speech output begins.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.  PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.  REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: There is no interference with the function of assistive technology.)</p>

<p>5.1.3.6 Speech output for non-text content Where ICT presents non-text content, the alternative for non-text content shall be presented to users via speech output unless the non-text content is pure decoration or is used only for visual formatting. The speech output for non-text content shall follow the guidance for "text alternative" described in WCAG 2.1 Success Criterion 1.1.1.</p>	<p>HARDWARE: Does not support PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: The result for WCAG 1.1.1 is "Partially supports".)</p>
<p>5.1.3.7 Speech output for video information Where pre-recorded video content is needed to enable the use of closed functions of ICT and where speech output is provided as non-visual access to closed functionality, the speech output shall present equivalent information for the pre-recorded video content.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: No video information is used. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: There is no video content.)</p>
<p>5.1.3.8 Masked entry Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Although the administrator password is masked, generally private listening mechanism can be connected to user's PC, or the user preference of screen reader can be selected not read out the masked entries.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: Masking characters are not read out while using assistive technology.)</p>
<p>5.1.3.9 Private access to personal data Where auditory output is provided as non-visual access to closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Canon global privacy provides to all individuals the same degree of privacy. User can generally listen privately by connecting hearing device, such as headset, to PC.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: Personal listening is not eliminated while using assistive technology.)</p>
<p>5.1.3.10 Non-interfering audio output Where auditory output is provided as non-visual access to closed functionality, the ICT shall not automatically play, at the same time, any interfering audible output that lasts longer than three seconds.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>

<p>5.1.3.11 Private listening Where auditory output is provided as non-visual access to closed functionality and is delivered through a mechanism for private listening, ICT shall provide at least one non-visual mode of operation for controlling the volume.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: It does not interfere with PC or OS functions using AT.)</p>
<p>5.1.3.12 Speaker volume Where auditory output is provided as non-visual access to closed functionality and is delivered through speakers on ICT, a non-visual incremental volume control shall be provided with output amplification up to a level of at least 65 dBA (-29 dBPaA).</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.1.3.13 Volume reset Where auditory output is provided as non-visual access to closed functionality, a function that resets the volume to be at a level of 65 dBA or less after every use, shall be provided, unless the ICT is dedicated to a single user.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.1.3.14 Spoken languages Where speech output is provided as non-visual access to closed functionality, speech output shall be in the same human language as the displayed content provided, except: a) for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text; b) where the content is generated externally and not under the control of the ICT vendor, the present clause shall not be required to apply for languages not supported by the ICT's speech synthesizer; c) for displayed languages that cannot be selected using non-visual access; d) where the user explicitly selects a speech language that is different from the language of the displayed content.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: The speech output uses the same human language as displayed.)</p>
<p>5.1.3.15 Non-visual error identification Where speech output is provided as non-visual access to closed functionality and an input error is automatically detected, speech output shall identify and describe the item that is in error.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*. (Ref.: Errors are shown, but not read automatically)</p>
<p>5.1.3.16 Receipts, tickets, and transactional outputs Where ICT is closed to visual access and provides receipts, tickets or other outputs as a result of a self-service transaction, speech output shall be provided which shall include all information necessary to complete or verify the transaction. In the case of ticketing machines, printed copies of itineraries and maps shall not be required to be audible.</p>	<p>HARDWARE: Not Applicable PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER: This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI: This requirement is not applied to the product, which is not a self-service equipment, nor a product closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p>

<p>5.1.4 Functionality closed to text enlargement</p> <p>Where any functionality of ICT is closed to the text enlargement features of platform or assistive technology, the ICT shall provide a mode of operation where the text and images of text necessary for all functionality is displayed in such a way that a non-accented capital "H" subtends an angle of at least 0,7 degrees at a viewing distance specified by the supplier.</p> <p>The subtended angle, in degrees, may be calculated from:  <math>\Psi = (180 \times H) / (\pi \times D)</math></p> <p>Where:  <math>\psi</math> is the subtended angle in degrees  H is the height of the text  D is the viewing distance  D and H are expressed in the same units</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  The visual angle satisfies the requirement by approaching a viewing distance of about 20 cm. It can be easily approached to ensure this distance.</p> <p>PRINTER DRIVER:  This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.  (Ref.: The character enlargement function of the OS can be used.)</p>
<p>5.1.5 Visual output for auditory information</p> <p>Where auditory information is needed to enable the use of closed functions of ICT, the ICT shall provide visual information that is equivalent to the auditory output.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  Messages are displayed when the signal sounds are used for notification and warning.</p> <p>PRINTER DRIVER:  This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  This requirement is not applied to the product, which is not closed to AT. The case without any target is stated "Supports", as explained in the Terms*.  (Ref.: Visual information can be provided using assistive technology.)</p>
<p>5.1.6.1 Closed functionality</p> <p>Where ICT functionality is closed to keyboards or keyboard interfaces, all functionality shall be operable without vision as required by clause 5.1.3.</p>	<p>See information in 5.1.3, 5.1.3.1 to 5.1.3.16, as advised on the original VPAT of ITI.</p>	
<p>5.1.6.2 Input focus</p> <p>Where ICT functionality is closed to keyboards or keyboard interfaces and where input focus can be moved to a user interface element, it shall be possible to move the input focus away from that element using the same mechanism, in order to avoid trapping the input focus.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  The elements of user interface can be displayed and selected using the consistent mechanism using the arrow keys, the OK key and the back key.</p> <p>PRINTER DRIVER:  Focus can be moved away from the component using only a keyboard interface.</p> <p>REMOTE UI:  This requirement is not applied to the product, which is not closed to keyboard interface. The case without any target is stated "Supports", as explained in the Terms*.  (Ref.: Remote UI is keyboard-accessible with assistive technology.)</p>
<p>5.1.7 Access without speech</p> <p>Where speech is needed to operate closed functions of ICT, the ICT shall provide at least one mode of operation using an alternative input mechanism that does not require speech.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  The product does not require voice input. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  This requirement is not applied to the product, which is software. (There is no access requiring speech.) The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  There is no access requiring speech. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.2 Activation of accessibility features</p> <p>Where ICT has documented accessibility features, it shall be possible to activate those documented accessibility features that are required to meet a specific need without relying on a method that does not support that need.</p>	<p>HARDWARE: Partially Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  The controls of key repeat and alarm volume cannot be operated easily without vision.</p> <p>PRINTER DRIVER:  The printer driver can be used without disruption and prevention of activating of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).</p> <p>REMOTE UI:  The product does not interfere with the accessibility functions of the OS or the functions of assistive technologies such as screen reading</p>

<p>5.3 Biometrics Where ICT uses biological characteristics, it shall not rely on the use of a particular biological characteristic as the only means of user identification or for control of ICT.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>Biometric forms of user identification are not used. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.4 Preservation of accessibility information during conversion Where ICT converts information or communication it shall preserve all documented non-proprietary information that is provided for accessibility, to the extent that such information can be contained in or supported by the destination format.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>Functionality that transmits and converts information or communication is not provided. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.5.1 Means of operation Where ICT has operable parts that require grasping, pinching, or twisting of the wrist to operate, an accessible alternative means of operation that does not require these actions shall be provided.</p>	<p>HARDWARE: Partially Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: There is no alternative in the operation part that requires a pinching operation.  PRINTER DRIVER &amp; REMOTE UI: This requirement is not applied to the product, which is software. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.5.2 Operable parts discernibility Where ICT has operable parts, it shall provide a means to discern each operable part, without requiring vision and without performing the action associated with the operable part.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Partially Supports</p>	<p>HARDWARE: The Start key and the Stop key tactilely distinguishable, among the existing keys.  PRINTER DRIVER: In case of softwares, this requirement can be comprehended to meet by operating through keyboards, the focus moving without stucked at specific elements, and the elements not activating just by receiving focus. The product does meet them.  REMOTE UI: Basically, the focus moves to the operable parts and the voice output is provided throught AT, however, operation through a keyboard are not provided in some specific functions.</p>
<p>5.6.1 Tactile or auditory status Where ICT has a locking or toggle control and the status of that control is visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be determined either through touch or sound without operating the control.</p>	<p>HARDWARE: Does not support PRINTER DRIVER: Partially Supports REMOTE UI: Partially Supports</p>	<p>HARDWARE: The status indications on display cannot be distinguished by touch nor hearing.  PRINTER DRIVER: Text is provided for structures and information that can be interpreted programmatically. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement.  REMOTE UI: Voice identification of selection status using assistive technology. In some contents, the item name of the check box is read out one step apart.</p>
<p>5.6.2 Visual status Where ICT has a locking or toggle control and the status of the control is non-visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be visually determined when the control is presented.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: The status of product can be distinguished visually.  PRINTER DRIVER: The visual status can be determined whichever it is a locking or toggle control.  REMOTE UI: There is no non-visually presented status. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>5.7 Key repeat Where ICT has a key repeat function that cannot be turned off: a) the delay before the key repeat shall be adjustable to at least 2 seconds; and b) the key repeat rate shall be adjustable down to one character per 2 seconds.</p>	<p>HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports</p>	<p>HARDWARE: This product has key repeat function, but this function can be disabled.  PRINTER DRIVER: The printer driver can be used with the "Filter key function" of the OS function.  REMOTE UI: Key repeat and bounce key settings provided by the OS are not inhibited.</p>



<p>5.8 Double-strike key acceptance</p> <p>Where ICT has a keyboard or keypad, the delay after any keystroke, during which an additional key-press will not be accepted if it is identical to the previous keystroke, shall be adjustable up to at least 0,5 seconds.</p>	<p>HARDWARE: Does not support  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  Bounce key function is not supported.</p> <p>PRINTER DRIVER:  The printer driver can be used with the "Filter key function" of the OS function.</p> <p>REMOTE UI:  Key repeat and bounce key settings provided by the OS are not inhibited.</p>
<p>5.9 Simultaneous user actions</p> <p>Where ICT has a mode of operation requiring simultaneous user actions for its operation, such ICT shall provide at least one mode of operation that does not require simultaneous user actions to operate the ICT.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports</p>	<p>HARDWARE:  There is no place that requires simultaneous operations.</p> <p>PRINTER DRIVER:  In case of softwares, this requirement can be met by avoid pressing two or more keys at the same time.  The product can be operated by using keyboards, and can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).</p> <p>REMOTE UI:  A simultaneous user action is not required.</p>

## Chapter 8: Hardware

Criteria	Conformance Level	Remarks and Explanations
<p>8.1.2 Standard connections</p> <p>Where an ICT provides user input or output device connection points, the ICT shall provide at least one input and/or output connection that conforms to an industry standard non-proprietary format, directly or through the use of commercially available adapters.</p>	Supports	This product provides connections that conform industry standards.
<p>8.1.3 Colour</p> <p>Where the ICT has hardware aspects that use colour, colour shall not be used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>	Supports	All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.
<p>8.3.4.1 Change in level</p> <p>Where stationary ICT has a floor within it, then any change of floor level within it or entering it shall be ramped with a slope no steeper than 1:48.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate floor which the user prepares.
<p>8.3.4.2 Clear floor or ground space</p> <p>Where stationary ICT has an operating area within it, it shall provide a clear floor area that has the minimum dimensions of 760 mm (30 inches) by 1 220 mm (48 inches) from which to operate the ICT.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate floor which the user prepares.
<p>8.3.4.3.1 General</p> <p>Where stationary ICT has an access space inside it, at least one full side of the space shall be unobstructed.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate floor which the user prepares.
<p>8.3.4.3.2 Forward approach</p> <p>Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 610 mm (24 inches), and where a forward approach is necessary, the dimension of the access space shall be a minimum of 915 mm (36 inches) wide.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate floor which the user prepares.
<p>8.3.4.3.3 Parallel approach</p> <p>Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 380 mm (15 inches), and where a parallel approach is possible, the dimension of the access space shall be a minimum of 1 525 mm (60 inches) wide.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate floor which the user prepares.
<p>8.3.2.4 Knee and toe clearance width</p> <p>Where the space under an obstacle that is an integral part of the stationary ICT is part of access space, the clearance shall be at least 760 mm (30 inches) wide.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.

<p>8.3.2.5 Toe clearance Where an obstacle is an integral part of the stationary ICT, a space under the obstacle that is less than 230 mm (9 inches) above the floor is considered toe clearance and shall:</p> <ul style="list-style-type: none"> <li>a) extend 635 mm (25 inches) maximum under the whole obstacle;</li> <li>b) provide a space at least 430 mm (17 inches) deep and 230 mm (9 inches) above the floor under the obstacle;</li> <li>c) extend no more than 150 mm (6 inches) beyond any obstruction at 230 mm (9 inches) above the floor.</li> </ul>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.6 Knee clearance Where an obstacle is an integral part of the stationary ICT, the space under the obstacle that is between 230 mm (9 inches) and 685 mm (25 inches) above the floor is considered knee clearance and shall:</p> <ul style="list-style-type: none"> <li>a) extend no more than 635 mm (25 inches) under the obstacle at a height of 230 mm (9 inches) above the floor;</li> <li>b) extend at least 280 mm (11 inches) under the obstacle at a height of 230 mm (9 inches) above the floor;</li> <li>c) extend at least 205 mm (8 inches) under the obstacle at a height of 685 mm (27 inches) above the floor;</li> <li>d) be permitted to be reduced in depth at a rate of 25 mm (1 inch) for each 150 mm (6 inches) in height.</li> </ul>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.1 Unobstructed high forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no higher than 1 220 mm (48 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.2 Unobstructed low forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no lower than 380 mm (15 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.3.1 Clear space Where an obstruction is an integral part of the stationary ICT and hinders the access to any type of operable part, the ICT shall provide a clear space which extends beneath the obstructing element for a distance not less than the required reach depth over the obstruction.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.3.2 Obstructed (&lt; 510 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is less than 510 mm (20 inches), the forward reach to at least one of each type of operable part shall be no higher than 1 220 mm (48 inches) above the floor contact of the ICT.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.2.3.3 Obstructed (&lt; 635 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is not less than 510 mm (20 inches) but is less than 635 mm (25 inches) maximum, the forward reach to at least one of each type of operable part shall be no higher than 1 220 mm (44 inches) above the floor contact of the ICT.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.3.1 Unobstructed high side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a high side reach which is less than or equal to 1 220 mm (48 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.3.2 Unobstructed low side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a low side reach which is greater than or equal to 380 mm (15 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.3.3.1 Obstructed (≤ 255 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is less than or equal to 255 mm (10 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 220 mm (48 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>8.3.3.3.2 Obstructed (≤ 610 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is greater than 255 mm (10 inches) with a maximum depth of 610 mm (24 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 170 mm (46 inches) above the floor of the access space.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.

8.3.5 Visibility Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be positioned such that the information on the screen is legible from a point located 1 015 mm (40 inches) above the centre of the floor of the operating area).	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
8.3.6 Installation instructions Installation instructions shall be made available for all stationary ICT. These instructions shall give guidance on how to install the ICT in a manner that takes into account applicable requirements for accessibility of the built environment as they apply to the installation of the ICT. Where there are no such requirements the instructions should require that the dimensions of the installed ICT conform to clauses 8.3.2 to 8.3.5 of the present document.	Supports	The product is not intended to instale on a floor. The information of product size is provided, and it is possible to meet the requirement with the appropriate pedestal which the user prepares.
8.4.1 Numeric keys Where provided, physical numeric keys arranged in a rectangular keypad layout shall have the number five key tactilely distinct from the other keys of the keypad.	Supports	Numeric keys are not provided. The Start key and the Stop key is tactilely distinguishable.
8.4.2.1 Means of Operation of mechanical parts Where a control requires grasping, pinching, or twisting of the wrist to operate it, an accessible alternative means of operation that does not require these actions shall be provided.	Partially Supports	There is no alternative in the operation part that requires a pinching operation.
8.4.2.2 Force of operation of mechanical parts Where a control requires a force greater than 22,2 N to operate it, an accessible alternative means of operation that requires a force less than 22,2 N shall be provided.	Partially Supports	There are places where the operating force for changing the paper size exceeds 22.2 N, but there is no alternative. Other places meet the regulations.
8.4.3 Keys, tickets and fare cards Where ICT provides keys, tickets or fare cards, and their orientation is important for further use, they shall have an orientation that is tactilely discernible.	Supports	This product does not require use of card. The case without any target is stated "Supports", as explained in the Terms*.
8.5 Tactile indication of speech mode Where ICT is designed for shared use and speech output is available, a tactile indication of the means to initiate the speech mode of operation shall be provided.	Not Applicable	Speech output is not provided by the product itself.

## Chapter 9: Web

Criteria	Conformance Level	Remarks and Explanations
9.1.1.1 through 9.4.1.3	See WCAG section.	See WCAG section.

## Chapter 10: Non-web Documents

Criteria	Conformance Level	Remarks and Explanations
10.1.1.1 through 10.4.1.3	See WCAG section.	See WCAG section.
10.5 Caption positioning Where ICT is a non-web document that contains synchronized media with captions, the captions should not obscure relevant information in the synchronized media.	DOCUMENT: Supports	DOCUMENT: Non-web document is not provided. The case without any target is stated "Supports", as explained in the Terms*.
10.6 Audio description timing Where ICT is a non-web document that contains synchronized media with audio description, the audio description should not interfere with relevant audio information in the synchronized media.	DOCUMENT: Supports	DOCUMENT: Non-web document is not provided. The case without any target is stated "Supports", as explained in the Terms*.

## Chapter 11: Software

Criteria	Conformance Level	Remarks and Explanations
11.1.1.1 through 11.4.1.3	See WCAG section.	See WCAG section.
11.5.2.1 Platform accessibility service support for software that provides a user interface Platform software shall provide a set of documented platform services that enable software that provides a user interface running on the platform software to interoperate with assistive technology. Where a user interface concept corresponding to one of the clauses 11.5.2.5 to 11.5.2.17 is supported within the software environment, the platform software should support that requirement. For example, selection attributes from 11.5.2.14 (Modification of focus and selection attributes) may not exist in environments that do not allow selection, which is most commonly associated with copy and paste.	See information in 11.5.2.5 through 11.5.2.17, as adviced on the original VPAT of ITI.	

<p>11.5.2.2 Platform accessibility service support for assistive technologies</p> <p>Platform software shall provide a set of documented platform accessibility services that enable assistive technology to interoperate with software that provides a user interface running on the platform software.</p> <p>Where a user interface concept corresponding to one of the clauses 11.5.2.5 to 11.5.2.17 is supported within the software environment, the platform software should support that requirement. For example, selection attributes from 11.5.2.14 (Modification of focus and selection attributes) may not exist in environments that do not allow selection, which is most commonly associated with copy and paste.</p>	<p>See information in 11.5.2.5 through 11.5.2.17, as advised on the original VPAT of ITI.</p>	
<p>11.5.2.3 Use of accessibility services</p> <p>Where the software provides a user interface it shall use the applicable documented platform accessibility services. If the documented platform accessibility services do not allow the software to meet the applicable requirements of clauses 11.5.2.5 to 11.5.2.17, then software that provides a user interface shall use other documented services to interoperate with assistive technology.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: The result of cited requirements 11.5.2.5-11.5.2.17 consists 1 'Does not Supports', other 3 Supports with some conditions, and 9 'Supports'.</p>
<p>11.5.2.4 Assistive technology</p> <p>Where the ICT is assistive technology it shall use the documented platform accessibility services.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: The product is not an assistive technology. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>11.5.2.5 Object information</p> <p>Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the user interface elements' role, state(s), boundary, name, and description programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting.</p>
<p>11.5.2.6 Row, column, and headers</p> <p>Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the row and column of each cell in a data table, including headers of the row and column if present, programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Does not Support</p>	<p>PRINTER DRIVER: Header cell and job data cells below the header are not read as set, and these are read in each row. Therefore it is hard to understand the meaning.</p>
<p>11.5.2.7 Values</p> <p>Where the software provides a user interface, it shall, by using the services as described in clause 11.5.2.3, make the current value of a user interface element and any minimum or maximum values of the range, if the user interface element conveys information about a range of values, programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Supports when combined with Compatible AT</p>	<p>PRINTER DRIVER: The currently set value can be recognized programmatically for any UI object in the printer driver for which a value can be entered. However, for recognizing range of value, the use of assistive technology (e.g.JAWS) is needed.</p>
<p>11.5.2.8 Label relationships</p> <p>Where the software provides a user interface it shall expose the relationship that a user interface element has as a label for another element, or of being labelled by another element, using the services as described in clause 11.5.2.3, so that this information is programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Partially Supports</p>	<p>PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically. However, for recognizing some labels, the use of assistive technology (e.g. JAWS) is needed.</p>
<p>11.5.2.9 Parent-child relationships</p> <p>Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the relationship between a user interface element and any parent or children elements programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: The labels associated with UI components in the printer driver can be recognized programmatically.</p>
<p>11.5.2.10 Text</p> <p>Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make the text contents, text attributes, and the boundary of text rendered to the screen programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: In the printer driver, the attributes of UI objects for which text can be entered, as well as the boundary of text displayed on the screen, can be recognized programmatically.</p>
<p>11.5.2.11 List of available actions</p> <p>Where the software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make a list of available actions that can be executed on a user interface element, programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER: Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers.</p>

<p>11.5.2.12 Execution of available actions</p> <p>Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow the programmatic execution of the actions exposed according to clause 11.5.2.11 by assistive technologies.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>Operations that can be executed on a UI object in the printer driver can be recognized with the use of screen readers.</p>
<p>11.5.2.13 Tracking of focus and selection attributes</p> <p>Where software provides a user interface it shall, by using the services as described in clause 11.5.2.3, make information and mechanisms necessary to track focus, text insertion point, and selection attributes of user interface elements programmatically determinable by assistive technologies.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>Changes of focus, component attributes, and text insertion points can be recognized in the printer driver.</p>
<p>11.5.2.14 Modification of focus and selection attributes</p> <p>Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to programmatically modify focus, text insertion point, and selection attributes of user interface elements where the user can modify these items.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>Changes of focus, component attributes, and text insertion points can be recognized in the printer driver.</p>
<p>11.5.2.15 Change notification</p> <p>Where software provides a user interface it shall, by using the services as described in clause 11.5.2.3, notify assistive technologies about changes in those programmatically determinable attributes of user interface elements that are referenced in requirements 11.5.2.5 to 11.5.2.11 and 11.5.2.13.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>When changes of UI components occur, the printer driver can notify it programmatically.</p>
<p>11.5.2.16 Modifications of states and properties</p> <p>Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to programmatically modify states and properties of user interface elements, where the user can modify these items.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>The roles, states, boundary, names, and description of UI objects in the printer driver can be recognized programmatically. However, there are some UI objects not able to change the setting.</p>
<p>11.5.2.17 Modifications of values and text</p> <p>Where permitted by security requirements, software that provides a user interface shall, by using the services as described in clause 11.5.2.3, allow assistive technologies to modify values and text of user interface elements using the input methods of the platform, where a user can modify these items without the use of assistive technology.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>Texts and Values can be set by user are capable to be set programmatically through the program.</p>
<p>11.6.1 User control of accessibility features</p> <p>Where software is a platform it shall provide sufficient modes of operation for user control over those platform accessibility features documented as intended for users.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>The printer driver is not a platform. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>11.6.2 No disruption of accessibility features</p> <p>Where software provides a user interface it shall not disrupt those documented accessibility features that are defined in platform documentation except when requested to do so by the user during the operation of the software.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).</p>
<p>11.7 User preferences</p> <p>Where software is not designed to be isolated from its platform, and provides a user interface, that user interface shall follow the values of the user preferences for platform settings for: units of measurement, colour, contrast, font type, font size, and focus cursor except where they are overridden by the user.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>The printer driver can be used without disruption of the accessibility features of the platform (verified with the accessibility functionality of Windows 10).</p>
<p>11.8.2 Accessible content creation</p> <p>Authoring tools shall enable and guide the production of content that conforms to clauses 9 (Web content) or 10 (Non-Web content) as applicable.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>This requirement is not applied to the printer driver, which is not an authoring tool. The case without target is stated "Supports", as explained in the Terms*.</p>
<p>11.8.3 Preservation of accessibility information in transformations</p> <p>If the authoring tool provides restructuring transformations or re-coding transformations, then accessibility information shall be preserved in the output if equivalent mechanisms exist in the content technology of the output.</p>	<p>PRINTER DRIVER: Supports</p>	<p>PRINTER DRIVER:</p> <p>This requirement is not applied to the printer driver, which is not an authoring tool. The case without target is stated "Supports", as explained in the Terms*.</p>

11.8.4 Repair assistance If the accessibility checking functionality of an authoring tool can detect that content does not meet a requirement of clauses 9 (Web) or 10 (Non-web documents) as applicable, then the authoring tool shall provide repair suggestion(s).	PRINTER DRIVER: Supports	PRINTER DRIVER: This requirement is not applied to the printer driver, which is not an authoring tool. The case without target is stated "Supports", as explained in the Terms.*.
11.8.5 Templates When an authoring tool provides templates, at least one template that supports the creation of content that conforms to the requirements of clauses 9 (Web) or 10 (Non-web documents) as applicable shall be available and identified as such.	PRINTER DRIVER: Supports	PRINTER DRIVER: This requirement is not applied to the printer driver, which is not an authoring tool. The case without target is stated "Supports", as explained in the Terms.*.

## Chapter 12: Documentation and Support Services

Criteria	Conformance Level	Remarks and Explanations
12.1.1 Accessibility and compatibility features Product documentation provided with the ICT whether provided separately or integrated within the ICT shall list and explain how to use the accessibility and compatibility features of the ICT.	Supports	This VPAT lists and explains the features required by EN 301 549 requirements.
12.1.2 Accessible documentation Product documentation provided with the ICT shall be made available in at least one of the following electronic formats: a) a Web format that conforms to the requirements of clause 9, or b) a non-web format that conforms to the requirements of clause 10.	Supports	The WCAG is applied to the documentation. See WCAG section for the results.
12.2.2 Information on accessibility and compatibility features ICT support services shall provide information on the accessibility and compatibility features that are mentioned in the product documentation.	Supports	Support services will provide information about functions related to accessibility by means according to user's requests.
12.2.3 Effective communication ICT support services shall accommodate the communication needs of individuals with disabilities either directly or through a referral point.	Supports	You can reach contact support from below URL. <a href="https://www.canon-europe.com/support/consumer_products/contact_support/">https://www.canon-europe.com/support/consumer_products/contact_support/</a> Please choose proper country. Phone number and e-mail address are described.  If there is not proper country, please access below and contact each office in your country. <a href="https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/">https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/</a>
12.2.4 Accessible documentation Documentation provided by support services shall be made available in at least one of the following electronic formats: a) a Web format that conforms to clause 9, or b) a non-web format that conforms to clause 10.	Supports	The WCAG is applied to the documentation. See WCAG section for the results.

# WCAG Web Contents Accessibility Guidelines

## WCAG Report (Level A & AA)

Criteria	Conformance Level	Remarks and Explanations
1.1.1 Non-text Content(A): All non-text content that is presented to the user has a text alternative that serves the equivalent purpose, except for the situations listed below.	HARDWARE: Does not Support PRINTER DRIVER: Partially Supports REMOTE UI: Partially Supports DOCUMENT: Supports	HARDWARE: Non-text content has accompanying text on the product screen. All information on the screen can not be audio-output by the unit.  PRINTER DRIVER: The non-text content items in the UI of the printer driver are visual representations of various setting values, and provide text alternative for them. However, alternative means are necessary for some of them to give their information.  REMOTE UI: The remaining ink level and some of the non-text content items (icons) have no text explanation.  DOCUMENT: All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.
1.2.1 Audio-only and Video-only (Prerecorded)(A): For prerecorded audio-only and prerecorded video-only media, the following are true, except when the audio or video is a media alternative for text and is clearly labeled as such: - Prerecorded Audio-only - Prerecorded Video-only	HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports DOCUMENT: Supports	HARDWARE, PRINTER DRIVER & REMOTE UI: Prerecorded audio-only nor prerecorded video-only contents are not used. The case without any target is stated "Supports", as explained in the Terms*.  DOCUMENT: Information equal to prerecorded video is provided by using screen reader.
1.2.2 Captions (Prerecorded)(A): Captions are provided for all prerecorded audio content in synchronized media, except when the media is a media alternative for text and is clearly labeled as such.	HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports DOCUMENT: Supports	HARDWARE, PRINTER DRIVER & REMOTE UI: Prerecorded audio content is not included in synchronized media. The case without any target is stated "Supports", as explained in the Terms*.  DOCUMENT: Captions are provided for the prerecorded audio contents, and the captions can be read out.
1.2.3 Audio Description or Media Alternative (Prerecorded)(A): An alternative for time-based media or audio description of the prerecorded video content is provided for synchronized media, except when the media is a media alternative for text and is clearly labeled as such.	HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports DOCUMENT: Supports through Equivalent Facilitation	HARDWARE, PRINTER DRIVER & REMOTE UI: Prerecorded audio-only and prerecorded video-only contents are not used. The case without any target is stated "Supports", as explained in the Terms*.  DOCUMENT: Audio description is not provided, however the contents can be read out with screen reader.
1.2.4 Captions (Live)(AA): Captions are provided for all live audio content in synchronized media.	HARDWARE: Supports PRINTER DRIVER: Supports REMOTE UI: Supports DOCUMENT: Supports	Live audio is not provided. The case without any target is stated "Supports", as explained in the Terms*.
1.2.5 Audio Description (Prerecorded)(AA): Audio description is provided for all prerecorded video content in synchronized media.	HARDWARE: Support PRINTER DRIVER: Supports REMOTE UI: Supports DOCUMENT: Supports through Equivalent Facilitation	HARDWARE, PRINTER DRIVER & REMOTE UI: Prerecorded audio-only and prerecorded video-only contents are not used. The case without any target is stated "Supports", as explained in the Terms*.  DOCUMENT: Audio description is not provided, however the contents can be read out with screen reader.

<p>1.3.1 Info and Relationships(A): Information, structure, and relationships conveyed through presentation can be programmatically determined or are available in text.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Partially Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER:  Text is provided for structures that can be interpreted programmatically. However, for some of them, the use of assistive technology (e.g. JAWS) is needed for cursor movement.</p> <p>REMOTE UI:  Some ink levels and some non-text content (icons) are not read or have no information. Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies. (JAWS 2021)</p> <p>DOCUMENT:  Explanations are conveyed primarily via text.</p>
<p>1.3.2 Meaningful Sequence(A): When the sequence in which content is presented affects its meaning, a correct reading sequence can be programmatically determined.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Partially Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER:  In the printer driver, the order in which the UI content is read by screen readers matches the order in which it is presented, and information can be provided in the correct order. However, for some UI contents, the use of assistive technology (e.g.JAWS) is needed.</p> <p>REMOTE UI:  Some ink level reports and some non-text content (icons) are not read. Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies.</p> <p>DOCUMENT:  For cases where the order in which information is presented could affect its meaning, that information is presented in the same order. A part of contents can be recognized by using assistive technology (e.g.JAWS).</p>
<p>1.3.3 Sensory Characteristics(A): Instructions provided for understanding and operating content do not rely solely on sensory characteristics of components such as shape, color, size, visual location, orientation, or sound.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Partially Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER:  Printer Driver provides texts for understanding and operating contents in UI. Therefore, it does not rely solely on sensory characteristics. However, some non-text contents (icons) do not have texts.</p> <p>REMOTE UI:  Some ink level reports and some non-text content (icons) are not read.</p> <p>DOCUMENT:  There is no content that rely on sensory characteristics of components.</p>
<p>1.3.4 Orientation(AA):Content does not restrict its view and operation to a single display orientation, such as portrait or landscape, unless a specific display orientation is essential.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The product is not a mobile equipment, and is to be stationed on a desk or other pedestals to work properly. It is essential that the display orientation is limited to the view angle. As there is no underlying problem to be solved, it is expressed 'Supports'.</p> <p>PRINTER DRIVER, REMOTE UI &amp; DOCUMENT:  The product does not restrict its view to a single display orientation.</p>
<p>1.3.5 Identify Input Purpose(AA):The purpose of each input field collecting information about the user can be programmatically determined when:  The input field serves a purpose identified in the Input Purposes for User Interface Components section; and  The content is implemented using technologies with support for identifying the expected meaning for form input data.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER &amp; DOCUMENT:  The product does not provide any input field collecting user information. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  The purpose of each input field collecting information about the user is obvious.</p>



<p>1.4.1 Use of Color(A): Color is not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The product has a monochrome display, which do not convey meaning by colour.</p> <p>PRINTER DRIVER, REMOTE UI &amp; DOCUMENT:  colour is not used for the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>
<p>1.4.2 Audio Control(A): If any audio on a Web page plays automatically for more than 3 seconds, either a mechanism is available to pause or stop the audio, or a mechanism is available to control audio volume independently from the overall system volume level.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE, PRINTER DRIVER &amp; REMOTE U :  The product has no audio that plays automatically more than 3 seconds. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>DOCUMENT:  There is a mechanism to pause (or stop) the audio, and a mechanism to adjust the volume.</p>
<p>1.4.3 Contrast (Minimum)(AA): The visual presentation of text and images of text has a contrast ratio of at least 4.5:1.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The contrast of display is clear enough, and meets the requirement.</p> <p>PRINTER DRIVER, REMOTE UI &amp; DOCUMENT:  Displayed text meets contrast requirements/standards.</p>
<p>1.4.4 Resize text(AA): Except for captions and images of text, text can be resized without assistive technology up to 200 percent without loss of content or functionality.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The text on display cannot be enlarged.</p> <p>PRINTER DRIVER:  The UI text in the printer driver can be resized using functionality provided by the OS without loss of printer driver functionality, and there is no functionality in the printer driver that impedes there sizing of text.</p> <p>REMOTE UI:  Users may resize text while operating the device via the remote UI on a standard PC browser without any loss of functionality.</p> <p>DOCUMENT:  Text can be resized without assistive technology up to 200 percent without loss of content or functionality.</p>
<p>1.4.5 Images of Text(AA): If the technologies being used can achieve the visual presentation, text is used to convey information rather than images of text.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The visual appearance of text on display cannot be changed.</p> <p>PRINTER DRIVER, REMOTE UI &amp; DOCUMENT :  No test image is used.</p>
<p>1.4.10 Reflow(AA):Content can be presented without loss of information or functionality, and without requiring scrolling in two dimensions for:  •Vertical scrolling content at a width equivalent to 320 CSS pixels;  •Horizontal scrolling content at a height equivalent to 256 CSS pixels.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Scrolling in two directions is not required.</p> <p>PRINTER DRIVER:  The Printer Driver's windows are small and static, which basically does not require scrolling. In case of scolloing, the influence stays minute.</p> <p>REMOTE UI:  The remote UI does not use two-way scrolling.</p> <p>DOCUMENT:  Content can be presented vertical scrolling at a width equivalent to 320CSS pixels and adjusted for the screen without loss of information or functionality.</p>

<p>1.4.11 Non-text Contrast(AA):The visual presentation of the following have a contrast ratio of at least 3:1 against adjacent color(s):</p> <ul style="list-style-type: none"> <li>•User Interface Components: Visual information required to identify user interface components and states, except for inactive components or where the appearance of the component is determined by the user agent and not modified by the author;</li> <li>•Graphical Objects: Parts of graphics required to understand the content, except when a particular presentation of graphics is essential to the information being conveyed.</li> </ul>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The contrast of display is clear enough, and meets the requirement.</p> <p>PRINTER DRIVER:  The visual presentation of user interface components and graphical objects have a contrast ratio of at least 3:1 against adjacent colour(s)</p> <p>REMOTE UI:  The visual user Interface components and graphical objects meet a contrast ratio standard against adjacent colors.</p> <p>DOCUMENT:  The visual presentation of user interface components and graphical objects have a contrast ratio of at least 3:1 against adjacent colour(s)</p>
<p>1.4.12 Text Spacing(AA):In content implemented using markup languages that support the following text style properties, no loss of content or functionality occurs by setting all of the following and by changing no other style property:</p> <p>Line height (line spacing) to at least 1.5 times the font size;  Spacing following paragraphs to at least 2 times the font size;  Letter spacing (tracking) to at least 0.12 times the font size;  Word spacing to at least 0.16 times the font size.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Markup Language is not used. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  Printer Driver does not use markup languages. Therefore, it does not change the following setting:  Line height (line spacing);  Spacing following paragraphs;  Letter spacing (tracking);  Word spacing.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  Remote UI uses markup language, and possible to apply style sheet.</p> <p>DOCUMENT:  It does not provide the means to change letter spacing (tracking). The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>1.4.13 Content on Hover or Focus(AA): Where receiving and then removing pointer hover or keyboard focus triggers additional content to become visible and then hidden, the following are true:</p> <p>Dismissible: A mechanism is available to dismiss the additional content without moving pointer hover or keyboard focus, unless the additional content communicates an input error or does not obscure or replace other content;</p> <p>Hoverable: If pointer hover can trigger the additional content, then the pointer can be moved over the additional content without the additional content disappearing;</p> <p>Persistent : The additional content remains visible until the hover or focus trigger is removed, the user dismisses it, or its information is no longer valid.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Partially Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>No additional content is displayed by hover or focus. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>2.1.1 Keyboard(A): All functionality of the content is operable through a keyboard interface without requiring specific timings for individual keystrokes, except where the underlying function requires input that depends on the path of the user's movement and not just the endpoints.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The firmware is operable only with physical keys of the product itself (There is no touch panel nor touch key). Keyboard interface operation is not available. Speech output is not provided by the product itself.</p> <p>PRINTER DRIVER:  The printer driver runs on systems with keyboards, and all functionality can be operated solely with the keyboard.</p> <p>REMOTE UI:  In some function, operation through a keyboard are not provided.</p> <p>DOCUMENT:  All functionality are operable with keyboard interface and does not depend on operation timing.</p>

<p>2.1.2 No Keyboard Trap(A): If keyboard focus can be moved to a component of the page using a keyboard interface, then focus can be moved away from that component using only a keyboard interface, and, if it requires more than unmodified arrow or tab keys or other standard exit methods, the user is advised of the method for moving focus away.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The elements of user interface can be displayed and selected using the consistent mechanism using the arrow keys, the OK key and the back key.</p> <p>PRINTER DRIVER:  Focus can be moved away from the component using only a keyboard interface.</p> <p>REMOTE UI:  The focus which moves by using keyboard moves without trapped at any particular component.</p> <p>DOCUMENT:  Keyboard focus can be moved using a keyboard interface without keyboard trap in a specific component.</p>
<p>2.1.4 Character Key Shortcuts(A): If a keyboard shortcut is implemented in content using only letter (including upper- and lower-case letters), punctuation, number, or symbol characters, then at least one of the following is true:  Turn off: A mechanism is available to turn the shortcut off;  Remap: A mechanism is available to remap the shortcut to use one or more non-printable keyboard characters (e.g. Ctrl, Alt, etc);  Active only on focus: The keyboard shortcut for a user interface component is only active when that component has focus.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Does not Support  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE, REMOTE UI &amp; DOCUMENT:  There is no component that implements a keyboard shortcut. The case without any target is stated "Supports", as explained in the Terms*. There is no keyboard shortcuts. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  Keyboard shortcut is implemented in printer driver content. However, it is not available to turn the shortcut off, and to remap the shortcut.</p>
<p>2.2.1 Timing Adjustable(A): For each time limit that is set by the content, at least one of the following is true:  • Turn off: The user is allowed to turn off the time limit before encountering it; or  • Adjust: The user is allowed to adjust the time limit before encountering it over a wide range that is at least ten times the length of the default setting; or  • Extend: The user is warned before time expires and given at least 20 seconds to extend the time limit with a simple action (for example, "press the space bar"), and the user is allowed to extend the time limit at least ten times; or  • Real-time Exception: The time limit is a required part of a real-time event (for example, an auction), and no alternative to the time limit is possible; or  • Essential Exception: The time limit is essential and extending it would invalidate the activity; or  • 20 Hour Exception: The time limit is longer than 20 hours.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  There is a screen lock by timeout in the secure print function. The screen lock function can be disabled.</p> <p>PRINTER DRIVER, REMOTE UI &amp; DOCUMENT:  It has no contents that set time limit. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>2.2.2 Pause, Stop, Hide(A): For moving, blinking, scrolling, or auto-updating information, all of the following are true:  •Moving, blinking, scrolling: For any moving, blinking or scrolling information that (1) starts automatically, (2) lasts more than five seconds, and (3) is presented in parallel with other content, there is a mechanism for the user to pause, stop, or hide it unless the movement, blinking, or scrolling is part of an activity where it is essential; and  •Auto-updating: For any auto-updating information that (1) starts automatically and (2) is presented in parallel with other content, there is a mechanism for the user to pause, stop, or hide it or to control the frequency of the update unless the auto-updating is part of an activity where it is essential.</p>	<p>HARDWARE: Partially Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  For the long messages, they keep on move on the display, and there is no mechanism for the user to pause, stop, or hide.</p> <p>PRINTER DRIVER:  There are no UI components in the printer driver that automatically move or update.</p> <p>REMOTE UI:  The remote UI does not have any components which auto-update.</p> <p>DOCUMENT:  Content with automatic movement has a mechanism to pause.</p>
<p>2.3.1 Three Flashes or Below Threshold(A): Web pages do not contain anything that flashes more than three times in any one second period, or the flash is below the general flash and red flash thresholds.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The display of the product itself does not have flashing. The LED, near the display, has no flashing which may affect users.</p> <p>PRINTER DRIVER:  There are no UI components in the printer driver that flash.</p> <p>REMOTE UI:  There are no Blinking or flashing objects applied in Remote UI.</p> <p>DOCUMENT:  The flashing meets the requirements/criteria.</p>

<p>2.4.1 Bypass Blocks(A): A mechanism is available to bypass blocks of content that are repeated on multiple Web pages.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Does not Support  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The product does not contain a web page.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  A mechanism to bypass blocks of tab menu that are repeated is not provided in Remote UI.</p> <p>DOCUMENT:  It is available to bypass blocks of content which are repeated on multiple Web pages.</p>
<p>2.4.2 Page Titled(A): Web pages have titles that describe topic or purpose.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Partially Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  Each screen of the printer driver has a title that indicates the purpose of the screen. However, for the reading of the title, the use of assistive technology (e.g. JAWS) is needed.</p> <p>REMOTE UI:  Each remote UI page displays a title or tab that explains the purpose of the screen on which it is displayed.</p> <p>DOCUMENT:  All pages have titles that describe topic.</p>
<p>2.4.3 Focus Order(A): If a Web page can be navigated sequentially and the navigation sequences affect meaning or operation, focusable components receive focus in an order that preserves meaning and operability.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The Focus moves in an order that ensures and maintains the meaning and usability.</p> <p>PRINTER DRIVER:  The order of focus preserves meaning and operability.</p> <p>REMOTE UI:  Users need to acknowledge that the items in lower hierarchies are read out directly after a series of upper hierarchies.</p> <p>DOCUMENT:  Focusable components receive focus in an order that preserves meaning and operability.</p>
<p>2.4.4 Link Purpose (In Context)(A): The purpose of each link can be determined from the link text alone or from the link text together with its programmatically determined link context, except where the purpose of the link would be ambiguous to users in general.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  No link is used. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The product does not contain any link.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  The purpose of each link in the remote UI can be determined from the link text.</p> <p>DOCUMENT:  Each link can be easily understood the purpose of it.</p>

<p>2.4.5 Multiple Ways(AA): More than one way is available to locate a Web page within a set of Web pages except where the Web Page is the result of, or a step in, a process.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Does not Support  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The product does not contain a web page.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  When using the remote UI, it is not possible to reach a page without going through the required pages in the required order.</p> <p>DOCUMENT:  "Contents" and "Search" are provided for available to locate a Web page.</p>
<p>2.4.6 Headings and Labels(AA): Headings and labels describe topic or purpose.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The headings convey the intentions.</p> <p>PRINTER DRIVER:  Headings and Labels describe the purpose.</p> <p>REMOTE UI:  Each label and heading displayed in the remote UI describes purpose.</p> <p>DOCUMENT:  All headings and labels describe topic.</p>
<p>2.4.7 Focus Visible(AA): Any keyboard operable user interface has a mode of operation where the keyboard focus indicator is visible.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The focus is controllable by the hard keys of product itself, and the focused item is visible on the display.</p> <p>PRINTER DRIVER:  The keyboard focus can be recognized visually in the keyboard operable user interface.</p> <p>REMOTE UI:  The remote UI uses assistive technology (For example, JAWS) to allow the keyboard to recognize focus.</p> <p>DOCUMENT:  The keyboard focus can be recognized visually in the keyboard operable user interface.</p>
<p>2.5.1 Pointer Gestures(A):All functionality that uses multipoint or path-based gestures for operation can be operated with a single pointer without a path-based gesture, unless a multipoint or path-based gesture is essential.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The display of the product does not require multipoint or path-based gestures for operation.</p> <p>PRINTER DRIVER:  Functionality that uses path-based gestures for operation can be operated with a single pointer.</p> <p>REMOTE UI:  No function that uses multipoint or path-based gestures for operation in Remote UI.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>DOCUMENT:  All functionality that uses multipoint gestures for operation can be operated with a single pointer.</p>
<p>2.5.2 Pointer Cancellation(A):For functionality that can be operated using a single pointer, at least one of the following is true:  No Down-Event: The down-event of the pointer is not used to execute any part of the function;  Abort or Undo: Completion of the function is on the up-event, and a mechanism is available to abort the function before completion or to undo the function after completion;  Up Reversal: The up-event reverses any outcome of the preceding down-event;  Essential: Completing the function on the down-event is essential.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The product has no touch panel. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  For functionality that can be operated using a single pointer, it is easily available to abort or undo the function.</p> <p>REMOTE UI:  The scrollbar operates in a down event, but there are other workarounds and it is not necessary to operate in a down event.</p> <p>DOCUMENT:  Pointer cancellation is available. User can abort the function before completion or to undo the function after completion.</p>

<p>2.5.3 Label in Name(A):For user interface components with labels that include text or images of text, the name contains the text that is presented visually.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself. The contents of display is not programmatically interpretable.</p> <p>PRINTER DRIVER:  For user interface components with labels, the name contains the text that is presented visually.</p> <p>REMOTE UI:  For user interface components with labels, the name contains the text that is presented visually.  In some contents, the item name of the check box is read out one step apart.</p> <p>DOCUMENT:  For user interface components with labels, the name contains the text that is presented visually.</p>
<p>2.5.4 Motion Actuation(A):Functionality that can be operated by device motion or user motion can also be operated by user interface components and responding to the motion can be disabled to prevent accidental actuation, except when:  Supported Interface: The motion is used to operate functionality through an accessibility supported interface;  Essential: The motion is essential for the function and doing so would invalidate the activity.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>There is no function that can be operated by device motion or user motion in the printer driver.The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>3.1.1 Language of Page(A): The default human language of each Web page can be programmatically determined.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself. The contents of display is not programmatically interpretable.</p> <p>PRINTER DRIVER:  The default human language are programmatically determined.</p> <p>REMOTE UI:  The language used by RemoteUI is recognized by assistive technology. In some contents, the item name of the check box is read out one step apart.</p> <p>DOCUMENT:  Human language can be recognized by using assistive technology.</p>
<p>3.1.2 Language of Parts(AA): The human language of each passage or phrase in the content can be programmatically determined except for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The human language of each parts are programmatically determined.</p> <p>REMOTE UI:  The language used by RemoteUI is recognized by assistive technology. In some contents, the item name of the check box is read out one step apart.</p> <p>DOCUMENT:  Human language can be recognized by using assistive technology.</p>
<p>3.2.1 On Focus(A): When any user interface component receives focus, it does not initiate a change of context.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The focus is controllable by the hard keys of product itself, and the items do not initiate a change of context just by receiving focus.</p> <p>PRINTER DRIVER, REMOTE U &amp; DOCUMENT:  There is no component that initiates a change of context when receives focus.</p>

<p>3.2.2 On Input(A): Changing the setting of any user interface component does not automatically cause a change of context unless the user has been advised of the behavior before using the component.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  The focus is controllable by the hard keys of product itself, and the items do not cause serious unpredictable change of context, automatically.</p> <p>PRINTER DRIVER:  There are no circumstances in which changing the settings in the printer driver result in other settings being changed.</p> <p>REMOTE UI:  Some buttons or radio button clicks display additional settings, but additional settings are predictable.</p> <p>DOCUMENT:  Changing the setting of any user interface component does not cause a change of context.</p>
<p>3.2.3 Consistent Navigation(AA): Navigational mechanisms that are repeated on multiple Web pages within a set of Web pages occur in the same relative order each time they are repeated, unless a change is initiated by the user.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The product does not contain a web page.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  Navigational mechanisms that are repeated throughout the Remote UI occur in the same order each time they are repeated.</p> <p>DOCUMENT:  Navigational mechanisms that are repeated on occur in the same relative order each time they are repeated.</p>
<p>3.2.4 Consistent Identification(AA): Components that have the same functionality within a set of Web pages are identified consistently.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  The product does not contain a web page.  The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  The same terminology is used for the naming/labeling of components within the Remote UI which have the same functionality.</p> <p>DOCUMENT:  Components that have the same functionality are identified consistently.</p>
<p>3.3.1 Error Identification(A): If an input error is automatically detected, the item that is in error is identified and the error is described to the user in text.</p>	<p>HARDWARE: Does not Support  PRINTER DRIVER: Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Speech output is not provided by the product itself. The content on display is not programmatically interpretable.</p> <p>PRINTER DRIVER:  In the printer driver, when errors are occurred, the error can be recognized programmatically and display the error content.</p> <p>REMOTE UI:  If an input error is automatically detected, the item that is in error can be identified.  However, it can not be identified by reading.</p> <p>DOCUMENT:  There is no component that an input error occurs.  The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>3.3.2 Labels or Instructions(A): Labels or instructions are provided when content requires user input.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  Visual label is provided for user inputs on the display of the product itself.</p> <p>PRINTER DRIVER:  All entry fields in the user interface of the printer driver are labeled.</p> <p>REMOTE UI:  Any content in the Remote UI (such as text boxes), which require a user's input are appropriately labeled.</p> <p>DOCUMENT:  All content requires user input is provided labels or instructions.</p>

<p>3.3.3 Error Suggestion(AA): If an input error is automatically detected and suggestions for correction are known, then the suggestions are provided to the user, unless it would jeopardize the security or purpose of the content.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Partially Supports  REMOTE UI: Does not Support  DOCUMENT: Supports</p>	<p>HARDWARE:  On the product screen, detection is performed for input errors and a notice to that effect is displayed.</p> <p>PRINTER DRIVER:  Messages with instructions for correcting errors are displayed in the UI of the printer driver for all locations where errors can occur. However, for the reading of the range of value, the use of assistive technology (e.g. JAWS) is needed.</p> <p>REMOTE UI:  Suggestions for the correction of errors are not offered in Remote UI.</p> <p>DOCUMENT:  There is no component that an input error occurs. The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>3.3.4 Error Prevention (Legal, Financial, Data)(AA): For Web pages that cause legal commitments or financial transactions for the user to occur, that modify or delete user-controllable data in data storage systems, or that submit user test responses, at least one of the following is true:</p> <ol style="list-style-type: none"> <li>1. Reversible: Submissions are reversible.</li> <li>2. Checked: Data entered by the user is checked for input errors and the user is provided an opportunity to correct them.</li> <li>3. Confirmed: A mechanism is available for reviewing, confirming, and correcting information before finalizing the submission.</li> </ol>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  There is no legal and financial screen in the device UI. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  There is no case in printer driver. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  In the IJ Cloud Printing Center setup, there is an option to accept the license, and user can undo it later.</p> <p>DOCUMENT:  Not applicable  The case without any target is stated "Supports", as explained in the Terms*.</p>
<p>4.1.1 Parsing(A): In content implemented using markup languages, elements have complete start and end tags, elements are nested according to their specifications, elements do not contain duplicate attributes, and any IDs are unique, except where the specifications allow these features.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  No part of the printer driver is implemented using markup languages. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  The HTML used in the remote UI adheres to the appropriate standards.</p> <p>DOCUMENT:  Markup languages used are nested according to their specifications.</p>
<p>4.1.2 Name, Role, Value(A): For all user interface components (including but not limited to: form elements, links and components generated by scripts), the name and role can be programmatically determined; states, properties, and values that can be set by the user can be programmatically set; and notification of changes to these items is available to user agents, including assistive technologies.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Partially Supports  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  In the printer driver, names and roles of UI components can be recognized and configured programmatically, and notification of changes can be made available.</p> <p>REMOTE UI:  The interface elements used by RemoteUI are recognizable by assistive technology. In some contents, the item name of the check box is read out one step apart.</p> <p>DOCUMENT:  HTML used adheres to the appropriate standards.</p>



<p>4.1.3 Status Messages(AA):In content implemented using markup languages, status messages can be programmatically determined through role or properties such that they can be presented to the user by assistive technologies without receiving focus.</p>	<p>HARDWARE: Supports  PRINTER DRIVER: Supports  REMOTE UI: Does not Support  DOCUMENT: Supports</p>	<p>HARDWARE:  This requirement is not applied to firmwares in accordance with EN 301 549. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>PRINTER DRIVER:  No part of the printer driver is implemented using markup languages. The case without any target is stated "Supports", as explained in the Terms*.</p> <p>REMOTE UI:  The status message in Remote UI can be confirmed with moving focus on the status message.</p> <p>DOCUMENT:  It has no content to display status messages. The case without any target is stated "Supports", as explained in the Terms*.</p>
--	--	---

**Chapter 5: Functional Performance Statements**

Criteria	Conformance Level	Remarks and Explanations
5.1.2 Blindness	Partially Supports	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. Speech output is not provided by the product itself. Some of the operable parts can not be discernible without vision. Keys on the operational panel are rather difficult to discern without vision. The stop key is tactilely distinguishable. The status indications on display cannot be distinguished by touch nor hearing.</p> <p><b>REMOTE UI*:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> Printer Driver can be operated with keyboard through hearing by using screen reader.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p> <p>*Access to Remote UI : Access to HTTP:XXX.XXX.XXX.XXX ( the IP address of your Canon device) to start its RemoteUI . Mainly the arrow-keys are used to move between the UI elements. For the Remote UI of this version, the child elements (lower hierarchy) follows after the parent elements serially.</p>
5.1.3 Low vision	Partially Supports	<p><b>HARDWARE:</b> GX3000 Series has a monochrome non-operable display. The controls of key repeat and alarm volume cannot be operated easily without vision. Keys are rather difficult to discern without vision. Alphabetic keys and numeric keys are not provided. The stop key is tactilely distinguishable, among the existing keys. The scale of the ink capacity when refilling ink may be difficult to see because of the engraved mark. Other signs are easy to see. The status indications on display cannot be distinguished by touch nor hearing. Speech output is not provided by the product itself.</p> <p><b>REMOTE UI:</b> In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message in can be confirmed only when the focus is on the status message.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> All non-text content that is presented to the user has a text alternative that serves the equivalent purpose.</p>
5.1.4 Colour blindness	Supports	<p><b>HARDWARE:</b> The product has a monochrome display, which do not convey meaning by colour. All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.</p> <p><b>REMOTE UI:</b> There is information in text for the items which conveys meaning.</p> <p><b>PRINTER DRIVER:</b> The text has considerable contrast with the background.</p> <p><b>DOCUMENTS:</b> Colour on display and on operable parts are not used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>
5.1.5 Deafness	Supports	<p>The product is basically operable without user hearing.</p> <p><b>HARDWARE:</b> The alarm volume is controllable.</p>

5.1.6 Hearing impairment	Supports	The product is basically operable without user hearing. HARDWARE: The alarm volume is controllable.
5.1.7 Speech impairment	Supports	The product does not require user speech.
5.1.8 Impairment that limits upper limb strength and action (limited manipulation)	Partially Supports	HARDWARE: There is no alternative in the operation part that requires pinching. The key repeat is controllable. <GX4000 Series> Bounce key function is not supported. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
5.1.8 Impairment that limits upper limb strength and action (limited strength)	Partially Supports	HARDWARE: There are places where the operating force for changing the paper size, but there is no alternative. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
5.1.9 Impairment that limits reach ranges	Supports	HARDWARE: The product is not intended to instale on a floor. It is possible to meet the requirements with the appropriate pedestal which the user prepares. REMOTE UI: Some cases are not operable through a keyboard interface, but are operable with a mouse interface. PRINTER DRIVER & DOCUMENTS: All functionality are operable with keyboard interface and does not depend on operation timing.
5.1.10 Photosensitive seizure	Supports	The product does not have any component which may trigger photosensitive seizures.
5.1.11 Cognitive, language, or learning disorders	Partially Supports	HARDWARE: Speech output is not provided by the product itself. The status indications on display cannot be distinguished by touch nor hearing. REMOTE UI: In some function, operation through a keyboard are not provided. A mechanism to bypass blocks the repeated tab menu is not provided. Some function does not have more than one way to access. The suggestions for the correction of errors are not offered. The status message can be confirmed only when the focus is on the status message. PRINTER DRIVER: User can use the function that meets the purpose without interrupted by using accessibility feature. DOCUMENTS: Components that have the same functionality are identified consistently.

## Chapter 6: Requirements

Criteria	Conformance Level	Remarks and Explanations
6.1 General The basic requirements which shall be followed with respect to office equipment in order to ensure and improve accessibility are as specified in 6.2 to 6.13.	No response required	
6.2 Closed functionality 6.2.1 General Office equipment with closed functionality shall be operable without requiring the user to attach or install assistive technology and shall conform to the following items.	No response required	

6.2.2 Speech-output enabled 6.2.2.1 General For the operation of a screen, such as the control panel, an operation with voice guidance shall be provided.	No response required	
6.2.2.2 Information displayed on-screen Voice guidance shall be provided for all information displayed on-screen.	Does not support	Speech output is not provided by the product itself.
6.2.2.3 Spoken languages Voice guidance shall be output in the same human language as the displayed language.	Not Applicable	Speech output is not provided by the product itself.
6.2.2.4 Speech delivery type and coordination Voice guidance shall be delivered in a mechanism that can be easily used by all users. Examples include, but are not limited to, direct audio output (or bundled audio output), industry standard connectors, telephone handsets, and the like. Speech shall be recorded or digitized human or synthesized. Voice guidance shall be coordinated with information displayed on the screen.	Not Applicable	Speech output is not provided by the product itself.
6.2.2.5 User control Voice guidance for any single function shall be automatically interrupted when a transaction is selected. Voice guidance shall be capable of being repeated and paused. Where it is essential that the user hears the entire message, for example a safety instruction or warning, office equipment shall block all user action so that speech is not interrupted.	Not Applicable	Speech output is not provided by the product itself.
6.2.2.6 Non-interfering audio output During voice guidance, another guidance (warning notification) or auditory signal that lasts three seconds or longer shall not be automatically played.	Not Applicable	Speech output is not provided by the product itself.
6.2.2.7 Tactile indication of speech output mode Where voice guidance is provided, a tactile symbol to initiate the guidance shall be provided.	Not Applicable	Speech output is not provided by the product itself.
6.2.3 Volume 6.2.3.1 General Where sound such as voice guidance is delivered, volume control and output amplification conforming to 6.2.3.2 and 6.2.3.3 shall be provided. Deliver the voice guidance as the main operation means, and when the use by the hearing impairment users is assumed, a) volume shall be adjusted within a range of at least 18 dB, b) at least one intermediate step of 12 dB above the lowest volume level shall be provided.	Supports	The product does not have communication function. The case without any target is stated "Supports", as explained in the Terms*.
6.2.3.2 Private listening Where private listening is provided, non-visual mode of operation for controlling the volume shall be provided.	Not Applicable	Speech output is not provided by the product itself.
6.2.3.3 Non-private listening Where non-private listening is provided, a) speaker volume can be amplified up to a level of at least 65 dB (both speech and auditory signals), b) the volume shall be automatically reset to the default level after every use. (only speech). For personal authentication, it may have a function not to reset.	Not Applicable	Speech output is not provided by the product itself.
6.2.4 Characters on display screens At least one mode of characters displayed on the screen shall be in a sans serif font. Where a screen enlargement feature is not provided, characters shall be 4,8 mm or higher based on the uppercase letter "I" or "H".	Partially Supports	The on-screen text size is about 2.5 mm, which doesn't meet the requirements, but the ample contrast makes it easy to see.
6.3 Biometrics Where provided, biometrics shall not be the only means for user identification or control. Exception: Where at least two biometric options that use different biological characteristics are provided, using biometrics shall be permitted as the only means for user identification or control.	Supports	Biometric forms of user identification are not used. The case without any target is stated "Supports", as explained in the Terms*.

6.4 Preservation of information provided for accessibility Where video and other contents with information added for accessibility are delivered to multi-function devices, non-proprietary information provided for accessibility shall not be removed or shall be restored upon delivery.	Supports	Functionality that transmits and converts information or communication is not provided. The case without any target is stated "Supports", as explained in the Terms*.
6.5 Privacy 6.5.1 General The same degree of privacy of input and output shall be provided to all individuals.	Supports	Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Canon global privacy provides to all individuals the same degree of privacy. RemoteUI does not have function to make the PC display invisible.
6.5.2 Masked entry Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.	Supports	Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Although the administrator password is masked, generally private listening mechanism can be connected to user's PC, or the user preference of screen reader can be selected not read out the masked entries.
6.5.3 Private access to personal data Where auditory output is provided as non-visual access to a closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.	Supports	Speech output is not provided by the product itself. Some functions are provided by RemoteUI on PC, which can be read out by screen reader. Canon global privacy provides to all individuals the same degree of privacy. User can generally listen privately by connecting hearing device, such as headset, to PC.
6.6 Standard connections Where data connections used for input and output are provided, at least one of each type of connection shall conform to industry standard non-proprietary formats.	Supports	This product provides connections that conform industry standards.
6.7 Operable parts 6.7.1 General Operable parts used in the normal operation of office equipment shall conform to 6.7.	No response required	
6.7.2 Contrast Where operation parts such as hard keys and levers are provided, they shall ensure to contrast visually from background surfaces. Characters and symbols printed on office equipment shall ensure to contrast visually from background surfaces with either light characters or symbols on a dark background or dark characters or symbols on a light background.	Partially Supports	The scale of the ink capacity when refilling ink may be difficult to see because of the engraved mark. Other signs are easy to see.
6.7.3 Input controls 6.7.3.1 General At least one input control conforming to 6.7.3.2, 6.7.3.3, or 6.7.3.4 shall be provided for each function of office equipment.	No response required	
6.7.3.2 Tactilely discernible Where office equipment has operable parts by hand, it shall provide a means to tactilely discern each operable part. It shall also be discernible by touch without activation.	Supports	The Start key and the Stop key tactilely distinguishable, among the existing keys.
6.7.3.3 Alphabetic keys Where provided, individual alphabetic keys shall be arranged in a QWERTY-based keyboard layout and the "F" and "J" keys shall be tactilely distinct from the other keys.	Supports	Alphabetic keys are not provided. The Start key and the Stop key tactilely distinguishable.
6.7.3.4 Numeric keys Where provided, numeric keys shall be arranged in a 12-key ascending or descending keypad layout. The number five key shall be tactilely distinct from the other keys. Where the office equipment provides an alphabetic overlay on numeric keys, the relationships between letters and digits shall conform to ITU-T E.161.	Supports	Numeric keys are not provided. The Start key and the Stop key is tactilely distinguishable.
6.7.4 Key repeat Where a keyboard with key repeat is provided and the key repeat cannot be turned off, the time before the key repeat is activated shall be fixed at 2 s, or adjustable to 2 or more seconds. The key repeat rate shall be adjustable to 2 or more seconds per character.	Supports	This product has key repeat function, but this function can be disabled.

<p>6.7.5 Double-strike key Where a keyboard or keypad is provided and the same operation as the previous keystroke was performed, the time during which the next keystroke will not be accepted shall be adjustable 0,5 s or more.</p>	Does not support	Bounce key function is not supported.
<p>6.7.6 Timed response Where a timed response is required, and the timed response function cannot be turned off, the user shall be alerted visually, as well as by touch or sound, and shall be given the opportunity to indicate that more time is needed.</p>	Supports	In the secure print function and multi-user, the screen locks when time passes. Screen lock function can be disabled.
<p>6.7.7 Simultaneous user actions Where office equipment requires simultaneous user actions for the user, office equipment shall provide at least one action that does not require simultaneous user actions.</p>	Supports	There is no place that requires simultaneous operations.
<p>6.7.8 Physical operation At least one mode of operation shall be operable with one hand and the operation shall not require tight grasping, pinching, or twisting of the wrist. The operation shall require a maximum force of 22,2 N.</p>	Partially Supports	Some operations require pinching.
<p>6.7.9 Fare cards and key cards Where operation of office equipment requires fare cards or key cards and orientation is important to use, orientation shall be tactilely discernible.</p>	Supports	This product does not require use of card. The case without any target is stated "Supports", as explained in the Terms*.
<p>6.7.10 Reach height and depth 6.7.10.1 General At least one of each type of operable part of floor type office equipment shall be at a height conforming to 6.7.10.3 or 6.7.10.4 according to its position established by the vertical reference plane specified in 6.7.10.2 for a side reach or a forward reach. Operable parts used with speech output required by 6.2.2 shall not be the only type of operable part complying with 6.7.10 unless that part is the only operable part of its type.</p>	No response required	
<p>6.7.10.2 Vertical reference plane 6.7.10.2.1 General Operable parts shall be positioned for a side reach or a forward reach determined with respect to a vertical reference plane. The vertical reference plane shall be located in conformance to 6.7.10.2.2 or 6.7.10.2.3.</p>	No response required	
<p>6.7.10.2.2 Vertical plane for side reach Where a side reach is provided, the vertical reference plane shall be 1 220 mm (48 inches) long minimum.</p>	Supports	The product is not intended to instale on a floor. It is possible to locate a vertical referene plane.
<p>6.7.10.2.3 Vertical plane for forward reach Where a forward reach is provided, the vertical reference plane shall be 760 mm (30 inches) long minimum.</p>	Supports	The product is not intended to instale on a floor. It is possible to locate a vertical referene plane.
<p>6.7.10.3 Side reach 6.7.10.3.1 General Operable parts of office equipment providing a side reach shall conform to 6.7.10.3.2 or 6.7.10.3.3. The vertical reference plane shall be centred on the operable part and placed at the leading edge of the maximum protrusion of the office equipment within the length of the vertical reference plane. Where a side reach requires a reach over a portion of the office equipment, the height of that portion of the office equipment shall be 865 mm (34 inches) maximum.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.3.2 Unobstructed side reach Where the operable part is located 255 mm (10 inches) or less beyond the vertical reference plane, the operable part shall be 1 220 mm (48 inches) high maximum and 380 mm (15 inches) high minimum above the floor.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.3.3 Obstructed side reach Where the operable part is located more than 255 mm (10 inches), but not more than 610 mm (24 inches), beyond the vertical reference plane, the height of the operable part shall be 1 170 mm (46 inches) high maximum and 380 mm (15 inches) high minimum above the floor. The operable part shall not be located more than 610 mm (24 inches) beyond the vertical reference plane.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.

<p>6.7.10.4 Forward reach</p> <p>6.7.10.4.1 General</p> <p>Operable parts of office equipment providing a forward reach shall conform to 6.7.10.4.2 or 6.7.10.4.3. The vertical reference plane shall be centred, and intersect with, the operable part. Where a forward reach allows a reach over a portion of the office equipment, the height of that portion of the office equipment shall be 865 mm (34 inches) maximum.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.4.2 Unobstructed forward reach</p> <p>Where the operable part is located at the leading edge of the maximum protrusion within the length of the vertical reference plane of the office equipment, the operable part shall be 1 220 mm (48 inches) high maximum and more than 380 mm (15 inches) high minimum above the floor.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.4.3 Obstructed forward reach</p> <p>6.7.10.4.3.1 General</p> <p>Where the operable part is located beyond the leading edge of the maximum protrusion within the length of the vertical reference plane, the operable part shall conform to 6.7.10.4.3.2 and 6.7.10.4.3.3. The maximum allowable forward reach to an operable part shall be 635 mm (25 inches).</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.4.3.2 Operable part height for office equipment with obstructed forward reach</p> <p>Reach depth: 510 mm (20 inches) or less, Operable part height: 1 220 mm (48 inches) maximum</p> <p>Reach depth: More than 510 mm (20 inches) to 635 mm (25 inches) or less, Operable part height: 1 120 mm (44 inches) maximum</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.7.10.4.3.3 Knee and toe space under office equipment with obstructed forward reach</p> <p>Knee and toe space under the office equipment shall be 685 mm (27 inches) high minimum, 635 mm (25 inches) deep maximum, and 760 mm (30 inches) wide minimum and shall be clear of obstructions.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.8 Visibility of display screens</p> <p>Where office equipment provides one or more display screens, at least one of each type of display screen shall be visible from a point located 1 015 mm (40 inches) above the floor.</p>	Supports	The product is not intended to instale on a floor. It is possible to meet the requirement with the appropriate pedestal which the user prepares.
<p>6.9 Flashing</p> <p>Where office equipment emits lights in flashes, there shall be no more than three flashes in any one-second period.</p>	Supports	There are no flashing lights that would affect the user.
<p>6.10 Status indicators</p> <p>Where provided, status indicators shall be discernible visually and by touch or sound.</p>	Does not support	The status indications on display cannot be distinguished by touch nor hearing.
<p>6.11 Colour coding</p> <p>Where provided, colour coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.</p>	Supports	All information that uses colour is also displayed in text. The amounts of remaining ink can be checked through the windows in front of the product, and their colours are distinguishable in texts by opening the top cover, inside of the product.
<p>6.12 Audible signals</p> <p>Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response.</p>	Supports	All the informtion of audible signals or cues during operation are also given by the LED lights and other components visually .
<p>6.13 Software requirements for closed functionality</p> <p>6.13.1 General</p> <p>Office equipment with software closed to assistive technologies shall conform to 6.13.2 to 6.13.12.</p> <p>NOTE The following requirements are premised the use of office equipment, harmonizing with the related requirements of WCAG 2.1, as EN 301 549 requires to satisfy WCAG 2.1.</p>	No response required	
<p>6.13.2 Sensory characteristics</p> <p>Instructions provided for understanding and operating content do not rely solely on sensory characteristic of components such as shape, colour, size, visual location, orientation, or sound (WCAG 2.1:2018, 1.3.3).</p>	Does not Support	Speech output is not provided by the product itself.

6.13.3 Audio control If any audio on an office equipment plays automatically for more than 3 s, either a mechanism is available to pause or stop the audio, or a mechanism is available to control audio volume independently from the overall system volume level (WCAG 2.1:2018, 1.4.2).	Supports	The product has no audio content.
6.13.4 Text contrast The visual presentation of text and images of text has a contrast ratio of at least 4.5:1, except for the following (WCAG 2.1:2018, 1.4.3):	Supports	The contrast of display is clear enough, and meets the requirement.
6.13.5 Non-text contrast The visual presentation of the following has a contrast ratio of at least 3:1 against adjacent colour(s) (WCAG 2.1:2018, 1.4.11):	Supports	The contrast of display is clear enough, and meets the requirement.
6.13.6 No-key trap If focus can be moved between components using a key interface, then focus can be moved away from that component using only a key interface, and, if it requires more than usual methods, the user is advised of the method for moving focus away (WCAG 2.1:2018, 2.1.2).	Supports	The elements of user interface can be displayed and selected using the consistent mechanism using the arrow keys, the OK key and the back key.
6.13.7 Pause, stop, hide For moving, blinking, scrolling, or auto-updating information, all of the following are true (WCAG 2.1:2018, 2.2.2):	Partially Supports	For the long messages, they keep on move on the display, and there is no mechanism for the user to pause, stop, or hide.
6.13.8 Focus order If a display can be navigated sequentially and the navigation sequences affect meaning or operation, focusable components receive focus in an order that preserves meaning and operability (WCAG 2.1:2018, 2.4.3)	Supports	The Focus moves in an order that ensures and maintains the meaning and usability.
6.13.9 Focus visible Any key-operable user interface has a mode of operation where the focus indicator is visible (WCAG 2.1:2018, 2.4.7).	Supports	The focus is controllable by the hard keys of product itself, and the focused item is visible on the display.
6.13.10 Pointer gestures All functionality that uses multipoint or path-based gestures for operation can be operated with a single pointer without a path-based gesture, unless a multipoint or path-based gesture is essential (WCAG 2.1:2018, 2.5.1)	Supports	The display of the product does not require multipoint or path-based gestures for operation.
6.13.11 Label in name For user interface of speech input, which have labels that include text or image of text, the name contains the text that is presented visually (WCAG 2.1:2018, 2.5.3).	Does not Support	Speech output is not provided by the product itself. The contents of display is not programmatically interpretable.
6.13.12 On focus When any user interface component receives focus, it does not initiate a change of context (WCAG 2.1:2018, 3.2.1).	Supports	The focus is controllable by the hard keys of product itself, and the items do not initiate a change of context just by receiving focus.

## Chapter 7: Support Documentation and Services

Criteria	Conformance Level	Remarks and Explanations
7.1 Disclosure of information related to accessibility When users purchase and use office equipment, the provider of office equipment shall provide the user with information related to the accessibility of the office equipment, so that the user can easily select an office equipment with the appropriate accessibility features to match the user needs.	Supports	This VPAT lists and explains the features required by EN 301 549 requirements.
7.2 Requirements for user documentation and support services Customer service representatives or equivalent services shall be provided to users, and multiple access methods shall be available to users to communicate with these services.	Supports	<p>The WCAG is applied to the documentation. See WCAG section for the results.</p> <p>Support services will provide information about functions related to accessibility by means according to user's requests.</p> <p>Europe, Middle East &amp; Africa : You can reach contact support from below URL. <a href="https://www.canon-europe.com/support/consumer_products/contact_support/">https://www.canon-europe.com/support/consumer_products/contact_support/</a> Please choose proper country. Phone number and e-mail address are described.</p> <p>If there is not proper country, please access below and contact each office in your country. <a href="https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/">https://www.canon-europe.com/contact_us/canon_europe_middle_east_and_africa_offices/</a></p> <p>US: Canon U.S.A., Inc. provides support services accommodating users with disabilities through 1(800) OKCANON (652-2666) assistance, TTY support at (866)251-3752. Canon otherwise available to U.S. federal government agencies through Federal Relay.</p>



**Note1:** This document was prepared based on normal walk-up functionality. It does not include maintenance and troubleshooting procedures. The information contained in this document is proprietary information and is not for reproduction, publication or manipulation in any way or form. This document addresses a multitude of the product's features; however, any specific inquiries should be made to the Canon Marketing Representative.

**Note2:** Comments in the "Conformance Level" column are based on the Information Technology Industry Council's suggested language for use when filling out the Voluntary Product Accessibility Template. The Remarks and Explanations column provides additional information on the evaluation results, and explains the standard functions of the product that can accommodate users with disabilities.

**Note3:** This document is for informational purposes only. This information is based on Canon's current understanding of the standards. It is not intended to address applicability of these laws to a particular end-user, customer, application or procurement.

**Note4:** All product design and specifications are subject to change. Some of the information may be based upon data collected or tests conducted on similar product modules.

**Note5:** The information in this Report should not be considered a contractual agreement by Canon. FURTHER, THE INFORMATION AND MATERIALS PROVIDED IN THIS REPORT ARE "AS IS" WITHOUT WARRANTIES OF ANY KIND, INCLUDING WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. Canon does not warrant the accuracy and completeness of the information or materials in this Report. Canon may make changes to the information in this Report, or to the products described in this Report at any time, without notice.